

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
Allerton Harbor							
<i>Aids maintained from May 15 to Sep. 30.</i>							
12125	Buoy 1	42 17 55 N 70 53 19 W		3	2	Green.	Private aid.
	*	*	*				1/10
12130	Buoy 2	42 17 56 N 70 53 18 W		3	2	Red.	Private aid.
	*	*	*				* 1/10
12140	- Buoy 4	42 18 08 N 70 53 14 W				Red nun.	Private aid.
		*					1/10
34990	<i>Gowanus Flats Lighted Bell Buoy 32</i>	40 40 19 N 74 02 24 W	FIR 4s		3	Red.	
					*		1/10
35877	- Buoy 30A					Red nun.	* 1/10
35885	- Channel Buoy 32					Red nun.	* 1/10
35905	- Channel Buoy 35					Green can.	* 1/10
35930	- Channel Buoy 39					Green can.	* 1/10
35940	- Channel Buoy 42					Red nun.	* 1/10
35945	- Channel Buoy 44	40 19 23 N 73 59 46 W				Red nun.	* 1/10
35950	- Channel Buoy 46					Red nun.	* 1/10
35955	- Channel Buoy 47					Green can.	* 1/10
35990	- Danger Buoy B	40 23 03 N 73 58 43 W				White with orange bands.	* 1/10
35995	- Danger Buoy C	40 23 00 N 73 58 46 W				White with orange bands.	* 1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
36070	- Lighted Buoy 20	40 22 07 N 74 03 05 W	F I R 4s		2	Red.	* 1/10
37746	WHOI Research Lighted Buoy TC						Remove from list. * 1/10
37806	WHOI Research Lighted Buoy HC						Remove from list. * 1/10
37807	WHOI Research Lighted Buoy HS						Remove from list. * 1/10

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*3017.2	DIAMOND STATE PIER LIGHT Q	39 42 28 N 75 30 50 W	F I Y 2.5s	12		On mooring dolphin.	Private aid. 1/10
*3017.3	DIAMOND STATE PIER LIGHT R	39 42 27 N 75 30 50 W	F I Y 2.5s	12		On mooring dolphin.	Private aid. 1/10
Brewerton Channel Eastern Extension							
<i>Channel buoys located 75 feet outside channel limit.</i>							
8385	Brewerton Channel Eastern Extension Lighted Buoy 2BE	39 08 55 N 76 19 59 W	F I R 2.5s		6	Red.	Replaced by LIB of reduced intensity from Dec. 1 to Mar. 15. * 1/10
11230	- ENTRANCE LIGHT 8		F I R 4s	15	3	TR on pile.	* 1/10
*18823	ST. JEROME CREEK LIGHT 11	38 07 23 N 76 20 43 W	F I G 4s	15	4	SG on pile.	Light equipment removed from Dec. 1 to Mar 15. 1/10
Locust Point West Channel							
21240	-Locust Point West Channel Lighted Buoy 1LW	39 15 25 N 76 35 54 W	F I G 2.5s		5	Green.	* 1/10
21245	Locust Point West Channel Lighted Buoy 2W	39 15 25 N 76 35 44 W	F I R 2.5s		5	Red.	* 1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2009							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
21250	-Locust Point West Channel Lighted Buoy 4W		FI R 4s		5	Red.	
	*		*		*	*	1/10
29655	- Buoy 1	34 31 27 N 77 19 50 W				Green can.	
		*					1/10
30165	- Buoy 4	35 10 42 N 77 48 14 W				Red nun.	
		*					1/10
32315	FRISCO LIGHT 10	35 15 26 N 75 36 36 W	FI R 6s	15	3	TR on pile.	
		*					1/10

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO - ECONFINA RIVER, FLORIDA TO THE RIO GRANDE, TEXAS, 2009							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*257	Shell Mooring Buoy	30 10 45 N 88 04 56 W				White with blue band.	Private aid.
							1/10
*493	Newfield-108-2 Lighted Buoy	28 57 23 N 89 45 07 W	FI W 2.5s			White with orange bands.	SIGN: NEC-WD-72-10. Private aid.
							1/10
5240	- LIGHT 45 250 feet outside channel limit.		Q G	17	4	SG on piles.	Ra ref.
						*	1/10
5310	- LIGHT 55 200 feet outside channel limit.	30 29 18 N 88 01 12 W	FI G 4s	17	4	SG on piles.	Ra ref.
						*	1/10
5375	- LIGHT 69 200 feet outside channel limit.		FI G 4s	17	4	SG on piles.	Ra ref.
						*	1/10

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
105	HUNTINGTON BEACH PIER LIGHT	33 39 12 N 118 00 24 W	FI W 4s	32		At end of concrete pier	Private aid.
				*			1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
190 3585	Point Hueneme Light	34 08 42 N 119 12 35 W	FI (5) W 30s 0.1s fl 4.9s ec. 0.1s fl 4.9s ec. 0.1s fl 4.9s ec. 0.1s fl 9.9s ec.	52	20	White square tower on building. 48	Light obscured from 296° to 155°. The sound signal can be activated upon request to the Coast Guard via VHF-FM Ch 16. HORN: 1 blast ev 30s (3s bl). 251 feet from light.
							* 1/10
203	PLATFORM HARVEST LIGHT	34 28 09 N 120 40 57 W	FI W 6s	60	10	Platform	
						*	1/10
	POINT SUR TO SAN FRANCISCO (Chart 18680)						
280	Point Sur Light	36 18 23 N 121 54 06 W	FI W 15s	250	25	Light House 48	Emergency light of reduced intensity when main light is extinguished.
						*	1/10
282	<i>-Scripps Waverider Lighted Research Buoy "157"</i>	36 20 16 N 122 06 05 W	FI(5)Y 20s			Yellow.	Private aid.
	*						1/10
289	<i>-Scripps Waverider Lighted Research Buoy "156"</i>	36 45 39 N 121 56 49 W	FI (5) Y 20s			Yellow.	Private aid.
	*						1/10
290	Point Pinos Light	36 38 00 N 121 56 01 W	Oc W 4s	89	17	Building 28	Emergency light of reduced intensity when main light is extinguished.
						*	1/10
320	Pigeon Point Light	37 10 54 N 122 23 38 W	FI W 10s	148	20	Cylindrical 155	Emergency light of reduced intensity when main light is extinguished.
						*	1/10
381	<i>-Scripps Waverider Lighted Research Buoy 029</i>	37 56 45 N 123 28 12 W	FI (5) Y 20s			Yellow sphere with whip antenna.	Private aid.
	*						1/10
420	Point Arena Light	38 57 17 N 123 44 26 W	FI W 15s	155	25	Light House 115	Emergency light of reduced intensity when main light is extinguished.
						*	1/10
450	Point Cabrillo Light	39 20 54 N 123 49 33 W	FI W 10s	81	22	Light House 47	Emergency light of reduced intensity when main light is extinguished.
						*	1/10
478	<i>Scripps Waverider Lighted Research Buoy 094</i>	40 17 38 N 124 44 25 W	FI (5) Y 20s			Yellow sphere with whip antenna.	Private aid.
	*						1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
487	<i>-Scripps Waverider Lighted Research Buoy 128</i>	40 45 12 N 124 18 48 W	FI (5) Y 20s			Yellow sphere with whip antenna.	Private aid.
	*						1/10
TRINIDAD HEAD TO CAPE BLANCO (Chart 18600)							
525	Trinidad Head Light	41 03 06 N 124 09 05 W	Oc W 4s	196	14	Lighted House 25	Light obscured northward of 140°. Emergency light of reduced intensity when main light is extinguished. HORN: 1 blast ev 30s (3s bl).
						*	1/10
590	<i>NOAA Environmental Lighted Buoy 46015</i>	42 44 44 N 124 49 24 W	FI (4) Y 20s			Yellow disc-shaped buoy.	Aid maintained by NOAA.
	*	*					1/10
641	<i>NOAA Environmental Lighted Buoy 46050</i>	44 37 27 N 124 30 00 W	FI (4) Y 20s			Yellow disc-shaped buoy.	Aid maintained by NOAA.
	*						1/10
685 9875	Nehalem River Approach Whistle Buoy NR	45 39 17 N 123 57 33 W				Red and white stripes.	No topmark will be shown on this aid as required by IALA standards due to weather.
							* 1/10
688	<i>NOAA Environmental Lighted Buoy 46029</i>	46 08 31 N 124 30 37 W	FI (4) Y 20s			Yellow disk-shaped buoy.	Aid maintained by NOAA.
	*						1/10
689	<i>NOAA Environmental Lighted Buoy 46089</i>	45 53 36 N 125 49 09 W	FI (4) Y 20s			Yellow disc-shaped buoy.	Aid maintained by NOAA.
	*						1/10
690	<i>Columbia River Approach Lighted Whistle Buoy CR</i>	46 11 05 N 124 11 03 W	Mo (A) W		5	Red and white stripes.	RACON: M (-). No topmark will be shown on this aid as required by IALA standards due to weather.
							* 1/10
733	<i>NOAA Environmental Lighted Buoy 46041</i>	47 21 10 N 124 43 50 W	FI (4) Y 20s			Yellow disc-shaped buoy.	Aid maintained by NOAA.
	*	*					1/10
755 16135	<i>Strait of Juan de Fuca Traffic Separation Lane Lighted Buoy J</i>	48 29 37 N 125 00 00 W	FI Y 2.5s		6	Yellow.	RACON: O (- - -).
	*						1/10
756 16136	<i>Straight of Juan De Fuca Traffic Lane Separation Lighted Buoy JA</i>	48 29 38 N 124 43 38 W	FI Y 2.5s		3	Yellow.	
	*						1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
SAN DIEGO TO ALEUTIAN ISLANDS AND HAWAIIAN ISLANDS (Chart 530)							
765.1	NOAA Environmental Lighted Buoy 46002	42 34 12 N 130 27 36 W	FI (4) Y 20s			Yellow boat-shaped hull.	Aid Maintained by NOAA.
	*						1/10
765.2	NOAA Environmental Lighted Buoy 46005	46 03 00 N 131 01 12 W	FI (4) Y 20s			Yellow boat-shaped hull.	Aid maintained by NOAA.
	*						1/10
765.7	DART Tsunami Warning Lighted Buoy 46419	48 45 42 N 129 37 00 W	FI (4) Y 20s			Yellow disc shaped hull.	Aid maintained by NOAA.
	*	*				*	1/10
905	LOOKOUT ISLAND LIGHT (C)	49 59 54 N 127 27 00 W	F I G 4s	48	9	White circular tower with green band at top, on white rectangular building. 23	HORN: 1 blast ev 20s (2s bl).
			*				1/10
982	NOAA Data Lighted Buoy 46080	58 02 06 N 149 59 38 W	FI (4) Y 20s			Yellow boat-shaped hull.	
		*					1/10
984.1	NOAA Data Lighted Buoy 46066	52 44 14 N 154 57 40 W	FI (4) Y 20s			Yellow boat-shaped hull.	
		*					1/10
984.2	NOAA Tsunami Warning Lighted Buoy 46403	52 38 11 N 156 55 54 W	FI(4) Y 20s			Red and white disc shaped hull.	Aid maintained by NOAA.
	*	*					1/10
984.3	NOAA Tsunami Warning Lighted Buoy 46402	51 04 10 N 164 00 38 W	FI Y 20s			Red and White disc shaped hull.	Aid maintained by NOAA.
	*						1/10
984.4	NOAA Tsunami Warning Lighted Buoy 46408	49 37 34 N 169 52 17 W	FI(4)Y 20s			Yellow disc shaped hull.	Aid maintained by NOAA.
	*						1/10
984.5	NOAA Tsunami Warning Lighted Buoy 46409	55 18 03 N 148 29 42 W	FI (4)Y 20s			Red and White Disc Shaped Hull	Aid Maintained by NOAA
	*	*					1/10
984.6	NOAA Tsunami Warning Lighted Buoy 46410	57 38 00 N 143 48 13 W	FI (4)Y 20s			Red and White Disc Shaped hull.	Aid Maintained by NOAA.
	*						1/10
984.7	NOAA Tsunami Warning Lighted Buoy 46413	48 40 18 N 174 35 36 W	FI (4)Y 20s			Red and white disc-shaped hull	Aid maintained by NOAA.
	*						1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
984.8	NOAA Tsunami Warning Lighted Bouy 21414	48 56 17 N 178 16 52 W	FI(4)Y 20s			Red and white disc shaped hull.	Aid maintained by NOAA.
	*	*					1/10
984.85	NOAA Tsunami Warning Lighted Buoy 21415	50 11 00 N 171 59 36 E	FI(4)Y20s			Yellow disc shaped hull.	Aid maintained by NOAA.
	*	*					1/10
1082	NOAA Data Lighted Buoy 46083	58 14 33 N 137 59 36 W	FI (4) Y20s			Yellow boat-shaped hull.	
		*					1/10
1097	NOAA Data Lighted Buoy 46082	59 41 17 N 143 23 56 W	FI (4) Y 20s			Yellow boat-shaped hull.	
		*					1/10
1131	NOAA Data Lighted Buoy 46061	60 13 04 N 146 49 30 W	FI(4)Y 20s			Yellow boat-shaped weather buoy.	Aid maintained by NOAA.
							1/10
1187	NOAA DATA LIGHTED BUOY 46078	56 04 25 N 152 34 20 W	FI (4)Y 20s			Yellow boat-shaped buoy.	
		*					1/10
1570	BALLAST POINT LIGHT B	32 41 10 N 117 13 57 W	FI W 4s	16	10	NG on platform on dolphin.	HORN: 1 blast ev 15s (2s bl).
	*						1/10
1571	Ballast Point Shoal Buoy	32 41 12 N 117 14 00 W				White can labeled SHOAL, with orange bands.	
						*	1/10
San Diego Bay							
1800	San Diego Bay Pier B Sound Signal	32 43 03 N 117 10 35 W					HORN: 1 blast ev 15s (2s bl).
	*						1/10
2052.1	SAN DIEGO BAY SPEED CONTROL LIGHT A	32 38 34 N 117 07 38 W	FI W 4s	11		White sign with orange border on pile.	Private aid.
	*						1/10
2052.2	SAN DIEGO BAY SPEED CONTROL LIGHT B	32 38 30 N 117 07 46 W	FI W 4s	11		White sign with orange border on pile.	Private aid.
							* 1/10
2110	- LIGHT 13	32 37 50 N 117 07 48 W	Q G	14		SG on pile.	Private aid.
				*			1/10
2289.1	Scripps Waverider Lighted Research Buoy "100"	32 55 49 N 117 23 33 W	FI (5) Y 20s			Yellow sphere with whip antenna.	Private aid.
	*						1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2289.2	<i>Scripps Waverider Lighted Research Buoy "45"</i>	33 10 46 N 117 28 17 W	FI (5) Y 20s			Yellow sphere with whip antenna.	Private aid.
	*						1/10
2289.6	<i>Scripps Waverider Lighted Research Buoy "043"</i>	33 13 12 N 117 26 23 W	FI (5) Y 20s			Yellow.	Private aid.
	*						1/10
GULF OF SANTA CATALINA (Chart 18774)							
Oceanside							
<i>Due to frequently changing conditions, positions of buoys are not listed.</i>							
2290	<i>- Approach Lighted Whistle Buoy OC</i>	33 12 06 N 117 24 29 W	Mo (A) W		5	Red and white stripes.	No topmark will be shown on this aid as required by IALA standards due to weather.
							* 1/10
2395	<i>- BREAKWATER LIGHT 3</i>	33 27 15 N 117 41 29 W	FIG 4s	32	6	SG on post.	The sound signal can be activated upon request to the Coast Guard via VHF-FM Ch 16. HORN: 1 blast ev 10s (1s bl).
							* 1/10
2536	<i>Scripps Waverider Lighted Buoy 028</i>						<i>Remove from list.</i>
							* 1/10
2560	-Wilson Cove Sound Signal	33 00 26 N 118 33 38 W					HORN: 1 blast ev 15s (2s bl).
	*						1/10
2775	<i>- Entrance Lighted Whistle Buoy 2 50 feet outside channel limit.</i>	33 43 00 N 118 06 36 W	Q R		3	Red.	
		*					* 1/10
2780	<i>- RANGE FRONT LIGHT</i>	33 44 12 N 118 05 32 W	Q G	45		KRW on skeleton tower.	Visible 4° each side of rangeline. Lighted throughout 24 hours.
							* 1/10
2790	<i>- Entrance Buoy 3 50 feet outside channel limit.</i>					Green.	
							* 1/10
2795	<i>- Entrance Buoy 4 50 feet outside channel limit.</i>					Red.	
							* 1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2800	- WEST JETTY LIGHT 5	33 43 39 N 118 06 06 W	FI G 2.5s	31	4	SG on post.	The sound signal can be requested to the Coast Guard via VHF-FM CH 16. HORN: 2 blasts ev 20s (2s bl-2s si-2s bl-14s si). * 1/10
2810	- Channel Buoy 7					Green. *	1/10
2815	- Channel Buoy 8					Red. *	1/10
2827	- Channel Buoy 13					Green. *	Buoy maybe frequently relocated due to changing conditions. * 1/10
2828	- Channel Buoy 15	33 43 56 N 118 05 20 W				Green can.	Buoy maybe frequently relocated due to changing conditions. * 1/10
2829	- Channel Buoy 17					Green. *	Buoy maybe frequently relocated due to changing conditions. * 1/10
2835	- WEST JETTY LIGHT 1	33 44 14 N 118 07 19 W	FI G 2.5s	16	4	SG on post.	The sound signal can be activated upon request to the Coast Guard via VHF-FM Ch 16. BELL: 1 stroke ev 15s. * 1/10
Long Beach Harbor							
2845	LONG BEACH BREAKWATER EAST END LIGHT 1	33 43 23 N 118 08 13 W	FI G 6s	43	5	SG on skeleton tower.	The sound signal can be activated upon request to the Coast Guard via VHF-FM Ch 16. HORN: 1 blast ev 15s (2s bl). * 1/10
3345	KING HARBOR BASIN 2 LIGHT 1		FG	5		On post.	Private aid. * 1/10
3350	KING HARBOR BASIN 2 LIGHT 2		FR	5		On post.	Private aid. * 1/10
3360	- BASIN 1 LIGHT 2		FR	5		On post.	Private aid. * 1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3455	- LIGHT 3	33 57 46 N 118 27 42 W	FI G 4s	45	6	SG on white building.	Obscured 151° to 331°. The fog signal can be activated upon request to the Coast Guard via VHF- FM Ch 16. HORN: 2 blasts ev 20s (2s bl-2s sl-2s bl-14s sl). * 1/10
3595	- Entrance Lighted Whistle Buoy PH	34 08 18 N 119 13 00 W	Mo (A) W		6	Red and white stripes. No topmark will be shown on this aid as required by IALA standards due to weather. * 1/10	
3690	- Ventura Marina Buoy 4	34 14 33 N 119 16 27 W				Red nun. * 1/10	
3755	- Lighted Bell Buoy SB	34 24 06 N 119 40 48 W	Mo (A) W		5	Red and white stripes. No topmark will be shown on this aid as required by IALA standards due to the weather. * 1/10	
3796	Scripps Waverider Lighted Research Buoy 071	34 27 28 N 120 46 49 W	FI (5) Y 20s			Yellow sphere with whip antenna. Private aid. * 1/10	
3820	San Luis Obispo Buoy 2	35 09 24 N 120 43 54 W				Red. * 1/10	
3833	Scripps Waverider Lighted Research Buoy 076	35 12 14 N 120 51 34 W	FI (5) Y 20s			Yellow sphere with whip antenna. Private aid. * 1/10	
Morro Bay Channel							
<i>Buoys inside the harbor are set to best mark the channel and are not charted.</i>							
3840	Morro Bay Approach Lighted Whistle Buoy MB	35 21 36 N 120 52 50 W	Mo (A) W		5	Red and white stripes. No topmark will be shown on this aid as required by IALA standards due to weather. * 1/10	
3964	Scripps Waverider Lighted Research Buoy 158	36 37 35 N 121 54 26 W	FI(5)Y 20s			Yellow sphere with whip antenna. Private aid. * 1/10	
*3971.1	Monterey Bay Special Purpose Buoy MY1	36 37 16 N 121 53 05 W	FI Y 4s			Yellow. Private aid. 1/10	

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*3971.2	<i>Monterey Bay Special Purpose Buoy MY2</i>	36 37 59 N 121 54 16 W	FI Y 4s			Yellow	Private aid. 1/10
*3971.3	<i>Monterey Bay Special Purpose Buoy MY3</i>	36 38 42 N 121 55 24 W	FI Y 4s			Yellow.	Private aid. 1/10
*3971.4	<i>Monterey Bay Special Purpose Buoy MY4</i>	36 40 00 N 121 54 24 W	FI Y 4s			Yellow	Private aid. 1/10
*3971.5	<i>Monterey Bay Special Purpose Buoy MY6</i>	36 38 18 N 121 51 18 W	FI Y 4s			Yellow	Private aid. 1/10
*3971.6	<i>Monterey Bay Special Purpose Buoy MY7</i>	36 36 54 N 121 52 30 W	FI Y 4s			Yellow	Private aid. 1/10
4000	- HARBOR ENTRANCE RANGE FRONT LIGHT	36 48 33 N 121 47 07 W	Q G	15		KRW on red pile.	Visible 5.5° each side of rangeline. * 1/10
4005	- HARBOR ENTRANCE RANGE REAR LIGHT 63 yards, 052° from front light.	36 48 34 N 121 47 05 W	Iso G 6s	25		KRW on red pile.	Visible 5.5° each side of the rangeline. * 1/10
Santa Cruz							
<i>Buoys inside the harbor are set to best mark the channel and are not charted.</i>							
4080	- <i>Lighted Whistle Buoy SC</i>	36 56 20 N 122 00 35 W	Mo (A) W		6	Red and white stripes.	No topmark will be shown on this aid as required by IALA standards due to weather. * 1/10
4085 300	- WEST BREAKWATER LIGHT	36 57 36 N 122 00 06 W	Oc G 4s	36	6	White cylindrical structure.	HORN: 1 blast ev 30s (2s bl). Operates from May 01 to Oct 20 * 1/10
4187	<i>Scripps Waverider Lighted Research Buoy 142</i>	37 46 53 N 122 35 56 W	FI(5)Y 20s			Yellow.	3 foot sphere with whip antenna. Private aid. * 1/10
6252	OZOL PIER WEST LIGHT	38 01 46 N 122 09 47 W	FR	12		West pier corner.	Private aid. * 1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6253	Ozol Pier East Light	38 01 41 N 122 09 37 W	F R	12		East Pier Conner	Private aid
				*			1/10
6362	AVON TURNING BASIN SOUTH LIGHT	38 02 52 N 122 05 49 W	FI W 4s	18		Single pile.	Private aid.
				*			1/10
6363	AVON TURNING BASIN NORTH LIGHT	38 03 06 N 122 05 56 W	FI W 4s	18		Single pile.	Private aid.
				*			1/10
6970	- RANGE C REAR LIGHT 300 yards, 306° from front light.	38 02 47 N 121 30 17 W	Iso W 6s	35		KRW on pile.	Visible all around; higher intensity on rangeline.
		*					* 1/10
7010	- RANGE E REAR LIGHT 170 yards, 126° from front light.	38 01 21 N 121 27 50 W	Iso G 6s	35		KRW on pile.	Visible all around; higher intensity on the rangeline.
							* 1/10
7100	- RANGE H FRONT LIGHT	37 59 05 N 121 23 19 W	Q G	25		KRW on pile.	Visible all around; higher intensity on the rangeline.
							* 1/10
7105	- RANGE H REAR LIGHT 657 yards, 115° from front light.	37 58 57 N 121 22 56 W	Iso G 6s	51		KRW on skeleton tower.	Visible all around; higher intensity on the rangeline.
							* 1/10
7120	- RANGE J FRONT LIGHT	37 59 11 N 121 23 31 W	Q W	20		KRW on pile.	Visible all around; higher intensity on the rangeline.
							* 1/10
7125	- RANGE J REAR LIGHT 750 yards, 317° from front light.	37 59 23 N 121 23 45 W	Iso W 6s	65		KRW on pile.	Visible all around; higher intensity on the rangeline.
							* 1/10
7575	- RANGE E REAR LIGHT 370 yards, 000° from front light.	38 32 49 N 121 35 04 W	Iso W 6s	40		KRW on white column.	Visible all around; higher intensity on the rangeline.
							* 1/10
7785	- CHANNEL RANGE A FRONT LIGHT 3	38 18 19 N 123 03 24 W	Q G	13		KRW on pile, SG facing upstream.	Visible all around; higher intensity on the rangeline.
							* 1/10
7790	- CHANNEL RANGE A-B REAR LIGHT 153 yards, 269° from range A front light. 193 yards, 209° from range B front light.	38 18 19 N 123 03 30 W	Iso G 6s	25		KRW on frame.	Visible all around; higher intensity on the rangelines.
						*	* 1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
7850	- CHANNEL RANGE C REAR LIGHT 225 yards, 179° from front light.	38 18 41 N 123 03 07 W	Iso R 6s	23		KRW on pile.	Visible all around; higher intensity on rangeline. * 1/10
7970	- CHANNEL RANGE D REAR LIGHT 275 yards, 359.5° from front light.	38 20 05 N 123 03 09 W	Iso G 6s	23		KRW on white timber structure.	Visible all around; higher intensity on rangeline. * 1/10
8145	- APPROACH RANGE REAR LIGHT 167 yards, 105° from front light.	40 45 51 N 124 13 47 W	Oc W 4s	55	12	KRW on pile. On same structure as Humboldt Bay Light.	Visible 4° each side of rangeline. Lighted throughout 24 hours. * 1/10
8300	- RANGE REAR LIGHT 100 yards, 326.5° from front light.	40 44 36 N 124 13 40 W	Iso R 6s	30	6	KRW on pile.	Visible all around; higher intensity on rangeline. * 1/10
8627	Chetco River Sound Signal	42 02 40 N 124 16 13 W					HORN: 1 blast ev 30s (3s bl). HORN is activated by keying the mic 5 times on VHF-FM Channel 79A (156.975mhz). HORN will operate for 45 minutes. * 1/10
8660	- NORTH JETTY LIGHT 3	42 25 14 N 124 25 59 W	FI G 2.5s	23	4	SG on skeleton structure.	HORN: Light and sound signal maintained from May 20 to Oct. 1 1 blast ev 30s (3s bl). Operates continuously. * 1/10
8762	- North Jetty Sound Signal	43 21 31 N 124 20 41 W		6			HORN: 1 blast ev 30s(3s bl). (3s bl). Fog signal sounded continuously from May 20 to Oct 01. * 1/10
9150	- Regulated Boating Area Warning Sign (2)	43 20 51 N 124 19 16 W	Q Y	10		NW worded ROUGH BAR.	Lights flashing when seas exceed four feet in height, lights extinguished for lesser sea conditions, but with no guarantee that bar is safe. * 1/10
9247	-South Jetty Sound Signal	43 39 59 N 124 13 10 W					HORN: 1 blast ev 15s (2s bl). Maintained from May 20 to Oct 01 * 1/10
9287	<i>Winchester Bay West Basin Regulatory Lighted Buoy A</i>	43 40 58 N 124 11 03 W	FI W 4s			White and orange.	Private aid. Maintained from Jun 01 to Sep 30. * 1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9289	Winchester Bay West Basin Regulatory Lighted Buoy B	43 40 56 N 124 10 58 W	FI W 4s			White can.	Private aid. Maintained from Jun 01 to Sep 30. * 1/10
9297	Winchester Bay East Basin Regulatory Lighted Buoy A	43 41 02 N 124 10 46 W	FI W 4s			White and orange.	Private aid. Maintained from Jun 01 to Sep 30. * 1/10
9299	Winchester Bay East Basin Regulatory Lighted Buoy B	43 41 01 N 124 10 46 W	FI W 4s			White and orange.	Private aid. Maintained from Jun 01 to Sep 30. * 1/10
9452	- North Jetty Sound Signal.	44 01 09 N 124 08 46 W					Maintained from May 20 to Oct. 01. HORN: 1 blast ev 30s (3s bl). * 1/10
9607	- South Jetty Sound Signal	44 36 32 N 124 04 51 W					HORN 1 blast ev 15s (2s bl) Operates continuously Maintained from May 20 to Oct 01. . * 1/10
9790	-Sound Signal	44 48 29 N 124 03 40 W				White square house.	HORN: 1 blast ev 30s (3s bl). HORN is activated by keying the mic 5 times on VHF-FM Channel 79A (156.975mhz). HORN will operate for 15 minutes. * 1/10
9822	- North Jetty Sound Signal	45 34 14 N 123 57 51 W					HORN 1 blast ev 30s (3s bl) Maintained from Jun 01 to Oct 01. . * 1/10
9837	- Regulated Boating Area Warning Sign (2)	45 34 13 N 123 57 22 W	Q Y			NW worded ROUGH BAR.	Lights flashing when seas exceed four feet in height. Lights extinguished for lesser sea conditions with no guarantee that bar is safe. * 1/10
Tillamook Bay							
9865	- Tillamook Bay Boat Basin Small Boat Warning Sign	45 33 16 N 123 55 08 W	Q Y	12		NW worded ROUGH BAR.	Visible from 234° to 333°. Lights flashing when seas exceed four feet in height. Lights extinguished for lesser sea conditions with no guarantee that bar is safe. * 1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
NEHALEM RIVER (Chart 18556)							
Nehalem River							
9875 685	- Approach Whistle Buoy NR	45 39 17 N 123 57 33 W				Red and white stripes.	No topmark will be shown on this aid as required by IALA standards due to weather. * 1/10
9880	- Entrance Range Front Daybeacon	45 39 36 N 123 55 48 W				KRW on multi-pile structure. *	Due to seasonal changes in entrance channel, use only with local knowledge. Private aid. 1/10
9885	- Entrance Range Rear Daybeacon 120 yards, 085° from front daybeacon.					KRW on multi-pile structure. *	Private aid. 1/10
Desdemona Sands							
9975	- CHANNEL LEADING LIGHT	46 16 10 N 124 02 21 W	FI W 4s	31	6	Black and White stripes on pile structure. *	1/10
10005	FORT STEVENS WHARF LIGHT 26	46 12 27 N 123 57 05 W	FI R 6s	35	5	TR on multi-pile. *	1/10
10105	- LOWER RANGE FRONT LIGHT	46 11 29 N 123 50 10 W	Iso R 2s	40		KRB on roof.	Visible 1.5° each side of channel. Lighted throughout 24 hours. * 1/10
10110	- LOWER RANGE REAR LIGHT 570 yards, 241.2° from front light.	46 11 21 N 123 50 32 W	Oc R 4s	175		KRB on pile structure.	Visible 1.5° each side of channel. Lighted throughout 24 hours. * 1/10
10633	COLUMBIA RIVER GEODETIC SURVEY LIGHT	46 11 06 N 123 11 12 W	FI Y 10s	10		On steel dolphin.	Maintained by U.S. Geological Survey. Private aid. * 1/10
15940	DAMON POINT LIGHT	46 57 02 N 124 06 21 W	FI Y 4s	20	5	NW on pile structure. *	Ra ref. 1/10
STRAIT OF JUAN DE FUCA ENTRANCE (Chart 18460)							
Strait of Juan De Fuca							
16135 755	<i>Strait of Juan De Fuca Traffic Separation Lane Lighted Buoy J</i>	48 29 37 N 125 00 00 W	FI Y 2.5s		6	Yellow.	RACON: O (- - -). * 1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
16136 756	- Traffic Separation Lane Lighted Buoy JA	48 29 38 N 124 43 38 W	FI Y 2.5s		3	Yellow.	
	*						1/10
19180	- Lighted Buoy 6	48 35 27 N 122 39 07 W	FI R 4s		3	Red.	
					*		1/10
Portland Inlet							
21860	LIZARD POINT LIGHT (C)	54 50 00 N 130 16 30 W	FI W 6s	24	7	White circular tower.	
					*		1/10
21865	RAMSDEN POINT LIGHT (C)	54 59 00 N 130 06 16 W	FI (3) W 12s	27	5	Orange ball daymark on pole.	Obscured from 117.5° to 260°.
		*			*		1/10
Pearse Canal							
21870	- ISLAND LIGHT (C)	54 47 02 N 130 36 36 W	FI W 4s	18	5	White square daymarks on E., S. and W. sides of square skeleton tower.	
		*			*		1/10
21880	HATTIE ISLAND LIGHT (C)	55 17 15 N 129 58 29 W	FI W 6s	21	5	Orange circular slatwork daymark on pole.	Visible from 171° to 336°.
		*					1/10
21900	STEWART LIGHT (C)	55 54 38 N 129 59 29 W	FI (3) W 12s 0.5s fl 2s ec. 0.5s fl 2s ec. 0.5s fl 6.5s ec.	12	5	Square skeleton tower.	
		*			*		1/10
21905	STEWART DOLPHIN WEST LIGHT (C)	55 54 46 N 130 00 17 W	FI G 4s	23	4	Three pile dolphin.	
		*	*		*	*	1/10
28021	LAUPAHOEHOE HARBOR BREAKWATER LIGHT 2	19 59 30 N 155 14 23 W	FI R 4s	27	3	TR on post.	
						*	1/10
28130	Cape Kumukahi Light	19 30 59 N 154 48 39 W	FI W 15s	156	24	White pyramidal skeleton tower. 153	Lighted throughout 24 hours. Obscured from 015° to 120°. Emergency light of reduced intensity when main light is extinguished. Emergency light operates during periods of darkness only.
						*	1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
28345	- ENTRANCE RANGE REAR LIGHT 470 yards, 177° from front light.	20 53 13 N 156 28 18 W	F R	91		KRW on post.	Visible 4° each side of rangeline. Lighted throughout 24 hours.
						*	1/10
Maui Island							
28415	McGregor Point Light	20 46 39 N 156 31 22 W	Iso G 6s	72	10	On white tower. 20	Obscured from 082° to 221°.
							1/10
	*						
28524	-UH Wave Lighted Buoy 146	20 47 25 N 157 00 50 W	FI Y 20s			Yellow spherical buoy.	Private aid.
							1/10
	*						
28675.1	WECB Lighted Buoy G	21 27 57 N 157 45 02 W	FI Y 4s			Yellow buoy with black letter "G". Radar reflector.	Private aid.
							1/10
	*						
28815	- RANGE REAR LIGHT 475 yards, 217.2° from front light.	21 25 54 N 157 48 27 W	Iso R 6s	80	15	KRW on post. 40	Visible 4° each side of rangeline.
							1/10
			*				
28890	- UH Wave Lighted Buoy 098	21 25 00 N 157 40 00 W	FI Y 20s			Yellow spherical buoy.	Private aid.
							1/10
	*						
OAHU ISLAND (Chart 19357)							
29060	Diamond Head Light	21 15 21 N 157 48 34 W	Oc (2) W 10s (R sector)	147	W 17 R 14	Lighthouse. 64	Obscured from 110° to 272°, red from 099° to 110°. Between 105° to 110°, red sector may be obscured by vegetation. Emergency light of reduced intensity when main light is extinguished.
			2s fl 1.5s ec. 5s fl 1.5s ec.				1/10
							*
29100	- CHANNEL RANGE FRONT LIGHT	21 17 18 N 157 50 36 W	F R	30		KRW on post.	Private aid.
							1/10
							*
29105	- CHANNEL RANGE REAR LIGHT 90 yards, 013.5° from front light.		Q R	48		KRW on post.	Private aid.
							1/10
							*
29175	-Honolulu Harbor Entrance Lighted Buoy H	21 16 51 N 157 52 48 W	Mo (A) W		6	Red and white stripes with red spherical topmark.	RACON: O (— — —).
							1/10
	*						

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
29380	-PEARL HARBOR ENTRANCE RANGE FRONT LIGHT LIGHT	21 19 36 N 157 58 15 W	Q R	51		KRW on post. 50	Visible 4° on either side of rangeline.
	*						1/10
29734.5	-UH Wave Lighted Buoy 106	21 40 22 N 158 06 57 W	FI (4) Y 20s			Yellow spherical buoy.	Private aid.
	*						1/10
Nawiliwili Harbor							
29755	KUKII POINT LIGHT	21 57 24 N 159 20 53 W	FI W 2.5s (two R sectors)	47	W 6 R 5	White pyramidal concrete tower. 17	Red from 045° to 065° and 250° to 290°.
			*				1/10
*29898	-PORT ALLEN SMALL BOAT HARBOR BREAKWATER LIGHT 2	21 54 03 N 159 35 21 W	FI R 2s	20		Pole on concrete base.	Private aid.
							1/10
29908	PMRF Mooring Buoy T	22 00 20 N 159 47 20 W				White.	Maintained by U.S. Navy.
						*	1/10
30261	-Ta'u Harbor Range Rear Daybeacon 33 yards, 045° from front daybeacon.	14 14 20 N 169 30 38 W		33		KRW on spindle. 25	
	*						1/10
Faleasao Harbor							
30265	-Faleasao Harbor Range Front Daybeacon	14 13 17 S 169 30 54 W				KRW on spindle. 13	
	*						1/10
30266	- Faleasao Harbor Range Rear Daybeacon 66 yards, 200.5° from front daybeacon.	14 13 18 N 169 30 54 W				KRW on spindle. 23	
	*						1/10
30680	-AGAN SMALL BOAT BASIN APPROACH LIGHT 2	13 28 56 N 144 45 12 E	FI R 2.5s	22	4	SR on pile.	
	*						1/10
Apra Outer Harbor							
30690	-Apra Outer Harbor Entrance Lighted Buoy 1	13 27 02 N 144 37 24 E	FI G 4s		4	Green.	
	*						1/10
30725	-APRA OUTER HARBOR PIER DOG LIGHT	13 27 47 N 144 38 54 E	FI W 4s	25	6	NB on post.	Obscured from 090° to 270°.
	*						1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
Cabras Island Channel							
30735	-Cabras Island Channel Lighted Buoy 2	13 27 33 N 144 39 19 E	FI R 2.5s		3	Red.	
	*						1/10
30751	Piti Channel Entrance Light 1	13 27 35 N 144 40 25 E	FI G 4s	10	4	TG on pile.	
	*						1/10
30770	-Apra Outer Harbor Lighted Buoy 8	13 27 09 N 144 39 36 W	FI R 6s		4	Red.	
	*	*					1/10
30810.5	ACOE Wave Meter Lighted Buoy	13 22 12 N 144 38 36 E	FI Y 4s			Yellow sphere.	Aid Maintained by U.S. Army Corps of Engineers.
							* 1/10
30811	Agat Harbor Entrance Lighted Buoy AG	13 22 04 N 144 38 31 E	Mo (A) W		3	Red and white stripes with red spherical topmark.	
	*						1/10
SAIPAN (Chart 81076)							
Tanapag Harbor							
30855	-Tanapag Harbor Approach Lighted Buoy T	15 12 11 N 145 40 29 E	Mo (A) W		6	Red and white stripes with red spherical topmark.	
	*						1/10
30870	-Tanapag Harbor Channel Lighted Buoy 2	15 13 13 N 145 41 25 E	Q R		4	Red.	
	*						1/10
30880	-TANAPAG HARBOR RANGE REAR LIGHT 1,100 yards, 088.4° from front light.	15 13 43 N 145 44 52 W	Iso G 6s	97		KRW on skeleton tower.	Visible 4° each side of rangeline.
	*	*					1/10
30885	-Tanapag Harbor Channel Lighted Buoy 3	15 13 39 N 145 42 06 E	FI G 2.5s		4	Green.	
	*						1/10
30905	-Tanapag Harbor Channel Lighted Buoy 7	15 13 42 N 145 43 03 E	FI G 4s		3	Green.	
	*						1/10
Sugar Dock Channel							
30918	Sugar Dock Channel Buoy 3	15 08 55 N 145 41 50 E				Green can.	Private aid.
	*						1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
30918.1	Sugar Dock Channel Buoy 4	15 08 57 N 145 41 49 E				Red nun.	Private aid.
	*						1/10
30918.2	-Sugar Dock Channel Buoy 5	15 09 01 N 145 41 54 E				Green can.	Private aid.
	*						1/10
30918.3	-Sugar Dock Channel Buoy 6	15 09 01 N 145 41 53 E				Red Nun.	Private aid.
	*						1/10
30918.4	-Sugar Dock Channel Buoy 7	15 09 03 N 145 41 56 E				Green can.	Private aid.
	*						1/10
30918.5	-Sugar Dock Channel Buoy 8	15 09 07 N 145 41 59 E				Red nun.	Private aid.
	*						1/10
30918.6	-Sugar Dock Channel Buoy 10	15 09 06 N 145 41 57 E				Red nun.	Private aid.
	*						1/10
30918.7	-Sugar Dock Channel Buoy 12	15 09 07 N 145 41 59 E				Red nun.	Private aid.
	*						1/10
30919	USHI POINT LIGHT	15 06 02 N 145 38 39 E	FI W 2.5s	18	6	NB on pile.	
						*	1/10
30925	- <i>Tinian Harbor Channel Lighted Buoy 2</i>	14 57 24 N 145 37 22 E	FI R 2.5s		3	Red.	
	*						1/10
30940	-TINIAN HARBOR CHANNEL LIGHT 5	14 57 51 N 145 37 24 E	FI G 4s	20	4	TG on post. On corner of pier. 12	
	*						1/10

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4025	-GLERL Cleveland	41 44 01 N 81 41 54 W	FI Y 4s				Secured with two-point mooring system, lighted spar buoys with the same flash characteristics marking mooring locations. Private aid.
	*	*				*	1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2009							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4025.1	Lake Erie Research Lighted Buoy B						Remove from list. * 1/10
4025.2	Lake Erie Research Lighted Buoy C						Remove from list. * 1/10
4036	Lake Erie Research Lighted Buoy D						Remove from list. * 1/10
4036.1	Lake Erie Research Lighted Buoy E						Remove from list. * 1/10
4036.2	Lake Erie Research Lighted Buoy F						Remove from list. * 1/10
*6029	-GLERL Maumee	41 45 14 N 83 13 53 W	FI Y 4s				Secured with two point mooring system, lighted spar buoys with the same flash characteristics marking mooring locations. Private aid. 1/10
*18704	-GLERL Muskegon	43 11 17 N 86 20 38 W	FI Y 4s				Secured with two point mooring system, lighted spar buoys with the same flash characteristics marking mooring locations. Private aid. 1/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.