

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
10620	UPPER TURN LIGHT 16	42 27 11 N 70 56 31 W	FIR 2.5s	28	4	TR on skeleton tower.	Higher intensity beam up and down channel.
			*				2/10
10965	Pier Four Wreck Buoy North						Remove from list.
							*
							2/10
10970	Pier Four Wreck Buoy South						Remove from list.
							*
							2/10
16230	- Hog Island Channel Lighted Buoy 23	41 43 48 N 70 38 05 W	FIG 4s		3	Green.	Replaced by LIB from Dec. 15 to Mar. 15.
		*					2/10
24067	New Haven Research Lighted Buoy						Remove from list.
							*
							2/10
30270	Great Gun Beach Channel Buoy 5	40 46 05 N 72 46 57 W	FIG 4s			Green can.	Private aid.
	*	*					2/10
30460	- Channel Buoy 4	40 47 09 N 72 49 12 W				Red.	Private aid.
	*	*	*				2/10
30470	Forge River Channel Buoy 6	40 47 11 N 72 49 11 W				Red.	Private aid.
	*		*				2/10
30735	- Buoy 6	40 51 23 N 72 31 29 W				Red.	Private aid.
	*	*	*				2/10
35536	- Buoy G						Remove from list.
							*
							2/10
35538	- Buoy I						Remove from list.
							*
							2/10

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2575	- Lighted Bell Buoy 2R	39 29 01 N 75 33 40 W	QR		5	Red.	Replaced by a LIB of reduced intensity from Jan. 1 to Feb. 28.
					*		2/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
19655	- LIGHT 17	38 57 12 N 76 33 44 W	FIG 2.5s	15	4	SG on pile.	
		*					2/10
	Severn River						
19935	Weems Creek Junction Daybeacon WC	39 00 05 N 76 29 56 W				JG on pile.	
		*					2/10
20035	- Daybeacon 3	38 59 38 N 76 26 53 W				SG on pile.	
		*					2/10
20040	- Daybeacon 5	38 59 41 N 76 26 56 W				SG on pile.	
		*					2/10
20080	- Daybeacon 6	39 00 03 N 76 25 55 W				TR on pile.	
		*					2/10
20085	- Daybeacon 7	39 00 26 N 76 25 57 W				SG on pile.	
		*					2/10
30160	Masonboro Inlet Buoy 3	34 10 41 N 77 48 19 W				Green can.	
		*					2/10
35460	- Lighted Buoy 115		FIG 4s		4	Green with yellow square.	Replaced by can from Nov. 15 to May 01.
				*		*	2/10

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COASTS - LITTLE RIVER, SOUTH CAROLINA TO ECONFINA RIVER, FLORIDA, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
33380	HICACAL BEACH LIGHT		FI W 2.5s	80		KRW on skeleton tower.	
	*		*			*	2/10
40555	- Daybeacon 2						Remove from list.
							2/10
40560	- Daybeacon 3						Remove from list.
							2/10
40575	- Daybeacon 6						Remove from list.
							2/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COASTS - LITTLE RIVER, SOUTH CAROLINA TO ECONFINA RIVER, FLORIDA, 2009							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
40585	- Daybeacon 8						<i>Remove from list.</i>
							* 2/10
CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO - ECONFINA RIVER, FLORIDA TO THE RIO GRANDE, TEXAS, 2009							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
337 8392	Ship Island Lighthouse						<i>Remove from list.</i>
							* 2/10
7575	- RANGE FRONT LIGHT						<i>Remove from list.</i>
							* 2/10
CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1350	POINT SPENCER LIGHT	65 16 38 N 166 50 56 W	FI W 6s	22	7	NR on skeleton tower.	Maintained from Jul. 1 to Nov. 1.
							* 2/10
9075	MARSHFIELD RANGE FRONT LIGHT	43 22 35 N 124 12 26 W	Q G	14		KRB on tower.	Visible all around.
							* 2/10
9080	MARSHFIELD RANGE REAR LIGHT 237 yards, 018.5° from front light.		Iso G 6s	36		KRB on tower.	Visible all around.
							* 2/10
Coos River							
9090	MARSHFIELD CHANNEL RANGE FRONT LIGHT	43 22 30 N 124 10 54 W	Q R	14		KRB on dolphin.	Visible all around.
							* 2/10
9095	MARSHFIELD CHANNEL RANGE REAR LIGHT 480 yards, 090° from front light.		Iso W 6s	21		KRB on skeleton tower.	Visible all around.
							* 2/10
9346	LEEDS ISLAND RANGE FRONT LIGHT	43 43 18 N 124 07 36 W	Q W	15		KRB on skeleton tower.	Visible 4° each side of rangeline.
							* 2/10
9347	LEEDS ISLAND RANGE REAR LIGHT 380 yards, 173° from front light.		Iso W 6s	30		KRB on skeleton tower.	Visible 4° each side of rangeline.
							* 2/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9795	- ENTRANCE RANGE FRONT LIGHT	44 48 34 N 124 03 43 W	Q R	42		KWR on skeleton tower.	Visible 4° each side of rangeline. Lighted throughout 24 hours. * 2/10
9800	- ENTRANCE RANGE REAR LIGHT 16 yards, 085.5° from front light.		Iso R 6s	54		KWR on skeleton tower.	Visible 4° each side of rangeline. Lighted throughout 24 hours. * 2/10
9895	- ENTRANCE RANGE FRONT LIGHT	46 16 33 N 124 03 05 W	F R	186		KWB on skeleton structure.	Visible 0.5° each side of rangeline. Lighted throughout 24 hours. * 2/10
9900	- ENTRANCE RANGE REAR LIGHT 625 yards, 045° from front light.		F G	240		KWB on skeleton structure.	Visible 0.5° each side of rangeline. Lighted throughout 24 hours. * 2/10
Wauna							
10430	- RANGE FRONT LIGHT	46 08 38 N 123 22 55 W	Q R			KRB on skeleton tower.	Visible 14° each side of rangeline. * 2/10
10435	- RANGE REAR LIGHT 673 yards, 137.5° from front light.	46 08 23 N 123 22 36 W	Iso R 6s	56		KRB on skeleton tower.	Visible 10° each side of rangeline. * 2/10
10825	COTTONWOOD ISLAND LOWER RANGE REAR LIGHT 327 yards, 115.8° from front light.		Iso W 6s	40		KRB on skeleton tower.	Visible 5.5° each side of rangeline. * 2/10
North Portland Harbor							
11280	- EAST END RANGE FRONT LIGHT	45 36 04 N 122 38 31 W	Q R	35		KRB on dike.	Visible all around; higher intensity on rangeline. * 2/10
11615	CAPE HORN RANGE FRONT LIGHT	45 34 05 N 122 11 36 W	Q R	26		KRB on pile.	Visible all around; higher intensity on rangeline. Ra ref. * 2/10
11990	BINGEN RANGE FRONT LIGHT	45 41 42 N 121 26 41 W	Q R	27	6	KRB on skeleton tower.	Visible 4° each side of rangeline. * 2/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11995	BINGEN RANGE REAR LIGHT 1,600 yards, 123° from front light.	45 41 16 N 121 25 46 W	Iso R 6s	60	9	KRB on skeleton tower.	Visible 5.5° each side of rangeline. * 2/10
15610	- SOUTH REACH RANGE A FRONT LIGHT	46 55 13 N 124 02 59 W	FI R 2.5s	21		KRB on pile structure.	Visible all around; higher intensity on rangeline. Ra ref. * 2/10
15665	GRAYS HARBOR SOUTH REACH RANGE AA FRONT LIGHT	46 55 05 N 124 03 41 W	Q R	21		KRB on pile structure.	Visible all around; higher intensity on rangeline. Ra ref. * 2/10
15670	SOUTH REACH RANGE AA REAR LIGHT 242 yards, 246.7° from front light.		Iso R 6s	38		KRB on skeleton tower on pile structure.	Visible 14° each side of rangeline. * 2/10
15890	- REACH RANGE L FRONT LIGHT	46 58 29 N 123 48 17 W	Q R	21		KRB on dolphin.	Visible 1.5° each side of rangeline. * 2/10
15895	- REACH RANGE L REAR LIGHT 350 yards, 050° from front light.		Iso R 6s	37		KRB on skeleton tower on pile structure.	Visible 1.5° each side of rangeline. * 2/10
17675	- RANGE FRONT LIGHT	47 57 42 N 122 41 06 W	Q R	17		KRB on tower.	Visible all around. * 2/10
17680	- RANGE REAR LIGHT 63 yards, 261.3° from front light.		Iso R 6s	28		KRB on skeleton tower.	Visible all around. * 2/10
18555	- RANGE REAR LIGHT 339 yards, 002.5° from front light.	48 01 05 N 122 13 27 W	Iso G 6s	40		KRB on same structure as Snohomish River Range C Rear Daybeacon.	Visible 14° each side of range line. * 2/10
18825	- RANGE REAR LIGHT 1,100 yards, 252° from front light.		Iso W 6s	50		KRW on skeleton tower.	Visible 14° each side of rangeline. * 2/10
19240	WHATCOM WATERWAY RANGE FRONT LIGHT	48 45 10 N 122 29 03 W	Q G	41		KRW on platform on building.	Visible 1.5° each side of rangeline. * 2/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
19245	WHATCOM WATERWAY RANGE REAR LIGHT 393 yards, 045.2° from front light.		Iso G 6s	70		KRW on skeleton tower.	Visible 1.5° each side of rangeline. * 2/10
Portland Inlet							
21860	LIZARD POINT LIGHT (C)	54 50 00 N 130 16 30 W	FI W 6s	24	7	Red cylindrical tower. *	2/10
21865	RAMSDEN POINT LIGHT (C)	54 59 00 N 130 06 16 W	FI (3) W 12s	27	5	Orange square skeleton tower. *	Obscured from 117.5° to 260°. 2/10
22162	<i>Tongass Narrows East Channel Lighted Buoy AGS</i>	55 20 08 N 131 37 59 W	FI W 4s			White with orange bands. *	Maintained from Jun. 25 to Sept. 10. Private aid. * 2/10
22163	<i>Trident Seafood Outfall Lighted Buoy "TSK"</i>	55 20 12 N 131 38 15 W	FI W 3s			White with orange bands. *	Maintained from Jul. 01 to Sept. 15. Private aid. * 2/10
22176	Ketchikan Berth No. 1 South Pier Light	55 20 18 N 131 38 36 W	F G	12		On post. *	Private aid. 2/10
*22773	Banana Point Breakwater Markers (4)	56 33 12 N 132 37 48 W				NW on breakwater.	Private aid. 2/10
23808	SMUGGLERS COVE SOUTH DOCK LIGHT	58 20 52 N 134 39 07 W	FI Y 2s	3		On dock. *	Private aid. 2/10
23809	SMUGGLERS COVE NORTH DOCK LIGHT	58 20 53 N 134 39 07 W	FI Y 2s	3		On dock. *	Private aid. 2/10
24084	TENAKEE HOUSE LIGHT	57 46 47 N 135 13 18 W	Q W	20		On residential house. *	Private aid. 2/10
27975	POINT SPENCER LIGHT	65 16 38 N 166 50 56 W	FI W 6s	22	7	KGW on skeleton tower.	Maintained from Jul. 1 to Nov. 1. * 2/10
	*	*	*	*	*	*	* 2/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2009

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
ISLAND OF HAWAII (Chart 19320)							
28010	Kauhola Point Light	20 14 47 N 155 46 17 W	FI W 15s	110	24	White cylindrical concrete tower. 86	Obscured from 306° to 101°. Lighted throughout 24 hours. Emergency light of reduced intensity when main light is extinguished. Emergency light operates during periods of darkness only. * 2/10
29380	-PEARL HARBOR ENTRANCE RANGE FRONT LIGHT LIGHT	21 19 36 N 157 58 15 W	Q R	51		KRW on post. 50	Visible 4° on either side of rangeline. Lighted throughout 24 hours. * 2/10
29385	- ENTRANCE RANGE REAR LIGHT 750 yards, 333.6° from front light.	21 19 56 N 157 58 26 W	Oc R 4s	97		KRW on skeleton tower. 83	Visible 4° each side of rangeline. Lighted throughout 24 hours. * 2/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.