

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2010

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
35 5590	Seguin Light	43 42 27 N 69 45 29 W	F W	180	18	Brick conical tower. 180	Emergency light of reduced intensity when main light is extinguished. Two emergency lights may be visible from 340° and 160°. HORN: 2 blasts ev 20s (2s bl-2s si-2s bl-14s si).
						*	42/10
295	Cape Ann Light	42 38 12 N 70 34 30 W	FI R 5s	166	17	Granite tower. 166	Emergency light of reduced intensity when main light is extinguished. HORN: 2 blasts ev 60s (3s bl-3s si-3s bl-51s si).
						*	42/10
485	Race Point Light	42 03 44 N 70 14 35 W	FI W 10s	41		On white tower. 41	Obscured from 220° to 292°. Emergency light of reduced intensity when main light is extinguished.
						*	42/10
1120	Libby Island Light	44 34 06 N 67 22 03 W	FI (2) W 20s	91	18	White tower. 91	Emergency light of reduced intensity when main light is extinguished. HORN: 1 blast ev 15s (2s bl).
						*	* 42/10
13159.5	Sesuit Harbor Buoy 6						<i>Remove from list.</i>
							* 42/10
*18406	NT Yacht Club Mid-Channel Buoy	41 44 50 N 71 21 19 W					Private aid.
							42/10
	*Delete Note:						
	<i>*Private aids are replaced by spar buoys from Nov. 1 to Apr. 15.</i>						
26815	- Buoy 1A						<i>Remove from list.</i>
							* 42/10
26820	- Buoy 2A						<i>Remove from list.</i>
							* 42/10
26825	- Buoy 3A						<i>Remove from list.</i>
							* 42/10
26830	- Buoy 4A						<i>Remove from list.</i>
							* 42/10
37275	- Channel Lighted Buoy 7	40 38 58 N 74 05 08 W	FI G 4s		3	Green.	
							* 42/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2010

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1095	- Lighted Buoy 40	39 47 31 N 74 09 26 W	QR		3	Red.	Replaced by nun from Nov 15 to May 1.
		*					42/10
2977	CHERRY ISLAND RANGE FRONT PASSING LIGHTS (2)	39 45 02 N 75 29 39 W	FIW 4s	15	5	Located on same structure as Cherry Island Range Front Light.	
	*						42/10
4115.1	KINKORA LOWER RANGE REAR PASSING LIGHT	40 07 07 N 74 47 10 W	FIW 4s	15	4	Located on same structure as Kinkora Lower Range Rear Light.	Located on corner of platform.
	*	*				*	42/10
4854	Isle of Wight Bay Buoy 8B	38 21 17 N 75 05 21 W				Red nun.	
						*	42/10
11040	- CHANNEL LIGHT 9	36 53 26 N 76 28 17 W	FIG 4s	15	4	SG pile.	
						*	42/10
14945	- LIGHT 4						<i>Remove from list.</i>
							* 42/10
*21903	- Channel Daybeacon 12A	37 40 16 N 75 50 19 W					
							42/10
22215	- Daybeacon 9	37 48 12 N 75 45 38 W				SG on pile.	
		*					42/10
28027	Oregon Inlet Buoy 13	35 46 31 N 75 31 53 W				Green can.	
		*					42/10
28275	- Buoy 11	35 43 58 N 75 36 50 W				Green can.	
		*					42/10
28475	- CHANNEL LIGHT 19	35 51 41 N 75 37 04 W	FIG 2.5s	15	3	SG on multi-pile structure.	Light equipment removed when endangered by ice.
		*					42/10
28820	- LIGHT 32	35 13 49 N 75 42 06 W	FIR 2.5s	15	3	TR on pile.	
		*					42/10
31330	- LIGHT 2KH	36 01 11 N 75 45 36 W	FIR 4s	16	4	TR on pile.	
		*					42/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2010							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*35647	- Buoy 160A	39 26 48 N 74 23 29 W				Red nun with yellow triangle.	42/10
*35649	- Buoy 161	39 26 48 N 74 23 28 W				Green can with yellow square.	42/10

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COASTS, 2010							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1095	Dry Tortugas Light	24 38 00 N 82 55 14 W	FI W 20s	151	20	Conical tower, lower half white, upper half black.	Emergency light (FI W 6s) of reduced intensity when main light is extinguished. RACON: K (- • -). * 42/10
7115	ST. JOHNS BAR CUT RANGE FRONT LIGHT	30 24 14 N 81 25 40 W	FI W 2.5s (Day) FI W 2.5s (Night)	22 19		On tower on piles.	DAY: Visible 0.5° each side of rangeline. NIGHT: Visible 1.5° each side of rangeline. * 42/10
33940	- Lighted Buoy 65	33 32 08 N 79 06 14 W	FI G 4s		3	Green with yellow square.	* 42/10
	*	*		*	*	*	42/10

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2010							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4075 31570	- NAVY RANGE FRONT LIGHT	30 20 05 N 87 18 59 W	FI G 2.5s	34	3	KRW on skeleton tower on piles.	Visible all around; higher intensity 1.5° each side of rangeline. * 42/10
5260	- LOWER REACH RANGE FRONT LIGHT	30 26 24 N 88 00 44 W	Q W	26	5	KGR on skeleton tower on piles.	Visible all around; higher intensity 1.5° each side of range line. * 42/10
6190	- OUTER RANGE FRONT LIGHT	30 28 36 N 88 00 43 W	Q W	27 25		KRW on skeleton tower on piles.	Visible all around; higher intensity 1.5° each side of range line. * 42/10
6290	- LIGHT 17 155 feet outside channel limit.	30 31 21 N 88 05 36 W	FI G 2.5s	17	3	SG on pile.	Ra ref. * 42/10
6955	- RANGE A FRONT LIGHT	30 17 57 N 88 30 52 W	FI R 2.5s (Night) FI W 2.5s (Day)	31 34		KRW on skeleton tower on piles.	Lighted throughout 24 hours. NIGHT: Visible 1.5° each side of rangeline. * 42/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2010

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6960	- RANGE A REAR LIGHT 1,666 yards, 354.1° from front light.	30 18 46 N 88 30 58 W	Iso R 6s (Night) Iso W 6s (Day)	94 91		KRW on skeleton tower on piles.	NIGHT: Visible 1.5° each side of rangeline. DAY: Visible 0.5° each side of rangeline. Passing light visible all around. * 42/10
7425	- LIGHT 10 130 feet outside channel limit.	30 19 22 N 88 30 43 W	Q R	17	3	TR on pile.	Ra ref. * 42/10
31570 4075	- NAVY RANGE FRONT LIGHT	30 20 05 N 87 18 59 W	FI G 2.5s	34	3	KRW on skeleton tower on piles.	Visible all around; higher intensity 1.5° each side of rangeline. * 42/10

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2010

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
86	<i>Scripps Offshore GEOCE Research Buoy</i>	33 12 35 N 118 23 32 W	FI (2) Y 4s			Yellow disk with skeleton tower.	Private aid. * 42/10
360	<i>San Francisco Approach Lighted Whistle Buoy SF</i>	37 45 00 N 122 41 34 W	Mo (A) W		5	Red and white stripes with spherical topmark.	RACON: M (— —). * 42/10
365 4245	Mile Rocks Light	37 47 34 N 122 30 37 W	FI W 5s	49	15	On cylindrical structure with white and orange bands.	HORN: 1 blast ev 30s (2s bl). Operates continuously. * 42/10
1520	- LIGHT Z	32 40 01 N 117 13 23 W	FI R 2.5s	28	6	NW on post worded DANGER SUBMERGED JETTY.	HORN: 1 blast ev 10s (1s bl). Operates continuously. * 42/10
1635	NORTH ISLAND LIGHT NW	32 42 30 N 117 13 12 W	FI W 2.5s	23	4	NR on post.	 * 42/10
4245 365	Mile Rocks Light	37 47 34 N 122 30 37 W	FI W 5s	49	15	On cylindrical structure with white and orange bands.	HORN: 1 blast ev 30s (2s bl). Operates continuously. * 42/10
*24157	HOONAH DOCK LIGHT	58 06 57 N 135 27 20 W	FI W 2.5s	15		On dock.	Private aid. 42/10
27810	EKUK RANGE FRONT LIGHT	58 47 56 N 158 33 16 W	Q W	44		KRW on skeleton tower.	Visible all around, higher intensity on rangeline. * 42/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2010

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
27815	EKUK RANGE REAR LIGHT 417 yards, 341° from front light.	56 48 08 N 158 33 24 W	Iso W 6s	64		KRW on skeleton tower.	Visible all around; higher intensity on rangeline.
				*			42/10
*28005.1	<i>NOAA Data Lighted Buoy</i> 51002	17 05 41 N 157 46 48 W	FI (4) Y 20s				Aid maintained by NOAA.
							42/10
*28005.3	<i>Moby Research Lighted Buoy</i>	20 49 00 N 157 11 36 W	FI Y 4s				Private aid.
							42/10
*28005.5	<i>NOAA DART Data Lighted</i> <i>Buoy 51407</i>	19 37 48 N 156 31 30 W	FI (4) Y 20s				Private aid.
							42/10
*28005.7	<i>NOAA Data Lighted Buoy</i> 51003	19 05 12 N 160 39 36 W	FI (4) Y 20s				Aid maintained by NOAA.
							42/10
*28005.9	<i>NOAA Data Lighted Buoy</i> 51001	23 26 42 N 162 16 43 W	FI (4) Y 20s				
							42/10
28006	<i>NOAA Data Lighted Buoy</i> 51001	23 26 42 N 162 16 43 W	FI (4) Y 20s				Aid maintained by NOAA.
	*	*				*	*
							42/10
28006.1	<i>NOAA Data Lighted Buoy</i> 51100	23 33 30 N 153 54 00 W	FI (4) Y 20s			Yellow.	
	*	*	*				*
							42/10
*28006.3	<i>NOAA Data Lighted Buoy</i> 51101	24 19 15 N 162 03 30 W	FI (4) Y 20s				
							42/10

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2010

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2080	- West Pierhead Light	43 28 24 N 76 31 01 W	Al WR 10s 0.1s W fl 4.9s ec. 0.1s R fl 4.9s ec.	57 17	11	White square tower on corner of square building.	Standby light Oc R 4s of reduced intensity. HORN: 1 blast ev 30s (3s bl). Operates by keying microphone five times on VHF-FM Ch. 79.
			*		*		42/10
5670	Perry Memorial Monument Light	41 39 15 N 82 48 41 W	Iso W 6s	341 104	15	On roof of monument.	
				*			42/10
6001	WARD CANAL WEST JETTY LIGHT 2	41 39 05 N 83 14 16 W	FI R 4s	28 9	5	TR on post.	
					*		42/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2010

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
12015	- Daybeacon 47	45 26 12 N 84 35 24 W				SG on pile.	
		*					42/10
15580	SAND ISLAND LIGHT	47 00 12 N 90 56 15 W	FI W 6s	60 18	9	Red tower on dwelling.	
					*		42/10
21060	- LIGHT 12	44 48 58 N 87 20 42 W	FI R 4s	21 6	4	TR on pile. 15	
					*		42/10
21791	Cedar River Buoy 2A						<i>Remove from list.</i>
							* 42/10
21792	Cedar River Buoy 2	45 24 24 N 87 21 01 W				Red nun.	Maintained from May 15 to Nov. 15.
	*						42/10

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.