

## SECTION II

## CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1920	Grindstone Ledge Junction Buoy GL	44-22-06.14N 68-05-13.16W *				Green can with red bands.	32/12
	<b>*Add Heading: Squamscott River</b>						
*8596	- Buoy SR1	43-03-55.80N 70-53-47.82W				Green can.	Private aid. 32/12
*8596.1	- Buoy SR2	43-03-56.10N 70-53-53.88W				Red nun.	Private aid. 32/12
*8596.2	- Buoy SR3	43-03-55.26N 73-53-53.50W				Green can.	Private aid. 32/12
*8596.3	- Buoy SR4	43-03-50.40N 70-54-15.18W				Red nun.	Private aid. 32/12
*8596.4	- Buoy SR5	43-03-45.84N 70-54-21.12W				Green can.	Private aid. 32/12
*8596.5	- Buoy SR6	43-03-45.96N 70-54-21.90W				Red nun.	Private aid. 32/12
*8596.6	- Buoy SR8	43-03-44.54N 70-54-27.86W				Red nun.	Private aid. 32/12
*8596.7	- Buoy SR9	43-03-42.24N 70-54-35.34W				Green can.	Private aid. 32/12
*8596.8	- Buoy SR10	43-03-41.64N 70-54-39.24W				Red nun.	Private aid. 32/12
*8596.9	- Buoy SR12	43-03-33.24N 70-54-46.44W				Red nun.	Private aid. 32/12
*8597	- Buoy SR13	43-03-16.08N 70-54-42.66W				Green can.	Private aid. 32/12
*8597.1	- Buoy SR14	43-03-08.22N 70-54-48.12W				Red nun.	Private aid. 32/12
*8597.2	- Buoy SR16	43-02-58.38N 70-54-50.82W				Red nun.	Private aid. 32/12
*8597.3	- Buoy SR18	43-02-50.28N 70-54-58.86W				Red nun.	Private aid. 32/12
*8597.4	- Buoy SR19	43-02-50.28N 70-54-57.18W				Green can.	Private aid. 32/12
*8597.5	- Buoy SR20	43-02-35.40N 70-55-14.70W				Red nun.	Private aid. 32/12
*8597.6	- Buoy SR22	43-02-27.66N 70-55-37.20W				Red nun.	Private aid. 32/12
*8597.7	- Buoy SR23	43-02-25.98N 70-55-37.50W				Green can.	Private aid. 32/12

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9320	- Entrance Buoy 6	42-41-25.34N 70-45-14.89W *				Red nun.	Position frequently shifted with changing conditions.  32/12
13026	Pilgrim Power Plant Security Zone Buoy A	41-57-00.49N 70-34-43.20W *				White with orange bands, can.	Marked "Restricted Area". Private aid.  32/12
13027	Pilgrim Power Plant Security Zone Buoy B	41-57-06.24N 70-34-48.92W *				White with orange bands, can.	Marked "Restricted Area". Private aid.  32/12
13028	<i>Pilgrim Power Plant Security Zone Lighted Buoy C</i>	41-57-13.06N 70-34-43.12W *	FI W 4s			White with orange bands.	Marked "Restricted Area". Private aid.  32/12
13029	Pilgrim Power Plant Security Zone Buoy D	41-57-08.35N 70-34-35.93W *				White with orange bands, can.	Marked "Restricted Area". Private aid.  32/12
13030	Pilgrim Power Plant Security Zone Buoy E	41-57-03.94N 70-34-31.69W *				White with orange bands, can.	Marked "Restricted Area". Private aid.  32/12
13031	Pilgrim Power Plant Security Zone Buoy F	41-57-00.79N 70-34-24.22W *				White with orange bands, can.	Marked "Restricted Area". Private aid.  * 32/12
13032	Pilgrim Power Plant Security Zone Buoy G	41-56-55.33N 70-34-17.77W *				White with orange bands, can.	Marked "Restricted Area". Private aid.  32/12
13033	Pilgrim Power Plant Security Zone Buoy H	41-56-52.19N 70-34-12.95W *				White with orange bands, can.	Marked "Restricted Area". Private aid.  32/12
13034	Pilgrim Power Plant Security Zone Buoy I	41-56-47.80N 70-34-05.66W *				White with orange bands, can.	Marked "Restricted Area". Private aid.  32/12
13034.1	<i>Pilgrim Power Plant Security Zone Lighted Buoy J</i>	41-56-42.73N 70-33-57.75W *	FI W 4s			White with orange bands.	Marked "Restricted Area". Private aid.  32/12
13034.2	Pilgrim Power Plant Security Zone Buoy K	41-56-40.54N 70-34-03.26W *				White with orange bands, can.	Marked "Restricted Area". Private aid.  32/12
13034.3	Pilgrim Power Plant Security Zone Buoy L	41-56-33.74N 70-34-06.43W *				White with orange bands, can.	Marked "Restricted Area". Private aid.  32/12
14210	Fish Reef Buoy FR						<i>Remove from list.</i>  * 32/12
14533	EDDIE WOODS ROCKFISH TRAP NORTH LIGHT	41-37-35.00N 70-18-28.00W	FI Y 6s			On pile.	Maintained from Mar. 1 to Jun. 30. Private aid.  * 32/12
14534	EDDIE WOODS ROCKFISH TRAP CENTER LIGHT	41-36-55.00N 70-18-00.00W	FI Y 6s			On pile.	Maintained from Mar. 1 to Jun. 30. Private aid.  * 32/12
14535	EDDIE WOODS ROCKFISH TRAP SOUTH LIGHT	41-36-49.00N 70-18-01.00W	FI Y 6s	10		On pile.	Maintained from Mar. 1 to Jun. 30. Private aid.  * 32/12
22451	- Entrance Buoy 1						<i>Remove from list.</i>  * 32/12

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
23480	- Channel Buoy 8	41-15-47.61N 72-31-33.55W *				Red nun.	32/12
28750	- <i>Lighted Buoy 22</i> On south point of Robins Island Shoal.	40-57-09.06N 72-27-01.10W	FI R 2.5s		3	Red.	Replaced by nun from Nov. 1 to Apr. 15. * 32/12
28785	- <i>Lighted Buoy 24</i>	40-55-57.36N 72-27-28.91W	FI R 4s		3	Red.	Replaced by nun from Nov. 1 to Apr. 15. * 32/12
32745	Haunt's Creek Buoy R7	40-36-35.46N 73-31-29.94W *				Green can.	Private aid. 32/12
35590	- LIGHT 7	40-25-26.90N 74-03-37.00W *	FI G 2.5s			On pile.	Private aid. 32/12
36022	<i>Barley Point Lighted Research Buoy</i>						<i>Remove from list.</i> * 32/12

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4757	<i>Ocean City Inlet Lighted Buoy 12</i>	38-19-38.97N 75-05-47.89W	FI R 2.5s		4	Red	* 32/12
7095	- TUNNEL SOUTH LIGHT	37-02-17.47N 76-04-28.01W	F Y	32		Mounted atop wall on centerline.	BELL: 1 stroke ev 10s. Operates during periods of low visibility only. Private aid. * 32/12
22800	- <i>Lighted Buoy 5</i> *	37-51-05.81N 75-56-57.03W	FI G 6s		5	Green.	Replaced by can when endangered by ice. 32/12
28003	- <i>Lighted Buoy 6</i> *	35-47-20.82N 75-31-12.19W	Q R		4	Red.	32/12
28029	- Buoy 14	35-46-27.46N 75-32-01.20W *				Red nun.	32/12
28030	- Buoy 15	35-46-25.21N 75-32-01.29W *				Green can.	32/12
28720	South Ferry Terminal Warning Daybeacon A Located 350 yards outside of channel. *	35-11-44.08N 75-46-22.93W				NW on pile worded DANGER SHOALING. * * * *	32/12
30705	- <i>Channel Lighted Buoy 38</i> *	34-02-54.40N 77-56-21.18W	Q R		4	Red.	Ra ref. 32/12
30720	- <i>Channel Lighted Buoy 39</i> *	34-03-48.22N 77-56-14.95W	FI G 4s		4	Green.	32/12

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
30725	- Channel Lighted Buoy 40	34-04-11.07N 77-56-00.61W *	FI R 4s		3	Red.	32/12
30785	- Channel Lighted Buoy 49	34-07-42.32N 77-56-16.09W *	FI G 2.5s		4	Green. Ra ref.	32/12
34815	- Buoy 3	34-42-21.13N 76-40-42.18W *				Green can.	32/12
39597	- Buoy 121	34-14-58.92N 77-46-56.17W *				Green can with yellow square.	32/12

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
25580	- Daybeacon 1	27-46-37.33N 82-47-37.08W *				SG on pile.	32/12
34185	- LIGHT 22	33-08-57.32N 79-19-08.17W	FI R 4s	12	5	TR-TY on pile. *	32/12
35215	- LIGHT 187	32-30-00.00N 80-32-01.76W	FI G 4s	12	5	SG-SY on pile. *	32/12
37095	- CUTOFF LIGHT 231	31-15-24.72N 81-23-41.82W	FI G 4s	12	5	SG-SY on pile. *	32/12
37985	- LIGHT 1	30-39-48.06N 81-29-03.06W	FI G 4s	12	5	SG-SY on pile. *	32/12
38003	- LIGHT 8	30-38-24.11N 81-29-22.98W	Q R	16	4	TR-TY on pile. *	32/12
38615	- LIGHT 48	30-14-46.84N 81-25-43.08W	FI R 4s	12	5	TR-TY on pile. *	32/12
38625	- LIGHT 3	30-06-34.80N 81-22-19.20W	FI G 4s	16	5	SG-SY on pile. *	32/12
45915.5	- LIGHT 240	27-10-03.74N 80-10-50.69W	FI R 6s	16	5	TR-TY on pile. *	32/12

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*15612	- Buoy 38A	29-11-08.82N 89-21-47.16W				Red nun.	32/12
*15677	- Buoy 52A	29-13-05.46N 89-21-02.64W				Red nun.	32/12

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2215	- LIGHT 13	32-37-59.26N 117-06-43.53W	FI G 2.5s			Green.	Private aid.
	*						32/12
19395	BELLE ROCK SECTOR LIGHT	48-29-34.75N 122-45-09.68W	FI W 2.5s	22	W 7 R 5	NB on skeleton tower on steel cylindrical base.	Red sector visible 1.5° either side of 175°.
						*	32/12
19397	<i>Belle Rock Lighted Isolated Danger Buoy BR</i>						<i>Remove from list.</i>
							* 32/12
25455	SOFTUK BAR CHANNEL LIGHT S	60-13-17.86N 144-59-00.89W	Oc (4)W 30s	12	6	NR on skeleton tower.	Maintained from May 1 to Oct. 1.
		*					32/12
25460	KOKENHENIC BAR CHANNEL LIGHT K	60-13-28.89N 145-09-32.18W	FI W 4s	12	6	NR on skeleton tower.	Maintained from May 1 to Oct. 1.
		*					32/12
25470	PETER DAHL BAR CHANNEL LIGHT P	60-18-22.88N 145-32-48.92W	FI W 2.5s	12	5	NR on skeleton tower.	Maintained from May 1 to Oct. 1.
		*					32/12
25615.2	- South Channel Buoy 2A	60-27-34.64N 145-58-39.31W				Red nun.	
		*					32/12
25615.25	- South Channel Buoy 3	60-27-56.44N 145-58-36.07W				Green can.	
		*					32/12
25615.3	- South Channel Buoy 4	60-28-08.53N 145-58-15.83W				Red nun.	
		*					32/12
27565	- Entrance Lighted Buoy 2	55-59-57.04N 160-39-13.35W	FI R 4s		4	Red ice buoy.	Year round lighted buoy.
	*		*		*	*	* 32/12
27570	- Entrance Lighted Buoy 3	55-59-15.05N 160-36-49.35W	FI G 4s		4	Green ice buoy.	Year round lighted buoy.
						*	32/12
27590	- Lighted Buoy 4	55-58-00.52N 160-39-35.68W	FI R 6s		4	Red ice buoy.	Year round lighted buoy.
						*	32/12
27595	- Lighted Buoy 5	55-57-55.39N 160-38-17.87W	FI G 6s		4	Green ice buoy.	Year round lighted buoy.
						*	32/12
27600	- Lighted Buoy 6	55-56-09.04N 160-42-31.34W	FI R 4s		4	Red ice buoy.	Year round lighted buoy.
						*	32/12
27605	- Lighted Buoy 7	55-55-51.04N 160-41-55.34W	FI G 4s		4	Green ice buoy.	Year round lighted buoy.
						*	32/12
27610	- Lighted Buoy 8	55-53-57.03N 160-47-07.34W	FI R 2.5s		4	Red ice buoy.	Year round lighted buoy.
						*	32/12
27615	- Lighted Buoy 9	55-53-35.50N 160-47-07.75W	FI G 2.5s		4	Green ice buoy.	Year round lighted buoy.
						*	32/12

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4685	SANDUSKY DOCK CHANNEL LIGHT 21 *	41-27-25.16N 82-43-16.30W	FI G 4s	19 6	5	SG on pile.	32/12
5085	SQUAW ISLAND LIGHT *	41-27-09.50N 82-59-41.20W	Q W	25 8	3	NW with daymarks worded "DANGER SHOALING"	32/12
13015	WINTER POINT RANGE FRONT LIGHT *	46-13-33.75N 84-08-38.57W	F W	46 14		KRW on white skeleton tower.	Visible 4° each side of rangeline. Lighted throughout 24 hours. * 32/12
13020	WINTER POINT RANGE FRONT PASSING LIGHT *	46-13-33.76N 84-08-38.62W	FI W 2.5s	43 13			Operational from Nov. 15 to Apr. 15. * 32/12
13025	WINTER POINT RANGE REAR LIGHT 3,921 feet, 322.1° from front light. *	46-14-04.29N 84-09-12.84W	F W	82 25		KRW on white skeleton tower.	Visible 4° each side of rangeline. Lighted throughout 24 hours. * 32/12
13145	POINT OF WOODS RANGE FRONT LIGHT *	46-16-19.42N 84-07-13.76W	F W	31 9		KRW on triangular skeleton tower.	Lighted throughout 24 hours. 32/12
13155	POINT OF WOODS RANGE REAR LIGHT 325 feet, 314.7° from front light. *	46-16-21.68N 84-07-17.06W	F W	42 13		KRW on square skeleton tower.	Lighted throughout 24 hours. 32/12
13170	DARK HOLE EAST RANGE FRONT LIGHT *	46-15-53.99N 84-06-54.78W	F G	40 12		KRG on square skeleton tower.	Range marks eastern half of channel. High intensity beam on range line. F G light operated from Nov. 15 to Apr. 15. Lighted throughout 24 hours. * 32/12
13175	DARK HOLE EAST RANGE REAR LIGHT 499 feet, 176.6° from front light. *	46-15-49.07N 84-06-54.36W	F G	75 23		KRG on square skeleton tower.	Range marks eastern half of channel. High intensity beam on range line. F G light operated from Nov. 15 to Apr. 15. Lighted throughout 24 hours. * 32/12
13180	DARK HOLE WEST RANGE FRONT LIGHT *	46-15-54.86N 84-06-57.71W	Q W	38 12		KRW on square skeleton tower.	Range marks western half of channel. Visible 1.5° each side of range line. Lighted throughout 24 hours. * 32/12
13185	DARK HOLE WEST RANGE REAR LIGHT 424 feet, 176.6° from front light. *	46-15-50.67N 84-06-57.36W	F W	73 22		KRW on square skeleton tower.	Range marks western half of channel. Visible 1.5° each side of range line. Lighted throughout 24 hours. * 32/12
13190	HARWOOD POINT EAST RANGE FRONT LIGHT *	46-19-17.25N 84-07-12.21W	F R	30 9		KRG on white cylindrical tower.	Range marks eastern half of channel. High intensity beam on range line. F R light operated from Nov. 15 to Apr. 15. Lighted throughout 24 hours. * 32/12
13195	HARWOOD POINT EAST RANGE REAR LIGHT 1,002 feet, 356.6° from front light. *	46-19-27.13N 84-07-13.06W	F R	65 20		KRG on white cylindrical tower.	Range marks eastern half of channel. High intensity beam on range line. F R light operated from Nov. 15 to Apr. 15. Lighted throughout 24 hours. * 32/12

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
13200	HARWOOD POINT WEST RANGE FRONT LIGHT	46-19-17.27N 84-07-15.06W	F W	32 10		KRW on white cylindrical tower.	Range marks western half of channel. Visible 1.5° each side of range line. Lighted throughout 24 hours.
		*		*			* 32/12
13205	HARWOOD POINT WEST RANGE REAR LIGHT 1,001 feet, 356.6° from front light.	46-19-27.14N 84-07-15.91W	F W	65 20		KRW on white cylindrical tower.	Range marks western half of channel. Visible 1.5° each side of range line. Lighted throughout 24 hours.
	*	*		*			* 32/12
13355	LOWER NICOLET EAST RANGE FRONT LIGHT	46-19-29.25N 84-10-32.67W	F G	54 16		KRG on skeleton tower.	Range marks eastern half of channel. High intensity beam on range line. F G light operated from Nov. 15 to Apr. 15. Lighted throughout 24 hours.
		*		*			* 32/12
13360	LOWER NICOLET EAST RANGE REAR LIGHT 1,758 feet, 150.5° from front light.	46-19-14.15N 84-10-20.32W	F G	75 23		KRG on skeleton tower.	Range marks eastern half of channel. High intensity beam on range line. F G light operated from Nov. 15 to Apr. 15. Lighted throughout 24 hours.
	*	*		*			* 32/12
13365	LOWER NICOLET WEST RANGE FRONT LIGHT	46-19-28.62N 84-10-35.41W	F W	60 18		KRW on skeleton tower.	Range marks western half of channel. Visible 1.5° each side of range line. Lighted throughout 24 hours.
		*		*			* 32/12
13370	LOWER NICOLET WEST RANGE REAR LIGHT 3,794 feet, 150.5° from front light.	46-18-56.03N 84-10-08.76W	F W	104 32		KRW on skeleton tower.	Range marks western half of channel. Visible 1.5° each side of range line. Lighted throughout 24 hours.
	*	*		*			* 32/12
13515	- OAK RIDGE RANGE FRONT LIGHT	46-17-08.13N 84-12-56.83W	F G	73 22		KRW on square skeleton tower.	Visible 1.5° each side of range line. Lighted throughout 24 hours.
		*		*		*	* 32/12
13520	- OAK RIDGE RANGE REAR LIGHT 1,947 feet, 181.5° from front light.	46-16-48.92N 84-12-57.57W	F G	144 44		KRW on square skeleton tower.	Visible 1.5° each side of range line. Lighted throughout 24 hours.
	*	*		*			* 32/12
14160	BAYFIELD ROCK RANGE FRONT LIGHT	46-29-19.96N 84-16-59.11W	F W	35 11		KRW on skeleton tower.	Visible 4° each side of range line. Lighted throughout 24 hours.
		*		*			* 32/12
14165	BAYFIELD ROCK RANGE REAR LIGHT 922 feet, 109.2° from front light.	46-29-16.97N 84-16-46.67W	F W	54 16		KRW on skeleton tower.	Visible 4° each side of range line. Lighted throughout 24 hours.
	*	*		*			* 32/12
14230	- RANGE FRONT LIGHT	46-30-14.11N 84-22-01.75W	Q R	32 10		KRW on skeleton tower.	Visible 1.5° each side of range line.
		*		*			* 32/12
14235	- RANGE REAR LIGHT 885 feet, 076.2° from front light.	46-30-16.20N 84-21-49.47W	Iso R 6s	66 20		KRW on skeleton tower.	Visible 1.5° each side of range line.
	*	*		*		*	* 32/12
14430	BIRCH POINT RANGE FRONT LIGHT	46-26-01.30N 84-31-24.09W	F R	63 19		KRW on skeleton tower.	Visible 1.5° each side of range line. Lighted throughout 24 hours.
		*		*			* 32/12

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
14435	BIRCH POINT RANGE REAR LIGHT 3,450 feet, 138.6° from front light.	46-25-35.73N 84-30-51.56W	F R	113 34		KRW on skeleton tower.	Visible on range line only. Visible 1.5° each side of range line. Lighted throughout 24 hours.
	*	*		*		*	* 32/12
15195	<b>Eagle Harbor Light</b>	47-27-35.13N 88-09-32.70W	Al WR 20s 0.1s W fl 9.9s ec. 0.1s R fl 9.9s ec.	60 18	23		Obscured 150° to 330°. Standby light of reduced intensity.
					*		32/12

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.