

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8305	- CHANNEL RANGE FRONT LIGHT	43-04-57.37N 70-42-26.84W *	Iso R 6s	59		KRW on skeleton tower.	Visible 4° each side of range line. * 48/12
8310	- CHANNEL RANGE REAR LIGHT 154 yards, 352.9° from front light. *	43-05-01.89N 70-42-27.61W *	F R	79		KRW on skeleton tower.	Visible 4° each side of range line. * 48/12
8355	PIERCES ISLAND RANGE FRONT LIGHT *	43-04-25.39N 70-44-25.18W *	Q G	51		KRW on skeleton tower.	Visible 4° each side of range line. * 48/12
8360	PIERCES ISLAND RANGE REAR LIGHT 88 yards, 266.6° from front light. *	43-04-25.24N 70-44-28.74W *	Iso G 6s	63		KRW on skeleton tower.	Visible 4° each side of range line. * 48/12
15345.5	<i>Tuckernuck Lagoon Lighted Buoy 3</i> *	41-17-23.88N 70-14-33.00W	FI G 4s			Green.	Private aid. * 48/12
39862	<i>Lake Champlain Bridge Temporary Lighted Buoy 1</i>						Remove from list. * 48/12
39862.1	<i>Lake Champlain Bridge Temporary Lighted Buoy 2</i>						Remove from list. * 48/12
39862.2	<i>Lake Champlain Bridge Temporary Lighted Buoy 3</i>						Remove from list. * 48/12
39862.3	<i>Lake Champlain Bridge Temporary Lighted Buoy 4</i>						Remove from list. * 48/12

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
685	<i>Cape Lookout Lighted Bell Buoy 14</i>	34-18-06.61N 76-23-59.19W	FI R 4s		6	Red.	* 48/12
1645	- <i>Lighted Buoy 42</i> *	39-21-04.72N 75-26-12.59W *	FI R 4s		6	Red.	Removed when endangered by ice. * 48/12
7380	- <i>Lighted Buoy 53</i> 75 feet outside channel limit.	37-37-09.53N 76-06-03.44W	FI G 4s		5	Green.	Replaced by can when endangered by ice. * 48/12
8365	- <i>Lighted Buoy 5</i>	39-06-02.01N 76-18-08.20W	Q G		5	Green.	Replaced by LIB of reduced intensity from Dec. 1 to Mar. 15. * 48/12
12065	GOOSE HILL CHANNEL RANGE FRONT LIGHT	37-10-20.79N 76-45-12.62W *	FI W 2.5s (Night) FI W 2.5s (Day)	16 19		On multi-pile structure.	Lighted throughout 24 hours. DAY: Visible 0.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line. * 48/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
12070	GOOSE HILL CHANNEL RANGE REAR LIGHT 635 yards, 228.3° from front light.	37-10-08.26N 76-45-30.21W	Iso W 6s (Night) Iso W 6s (Day)	43 40		On multi-pile structure.	Lighted throughout 24 hours. DAY: Visible 0.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line.
	*	*					48/12
12235	DANCING POINT SHOAL CHANNEL RANGE FRONT LIGHT	37-12-46.02N 76-54-29.61W	F W (Night) F W (Day)	24 27		On skeleton tower on platform.	Lighted throughout 24 hours. DAY: Visible 0.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line.
		*					48/12
12240	DANCING POINT SHOAL CHANNEL RANGE REAR LIGHT 934 yards, 264.3° from front light.	37-12-43.25N 76-55-03.06W	F W (Night) F W (Day)	57 54		On skeleton tower on platform.	Lighted throughout 24 hours. DAY: Visible 0.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line.
	*	*					48/12
12325	- CHANNEL LIGHT 76A	37-16-18.45N 77-04-23.94W	FI R 4s	15	5	TR on multi-pile structure.	Ra ref.
						*	48/12
12400	- James River Channel Lighted Buoy 90	37-18-12.58N 77-07-04.86W	FI R 2.5s		5	Red.	Replaced by nun when endangered by ice.
		*				*	48/12
28065	- Lighted Buoy 19	35-46-21.33N 75-32-19.40W	FI G 4s		4	Green.	
		*					48/12
29365	- Channel Lighted Buoy 11	34-40-34.65N 76-40-10.82W	FI G 2.5s		4	Green.	
		*					48/12
29388	- Channel Lighted Buoy 16A	34-41-28.23N 76-40-09.34W	FI R 2.5s		3	Red.	
		*					48/12
30330	BALD HEAD SHOAL CHANNEL RANGE FRONT LIGHT	33-52-44.96N 78-00-04.21W	Iso W 2s (Night) Iso W 2s (Day)	15 18		Skeleton tower on platform.	Lighted throughout 24 hours. DAY: Visible 0.5° either side of range line. NIGHT: Visible 5.5° either side of range line. Range line 100 feet southeast of channel centerline.
		*					48/12
30335	BALD HEAD SHOAL CHANNEL RANGE REAR LIGHT 2,863 yards, 043.4° from front light.	33-53-46.63N 77-58-54.16W	Iso W 6s (Night) Iso W 6s (Day)	73 70		Skeleton tower on multi-pile structure.	Lighted throughout 24 hours. DAY: Visible 0.5° either side of range line. NIGHT: Visible 4.0° either side of range line. Range line 100 feet southeast of channel centerline.
	*	*					48/12

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
22370	- Lighted Buoy 22	27-36-21.47N 82-42-58.26W	FI R 2.5s		5	Red.	
						*	48/12
23680	- Lighted Buoy 4G	27-47-12.90N 82-32-26.71W	FI R 2.5s		5	Red.	
						*	48/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
34665	- LIGHT 23	32-46-38.62N 80-03-08.30W	FI G 4s	16	5	SG-SY on dolphin.	
					*		48/12
41320	- LIGHT 35	28-35-30.20N 80-47-22.54W	FI G 4s	12	5	SG-SY on pile.	
					*		48/12
51860	- LIGHT 2	27-04-57.80N 80-47-37.01W	FI R 4s	16	5	TR on dolphin.	
					*		48/12
56110	- LIGHT 64	26-40-23.03N 82-13-14.64W	FI R 4s	16	5	TR-TY on dolphin.	
					*		48/12
60350	- LIGHT 9	27-39-05.82N 82-40-55.72W	FI G 4s	16	5	SG on pile.	
					*		48/12

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
190	W&T Offshore Mooring Buoy	30-10-45.24N 88-04-55.50W				White with blue band.	Private aid.
	*						48/12
995	Energy XXI-112-3	29-37-38.44N 93-18-11.50W				On El Paso Platform 1.	SIGN: EL PASO-WC-62-1 RACON: C (- • - •) BAND: S, X. Private aid.
	*						48/12
1080	<i>Tarpon-103-6</i> Marks subsea installation.						<i>Remove from list.</i>
							*
							48/12
17160	- LIGHT 3	29-09-54.39N 90-33-49.36W	FI G 4s	17	4	SG on pile.	Ra ref.
							*
							48/12
17165	- LIGHT 7	29-09-51.04N 90-31-39.12W	FI G 6s	17	4	SG on pile.	Ra ref.
							*
							48/12
17170	- LIGHT 11	29-09-47.65N 90-29-28.88W	FI G 4s	17	4	SG on pile.	Ra ref.
							*
							48/12
17175	- LIGHT 15	29-09-44.22N 90-27-18.65W	FI G 6s	17	4	SG on pile.	Ra ref.
							*
							48/12
17180	- LIGHT 19	29-09-40.76N 90-25-08.41W	FI G 4s	17	4	SG on pile.	Ra ref.
							*
							48/12
17185	- LIGHT 23	29-09-37.26N 90-22-58.19W	FI G 6s	17	4	SG on pile.	Ra ref.
							*
							48/12
17190	- LIGHT 27	29-09-33.81N 90-20-48.26W	Q G	17	4	SG on pile.	Ra ref.
							*
							48/12
17200	- LIGHT 31	29-08-30.35N 90-19-04.07W	FI G 4s	17	4	SG on pile.	Ra ref.
							*
							48/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
17222	- LIGHT 40A	29-08-05.12N 90-15-19.55W	FI R 2.5s	17	4	TR on pile.	Ra ref. * 48/12
24625	- Daybeacon 6	29-41-13.22N 94-58-26.48W *				TR on pile.	Ra ref. 48/12
25435	- LIGHT 119 131 feet outside channel limit.	29-44-24.05N 95-03-38.82W *	FI G 2.5s	17	4	SG on pile.	 48/12
27575	- G RANGE REAR LIGHT 115 yards, 231.7° from front light. *	28-38-05.40N 96-34-08.59W	Iso W 6s	25		KRW on tower.	Visible all around; higher intensity on range line. 48/12
33100	- Buoy 3	30-20-04.10N 87-18-47.59W *				Green can with yellow square.	 48/12
36345	- Junction Daybeacon						Remove from list. * 48/12

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1496	<i>Point Loma Ocean Outfall Lighted Buoy PLOO</i>						Remove from list. * 48/12
3009.1	- PIER J SOUTH FRONT RANGE LIGHT	33-44-13.92N 118-11-41.64W	F G	64		On COSCO building.	Private aid. * 48/12
3009.2	- PIER J SOUTH REAR RANGE LIGHT 140 yards, 270° from front light.	33-44-13.92N 118-11-46.68W	F G	80		On tower.	Private aid. * 48/12
*13963	<i>Knoxway Warning Lighted Buoy</i>	46-34-39.24N 117-18-43.62W	FI W 2s			White and orange.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14016	Chief Timothy No Wake Buoy A	46-24-56.46N 117-11-49.15W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14016.1	Chief Timothy Regulatory Daybeacon B	46-24-54.03N 117-11-44.99W				White and orange.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14016.2	Chief Timothy Regulatory Daybeacon C	46-24-54.36N 117-11-44.12W				White and orange.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14016.3	Chief Timothy Regulatory Buoy D	46-24-46.66N 117-11-36.02W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14016.4	Chief Timothy Regulatory Buoy E	46-24-48.25N 117-11-34.58W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*14016.5	Chief Timothy Regulatory Buoy F	46-24-48.99N 117-11-33.88W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14016.6	Chief Timothy Regulatory Buoy G	46-24-50.13N 117-11-32.80W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14016.7	Chief Timothy No Wake Buoy H	46-24-58.78N 117-10-53.67W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14016.8	Chief Timothy No Wake Buoy J	46-24-58.33N 117-10-51.94W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14016.9	Chief Timothy No Wake Buoy K	46-24-58.12N 117-10-49.12W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
14017	CHIEF TIMOTHY WATER INTAKE LIGHT	46-25-38.40N 117-09-11.34W	Q Y			On piling.	Maintained by U.S. Army Corps of Engineers. Private aid. * 48/12
*14040	Hells Canyon Marina Sand Bar Warning Buoy A	46-25-21.02N 117-04-20.41W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14040.1	Hells Canyon Marina Sand Bar Warning Buoy B	46-25-21.25N 117-04-19.26W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14040.2	<i>Slaughterhouse Warning Lighted Buoy C</i>	46-25-27.01N 117-04-10.51W	FI W 2s			White and orange.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14045	<i>Greenbelt Sand Bar Warning Lighted Buoy A</i>	46-25-22.89N 117-02-18.53W	FI W 2s			White and orange.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14045.1	<i>Greenbelt Sand Bar Warning Lighted Buoy B</i>	46-25-21.77N 117-02-17.67W	FI W 2s			White and orange.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14045.2	<i>Greenbelt Sand Bar Warning Lighted Buoy C</i>	46-25-20.65N 117-02-17.74W	FI W 2s			White and orange.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14045.3	<i>Greenbelt Sand Bar Warning Lighted Buoy D</i>	46-25-20.07N 117-02-17.96W	FI W 4s			White and orange.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14055	<i>Swallows Water Intake Lighted Buoy</i>	46-23-10.52N 117-02-49.38W	FI W 2s			White and orange.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14057	<i>Hells Gate Marina Entrance Lighted Buoy 1</i>	46-22-16.30N 117-03-21.64W	FI G 4s			Green.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14058	<i>Hells Gate Marina Entrance Lighted Buoy 2</i>	46-22-15.55N 117-03-23.09W	FI R 4s			Red.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*14060	Hells Gate Water Intake Buoy	46-21-10.51N 117-03-38.97W				White and orange.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.1	Palouse River Submerged Pipeline Danger Buoy A	46-36-21.63N 118-12-36.45W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.11	Palouse River Submerged Pipeline Danger Buoy K	46-36-01.75N 118-12-51.71W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.12	Palouse River No Water Ski Restricted Area Buoy L	46-36-11.47N 118-12-33.91W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.13	Palouse River No Water Ski Restricted Area Buoy M	46-36-08.25N 118-12-28.29W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.2	Palouse River Submerged Pipeline Danger Buoy B	46-36-20.11N 118-12-34.69W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.3	Palouse River Submerged Pipeline Danger Buoy C	46-36-19.38N 118-12-34.70W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.4	Palouse River Submerged Pipeline Danger Buoy D	46-36-14.65N 118-12-37.17W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.5	Palouse River Submerged Pipeline Danger Buoy E	46-36-11.37N 118-12-39.92W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.6	Palouse River Submerged Pipeline Danger Buoy F	46-36-09.53N 118-12-41.31W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.7	Palouse River Submerged Pipeline Danger Buoy G	46-36-05.16N 118-12-44.83W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.8	Palouse River Submerged Pipeline Danger Buoy H	46-36-02.67N 118-12-47.82W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*14065.9	Palouse River Submerged Pipeline Danger Buoy J	46-36-02.18N 118-12-49.62W				White and orange can.	Maintained by U.S. Army Corps of Engineers. Private aid. 48/12
*17223	MURPHY'S LANDING MARINA WARNING LIGHT	47-20-13.08N 122-35-21.62W	FI W 6s			White and orange on piling.	Private aid. 48/12
17730	POINT HANNON LIGHT 2	47-53-14.84N 122-36-41.17W	FI R 2.5s	15	4	TR on skeleton tower.	 48/12
		*					48/12
19875	Alden Bank Buoy 5						Remove from list. *
							48/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
21920	- Entrance Lighted Buoy 1 Marks shoal.	45-05-55.95N 87-34-33.99W	FI G 2.5s		4	Green can.	Replaced by can buoy from Nov. 14 to Apr. 21. * 48/12
21925	- Entrance Lighted Buoy 2 Marks shoal.	45-06-00.25N 87-34-40.79W	FI R 2.5s		4	Red nun.	Replaced by nun buoy from Nov. 14 to Apr. 21. * 48/12
22050	BAY SHORE COUNTY PARK LIGHT	44-38-19.00N 87-45-15.00W	FI R 4s	15 5		On pile.	Maintained from May 7 to Nov. 1. Private aid. * 48/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.