

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
430	<i>Thieves Ledge Lighted Whistle Buoy 1</i>	42-19-34.07N 70-49-49.33W	Q G		3		
					*		50/12
*30303	- Buoy 17A	40-46-57.03N 72-45-36.84W				Green.	50/12

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8210	- <i>Lighted Buoy 15</i>	39-11-56.12N 76-30-23.96W	FI G 2.5s		6	Green.	Replaced by can when endangered by ice.
					*		50/12
8995	- NORTH RANGE REAR LIGHT 3,275 yards, 042.5° from front light.	39-31-06.64N 75-54-31.81W	F W (Night) F W (Day)	140 137		On white skeleton tower.	Lighted throughout 24 hours. DAY: Visible on range line only. NIGHT: Visible 5.5° either side of range line.
							* 50/12
12235	DANCING POINT SHOAL CHANNEL RANGE FRONT LIGHT	37-12-46.02N 76-54-28.61W	F W (Night) F W (Day)	24 27		On skeleton tower on platform.	Lighted throughout 24 hours. DAY: Visible 0.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line.
		*					50/12
28300	- LIGHT 16 OH	35-43-00.95N 75-37-39.75W	FI R 4s	15	4	TR on multi-pile structure.	* 50/12
28730	- Channel Warning Daybeacon	35-11-56.75N 75-44-20.74W				NW on multi-pile structure worded DANGER SHOALING	* 50/12
	*						* 50/12
28750	- CHANNEL LIGHT 16	35-12-10.12N 75-43-32.27W	FI R 4s	15	3	TR on pile.	* 50/12
28785	- CHANNEL LIGHT 24	35-12-45.93N 75-42-45.64W	Q R	19	3	TR on pile.	* 50/12
28865	- LIGHT 42RC	35-16-45.63N 75-44-15.28W	FI R 2.5s	15	5	TR on multi-pile structure.	* 50/12
28970	- LIGHT 30	35-05-34.70N 75-59-51.54W	FI R 4s	15	3	TR on pile.	* 50/12
28975	- Daybeacon 31	35-05-50.09N 75-59-42.51W				SG on pile.	* 50/12
28985	- JUNCTION LIGHT SL	35-06-37.60N 75-59-30.73W	FI (2+1) R 6s	15	4	JR on multi-pile structure.	* 50/12
29030	- Daybeacon 3	35-06-48.89N 75-59-52.82W				SG on pile.	* 50/12
29056	- LIGHT 9A	35-08-33.76N 76-00-22.99W	FI G 4s	15	4	SG on pile.	* 50/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
29060	- Daybeacon 9B	35-08-45.67N 76-00-29.47W				SG on pile.	* 50/12
31990	- CHANNEL LIGHT 2SP	35-39-11.88N 75-43-08.76W	FI R 2.5s	15	5	TR on pile.	* 50/12
34805	- <i>Lighted Buoy 2</i>	34-42-17.46N 76-40-35.37W	Q R		3	Red.	* 50/12
34815	- <i>Lighted Buoy 3</i>	34-42-16.96N 76-40-37.42W	FI G 2.5s		3	Green.	* 50/12
37180	- LIGHT 6	36-42-19.53N 76-04-47.14W	FI R 4s	17	4	TR-TY on pile.	* 50/12
37310	- LIGHT 18	36-40-46.08N 76-04-07.85W	FI R 4s	15	4	TR-TY on pile.	* 50/12
37385	- LIGHT 40	36-37-29.74N 76-03-05.99W	FI R 4s	15	4	TR-TY on pile.	* 50/12
39548	- Buoy 99A	34-21-18.86N 77-40-50.51W				Green can yellow square.	* 50/12

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
21705	- CHANNEL LIGHT 13	27-20-18.27N 82-34-27.44W	Q G	16	4	SG on pile.	* 50/12
25600	- LIGHT 4	27-46-43.03N 82-47-11.94W	Q R	16	4	TR on pile.	* 50/12
32585	- <i>Lighted Buoy 3</i> On shoal about center to entrance to harbor.	18-19-18.63N 64-55-40.41W	FI G 4s		5	Green.	* 50/12
32590	- <i>Lighted Buoy 4</i>	18-19-21.01N 64-55-32.68W	FI R 4s		5	Red.	* 50/12
32880	- <i>Lighted Buoy 3</i> At west point of bank.	17-45-38.29N 64-41-43.78W	FI G 4s		5	Green.	* 50/12
40910	- LIGHT 5	28-53-08.48N 80-50-38.36W	FI G 4s	12	5	SG-SY on dolphin.	* 50/12
48395	- LIGHT 49	25-47-29.46N 80-10-51.36W	FI G 2.5s	12	5	SG-SY on pile.	* 50/12
51415	- LIGHT 4	26-58-44.74N 80-37-04.01W	FI R 2.5s	12	5	TR-TY on pile.	* 50/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
22410	SABINE PASS OUTER A RANGE FRONT LIGHT	29-39-18.92N 93-49-51.02W *	Q G	39		KRW on skeleton tower on piles.	Visible 2° each side of range line. 50/12
22415	SABINE PASS OUTER A RANGE REAR LIGHT 1,002 yards 334.9° from front light. *	29-39-46.43N 93-50-04.06W *	Iso G 6s	70		KRW on skeleton tower on piles.	Visible 2° each side of range line. 50/12
22785	- D RANGE FRONT LIGHT	29-45-16.16N 93-53-01.75W *	Q W	37		Skeleton tower on piles.	Lighted throughout 24 hours. 50/12
22790	- D RANGE REAR LIGHT 727 yards, 108.1° from front light. *	29-45-08.41N 93-52-38.66W *	Iso W 6s	76		Skeleton tower on piles.	Lighted throughout 24 hours. 50/12
22905 35710	- H RANGE FRONT LIGHT	29-52-05.83N 93-55-49.12W *	Q R	42		KRW-I on skeleton tower on block.	For upbound traffic Visible 2° each side of range line. 50/12
22910 35715	- H RANGE REAR LIGHT 328 yards, 037.6° from front light. *	29-52-13.27N 93-55-41.93W	Iso R 6s	51		KRW on skeleton tower on concrete block.	 50/12
22970 35630	- M UPPER RANGE FRONT LIGHT	29-58-16.80N 93-51-09.89W *	Q W	29		On skeleton tower.	For upbound traffic. Visible 2° each side of range line. Lighted throughout 24 hours. 50/12
22975 35635	-M UPPER RANGE REAR LIGHT 745 yards, 017.6° from front light. *	29-58-37.58N 93-51-01.13W	Iso W 6s	40		On skeleton tower on piles. On same structure as Neches River Outer Range R Rear Light.	Visible 2° each side of range line. Lighted throughout 24 hours. 50/12
23120 35510	- P RANGE FRONT LIGHT	30-01-06.72N 93-45-15.88W *	Q W	24		KRW-I on skeleton tower on piles.	Visible 4° either side of range line. 50/12
23125 35515	- P RANGE REAR LIGHT 1,208 yards, 048.1° from front light. *	30-01-34.67N 93-44-50.05W	Iso W 6s	47		KRW-I on skeleton tower on piles.	Visible 4° either side of range line. 50/12
23430	- T RANGE FRONT LIGHT	30-00-27.37N 93-58-41.63W *	F G F G	39 37		On skeleton tower on block.	Lighted throughout 24 hours. 50/12
23435	- T RANGE REAR LIGHT 304 yards, 106.5° from front light. *	30-00-24.43N 93-58-31.81W	F G F G	69 71		On skeleton tower on block.	Lighted throughout 24 hours. 50/12
24075	- LIGHT 40 235 feet outside channel limit. *	29-26-18.14N 94-50-08.37W *	FI (2) R 6s	17	3	TR on pile.	Ra ref. 50/12
25765	- LIGHT 136						Remove from list. * 50/12
25785	- LIGHT 145 150 feet outside channel limit.						Remove from list. * 50/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*25785.01	- Lighted Buoy 145	29-44-04.85N 95-08-28.88W	FI G 4s		4	Green.	
							50/12
25805	- LIGHT 151 355 feet outside channel limit.						<i>Remove from list.</i>
							*
							50/12
26035	- CUT A OUTER RANGE REAR LIGHT 1,085 yards, 116.6° from front light.	29-19-56.53N 94-44-45.72W	Iso G 6s	65		KRW on skeleton tower on piles.	
		*					50/12
35510 23120	- P RANGE FRONT LIGHT	30-01-06.72N 93-45-15.88W	Q W	24		KRW-I on skeleton tower piles.	Visible 4° either side of range line.
		*		*			50/12
35515 23125	- P RANGE REAR LIGHT 1,208 yards, 048.1° from front light.	30-01-34.67N 93-44-50.05W	Iso W 6s	47		KRW-I on skeleton tower on piles.	Visible 4° either side of range line.
	*						50/12
35630 22970	- M UPPER RANGE FRONT LIGHT	29-58-16.80N 93-51-09.89W	Q W	29		On skeleton tower.	For upbound traffic. Visible 2° each side of range line. Lighted throughout 24 hours.
		*		*			50/12
35635 22975	- M UPPER RANGE REAR LIGHT 745 yards, 017.6° from front light.	29-58-37.58N 93-51-01.13W	Iso W 6s	40		On skeleton tower on piles. On same structure as Neches River Outer Range R Rear Light.	Visible 2° each side of range line. Lighted throughout 24 hours.
	*						50/12
35710 22905	- H RANGE FRONT LIGHT	29-52-05.83N 93-55-49.12W	Q R	42		KRW-I on skeleton tower on block.	For upbound traffic. Visible 2° each side of range line.
		*		*			50/12
35715 22910	- H RANGE REAR LIGHT 328 yards, 037.6° from front light.	29-52-13.27N 93-55-41.93W	Iso R 6s	51		KRW on skeleton tower on concrete block.	Visible 2° each side of range line.
	*						50/12
42550.01	- Daybeacon 33	26-14-38.47N 97-17-32.00W				SG-SY on pile.	Ra ref.
		*					50/12
42755.01	- Daybeacon 67	26-06-52.92N 97-12-57.09W				SG-SY on pile.	Ra ref.
		*					50/12

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3860	- Lighted Buoy 5	35-21-57.17N 120-52-00.82W	FI G 4s		4	Green.	Buoys maybe frequently relocated due to changing conditions.
		*					50/12
8165	- ENTRANCE RANGE FRONT LIGHT	40-45-05.52N 124-13-35.51W	Q G	22		KRW on pile.	Visible 1.5° each side of range line. Lighted throughout 24 hours.
		*		*			50/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8170	- ENTRANCE RANGE REAR LIGHT 269 yards, 140.3° from front light.	40-44-59.40N 124-13-28.82W	Oc G 4s	41		KRW on pile.	Visible 1.5° each side of range line. Lighted throughout 24 hours.
	*	*		*			50/12

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3907	MAST Mooring Buoy "North Carolina"						Remove from list. * 50/12
3908	MAST Mooring Buoy "Queen Of The West"						Remove from list. * 50/12
4016	MAST Mooring Buoy "Sultan"						Remove from list. * 50/12
4252	MAST Mooring Buoy "Dundee"						Remove from list. * 50/12
4260	MAST Mooring Buoy "Hickory Stick"						Remove from list. * 50/12
4261	MAST Mooring Buoy "Admiral"						Remove from list. * 50/12
4262	MAST Mooring Buoy "Sand Merchant"						Remove from list. * 50/12
4263	MAST Mooring Buoy "Craftsman"						Remove from list. * 50/12
4400	MAST Mooring Buoy "Morning Star"						Remove from list. * 50/12
4540	MAST Mooring Buoy "City of Concord"						Remove from list. * 50/12
5567	MAST Mooring Buoy "F.H. Prince"						Remove from list. * 50/12
15640	- Lighted Buoy 3	46-42-06.51N 92-01-01.80W	FI G 4s		4	Green.	Replaced by can from Dec. 1 to Apr. 28. * 50/12
15680	- Lighted Buoy 4	46-42-30.21N 92-01-55.38W	FI R 4s		4	Red.	Maintained from Apr. 28 to Dec. 1. * 50/12
15705	- Lighted Buoy 2	46-42-51.39N 92-02-36.61W	Q R		4	Red.	Replaced by nun from Dec. 1 to Apr. 28. * 50/12
15770	- Lighted Buoy 6	46-43-13.93N 92-03-08.61W	FI R 4s		3	Red.	Maintained from Apr. 28 to Dec. 1. * 50/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
15790	- Lighted Buoy 10	46-43-39.04N 92-03-44.53W	FI R 4s		3	Red.	Maintained from Apr. 28 to Dec. 1. * 50/12
15805	- Lighted Buoy 14	46-44-03.11N 92-04-18.77W	FI R 4s		3	Red.	Maintained from Apr. 28 to Dec. 1. * 50/12
15820	- Lighted Buoy 18	46-44-30.78N 92-04-57.65W	FI R 4s		3	Red.	Replaced by nun from Dec. 1 to Apr. 28. * 50/12
15825	- Lighted Buoy 19	46-44-32.04N 92-05-11.29W	FI G 4s		3	Green.	Maintained from Apr. 28 to Dec. 1. * 50/12
15870	- Basin Traffic Lighted Buoy	46-46-29.57N 92-05-59.36W	Mo (A) W		5	Red and white stripes.	Maintained from Apr. 21 to Dec. 7. * 50/12
15875	- Basin Lighted Buoy 2	46-46-22.24N 92-06-11.55W	FI R 4s		4	Red.	Replaced by nun from Dec. 7 to Apr. 21. * 50/12
15880	- Basin Lighted Buoy 3	46-46-24.61N 92-05-43.10W	FI G 4s		3	Green.	Maintained from Apr. 21 to Dec. 7. * 50/12
15905	- Basin Lighted Buoy 5	46-46-03.61N 92-05-50.59W	FI G 4s		4	Green.	Maintained from Apr. 21 to Dec. 7. * 50/12
15925	- Basin Lighted Buoy 7	46-45-28.08N 92-05-24.69W	FI G 4s		4	Green.	Replaced by can from Dec. 7 to Apr. 21. * 50/12
15940	Rices Point Lighted Buoy 9	46-45-13.28N 92-05-18.69W	Q G		3	Green.	Replaced by can from Dec. 7 to Apr. 21. * 50/12
16030	- Lighted Buoy 3	46-44-35.55N 92-07-56.44W	Q G		4	Green.	Replaced by can from Dec. 1 to Apr. 21. * 50/12
16055	St. Louis Bay Junction Lighted Buoy	46-44-14.59N 92-08-26.39W	FI (2+1) R 6s		3	Red and green bands.	Replaced by nun from Dec. 1 to Apr. 28. * 50/12
16070	- Lighted Buoy 2A	46-44-48.50N 92-06-28.63W	FI R 4s		4	Red.	Replaced by nun from Dec. 1 to Apr. 21. * 50/12
16090	- Lighted Buoy 2	46-44-40.56N 92-07-05.97W	Q R		4	Red.	Replaced by nun from Dec. 1 to Apr. 21. * 50/12
16095	- Lighted Buoy 1	46-44-34.91N 92-07-38.64W	FI G 4s		4	Green.	Replaced by can from Dec. 1 to Apr. 21. * 50/12
16105	- Lighted Buoy 6	46-44-44.99N 92-07-23.69W	FI R 4s		4	Red.	Replaced by nun from Dec. 1 to Apr. 21. * 50/12
16145	- Lighted Buoy 9	46-44-21.06N 92-07-44.48W	FI G 4s		4	Green.	Maintained from Apr. 28 to Dec. 1. * 50/12
16165	- Lighted Buoy 13	46-44-07.22N 92-08-25.32W	Q G		3	Green.	Maintained from Apr. 28 to Dec. 1. * 50/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
16180	- Lighted Buoy 4	46-43-21.88N 92-08-39.79W	Q R		4	Red.	Replaced by nun from Dec. 1 to Apr. 28. * 50/12
16205	- Lighted Buoy 6	46-43-12.59N 92-08-50.69W	FI R 2.5s		3	Red.	Replaced by nun from Dec. 1 to Apr. 28. * 50/12
16210	- Lighted Buoy 7	46-43-08.85N 92-08-49.52W	Q G		4	Green.	Replaced by can Dec. 1 from to Apr. 28. * 50/12
16220	- Lighted Buoy 9	46-43-04.89N 92-09-10.23W	FI G 4s		4	Green.	Maintained from Apr. 28 to Dec. 1. * 50/12
16225	- Lighted Buoy 10	46-43-10.15N 92-09-17.31W	FI R 4s		3	Red.	Maintained from Apr. 28 to Dec. 1. * 50/12
16235	- Lighted Buoy 14	46-43-05.83N 92-09-40.88W	FI R 4s		4	Red.	Maintained from Apr. 28 to Dec. 1. * 50/12
16240	- Lighted Buoy 15	46-43-01.21N 92-09-58.98W	FI G 4s		4	Green.	Maintained from Apr. 28 to Dec. 1. * 50/12
16250	- Lighted Buoy 19	46-43-03.35N 92-10-13.81W	FI G 2.5s		4	Green.	Maintained from Apr. 28 to Dec. 1. * 50/12

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.