

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
485	<b>Race Point Light</b>	42-03-44.40N 70-14-34.90W	Fl W 10s	41	16	On white tower. 41	Obscured from 220° to 292°. Emergency light of reduced intensity when main light is extinguished.
					*		2/13
10000	HOSPITAL POINT RANGE FRONT LIGHT	42-32-47.36N 70-51-21.48W	F W	69		White pyramidal tower.	Visible all around; higher intensity on range line. Floodlighted sunset to sunrise.
		*		*			2/13
10005	HOSPITAL POINT RANGE REAR LIGHT 2,050 yards, 276.3° from front light.	42-32-53.94N 70-52-42.43W	F W	161			Visible 2° each side of range line.
		*		*			2/13
13080	- RANGE FRONT LIGHT	41-46-17.71N 70-30-32.52W	Oc G 4s	38		KRW on skeleton tower.	Visible 4° each side of range line.
		*		*			2/13
13085	- RANGE REAR LIGHT 267 yards, 244.9° from front light.	41-46-14.36N 70-30-42.08W	F G	51		KRW on skeleton tower.	Visible 4° each side of range line.
		*		*			2/13
15160	- REEF RANGE FRONT LIGHT	41-17-23.59N 70-05-32.36W	Q W	35		KRW on white wooden skeleton tower.	Higher intensity beam to seaward. Lighted throughout 24 hours.
		*					2/13
15165	- RANGE REAR LIGHT 89 yards, 162° from front light.	41-17-21.32N 70-05-31.38W	F W	51		KRW on white wooden skeleton tower.	Higher intensity beam to seaward. Lighted throughout 24 hours.
		*					2/13
15690	- DIRECTIONAL LIGHT	41-31-38.91N 70-40-32.96W	F RWG	45		On tower.	Red from 342.25° to 343.25°, white from 343.25° to 344.75°, green from 344.75° to 345.75°.
		*		*			2/13
15773	WOODS HOLD PASS DIRECTIONAL LIGHT	41-31-17.22N 70-40-16.51W	Oc W 4s	30		NR on dolphin.	Visible on course to steer 077° T.
		*		*			2/13
16085	RANGE FRONT LIGHT On southern end of Abiels Ledge	41-41-32.94N 70-40-27.51W	Q G	27		KRW on white tower.	Visible 4° each side of range line.
		*					2/13
16090	RANGE REAR LIGHT 3,167 yards, 015° from front light	41-43-03.30N 70-39-53.65W	F G	72		KRW on white skeleton tower.	Visible 1.5° each side of range line.
		*		*			2/13
25230	- RANGE FRONT LIGHT	41-01-48.88N 73-32-15.11W	Q W	26		KRW on skeleton tower.	Visible all around.
		*		*			2/13
25235	- RANGE REAR LIGHT 200 yards, 358° from front light.	41-01-55.11N 73-32-15.57W	Iso R 6s	48		KRW on skeleton tower.	Visible all around; higher intensity on range line.
		*		*			2/13
35135	- RANGE FRONT LIGHT	40-29-15.10N 73-59-35.12W	Q W (G sector) (R sector)	45	G 5 W 5 R 5	KGB (E section) KRW (Main section) on skeleton tower on concrete base.	Red from 063.0° to 073.0°. Green from 300.5° to 315.5°. RACON: C(- • - •).
		*		*			2/13

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
35140	- RANGE REAR LIGHT (EAST SECTION) 1,700 yards, 308° from front light.	40-29-46.75N 74-00-27.96W	Iso G 6s	94		KGB on skeleton tower.	Visible on range line only. Passing light Fl Y 4s, nominal range 5 miles.
		*		*			2/13
35145	- RANGE REAR LIGHT (MAIN SECTION) 315 yards, 067.5° from front light.	40-29-18.42N 73-59-24.30W	Iso R 6s	68		KRW on skeleton tower.	Visible on range line only. Passing light Fl Y 4s, nominal range 5 miles.
		*		*			2/13

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5358	- Buoy 19	37-54-24.20N 75-24-30.83W				Green can.	
		*					2/13
5365	- Buoy 21	37-54-52.91N 75-23-57.24W				Green can.	
		*					2/13
5380	- Lighted Buoy 23	37-55-06.73N 75-23-45.06W	Fl G 4s			Green.	
		*					2/13
5385	- Buoy 25	37-55-23.83N 75-23-38.85W				Green can.	
	*	*					2/13
9445	- Channel Lighted Buoy 1ER	36-59-16.63N 76-18-41.29W	Q G		6	Green.	
					*		2/13
12245	- Channel Lighted Buoy 65	37-13-10.08N 76-55-06.40W	Fl G 2.5s		5	Green.	
					*		2/13
28124	OLD HOUSE CHANNEL JUNCTION LIGHT OH	35-45-41.99N 75-35-26.37W	Fl (2+1) G 6s	15	3	JG on pile.	Light equipment removed when endangered by ice.
		*					2/13
28350	- Lighted Buoy 11	35-47-40.98N 75-33-05.24W	Fl G 4s		4	Green.	
		*					2/13
28520	- CHANNEL LIGHT 29	35-54-32.26N 75-38-39.43W	Fl G 2.5s	15	4	SG on pile.	
					*		2/13

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
515 6030	St. Simons Lighted Buoy STS	31-02-49.00N 81-14-25.20W	Mo (A) W		7	Red and white stripes with red spherical topmark.	RACON: B (- • • •).
					*		2/13
3745.1	- Buoy 12	32-38-35.93N 79-58-50.17W				Red nun.	
		*					2/13
6030 515	St. Simons Lighted Buoy STS	31-02-49.00N 81-14-25.20W	Mo (A) W		7	Red and white stripes with red spherical topmark.	RACON: B (- • • •).
					*		2/13

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6565	- Lighted Buoy 9	30-42-40.30N 81-20-47.51W	FI G 6s		5	Green.	
					*		2/13
6780 37815	- RANGE B FRONT LIGHT	30-44-25.58N 81-29-12.11W	Q G	16		KRW-I on pile.	Visible 4° each side of range line.
		*					2/13
6785 37820	- RANGE B REAR LIGHT 390 yards, 350.1° from front light.	30-44-36.99N 81-29-14.42W	Iso G 6s	30		KRW on skeleton tower on piles.	Visible 4° each side of range line.
	*	*		*			2/13
9543	- Buoy 7A	29-04-33.58N 80-55-09.20W				Green can.	
		*					2/13
10910	BOWLES BANK LIGHT 8	25-30-26.15N 80-08-44.14W	FI R 4s	16	5	TR on pile.	
					*		2/13
37815 6780	- RANGE B FRONT LIGHT	30-44-25.58N 81-29-12.11W	Q G	16		KRW-I on pile.	Visible 4° each side of range line.
		*					2/13
37820 6785	- RANGE B REAR LIGHT 390 yards, 350.1° from front light.	30-44-36.99N 81-29-14.42W	Iso G 6s	30		KRW on skeleton tower on piles.	Visible 4° each side of range line.
	*	*		*			2/13
39850	- LIGHT 7	29-20-30.24N 81-04-17.25W	FI G 4s	16	5	SG-SY on dolphin.	
					*		2/13

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*5993	ALABAMA DCNR BAYOU ST. JOHN DANGER LIGHTS (8)	30-17-38.24N 87-31-52.37W	FI W 2.5s			Marks submerged fishing reef.	Private aid.
							2/13
13615	LDH PORT NICKEL DOCK LIGHTS (2) LDB mile 76.4.	29-51-38.40N 89-58-21.80W	FI R 2.5s			On dock.	Private aid.
	*						2/13
13620	LDH PORT NICKEL DOCK LIGHT LDB mile 76.6	29-51-46.20N 89-58-20.30W	FI R 2.5s	12		On dolphin.	Private aid.
	*						2/13
18520	- Lighted Buoy 1	29-10-43.05N 91-33-21.80W	FI G 2.5s			Green.	
	*						2/13
*33493	ALABAMA DCNR ONO ISLAND DANGER LIGHTS (6)	30-18-07.12N 87-29-31.26W	FI W 2.5s			Marks submerged fishing reef.	Private aid.
							2/13
*33837	ALABAMA DCNR BON SECOUR BAY DANGER LIGHTS (6)	30-18-03.03N 87-48-26.31W	FI W 2.5s			Marks submerged fishing reef.	Private aid.
							2/13
*36438	- Daybeacon 26A	29-16-53.57N 94-51-28.20W				TR on pile.	
							2/13

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9440	- ENTRANCE RANGE FRONT LIGHT	44-01-01.44N 124-07-49.57W	Q R	35		KRB on skeleton tower. On same structure as Siuslaw River Inner Range Rear Light.	Visible 4° each side of range line.
	*			*			2/13
9445	- ENTRANCE RANGE REAR LIGHT 296 yards, 094.3° from front light.	44-01-00.78N 124-07-37.44W	Iso R 6s	61		KRB on skeleton tower.	Visible 4° each side of range line.
	*	*		*			2/13
9470	- INNER RANGE FRONT LIGHT	44-00-58.68N 124-07-49.62W	Q W	21		KRB on skeleton tower.	Visible all around; higher intensity on range line.
		*		*			2/13
9475	- INNER RANGE REAR LIGHT 92 yards, 001.4° from front light.	44-01-01.40N 124-07-49.53W	Iso W 6s	34		KRB on skeleton tower. On same structure as Siuslaw River Entrance Range Front Light.	Visible 14° each side of range line.
	*						2/13
* 14721	- <i>Lighted Buoy 2</i>	46-12-45.10N 123-45-22.62W	Q R		4	Red.	
							2/13

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.