

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
655	<i>Montauk Point Lighted Whistle Buoy MP</i>						<i>Remove from list.</i>
							* 5/13
665	<i>NOAA Data Lighted Buoy 44017</i>	40-41-34.82N 72-02-52.20W *	Fl (4) Y 20s		4	Yellow.	Aid maintained by NOAA.
							5/13
710	<i>Nantucket Traffic Lane Lighted Whistle Buoy NA</i>						<i>Remove from list.</i>
							* 5/13
10085	<i>- Lighted Buoy 21</i>	42-31-34.02N 70-51-44.37W	Fl G 4s		3	Green.	Replaced by can when endangered by ice.
							* 5/13
10495	<i>Roaring Bull Daybeacon 2 On rock.</i>	42-28-46.62N 70-50-12.81W *				TR on spindle.	
							5/13
12350	<i>- Buoy 9</i>	42-09-37.53N 70-42-46.89W *				Green can.	
							5/13
15650	<i>Coffin Rock Lighted Buoy 1</i>	41-30-42.81N 70-39-40.13W	Q G		3	Green.	
							* 5/13
24890	<i>- Buoy 22</i>	41-06-25.48N 73-22-41.23W				Red nun.	Removed when endangered by ice.
							* 5/13
24895	<i>- Buoy 24</i>	41-06-35.59N 73-22-37.41W				Red nun.	Removed when endangered by ice.
							* 5/13
24900	<i>- Buoy 26</i>	41-06-40.08N 73-22-29.66W				Red nun.	Removed when endangered by ice.
							* 5/13
24905	<i>- Buoy 27</i>	41-06-44.65N 73-22-23.69W				Green can.	Removed when endangered by ice.
							* 5/13
24910	<i>- Buoy 29</i>	41-06-49.45N 73-22-14.12W				Green can.	Removed when endangered by ice.
							* 5/13
29125.1	<i>- Buoy 4A</i>	40-37-44.92N 73-19-26.14W *				Red.	
							5/13
30335	<i>- Buoy 26</i>	40-47-03.20N 72-44-19.74W *				Red nun.	
							5/13
30340	<i>- Buoy 27</i>	40-47-05.76N 72-44-12.36W *				Green can.	
							5/13
31560	<i>- Buoy 12</i>	40-35-31.65N 73-44-48.51W *				Red nun.	
							5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5305	<i>Chinoteague Channel Lighted Buoy 8</i>	37-52-33.79N 75-25-08.02W *	FI R 2.5s		4	Red.	5/13
5310	<i>Chincoteague Channel Lighted Buoy 10</i>	37-52-54.96N 75-25-00.29W *	Q R		3		5/13
5315	<i>Chincoteague Channel Lighted Buoy 11</i>	37-53-00.00N 75-24-19.97W *	FI G 4s		4	Green.	5/13
5360	<i>- Lighted Buoy 20</i>	37-54-28.25N 75-24-22.73W *	FI R 2.5s		3	Red.	5/13
9815	<i>- Lighted Buoy 3PM</i>	36-51-41.52N 76-19-14.30W	Q G		4	Green.	5/13
12360	<i>- Channel Lighted Buoy 83 75 feet outside channel limit.</i>	37-18-35.73N 77-05-15.19W	FI G 4s		5	Green.	Replaced by can when endangered by ice. 5/13
12370	<i>- Channel Lighted Buoy 85 60 feet outside channel limit.</i>	37-18-42.03N 77-05-37.19W	FI G 2.5s		5	Green.	5/13
31660	KENDRICK CREEK CHANNEL ENTRANCE LIGHT 1KC 10 feet outside channel limit.	35-56-33.31N 76-36-42.44W	FI G 2.5s	15	4	SG on pile.	5/13
34803	<i>- Buoy 1</i>						<i>Remove from list.</i> * 5/13
37865	<i>- LIGHT 14</i>	35-53-00.07N 76-01-00.74W	FI R 2.5s	18	5	TR-TY on pile.	5/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
140	East Bank Buoy 2EB On northeasterly side of bank.	33-08-49.56N 79-08-07.28W *				Red nun.	5/13
840	<i>NOAA Data Lighted Buoy 41009</i>	28-31-18.00N 80-11-18.00W *	FI (4) Y 20s			Yellow boat shaped buoy.	Aid maintained by NOAA. 5/13
2375	<i>- Channel Lighted Buoy 8</i>	32-40-02.90N 79-41-29.41W	FI R 2.5s		5	Red.	5/13
6905 37740	<i>- RANGE D FRONT LIGHT</i>	30-46-44.92N 81-29-17.71W *	Q R	16		KRW-I on pile.	Visible all around; higher intensity on range line. 5/13
6910 37745	<i>- RANGE D REAR LIGHT 1,351 yards, 351.4° from front light.</i>	30-47-24.58N 81-29-24.69W *	Iso R 6s	38		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line. 5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6945 37700	- UPPER RANGE E FRONT LIGHT	30-47-34.55N 81-29-52.35W *	Q W	16		KRW-I on dolphin.	Visible all around. 5/13
6950 37705	- UPPER RANGE E REAR LIGHT 232 yards, 332.1° from front light. *	30-47-40.63N 81-29-56.09W *	Iso W 6s	34		KRW on dolphin.	Visible all around. 5/13
9225	ALEXANDER ISLAND LIGHT 114	28-50-45.28N 81-20-52.18W	FI R 4s	17	5	TR on dolphin.	 * 5/13
9235	LAKE MONROE LIGHT 116	28-50-26.71N 81-20-05.12W	FI R 4s	17	5	TR on dolphin.	 * 5/13
22555	- Lighted Buoy 12 *	27-38-03.34N 82-33-56.16W *	Q R		4	Red.	 * * 5/13
23230	- Lighted Buoy 19	27-50-18.24N 82-26-46.99W	FI G 2.5s		5	Green.	 * 5/13
23235	- Lighted Buoy 20	27-50-31.55N 82-26-38.89W	Q R		4	Red.	 * 5/13
23690	- Lighted Buoy 6G	27-47-20.60N 82-33-18.85W	FI R 4s		4	Red.	 * 5/13
23695	- Lighted Buoy 7G	27-47-21.51N 82-34-00.75W	Q G		4	Green.	 * 5/13
23930	- Lighted Buoy 10K	27-51-36.66N 82-33-13.71W	FI R 2.5s		4	Red.	 * 5/13
35035	- LIGHT 137	32-37-15.22N 80-21-30.08W	FI G 4s	18	5	SG-SY on dolphin.	 * 5/13
37700 6945	- UPPER RANGE E FRONT LIGHT	30-47-34.55N 81-29-52.35W *	Q W	16		KRW-I on dolphin.	Visible all around. 5/13
37705 6950	- UPPER RANGE E REAR LIGHT 232 yards, 332.1° from front light. *	30-47-40.63N 81-29-56.09W *	Iso W 6s	34		KRW on dolphin.	Visible all around. 5/13
37740 6905	- RANGE D FRONT LIGHT	30-46-44.92N 81-29-17.71W *	Q R	16		KRW-I on dolphin.	Visible all around; higher intensity on range line. 5/13
37745 6910	- RANGE D REAR LIGHT 1,351 yards, 351.4° from front light. *	30-47-24.58N 81-29-24.69W *	Iso R 6s	38		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line. 5/13
*50712	- Daybeacon 8A	27-10-00.54N 80-11-33.49W				TR-TY on pile.	 5/13
51825	- Daybeacon 96	26-43-34.79N 80-50-53.25W *				TR-TY on pile.	 5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
61313	- Daybeacon 1	27-48-49.60N 82-45-52.70W				SG on pile.	Private aid.
	*						5/13
61315	- Daybeacon 2	27-48-50.59N 82-45-49.87W				TR on pile.	Private aid.
	*						5/13
61320	- Daybeacon 4	27-48-52.09N 82-45-50.37W				TR on pile.	Private aid.
	*						5/13
61325	- Daybeacon 6	27-48-54.09N 82-45-50.37W				TR on pile.	Private aid.
	*						5/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
700	<i>Ship Shoal Wreck Lighted Buoy WR4</i> Marks jack up leg and pad.						<i>Remove from list.</i>
							* 5/13
13615	CCI PORT NICKEL DOCK LIGHTS (2) LDB mile 76.4.	29-51-38.40N 89-58-21.80W	F I R 2.5s			On dock.	Private aid.
	*						5/13
13620	CCI PORT NICKEL DOCK LIGHT LDB mile 76.6	29-51-46.20N 89-58-20.30W	F I R 2.5s	12		On dolphin.	Private aid.
	*						5/13
23325	- OUTER R RANGE REAR LIGHT 711 yards, 100.4° from front light.	29-58-37.58N 93-51-01.13W	Iso W 6s	49		KRW on skeleton tower on piles. On same structure as Sabine-Neches Canal Upper Range M Rear Light.	
	*						5/13
23370	- S RANGE REAR LIGHT 131 yards, 113.2° from front light.	29-59-19.08N 93-55-33.91W	Iso G 6s	53		KRW on skeleton tower on mud sills.	
	*						5/13
23445	- U RANGE REAR LIGHT 562 yards, 287.8° from front light.	30-01-22.84N 94-02-00.00W	F G	41		KRW on skeleton tower.	Visible 2° each side of rangeline.
	*						5/13
23695	- ENTRANCE CHANNEL RANGE A REAR LIGHT 4,476 yards, 301.1° from front light.	29-22-19.51N 94-44-54.33W	F W (Night) F W (Day)	125 122		Skeleton tower on block.	Lighted throughout 24 hours.
	*						5/13
26100	TEXAS CITY CUT B OUTER RANGE FRONT PASSING LIGHT	29-22-00.03N 94-49-15.70W	F I R 4s	17	3	On same structure as Texas City Channel Cut B Outer Range Front Light.	
		*					5/13
28880	- E RANGE REAR LIGHT 206 yards, 116.7° from front light.	27-48-59.16N 97-28-12.74W	Iso G 6s	37		KRW on skeleton tower on mud sills.	Lighted throughout 24 hours.
				*			5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
30400	- RANGE FRONT LIGHT	29-43-22.79N 84-58-48.43W	Q G	15		KRW-I on dolphin.	Visible all around; higher intensity each side of range line.
		*					* 5/13
30405	- RANGE REAR LIGHT 1,377 yards, 350.3° from front light.	29-44-03.11N 84-58-56.33W	F G	45		KRW-I on skeleton tower on piles.	
	*						* 5/13
34045	- C RANGE FRONT LIGHT	30-16-00.00N 88-11-25.47W	Q W	15		KRW-I on dolphin.	
							* 5/13
34055	- C RANGE REAR LIGHT 2,599 yards, 247.1° from front light.	30-15-29.62N 88-12-47.37W	Iso W 6s	57		KRW-I on piles.	
		*					* 5/13
34060	-C RANGE REAR PASSING LIGHT	30-15-29.62N 88-12-47.37W	Q W	14	5	On same structure as Pass Aux Herons C Range Rear Light.	
		*					5/13
36645	- F RANGE F FRONT LIGHT	29-17-24.92N 94-55-04.42W	Q W	15		KRW-I on pile structure.	For eastbound traffic.
		*					* 5/13
36650	- F RANGE REAR LIGHT 935 yards, 079.9° from front light.	29-17-29.79N 94-54-33.22W	Iso W 6s	35		KRW-I on skeleton tower on piles.	
	*						* 5/13
37095	- INNER A RANGE REAR LIGHT 600 yards, 345.7° from front light.	29-11-18.03N 95-08-29.82W	Iso W 6s	36		KRW on skeleton tower on pile.	Visible all around; higher intensity on range line.
	*						5/13
37125	- OUTER RANGE REAR LIGHT 745 yards, 142.8° from front light.	29-10-09.63N 95-07-51.42W	Iso W 6s	40		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line.
	*						5/13
37340	- B RANGE FRONT LIGHT	29-08-36.28N 95-09-45.33W	Q W	15		KRW-I on tower.	For westbound traffic. Visible all around; higher intensity on range line.
		*					5/13
37345	- B RANGE REAR LIGHT 699 yards, 235.4° from front light.	29-08-24.49N 95-10-04.80W	Iso W 6s	30		KRW-I on skeleton tower on piles.	Visible all around; higher intensity on range line.
	*						5/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1593	<i>Shelter Island Lighted Buoy 2</i>	32-42-16.14N 117-14-01.84W	FI (2) R 5s		3		
		*					5/13
2288	<i>Scripps Waverider Lighted Research Buoy 093</i>						<i>Remove from list.</i>
							* 5/13
5575	- LIGHT 14						<i>Remove from list.</i>
							* 5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
7785	- CHANNEL RANGE A FRONT LIGHT 3	38-18-19.17N 123-03-24.60W *	Q G	18 *		KRW on pile, SG facing upstream.	Visible all around; higher intensity on the range line. 5/13
7790	- CHANNEL RANGE AB REAR LIGHT 151 yards, 269.1° from Range A Front Light. 191 yards, 209.6° from Range B Front Light. *	38-18-19.10N 123-03-30.28W *	Iso G 6s	30 *		KRW on frame.	Visible all around; higher intensity on the range lines. 5/13
7800	- CHANNEL RANGE B FRONT LIGHT 5	38-18-24.02N 123-03-26.73W *	Q G	18 *		KRW on pile, SG facing downstream.	Visible all around; higher intensity on range line. 5/13
7845	- CHANNEL RANGE C FRONT LIGHT 14	38-18-47.45N 123-03-07.92W *	Q R	18 *		KRW on piles, TR facing downstream.	Visible all around; higher intensity on range line. 5/13
7850	- CHANNEL RANGE C REAR LIGHT 195 yards, 179.3° from front light. *	38-18-41.68N 123-03-07.83W *	Iso R 6s	32 *		KRW on pile.	Visible all around; higher intensity on range line. 5/13
7960	- CHANNEL RANGE D FRONT LIGHT 37	38-19-57.35N 123-03-09.00W *	Q G	13		KRW on pile; SG facing upstream.	Visible all around; higher intensity on range line. 5/13
7970	- CHANNEL RANGE D REAR LIGHT 268 yards, 359.2° from front light. *	38-20-05.30N 123-03-09.14W *	Iso G 6s	23		KRW on pile.	Visible all around; higher intensity on range line. 5/13
10325	- Channel Lighted Buoy 28	46-16-13.99N 123-29-56.90W	Q R		4	Red.	 5/13
14721	- Lighted Buoy 2	46-12-45.13N 123-45-21.32W *	Q R		4	Red.	 5/13
15630	- South Reach Lighted Buoy 15A	46-55-20.75N 124-05-26.46W *	FI G 4s		3	Green.	 5/13
28165	- ENTRANCE DIRECTIONAL LIGHT	19-33-42.89N 155-57-43.43W *	Q W (R & G sectors)	23 *	G 5 R 5 W 7	On same structure as Keauhou Bay Range Rear Daybeacon.	White 1° each side of channel centerline (bearing 069°). Red when right of white beam (068°-064°). Green when left of white beam (070°-074°) when entering from seaward. 5/13
28175	- Range Rear Daybeacon 21 yards, 069.7° from front daybeacon. *	19-33-42.89N 155-57-43.43W *				KRW on post. On same structure as Keauhou Bay Entrance Light. *	 5/13
30700	- ENTRANCE RANGE FRONT LIGHT	13-27-23.28N 144-40-00.00E *	Q G	39		KRW on post.	Visible 4° each side of range line. 5/13
30705	- ENTRANCE RANGE REAR LIGHT 661 yards, 083.7° from front light. *	13-27-25.45N 144-40-19.76E *	Iso G 6s	81		KRW on skeleton tower.	Visible 4° each side of range line. 5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
21360	- CHANNEL LIGHT 4	45-20-12.98N 86-56-07.51W	FI R 4s	32 10 *	4	TR on post.	5/13
21365	- CHANNEL LIGHT 5	45-20-16.84N 86-56-10.89W	FI G 2.5s	32 10 *	4	SG on post.	5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.