

## SECTION II

## CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2235	- Inner Harbor Buoy 1	44-16-31.58N 68-19-04.56W				Green can.	Removed when endangered by ice. * 6/13
2240	- Inner Harbor Buoy 3	44-16-36.04N 68-19-05.01W				Green can.	Removed when endangered by ice. * 6/13
10085	- <i>Lighted Buoy 21</i>	42-31-18.76N 70-52-01.08W *	FI G 4s		3	Green.	Replaced by can when endangered by ice. 6/13
10360	Hardy Rock Daybeacon HR	42-32-10.19N 70-48-00.00W *				NR on spindle.	6/13
10395	Satan Rock Daybeacon 6	42-30-36.86N 70-48-01.52W *				TR on spindle.	6/13
10405	Brimbles Daybeacon On rock.	42-31-16.54N 70-48-28.60W *				NR on spindle.	6/13
17405	- Buoy 5	41-44-16.77N 70-37-58.58W *				Green can.	6/13
*20531	Mystic River Fairway Channel Buoy 1	41-19-32.40N 71-58-40.20W					Maintained from May 15 to Oct. 1. Private aid. 6/13
*20531.1	Mystic River Fairway Channel Buoy 2	41-19-32.40N 71-58-37.80W					Maintained from May 15 to Oct. 1. Private aid. 6/13
*20531.2	Mystic River Fairway Channel Buoy 3	41-19-39.00N 71-58-46.80W					Maintained from May 15 to Oct. 1. Private aid. 6/13
*20531.3	Mystic River Fairway Channel Buoy 4	41-19-39.60N 71-58-45.00W					Maintained from May 15 to Oct. 1. Private aid. 6/13
*20531.4	Mystic River Fairway Channel Buoy 5	41-19-47.40N 71-58-46.90W					Maintained from May 15 to Oct. 1. Private aid. 6/13
*20531.5	Mystic River Fairway Channel Buoy 6	41-19-47.80N 71-58-44.90W					Maintained from May 15 to Oct. 1. Private aid. 6/13
22525	- <i>Lighted Buoy 5</i>	41-16-18.68N 72-20-29.99W	FI G 4s		3	Green.	Replaced by can when endangered by ice. * 6/13
22735	- Entrance Daybeacon 12						<i>Remove from list.</i> * 6/13
26730	- <i>Channel Lighted Buoy 1</i>	40-54-21.60N 73-22-56.76W *	FI G 3s			Green.	Private aid. 6/13

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
160	<i>McCrie Shoal Lighted Buoy 2MS</i>	38-50-29.21N 74-50-16.61W	FI R 4s		5	Red.	
	*						6/13
190 1490	<i>Hen and Chickens Shoal Lighted Gong Buoy 1HC</i> Off southeast end of shoal.	38-42-42.76N 74-58-55.89W	FI G 2.5s		5	Green.	
						*	6/13
1480	<i>- North Approach Lighted Buoy 4</i>	38-47-56.05N 74-58-33.02W	FI R 4s		5	Red.	
						*	6/13
1490 190	<i>Hen and Chickens Shoal Lighted Gong Buoy 1HC</i> Off southeast end of shoal.	38-42-42.76N 74-58-55.89W	FI G 2.5s		5	Green.	
						*	6/13
2690	- CHANNEL LIGHT 9	39-34-14.14N 75-30-58.99W	Q G	15	4	SG on multi-pile structure.	
						*	6/13
2695	- CHANNEL LIGHT 10	39-34-11.16N 75-30-55.64W	FI R 2.5s	15	4	TR on multi-pile structure.	
						*	6/13
2760	- LIGHT 3	39-33-07.99N 75-37-15.60W	FI G 2.5s	20	5	SG on pile.	Higher intensity towards center span of bridge.
						*	6/13
2977	CHERRY ISLAND RANGE FRONT PASSING LIGHTS (2)	39-45-02.17N 75-29-39.05W	FI W 4s	15	4	Located on same structure as Cherry Island Range Front Light.	
						*	6/13
3000	- SOUTH JETTY LIGHT 1	39-42-54.91N 75-30-45.01W	FI G 2.5s	21	6	SG on skeleton tower.	
						*	6/13
8356	SWAN POINT SOUTH RANGE REAR PASSING LIGHTS (2)	39-03-14.37N 76-17-25.43W	FI W 2.5s	25	4	On same structure as Swan Point South Range Rear Light.	
	*					*	6/13
28003	<i>- Lighted Buoy 6</i>	35-47-19.66N 75-31-23.32W	Q R		4	Red.	
		*					6/13
28025	<i>- Lighted Buoy 12</i>	35-46-32.80N 75-31-50.96W	FI R 2.5s		4	Red.	
		*					6/13
28029	- Buoy 14	35-46-25.06N 75-32-00.60W				Red nun.	
		*					6/13
28065	<i>- Lighted Buoy 19</i>	35-46-20.06N 75-32-20.34W	FI G 4s		4	Green.	
		*					6/13

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
155	Cape Romain Shoal Buoy 6CR 500 yards outside of shoal.	32-57-39.26N 79-17-08.63W				Red nun.	
		*					6/13

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2400.5	- Channel Lighted Buoy 14	32-42-08.41N 79-45-49.82W	FI R 2.5s		5	Red.	
					*		6/13
2405	- Channel Lighted Buoy 15	32-42-46.54N 79-47-36.50W	FI G 4s		5	Green.	
					*		6/13
2897	- Lighted Buoy 55	32-52-28.16N 79-57-58.89W	FI G 4s		5	Green.	
					*		6/13
2945	- Lighted Buoy 64	32-54-27.78N 79-56-22.87W	FI R 2.5s		5	Red.	
					*		6/13
6322	- Lighted Buoy 2A	31-07-39.34N 81-30-41.08W	FI R 2.5s		5	Red.	
					*		6/13
6324	- Lighted Buoy 3	31-07-29.26N 81-30-41.08W	FI G 2.5s		5	Green.	
					*		6/13
6525	- RANGE FRONT LIGHT	30-42-28.48N 81-27-52.70W	FI W 2.5s (Night) FI W 2.5s (Day)	19 22		KRW on tower. On same structure as Cumberland Sound Obstruction Light.	DAY: Visible on range line only. NIGHT: Visible 4° each side of range line.
		*		*			6/13
6530	- RANGE REAR LIGHT 1,936 yards, 267.8° from front light.	30-42-26.22N 81-28-59.18W	Iso W 6s (Night) Iso W 6s (Day)	95 87		KRW on tower.	DAY: Visible on range line only. NIGHT: Visible 4° each side of range line. Lighted throughout 24 hours.
	*	*		*			6/13
6595	- Lighted Buoy 15	30-42-35.51N 81-23-11.32W	FI G 6s		5	Green.	
					*		6/13
51585	- Daybeacon 48	26-51-23.83N 80-38-28.71W				TR-TY on pile.	
		*					6/13
51745	- Daybeacon 5	26-47-39.44N 80-42-05.08W				SG on pile.	
		*					6/13
56075	- Daybeacon 61	26-39-21.74N 82-13-06.16W				SG-SY on pile.	
		*					6/13

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
335 9580	SHIP ISLAND LIGHT	30-12-45.41N 88-57-58.74W	FI W 6s	82	6	Skeleton tower on block. On same structure as Ship Channel Upper Reach Outbound Range Rear Light.	
		*					6/13
*387	Taylor Energy Lighted Buoy A	28-56-12.62N 88-58-10.30W	FI Y 2.5s			Marks subsea containment system.	SIGN: TAYLOR ENERGY-MC-20. Private aid.
							6/13
8305	- Daybeacon 6	30-23-19.20N 88-33-50.95W				TR on pile.	Ra ref.
		*					6/13

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9580 335	SHIP ISLAND LIGHT	30-12-45.41N 88-57-58.74W	FI W 6s	82	6	Skeleton tower on concrete block. On same structure as Ship Channel Upper Reach Outbound Range Rear Light.	
		*					6/13
22855	- G RANGE REAR LIGHT 429 yards, 339.7° from front light.	29-49-46.43N 93-57-48.00W	Iso G 6s (Night) Iso G 6s (Day)	73 71			Lighted throughout 24 hours. Ra ref.
		*					6/13
28150	HARBOR ISLAND RANGE REAR LIGHT 1,500 yards, 301.2° from front light.	27-51-08.41N 97-04-24.07W	F W (Night) F W (Day)	123 125		Skeleton tower.	Visible 2° each side of range line. Lighted throughout 24 hours. FI Y 2.5s exhibited when range light is on emergency power.
				*			6/13

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
198	NOAA Lighted Buoy	34-15-57.00N 120-26-24.00W	FI (4) Y 20s			Yellow disc-shaped buoy.	Aid maintained by NOAA.
	*	*					6/13
*198.1	NOAA Environmental Lighted Buoy 46054	34-16-27.81N 120-27-33.84W	FI (4) Y 20s			Yellow 3-meter disc-shaped buoy.	Aid maintained by NOAA.
							6/13
7960	- CHANNEL RANGE D FRONT LIGHT 37	38-19-57.35N 123-03-09.00W	Q G	18		KRW on pile; SG facing upstream.	Visible all around; higher intensity on range line.
				*			6/13
7970	- CHANNEL RANGE D REAR LIGHT 268 yards, 359.2° from front light.	38-20-05.30N 123-03-09.14W	Iso G 6s	28		KRW on pile.	Visible all around; higher intensity on range line.
				*			6/13
8390	- RANGE FRONT LIGHT	41-45-00.00N 124-11-21.11W	FI G 2.5s	23	10	KRG on pile.	Visible 4° each side of range line.
						*	6/13
8395	- RANGE REAR LIGHT 79 yards, 359.9° from front light.	41-45-02.13N 124-11-21.12W	Oc G 4s	39	10	KRG on pile.	Visible 4° each side of range line.
						*	6/13
9145	- LIGHT 4 20 feet outside channel limit.	43-21-10.30N 124-19-07.51W	FI R 4s	15	3	TR on multi-pile structure.	
						*	6/13
26410	FIRE ISLAND RANGE FRONT LIGHT	61-10-20.63N 150-12-00.00W	Q W	91		KRB on multi-pile structure.	Visible 4° each side of range line.
		*		*			6/13
26415	FIRE ISLAND RANGE REAR LIGHT 510 yards, 242° from front light.	61-10-13.56N 150-12-27.07W	Iso W 6s	132		KRB on multi-pile structure.	Visible 4° each side of range line.
	*	*		*			6/13
26435	POINT WORONZOF RANGE FRONT LIGHT	61-12-06.33N 150-01-22.89W	Oc G 4s	59		KRW on single pile.	Visible 4° each side of range line. Lighted throughout 24 hours.
		*		*			6/13

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
26440	POINT WORONZOF RANGE REAR LIGHT 278 yards, 079° from front light.	61-12-07.90N 150-01-06.20W	F G	148		KRW on multi-pile structure.	Visible 4° each side of range line. Lighted throughout 24 hours.
	*	*		*			6/13
26765	- FRONT RANGE LIGHT	57-43-24.00N 152-28-50.47W	Q W	57		KRB on skeleton tower.	
		*		*			6/13
26770	- REAR RANGE LIGHT 661 yards, 211.1° from front light.	57-43-07.27N 152-29-09.34W	Oc W 4s	94		KRB on skeleton tower.	
	*	*		*			6/13
28170	- Range Front Daybeacon	19-33-42.67N 155-57-44.05W				KRW on post. 12	
		*					6/13

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.