

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
7890	- Buoy 2	43-31-52.05N 70-19-24.38W				Red nun.	
	*						9/13
12770	- Buoy 2	41-59-28.38N 70-39-18.00W				Red nun.	Private aid.
		*					9/13
12775	- Buoy 4	41-59-40.20N 70-39-48.36W				Red nun.	Private aid.
		*					9/13
12780	- Buoy 6	41-59-49.38N 70-40-18.42W				Red nun.	Private aid.
		*					9/13
26835	- <i>Lighted Buoy 1</i>	40-54-21.60N 73-22-56.76W	Fl G 3s			Green.	Private aid.
		*					9/13
26840	- Buoy 2	40-54-20.34N 73-22-57.60W				Red nun.	Private aid.
		*					9/13
26845	- Buoy 3	40-54-13.38N 73-22-54.66W				Green can.	Private aid.
		*					9/13
26850	- Buoy 4	40-54-12.42N 73-22-56.04W				Red nun.	Private aid.
		*					9/13
26855	- Buoy 5	40-54-03.24N 73-22-51.78W				Green can.	Private aid.
		*					9/13
26860	- Buoy 6	40-54-01.62N 73-22-52.92W				Red nun.	Private aid.
		*					9/13
26861	- Buoy 7	40-54-00.00N 73-22-46.80W				Green can.	Private aid.
		*					9/13
26862	- Buoy 8	40-53-57.60N 73-22-44.28W				Red nun.	Private aid.
		*					9/13
26863	- Buoy 9	40-53-52.32N 73-22-36.48W				Green can.	Private aid.
		*					9/13
26864	- Buoy 10	40-53-51.96N 73-22-37.26W				Red nun.	Private aid.
		*					9/13
28290	- Buoy 10	41-00-37.92N 72-15-57.30W				Red nun.	Private aid.
		*					9/13
29115	- Buoy 1	40-36-55.03N 73-19-11.21W				Green can.	
		*					9/13
29120	- <i>Lighted Buoy 2</i>	40-36-55.98N 73-19-03.38W	Fl R 4s		3	Red.	Replaced by nun when endangered by ice.
		*					9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
67	<i>Fisherman's Energy Lighted Data Buoy A</i>	39-18-51.90N 74-24-02.10W	FI Y 4s			Yellow boat-shaped hull lettered "A". Moored in close proximity to disc-shaped hull lettered "C".	Private aid.
						*	9/13
3680	- Channel Lighted Buoy 8	40-00-24.90N 75-03-05.02W	Q R		5	Red.	Replaced by LIB of reduced intensity from Dec. 15 to Mar. 15.
						*	9/13
3730	- Channel Lighted Buoy 14	40-01-07.20N 75-01-14.72W	FI R 4s		5	Red.	Replaced by nun when endangered by ice.
						*	9/13
3955	- Channel Lighted Buoy 43	40-05-00.00N 74-51-52.39W	Q G		6	Green.	Replaced by can when endangered by ice.
						*	9/13
6815	- Lighted Buoy 4	37-21-58.72N 75-43-11.40W	FI R 2.5s		4	Red.	
		*					9/13
6920	- LIGHT 8	37-28-22.07N 75-48-22.50W	FI R 4s	15	4	TR on multi-pile structure.	Light equipment removed when endangered by ice.
						*	9/13
9957 36807	- Lighted Buoy 2A	36-48-30.15N 76-17-25.85W	Q R		4	Red with yellow triangle.	
						*	9/13
9960 36810	- Buoy 3 75 feet outside channel limit.	36-47-32.23N 76-17-52.69W				Green can with yellow square.	
						*	9/13
9963 36813	- Lighted Buoy 3A	36-48-30.10N 76-17-23.15W	Q G		4	Green with yellow square.	
						*	9/13
9965 36815	- Buoy 5 75 feet outside channel limit.	36-47-27.73N 76-18-01.46W				Green can with yellow square.	
						*	9/13
9985 36835	- Buoy 10	36-47-14.40N 76-18-12.62W				Red nun with yellow triangle.	
						*	9/13
9990 36840	- Buoy 12	36-47-07.32N 76-18-15.75W				Red nun with yellow triangle.	
						*	9/13
10000 36850	- Buoy 15	36-46-54.52N 76-18-24.50W				Green can with yellow square.	
						*	9/13
10005 36855	- Buoy 17	36-46-49.53N 76-18-27.79W				Green can with yellow square.	
						*	9/13
10070 36920	- Buoy 26	36-46-06.88N 76-17-53.67W				Red nun with yellow triangle.	
						*	9/13
12535	- JUNCTION LIGHT AR	37-19-19.44N 77-16-43.37W	FI (2+1) G 6s	19	5	JG on pile.	
						*	9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
12665	- CHANNEL LIGHT 139	37-21-54.09N 77-18-35.41W *	FI G 6s	18	4	SG on pile.	9/13
12690	- CHANNEL LIGHT 147	37-22-43.83N 77-19-18.11W	FI G 4s	15	5	SG on pile. *	9/13
12740	- CHANNEL LIGHT 155A	37-23-38.51N 77-23-02.17W	FI G 2.5s	15	4	SG on pile. *	9/13
12760	- CHANNEL LIGHT 160	37-25-30.80N 77-24-08.87W	Q R	15	4	TR on pile. *	9/13
13465	- Entrance Channel Lighted Buoy 12	37-12-34.25N 76-17-02.45W	FI R 2.5s		5	Red. *	9/13
15650	- LIGHT 38	37-59-03.37N 76-54-06.69W	FI R 2.5s	15	4	TR on multi-pile structure. *	9/13
17635	- Channel Lighted Buoy 29 *	38-18-30.46N 76-59-28.90W	FI G 4s		5	Green.	Replaced by can when endangered by ice. 9/13
18900	- RESEARCH PIER LIGHT	38-19-02.46N 76-27-03.12W *	FI Y 4s	14		On post on top of pump house.	Private aid. 9/13
19395	- CHANNEL LIGHT 1	38-45-55.85N 76-33-08.99W *	FI G 4s	15	4	SG on pile.	9/13
26790	- CHANNEL LIGHT 34	39-10-07.50N 76-02-12.63W *	FI R 4s	15	3	TR on pile.	9/13
28030	- Buoy 15						Remove from list. *
28655	- Lighted Buoy 5	35-10-57.20N 75-45-57.19W	FI G 2.5s		4	Green. *	9/13
36807 9957	- Lighted Buoy 2A	36-48-30.15N 76-17-25.85W	Q R		4	Red with yellow triangle. *	9/13
36810 9960	- Buoy 3 75 feet outside channel limit.	36-47-32.23N 76-17-52.69W				Green can with yellow square. *	9/13
36813	- Lighted Buoy 3A	36-48-30.10N 76-17-23.15W	Q G		4	Green with yellow square. *	9/13
36815 9965	- Buoy 5 75 feet outside channel limit.	36-47-27.73N 76-18-01.46W				Green can with yellow square. *	9/13
36835 9985	- Buoy 10	36-47-14.40N 76-18-12.62W				Red nun with yellow triangle. *	9/13
36840 9990	- Buoy 12	36-47-07.32N 76-18-15.75W				Red nun with yellow triangle. *	9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
36850 10000	- Buoy 15	36-46-54.52N 76-18-24.50W				Green can with yellow square. *	9/13
36855 10005	- Buoy 17	36-46-49.53N 76-18-27.79W				Green can with yellow square. *	9/13
36920 10070	- Buoy 26	36-46-06.88N 76-17-53.67W				Red nun with yellow triangle. *	9/13
36945	- Daybeacon 4	36-45-20.16N 76-19-37.87W				TR-TY on pile. *	9/13
40340	- Buoy 81	33-54-25.50N 78-23-04.38W *				Green can with yellow square. *	9/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2465	- Channel Lighted Buoy 23	32-44-33.68N 79-51-05.43W	FI G 2.5s		5	Green. *	9/13
5090	- LIGHT 22	32-08-41.88N 81-08-25.01W	FI R 6s	16	5	TR on pile. *	9/13
5120	- LIGHT 26	32-09-10.14N 81-08-58.65W	FI R 4s	16	5	TR on pile. *	9/13
6120	ST. SIMONS NORTH TOWER LIGHT	31-08-55.17N 81-25-06.33W *	Iso R 6s	146		On tower.	Visible 2° each side of 303° bearing. 9/13
6125	ST. SIMONS SOUTH TOWER LIGHT	31-08-50.60N 81-25-04.52W *	Iso R 6s	147		On tower.	Visible 2° each side of 303° bearing. 9/13
6185.7 37259	- Lighted Buoy 21	31-06-30.07N 81-25-41.00W	Q G		4	Green. *	9/13
6740 37905	- LOWER RANGE A REAR LIGHT 196 yards, 114.5° from front light. *	30-42-17.35N 81-26-33.63W *	Iso W 6s	34	10	KRW on skeleton tower.	Obscured from 180° to 096°. Higher intensity on range line. 9/13
6745 37860	- RANGE FRONT LIGHT A-1 *	30-43-36.39N 81-29-31.50W *	Q R	17		KRW-I on dolphin.	Visible all around. 9/13
6750 37865	- RANGE REAR LIGHT A-1 316 yards, 301.6° from front light. *	30-43-41.30N 81-29-40.75W *	Iso R 6s	29		KRW on tower on piles.	Visible all around. 9/13
6775 37840	- Lighted Buoy 30	30-43-41.35N 81-28-58.34W	FI R 2.5s		5	Red with yellow square. *	9/13
9985.1	Fort Pierce City Marina Channel Daybeacon 3						Remove from list. * 9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9985.3	Fort Pierce City Marina Channel Daybeacon 4						<i>Remove from list.</i>
							* 9/13
9986.5	Fort Pierce City Marina Channel Junction Daybeacon						<i>Remove from list.</i>
							* 9/13
10800	- LIGHT 4	25-41-06.54N 80-11-01.29W	FI R 2.5s	16	5	TR on pile.	
							* 9/13
22315	- Lighted Buoy 15	27-36-48.39N 82-46-39.25W	FI G 4s		5	Green.	
							* 9/13
22825	- Lighted Buoy 4F	27-46-04.71N 82-31-19.39W	FI R 4s		5	Red.	
							* 9/13
25695	- LIGHT 6	27-57-54.32N 82-49-49.08W	FI R 4s	16	5	TR on pile.	
							* 9/13
25705	- LIGHT 8	27-57-46.98N 82-49-34.54W	FI R 2.5s	16	5	TR on pile.	
							* 9/13
32075.5	- ENTRANCE RANGE REAR PASSING LIGHT						<i>Remove from list.</i>
							* 9/13
37060	- LIGHT 223	31-16-37.56N 81-22-59.34W	FI G 4s	16	5	SG-SY on pile.	
							* 9/13
37259 6185.7	<i>St Simons Sound Lighted Buoy 21</i>	31-06-30.07N 81-25-41.00W	Q G		4	Green.	
							* 9/13
37610	- LIGHT 60	30-50-56.42N 81-28-41.67W	FI R 4s	12	5	TR-TY on pile.	
		*					9/13
37840 6775	- Lighted Buoy 30	30-43-41.35N 81-28-58.34W	FI R 2.5s		5	Red with yellow square.	
							* 9/13
37860 6745	- RANGE FRONT LIGHT A-1	30-43-36.39N 81-29-31.50W	Q R	17		KRW-I on dolphin.	Visible all around.
		*		*			9/13
37865 6750	- RANGE REAR LIGHT A-1 316 yards, 301.6° from front light.	30-43-41.30N 81-29-40.75W	Iso R 6s	29		KRW on tower on piles.	Visible all around.
	*	*		*			9/13
37905 6740	- LOWER RANGE A REAR LIGHT 196 yards, 114.5° from front light.	30-42-17.35N 81-26-33.63W	Iso W 6s	34	10	KRW on skeleton tower.	Obscured from 180° to 096° . Higher intensity on range line.
		*		*			9/13
38110	- LIGHT 37	30-34-08.06N 81-28-21.56W	FI G 4s	12	5	SG-SY on dolphin.	
							* 9/13
38215	- LIGHT 57	30-29-08.76N 81-27-29.67W	FI G 4s	12	5	SG-SY on pile.	
							* 9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
38230	- LIGHT 63	30-28-17.39N 81-27-28.35W	FI G 4s	12	5	SG-SY on pile.	
					*		9/13
38780	- LIGHT 41	29-59-59.89N 81-20-18.55W	FI G 4s	12	5	SG-SY on pile.	
					*		9/13
60155	- LIGHT 58	27-30-37.80N 82-41-22.57W	Q R	15	3	TR-TY on pile.	
	*					*	9/13
60160	- RANGE REAR LIGHT 265 yards, 144.7° from front light.						<i>Remove from list.</i>
							* 9/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
267	<i>Tana-117-20 Lighted Buoy</i>						<i>Remove from list.</i>
							* 9/13
24395	MORGANS POINT APPROACH OUTER RANGE FRONT LIGHT	29-35-46.91N 94-56-56.30W	FI G 2.5s (Night) FI W 2.5s (Day)	40 38		KRW on skeleton tower on piles.	Visible 2° each side of range line.
		*					9/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5	Point Loma Light	32-39-54.25N 117-14-33.55W	FI W 15s	88	14	Black house on white square pyramidal skeleton tower. 90	Emergency light of reduced intensity when main light is extinguished. HORN: 1 blast ev 30s (3s bl).
					*		9/13
2560	- Sound Signal						<i>Remove from list.</i>
							* 9/13
4307	FISHERMANS WHARF BREAKWATER LIGHT A	37-48-40.39N 122-25-21.48W	FI Y 2.5s	21	4	On post.	Ra ref.
						*	9/13
4308	FISHERMANS WHARF BREAKWATER LIGHT B	37-48-42.40N 122-25-16.38W	FI Y 2.5s	21	4	On post.	Ra ref.
						*	9/13
8951	- <i>Channel Lighted Buoy 21</i>	43-25-14.11N 124-16-20.23W	FI G 4s		3	Green.	
		*					9/13
8965	JARVIS UPPER RANGE B REAR LIGHT 409 yards, 079.4° from front light.	43-25-44.16N 124-13-06.36W	Iso W 6s	33		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line.
							* 9/13
9010	NORTH BEND LOWER RANGE FRONT LIGHT	43-25-29.81N 124-13-01.41W	Q G	15		KRB on multi-pile structure.	Visible all around; higher intensity on range line.
				*		*	9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9015	NORTH BEND LOWER RANGE REAR LIGHT 159 yards, 112.2° from front light.	43-25-28.03N 124-12-55.41W	Iso G 6s	30		KRB on skeleton tower on multi-pile structure. On same structure as North Bend Range Rear Light.	Visible all around; higher intensity on range line.
	*	*		*		*	9/13
9020	NORTH BEND RANGE FRONT LIGHT	43-25-23.15N 124-12-56.49W	Q G	18		KRB on multi-pile structure.	Visible all around; higher intensity on range line.
				*		*	9/13
9025	NORTH BEND RANGE REAR LIGHT 167 yards, 009.2° from front light.	43-25-28.03N 124-12-55.41W	Iso G 6s	30		KRB on skeleton tower on multi-pile structure. On same structure as North Bend Lower Range Rear Light.	Visible all around; higher intensity on range line.
	*	*		*		*	9/13
9050	FERNDALE LOWER RANGE FRONT LIGHT	43-24-03.23N 124-12-51.50W	Q W	19		KRB on multi-pile structure.	Visible 14° each side of range line.
		*		*		*	9/13
9055	FERNDALE LOWER RANGE REAR LIGHT 338 yards, 012.9° from front light.	43-24-13.01N 124-12-48.42W	Iso W 6s	33		KRB on multi-pile structure.	Visible 14° each side of range line.
	*	*				*	9/13
9305	BARRETTS RANGE FRONT LIGHT	43-43-52.00N 124-09-58.80W	Q W	19		KRB on multi-pile structure.	Visible all around; higher intensity on range line.
		*		*		*	9/13
9310	BARRETTS RANGE REAR LIGHT 264 yards, 331.2° from front light.	43-43-58.87N 124-10-04.00W	Iso W 6s	40		KRB on skeleton tower.	Visible all around; higher intensity on range line.
	*	*		*			9/13
9795	- ENTRANCE RANGE FRONT LIGHT	44-48-33.48N 124-03-42.81W	Q R	34		KWR on skeleton tower.	Visible 4° each side of range line. Lighted throughout 24 hours.
		*		*			9/13
9800	- ENTRANCE RANGE REAR LIGHT 16 yards, 086.2° from front light.	44-48-33.51N 124-03-41.16W	Iso R 6s	46		KWR on skeleton tower.	Visible 4° each side of range line. Lighted throughout 24 hours.
	*	*		*			9/13
14770	- Daybeacon 12						<i>Remove from list.</i>
							* 9/13
24490	- Entrance Range Front Daybeacon	55-28-29.95N 133-08-31.63W				KRW on skeleton tower.	
		*					9/13
24495	- Entrance Range Rear Daybeacon 35 yards, 054.2° from front daybeacon.	55-28-30.55N 133-08-30.16W				KRW on skeleton tower.	
	*	*					9/13
25405	- ENTRANCE RANGE FRONT LIGHT	58-37-35.63N 137-39-28.61W	Q W	28		KRW on skeleton tower.	Obscured from 048° to 348°; higher intensity on range line.
		*		*			9/13
25410	- ENTRANCE RANGE REAR LIGHT 238 yards, 007.8° from front light.	58-37-42.59N 137-39-26.79W	Iso W 6s	42		KRW on skeleton tower.	Obscured from 170° to 222°; higher intensity on range line.
	*	*		*			9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
27542	- RANGE FRONT LIGHT	51-51-09.11N 176-39-14.98W *	Q G	36 *		KRW on pile structure.	9/13
27543	- RANGE REAR LIGHT 494 yards, 253° from front light.	51-51-04.80N 176-39-37.73W *	Oc G 4s	101 *		KRW on pile.	9/13
27826	ST. GEORGE HARBOR RANGE REAR LIGHT 361 yards, 076.4° from front light. *	56-34-12.20N 169-39-52.34W	Iso Y 6s	76		KRW on tower.	9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.