

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
395	<i>Three And One-Half Fathom Ledge Lighted Bell Buoy 2</i>	42-21-04.98N 70-50-29.78W	FI R 4s		4	Red.	
						*	12/13
*3616	WALDO HANCOCK WEST LIGHT	44-33-39.27N 68-48-10.47W	FI W 2.5s	15		White.	Marks end of pier. Private aid.
							12/13
*3617	WALDO HANCOCK EAST LIGHT	44-33-35.52N 68-48-00.74W	FI W 2.5s			White.	Marks end of pier. Private aid.
							12/13
4915	- LIGHT 21	44-04-11.29N 69-10-47.16W	FI W 6s	14	7	SG on white skeleton tower.	
	*						12/13
5795	<i>Merrill Ledge Lighted Buoy 22</i>	43-58-02.26N 69-39-59.28W	FI R 4s		4	Red.	Replaced by nun when endangered by ice.
	*						12/13
*6716	Rhebins Ledge Buoy 1	43-45-00.00N 69-59-21.00W				Green can.	Private aid.
							12/13
12925	- CHANNEL LIGHT 12 50 feet west of channel limit.	41-58-47.27N 70-39-24.42W	Q R (W sector)	16	W 5 R 4	TR on skeleton tower on black cylindrical pier.	White from 195.5° to 199.5°.
							* 12/13
29125	- <i>Lighted Buoy 4</i>	40-37-30.95N 73-19-17.07W	FI R 2.5s		3	Red.	Replaced by nun when endangered by ice.
	*						12/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3	<i>NOAA Lighted Data Buoy 44066 (ODAS)</i>	39-35-00.71N 72-35-57.64W	FI(4)Y 20s		5	Yellow boat-shaped hull.	Aid maintained by National Oceanic and Atmospheric Administration.
		*					12/13
2275	- INLET NORTH JETTY LIGHT 2	38-56-13.81N 75-17-52.62W	FI R 4s	25	6	TR on skeleton tower.	
							* 12/13
2645	- <i>Channel Lighted Buoy 2</i>	39-32-39.66N 75-32-13.79W	FI R 4s		5	Red.	Replaced by LIB of reduced intensity from Jan. 1 to Feb. 28.
						*	12/13
2720	- <i>Lighted Buoy 1N</i>	39-33-06.47N 75-32-36.90W	Q G		5	Green.	Replaced by a LIB of reduced intensity from Jan. 1 to Feb. 28.
	*						12/13
2745	- <i>Junction Lighted Buoy CD</i>	39-33-51.77N 75-33-17.56W	FI (2+1) R 6s		4	Red with green band.	Replaced by LIB of reduced intensity from Jan. 1 to Feb. 28.
	*						12/13
6840	- Daybeacon 8	37-22-30.30N 75-45-04.84W				TR on pile.	
		*					12/13
7620	- <i>Lighted Buoy 76</i>	38-21-23.44N 76-18-32.41W	FI R 4s		5	Red.	Replaced by nun when endangered by ice.
	*						12/13
8195	- <i>Lighted Buoy 11</i>	39-11-41.57N 76-29-36.96W	FI G 6s		6	Green.	Replaced by can when endangered by ice.
						*	12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8200	- Lighted Buoy 12	39-11-51.01N 76-29-38.76W	FI R 6s		6	Red.	Replaced by nun when endangered by ice.
					*		12/13
8205	- Lighted Buoy 14	39-12-00.04N 76-30-08.17W	Q R		6	Red.	Replaced by nun when endangered by ice.
					*		12/13
8805	- ENTRANCE LIGHT 2S	39-20-07.20N 76-08-13.99W	FI R 2.5s	15	4	TR on multi-pile structure.	
					*		12/13
9995 36845	- Buoy 14	36-47-02.53N 76-18-19.69W				Red nun with yellow triangle.	
						*	12/13
10845	- Lighted Buoy 4	36-57-41.95N 76-21-06.64W	Q R		5	Red.	
		*					12/13
10855	- Lighted Buoy 6	36-57-35.23N 76-21-25.50W	FI R 4s		5	Red.	
		*					12/13
12220	- Channel Lighted Buoy 62	37-12-58.17N 76-52-18.55W	FI R 2.5s		5	Red.	
					*		12/13
18661	- Buoy 7	38-49-23.35N 77-01-56.57W				Green can.	
		*					12/13
20535	- LIGHT 6	39-13-04.97N 76-27-31.06W	FI R 4s	15	4	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
					*		12/13
20895	- Channel Lighted Buoy 6	39-13-20.47N 76-33-31.92W	FI R 4s		6	Red.	Replaced by nun when endangered by ice.
	*				*		12/13
22830	- LIGHT 4	37-58-02.54N 75-53-26.52W	FI R 4s	19	4	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
					*		12/13
26015	- LIGHT 1CC	38-50-08.69N 76-17-16.19W	FI G 4s	15	4	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.
	*						12/13
28280	- LIGHT 12	35-44-01.10N 75-36-53.33W	FI R 4s	15	4	TR on pile.	Light equipment removed when endangered by ice. Ra ref.
		*					12/13
28310	- LIGHT 3	34-47-22.44N 75-34-00.00W	FI G 4s	15	4	SG on pile.	
		*					12/13
29559	- Lighted Buoy 14	34-39-24.77N 77-06-21.80W	Q R		4	Red.	
					*		12/13
*35117	Barnegat Bay Research Daybeacon A	39-54-02.58N 74-05-48.48W				NW on pile.	Private aid.
							12/13
35125	- LIGHT 40	39-51-42.41N 74-07-21.06W	FI R 2.5s	17	3	TR-TY on multi-pile structure.	Maintained year round.
							*
							12/13
35130	BARNEGAT BAY LIGHT BB	39-49-21.42N 74-08-45.60W	Mo (A) W	17	5	MR-I on multi-pile structure.	Maintained year round.
							*
							12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
35135	BARNEGAT INLET LIGHT BI	39-47-31.97N 74-09-54.88W	Mo (A) W	17	5	MR-I on multi-pile structure.	Maintained year round. * 12/13
35155	- LIGHT 42	39-45-46.50N 74-10-14.28W	Q R	17	3	TR-TY on multi-pile structure.	Maintained year round. * 12/13
*35417	Little Egg Harbor Research Daybeacon A	39-33-22.38N 74-16-14.34W				NW on pile.	Private aid. 12/13
35467	- Buoy 116A	39-30-42.59N 74-18-03.10W				Red nun.	Maintained year round. * 12/13
35500	- LIGHT 126	39-30-28.53N 74-20-18.59W	Q R	15	4	TR-TY on multi-pile structure.	Maintained year round. * 12/13
35570	- LIGHT 139	39-29-52.74N 74-22-51.96W	Q G	15	3	SG-SY on multi-pile structure.	Maintained year round. * 12/13
35575	- LIGHT 141	39-29-24.66N 74-22-53.94W	Fl G 2.5s	15	3	SG-SY on multi-pile structure.	Maintained year round. * 12/13
36385	- Buoy 374	39-06-56.87N 74-43-30.86W				Red nun with yellow triangle.	Maintained year round. * 12/13
36393	- Buoy 376	39-06-30.42N 74-44-15.28W				Red nun with yellow triangle.	Maintained year round. * 12/13
36580	- LIGHT 437	39-01-58.08N 74-48-21.12W	Fl G 2.5s	15	4	SG-SY on pile.	 * 12/13
36845 9995	- Buoy 14	36-47-02.53N 76-18-19.69W				Red nun with yellow triangle. *	12/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2935	- RANGE A FRONT LIGHT	32-54-36.43N 79-55-38.55W	Q W	29		On skeleton tower on piles.	Visible 4° each side of range line. Lighted throughout 24 hours. * 12/13
2940	- RANGE A REAR LIGHT 318 yards, 081.2° from front light.	32-54-37.88N 79-55-27.46W	Iso W 6s	39		On white skeleton tower on piles.	Visible 4° each side of range line. Lighted throughout 24 hours. * 12/13
2965	- RANGE B FRONT LIGHT	32-54-24.37N 79-56-08.85W	Q G	15		KRW on pile.	Visible 2° each side of range line. * 12/13
2970	- RANGE B REAR LIGHT 318 yards, 214.3° from front light.	32-54-16.57N 79-56-15.15W	Iso G 6s	23		KRW on dolphin.	Visible 2° each side of range line. * 12/13
2995	- RANGE C FRONT LIGHT	32-56-01.19N 79-56-22.21W	Q G	27			Visible 1.5° each side of range line. Lighted throughout 24 hours. * 12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3000	- RANGE C REAR LIGHT 200 yards, 328.8° from front light. *	32-56-06.27N 79-56-25.86W *	Iso G 6s	34			Visible 1.5° each side of range line. Lighted throughout 24 hours. 12/13
3040	- RANGE D AND F FRONT LIGHT	32-56-23.33N 79-55-28.65W *	Q W	12 *		KRW on dolphin.	Visible all around. 12/13
3060	- RANGE E REAR LIGHT 183 yards, 208.4° from front light. *	32-56-02.92N 79-55-52.81W *	Iso W 6s	24 *		KRW on tower on piles.	Visible all around. 12/13
6225	<i>Brunswick Point Cut Lighted Buoy 27</i>	31-06-32.07N 81-28-02.53W	FI G 2.5s		5	Green.	* 12/13
6227	<i>Brunswick Point Cut Lighted Buoy 29</i>	31-06-55.27N 81-29-02.68W	FI G 2.5s		5	Green.	* 12/13
6228	<i>Brunswick Point Cut Lighted Buoy 30</i>	31-07-08.03N 81-29-18.05W	Q R		4	Red.	* 12/13
6700	- <i>Lighted Buoy 22</i>	30-42-41.35N 81-27-26.33W	Q R		4	Red.	* 12/13
8395	TURKEY ISLAND LIGHT 43	29-29-58.32N 81-42-00.00W	FI G 4s	16	5	SG on dolphin.	* 12/13
10695	- LIGHT 15	25-46-19.02N 80-10-35.41W *	FI G 6s	16	5	SG on pile.	* 12/13
13725	- LIGHT 2	24-41-14.55N 81-05-11.58W	FI R 4s	16	5	TR on pile.	* 12/13
13885	- ENTRANCE LIGHT 2	24-37-08.23N 81-24-25.53W	FI R 4s	16	5	TR on pile.	* 12/13
13980	LOGGERHEAD KEY LIGHT 50A	24-35-50.59N 81-27-17.13W	FI R 6s	16	5	TR on pile.	* 12/13
23205	- <i>Lighted Buoy 13</i>	27-48-55.23N 82-27-01.30W	FI G 2.5s		5	Green.	* 12/13
31635	<i>Bajo Snapper Lighted Buoy 8</i>	18-17-21.69N 65-16-17.52W *	Q R		4	Red.	* 12/13
43075	- LIGHT 6	28-07-29.69N 80-37-24.37W	FI R 4s	16	5	TR on pile.	* 12/13
44640	- Daybeacon 9	27-34-57.00N 80-20-33.10W *				SG on pile.	Private aid. 12/13
*47822	- Buoy 7	25-54-11.96N 80-07-47.68W				Green can with yellow square.	12/13
*47824	- Buoy 7A	25-54-08.95N 80-07-50.40W				Green can with yellow square.	12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
47828	- Buoy 7B *	25-54-06.58N 80-07-52.64W *				Green can with yellow square.	12/13
48085	Biscayne Bay Pipeline Buoy A						Remove from list. *
48150	Biscayne Bay Pipeline Buoy E						Remove from list. *
48155	Biscayne Bay Pipeline Buoy D						Remove from list. *
48160	Biscayne Bay Pipeline Buoy C						Remove from list. *
48585	- LIGHT 67	25-45-08.90N 80-11-02.26W	FI G 4s	16	5	SG-SY on pile.	12/13
					*		12/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
965	<i>Gulf Gateway Energy Bridge Deepwater Port Lighted Buoy A</i>						Remove from list. *
	*Add Heading: ALABAMA RIVER						12/13
*6801	UNITED LAND COMPANY DOLPHIN LIGHTS (2) LDB Mile 353.3		FI R 2.5s	15		On dolphins.	Private aids. 12/13
	*Add Heading and Note: BLACK WARRIOR RIVER <i>From mile 217 to mile 385.5, the river is marked with numerous unlisted daybeacons and unlighted buoys which are periodically relocated to meet minor changing conditions. Holt Lock and Bankhead Lake buoys and daybeacons have been discontinued and waterways marked with unlisted, unlighted buoys. Mulberry Fork - From mile 385.6 to mile 399.7, the river is marked with numerous unlisted daybeacons and unlighted buoys which are periodically relocated to meet minor changing conditions. Locust Fork - From mile 387.0 to mile 390.8, the river is marked with numerous unlisted daybeacons and unlighted buoys which are periodically relocated to meet minor changing conditions.</i>						
*6802	Lyon Park Range Front Daybeacon					KWR on pile.	Private aid. 12/13
*6803	Lyon Park Range Rear Daybeacon.					KRW on pile.	Private aid. 12/13
16205.01	- Lighted Buoy 13 *	29-19-07.56N 89-59-08.28W	FI G 4s			Green.	12/13
	*Add Heading: Vermilion Bay						12/13
*20573	Vermilion Parish Danger Daybeacons (6)	29-34-17.00N 92-11-16.00W				Marks submerged shoreline erosion protection structures.	Private aids. 12/13
20658	- JUNCTION LIGHT FW *	29-46-29.62N 92-10-15.04W *	FI (2+1) R 6s	17	2	JR-SY on pile.	12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
25075	LOWER RED LIGHT BEND OUTBOUND RANGE REAR LIGHT 174 yards, 096.8° from front light.	29-41-57.88N 94-59-44.69W	Iso R 6s	32		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line.
		*		*			12/13
33970	- A RANGE FRONT LIGHT	30-17-37.98N 88-07-17.07W	Q R	17		KRW-I on pile.	Visible 2° each side of range line.
		*					12/13
33975	- A RANGE FRONT PASSING LIGHT	30-17-37.98N 88-07-17.07W	Q W	18	5	On same structure as Pass Aux Herons A Range Front Light.	
		*					12/13
33980	- A RANGE REAR LIGHT 884 yards, 286.8° from front light.	30-17-45.58N 88-07-46.04W	Iso R 6s	35		KRW-I on pile structure.	Visible 2° each side of range line.
		*					12/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
213	<i>NOAA Environmental Lighted Buoy 46023</i>						<i>Remove from list.</i>
							* 12/13
665	Cape Kiwanda Bell Buoy CK	45-12-55.49N 123-59-55.17W				Yellow.	
		*					12/13
9230	- <i>Entrance Lighted Buoy 2</i>	43-39-58.37N 124-13-45.95W	FI R 4s		3	Red.	
	*	*	*		*	*	12/13
9620	- INNER RANGE FRONT LIGHT	44-37-44.24N 124-02-58.95W	Q R	17		KRB on multi-pile structure.	Visible 4° each side of range line.
		*				*	12/13
9625	- INNER RANGE REAR LIGHT 136 yards, 040.8° from front light.	44-37-47.28N 124-02-55.27W	Iso R 6s	30		KRB on skeleton tower on multi-pile structure.	Visible 5.5° each side of range line.
	*	*		*		*	12/13
9635	SOUTHBEACH MARINA LIGHT 2	44-37-25.93N 124-03-14.73W	FI R 4s	14	3	TR on pile.	
		*					12/13
10415	BUGBY HOLE LIGHT 46	46-10-53.82N 123-25-56.62W	Q R	15	3	TR on multi-pile structure.	
		*			*	*	12/13
11615	CAPE HORN RANGE FRONT LIGHT	45-34-04.74N 122-11-36.21W	Q R	43		KRB on multi-pile structure.	Visible all around; higher intensity on range line. Ra ref.
		*		*		*	12/13
11620	- RANGE REAR LIGHT 780 yards, 062.2° from front light.	45-34-15.49N 122-11-07.12W	Iso R 6s	60		KRB on skeleton tower on multi-pile structure.	Visible 5.5° each side of range line.
	*					*	12/13
11630	- LOWER RANGE FRONT LIGHT	45-35-06.41N 122-07-37.67W	Q G	40		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line; higher intensity on range line.
		*		*		*	12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11635	- LOWER RANGE REAR LIGHT 684 yards, 077.9° from front light.	45-35-10.66N 122-07-09.45W	Iso G 6s	58		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line.
	*	*		*		*	12/13
11665	- BAR RANGE FRONT LIGHT	45-34-50.66N 122-06-28.79W	Q R	53		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line.
		*		*		*	12/13
11670	- BAR RANGE REAR LIGHT 233 yards, 098.5° from front light.	45-34-49.63N 122-06-19.07W	Iso R 6s	72		KRB on skeleton tower.	Visible 4° each side of range line.
	*	*		*			12/13
11795	- LOWER RANGE FRONT LIGHT 8	45-39-32.65N 121-54-02.09W	Q W	43	5	KRB on skeleton tower, TR oriented down channel.	Visible all around; higher intensity on range line.
		*		*			12/13
11800	- LOWER RANGE REAR LIGHT 120 yards, 176.2° from front light.	45-39-29.10N 121-54-01.76W	Iso W 6s	69		KRB on skeleton tower.	Visible 14° each side of range line.
	*						12/13
12220	Hells Gate Range A Front Daybeacon	45-39-19.18N 120-54-18.25W				KGB on skeleton tower.	
		*					12/13
12225	Hells Gate Range A Rear Daybeacon 222 yards, 091.9° from front daybeacon.	45-39-18.96N 120-54-08.86W				KGB on skeleton tower.	
	*	*					12/13
12595	MESSNER MIDDLE RANGE FRONT LIGHT	45-51-34.86N 119-39-33.96W	Q W	37		KRB on square wooden tower.	Visible all around; higher intensity on range line.
		*		*		*	12/13
12600	MESSNER MIDDLE RANGE REAR LIGHT 134 yards, 076.2° from front light.	45-51-35.81N 119-39-28.46W	Iso W 6s	55		KRB on skeleton tower.	Visible 5.5° each side of range line.
	*	*		*			12/13
13840	- LIGHT 30	46-40-32.83N 117-31-28.08W	FI R 2.5s	18	4	TR on skeleton tower.	
					*	*	12/13
24112	- RANGE FRONT LIGHT	58-05-07.00N 134-46-27.18W	Q W	23		KRW on single pile.	Obscured from 202° to 066°.
		*		*			12/13
24113	- RANGE REAR LIGHT 400 yards, 178.3° from front light.	58-04-55.18N 134-46-26.53W	Iso W 6s	29		KRW on single pile.	Obscured from 194° to 125°.
	*	*		*			12/13
28271.2	- BREAKWATER LIGHT 5						Remove from list.
							*
							12/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8565	- Lighted Buoy 29	42-30-35.98N 82-42-02.66W	FI G 2.5s		4	Green.	Replaced by can from Dec. 21 to Mar. 28.
							*
							12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
18315	South Fox Island Shoals Buoy 3	45-17-19.05N 85-51-00.08W *				Green can.	12/13
18320	South Fox Island Shoals Buoy 4	45-18-56.21N 85-51-06.28W *				Red nun.	12/13
19520	- North Pier Inner Light	42-06-57.79N 86-29-36.48W	Iso W 2s *	53 16	7	Octagonal tower. 53	12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.