

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5225	- Channel Buoy 1						<i>Remove from list.</i> * 19/13
14760	<i>Cotuit Entrance Lighted Buoy C</i>	41-34-43.81N 70-24-36.18W	Mo (A) W		5	Red and white stripes with red spherical topmark.	Replaced by nun from Dec. 1 to Apr. 1. * 19/13
21825	New London Ledge Light On west side of Southwest Ledge.	41-18-21.14N 72-04-38.78W	Fl (3) W R 30s	58	W 17 R 14	Red brick dwelling on square pier. 58	Emergency light of Fl (3) W 30s and reduced intensity when main light is extinguished. HORN: 2 blast ev 20s (2s bl-2s si-2s bl-14s si). * 19/13
24735	- Buoy 1	41-08-25.02N 73-13-48.18W *				Green can.	Private aid. 19/13
24740	- Buoy 2	41-08-25.86N 73-13-47.82W *				Red nun.	Private aid. 19/13
24745	- Buoy 3	41-08-27.72N 73-13-51.84W *				Green can.	Private aid. 19/13
24750	- Buoy 4	41-08-28.56N 73-13-51.18W *				Red nun.	Private aid. 19/13
24755	- Buoy 5	41-08-31.38N 73-13-56.46W *				Green can.	Private aid. 19/13
24760	- Buoy 6	41-08-31.98N 73-13-55.92W *				Red nun.	Private aid. 19/13
29106.1	- West Cut Buoy 6W	40-46-24.71N 72-45-45.78W *				Red nun.	Removed when endangered by ice. 19/13
29355	- Buoy 37	40-43-50.60N 72-58-42.75W				Green can.	Maintained from Apr. 15 to Nov. 1. * 19/13
29360	- <i>Lighted Buoy 38</i>	40-43-57.44N 72-57-37.52W	Fl R 4s		3	Red.	Maintained from Apr. 15 to Nov. 1. * 19/13
29420	- Buoy 2	40-39-55.06N 73-13-42.62W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
29430	- Buoy 4	40-40-18.06N 73-14-57.02W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
29440	- Buoy 6	40-40-39.22N 73-16-00.00W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
30145	- <i>Lighted Buoy 6</i>	40-44-58.17N 72-54-30.46W	Q R		3	Red.	Maintained from Apr. 15 to Nov. 1. * 19/13
30160	- Buoy 9	40-44-28.62N 72-53-19.50W				Green can.	Maintained from Apr. 15 to Nov. 1. * 19/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
30303	- Buoy 17A	40-46-57.03N 72-45-36.84W				Green.	Removed when endangered by ice. * 19/13
31125	- Buoy 5	40-36-54.10N 73-29-57.94W				Green can.	Maintained from Apr. 1 to Nov. 15. * 19/13
31180	- Buoy 16	40-36-26.52N 73-28-42.05W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
31295	- Buoy 54	40-38-53.34N 73-19-18.78W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
31300	- Buoy 55	40-38-56.42N 73-19-12.00W				Green can.	Maintained from Apr. 1 to Nov. 15. * 19/13
31305	- Buoy 56	40-38-58.12N 73-18-55.72W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
31310	- <i>Lighted Buoy 57</i>	40-39-00.37N 73-18-53.50W	FI G 2.5s		4	Green.	Removed when endangered by ice. * 19/13
31315	- <i>Lighted Buoy 58</i>	40-38-59.27N 73-18-37.39W	FI R 4s		3	Red.	Removed when endangered by ice. * 19/13
31320	- Buoy 59	40-39-01.01N 73-18-34.92W				Green can.	Maintained from Apr. 1 to Nov. 15. * 19/13
31325	- Buoy 61	40-39-00.61N 73-18-21.22W				Green can.	Maintained from Apr. 1 to Nov. 15. * 19/13
31340	- Buoy 64	40-38-58.33N 73-17-52.22W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
31385	- Buoy 2	40-39-12.97N 73-17-36.30W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
31390	- Buoy 3	40-39-22.39N 73-17-42.86W				Green can.	Maintained from Apr. 1 to Nov. 15. * 19/13
31395	- Buoy 4	40-39-29.65N 73-17-45.16W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
31400	- Buoy 5	40-39-36.06N 73-17-50.28W				Green can.	Maintained from Apr. 1 to Nov. 15. * 19/13
31405	- Buoy 6	40-39-43.80N 73-17-52.58W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
31410	- Buoy 7	40-39-55.95N 73-18-01.36W				Green can.	Maintained from Apr. 1 to Nov. 15. * 19/13
31415	- Buoy 8	40-40-01.01N 73-18-02.08W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
31420	- Entrance Lighted Buoy 9	40-40-08.41N 73-18-08.81W	FI G 2.5s		4	Green.	Maintained from Apr. 1 to Nov. 15. * 19/13
31436	- Buoy 76	40-38-36.70N 73-16-00.13W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
31437	- Buoy 76A	40-38-34.93N 73-15-53.89W				Red nun.	Maintained from Apr. 1 to Nov. 15. * 19/13
31455	- Buoy 80	40-38-37.20N 73-15-06.27W				Red nun.	Removed when endangered by ice. * 19/13
31470	- Buoy 86	40-38-34.78N 73-14-47.90W				Green.	Removed when endangered by ice. * 19/13
36542	- Lighted Buoy 39						Remove from list. * 19/13
36544	- Lighted Buoy 43						Remove from list. * 19/13
36552	- Lighted Buoy 49						Remove from list. * 19/13
36554	- Lighted Buoy 51						Remove from list. * 19/13
36561	- Lighted Buoy 57						Remove from list. * 19/13
36567	- Lighted Buoy 65	40-29-15.00N 74-25-15.90W *	FI G 3s			Green.	Private aid. * 19/13
36570	- Lighted Buoy 69	40-29-22.80N 74-26-06.10W *	FI G 3s			Green.	Private aid. * 19/13
37846	HDR Research Lighted Buoy	41-13-13.20N 73-57-37.80W	FI W 4s			White and orange.	Private aid. * 19/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*2140	- Channel Buoy 16B	38-37-10.03N 75-05-33.52W				Red nun.	19/13
2148	- Channel Buoy 19	38-37-13.46N 75-05-36.25W *				Green can.	19/13
2151	- Channel Buoy 20	38-37-10.03N 75-05-33.52W *				Red nun.	19/13
2155	- Channel Buoy 21	38-37-00.62N 75-05-27.40W *				Green can.	19/13
2156	- Channel Buoy 21A						Remove from list. * 19/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2157	- Channel Buoy 22	38-36-54.90N 75-05-36.18W *				Red nun.	19/13
2160	- Channel Warning Daybeacon *	38-36-57.02N 75-05-59.07W				SG on pile.	19/13
2165	- Buoy 23 *	38-36-43.88N 75-05-32.12W *				Green can. *	19/13
2170	- Channel Daybeacon 27					<i>Remove from list.</i> *	19/13
2171	- Channel Buoy 28					<i>Remove from list.</i> *	19/13
4430	<i>Indian River Junction Lighted Buoy IR</i>	38-36-34.40N 75-05-30.95W *	FI (2+1) R 6s		3	Red and green bands.	Maintained from May 1 to Nov 15. 19/13
6915	- LIGHT 6					<i>Remove from list.</i> *	19/13
6925	- Daybeacon 10					<i>Remove from list.</i> *	19/13
*6927	- <i>Lighted Wreck Buoy WR10</i>	37-29-00.31N 75-48-00.73W	Q R		3	Red.	19/13
13860	- Buoy 18 *	37-17-56.23N 76-38-45.91W				Red nun. *	19/13
17125	- Channel Buoy 3A *	38-13-58.76N 76-44-33.45W				Green can.	19/13
19645	- LIGHT 15 *	38-56-42.04N 76-32-27.24W	FI G 4s	15	4	SG on multi-pile structure.	19/13
19655	- LIGHT 17 *	38-57-11.36N 76-33-43.54W	FI G 2.5s	15	4	SG on pile.	19/13
20435	- RANGE REAR LIGHT 1,000 yards, 353.6° from front. *	39-13-34.42N 76-27-47.19W	Iso G 6s	45		KRW on pile.	Private aid. 19/13
21580	- LIGHT 1MC *	37-23-21.83N 75-59-39.46W	FI G 4s	15	4	SG on pile.	Light equipment removed when endangered by ice. 19/13
28430	- CHANNEL LIGHT 16 *	35-50-36.50N 75-36-22.68W	FI R 2.5s	15	3	TR on pile.	19/13
31010	- Buoy 1 *	33-54-26.01N 78-14-27.13W				Green can.	19/13
31015	- Buoy 2 *	33-54-25.16N 78-14-24.05W				Red nun.	19/13
31020	- Buoy 3 *	33-54-32.33N 78-14-24.03W				Green can.	19/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
31025	- Buoy 4	33-54-36.18N 78-14-23.13W *				Red nun.	19/13
31027	- Buoy 5	33-54-41.92N 78-14-23.00W *				Green can.	19/13
31030	- Buoy 6	33-54-42.92N 78-14-21.03W *				Red nun.	19/13
31365	Powells Point Daybeacon 2PP	36-03-00.00N 75-50-17.51W *				TR on pile.	19/13
*32086	Long Shoal Oyster Sanctuary Daybeacon A	35-33-51.59N 75-49-46.01W				White with orange diamond on multi-pile structure worded OYSTER SANCTUARY DANGER SUBMERGED ROCKS.	Private aid. 19/13
*32086.1	Long Shoal Oyster Sanctuary Daybeacon B	35-33-45.06N 75-49-46.01W				White with orange diamond on multi-pile structure worded OYSTER SANCTUARY DANGER SUBMERGED ROCKS.	Private aid. 19/13
*32086.2	Long Shoal Oyster Sanctuary Daybeacon C	35-33-45.06N 75-49-53.99W				White with orange diamond on multi-pile structure worded OYSTER SANCTUARY DANGER SUBMERGED ROCKS.	Private aid. 19/13
*32086.3	Long Shoal Oyster Sanctuary Daybeacon D	35-33-51.59N 75-49-53.99W				White with orange diamond on multi-pile structure worded OYSTER SANCTUARY DANGER SUBMERGED ROCKS.	Private aid. 19/13
34785	- Warning Daybeacon						Remove from list. *
35417	LITTLE EGG HARBOR RESEARCH LIGHT A *	39-33-22.38N 74-16-14.34W	Fl W 6s			NW on pile.	Private aid. 19/13
37665	- Daybeacon 132	36-18-24.89N 75-58-16.71W *				TR-TY on pile.	19/13
37805	- Daybeacon 169	36-09-49.70N 75-53-24.74W *				SG-SY on pile.	19/13
40230	- Buoy 47A	33-55-15.27N 78-14-14.45W *				Green can with yellow square.	19/13
40340	- Buoy 81	33-54-25.09N 78-23-05.26W *				Green can with yellow square.	19/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
120	Georgetown Light	33-13-21.47N 79-11-06.18W	Fl (2) W 15s	85	15	White cylindrical tower.	
			*			*	* 19/13
2600	- <i>Lighted Buoy 38</i>	32-47-47.29N 79-54-58.12W	Fl R 4s		5	Red.	
					*		19/13
6230 37249	BRUNSWICK POINT CUT RANGE FRONT LIGHT 2	31-05-59.39N 81-26-23.08W	Q W Fl R 4s	27		TR-TY on skeleton tower on piles.	Visible 1.5° each side of range line. Secondary light visible all around. Lighted throughout 24 hours.
		*		*			19/13
6235	BRUNSWICK POINT CUT RANGE REAR LIGHT 629 yards, 112.8° from front light.	31-05-52.15N 81-26-03.06W	Iso W 6s	48		KRW on skeleton tower on piles.	Visible 1.5° each side of range line. Lighted throughout 24 hours.
	*	*					19/13
*17480.03	Keewaydin Island Danger Daybeacon A	26-05-18.99N 81-48-03.61W				NW on pile worded DANGER SUBMERGED ROCK.	Private aid.
							19/13
*17480.04	Keewaydin Island Danger Daybeacon B	26-05-12.98N 81-48-00.88W				NW on pile worded DANGER SUBMERGED ROCK.	Private aid.
							19/13
*17480.05	Keewaydin Island Danger Daybeacon C	26-05-19.04N 81-48-02.43W				NW on pile worded DANGER SUBMERGED ROCK.	Private aid.
							19/13
*17480.06	Keewaydin Island Danger Daybeacon D	26-05-14.31N 81-47-59.21W				NW on pile worded DANGER SUBMERGED ROCK.	Private aid.
							19/13
37249 6230	BRUNSWICK POINT CUT RANGE FRONT LIGHT 2	31-05-59.39N 81-26-23.08W	Q W Fl R 4s	27	3	TR-TY on skeleton tower on piles.	Visible 1.5° each side of range line. Secondary light visible all around. Lighted throughout 24 hours.
		*		*			19/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9160	- Daybeacon 1	30-25-24.52N 88-51-18.55W				SG on pile.	Private aid.
						*	19/13
11325	- RANGE REAR LIGHT 141 yards, 015° from front light.	30-22-46.58N 90-10-08.84W	Iso W 6s	49		White conical tower.	Visible all around; higher intensity on range line.
		*					19/13
15727	<i>Great Lakes Dredging Lighted Pipeline Buoy</i>						<i>Remove from list.</i>
							* 19/13
15727.01	<i>Great Lakes Dredging Lighted Pipeline Buoy</i>						<i>Remove from list.</i>
							* 19/13
15727.02	<i>Great Lakes Dredging Lighted Pipeline Buoy</i>						<i>Remove from list.</i>
							* 19/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
15727.03	Great Lakes Dredging Lighted Pipeline Buoy						Remove from list.
							* 19/13
15727.04	Great Lakes Dredging Lighted Pipeline Buoy						Remove from list.
							* 19/13
*15728.25	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-17.87N 89-36-28.04W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.26	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-17.67N 89-36-16.18W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.27	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-15.23N 89-36-16.67W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.28	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-13.41N 89-36-17.03W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.29	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-10.97N 89-36-17.53W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.31	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-11.05N 89-36-23.55W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.32	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-22.25N 89-35-58.05W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.33	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-22.64N 89-35-57.70W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.34	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-20.52N 89-35-55.21W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.35	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-20.18N 89-35-55.63W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.36	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-18.81N 89-35-53.84W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.37	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-15.95N 89-35-52.61W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.38	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-15.81N 89-35-53.15W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.39	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-18.51N 89-35-54.31W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
28300	- Daybeacon 26						Remove from list. * 19/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5	Point Loma Light	32-39-54.25N 117-14-33.55W	FI W 15s	88	14	Black house on white square pyramidal skeleton tower. 90	Emergency light of reduced intensity when main light is extinguished. HORN: 1 blast ev 30s (3s bl). 9/13
					*		
160	<i>San Pedro Channel Traffic Lane Lighted Buoy SP</i>						<i>Remove from list.</i> * 19/13
198	<i>NOAA Lighted Buoy</i>	34-15-57.00N 120-26-24.00W	FI (4) Y 20s			Yellow disc-shaped buoy.	Aid maintained by NOAA. 6/13
	*	*					
*198.1	<i>NOAA Environmental Lighted Buoy 46054</i>	34-16-27.81N 120-27-33.84W	FI (4) Y 20s			Yellow 3-meter disc-shaped buoy.	Aid maintained by NOAA. 6/13
213	<i>NOAA Environmental Lighted Buoy 46023</i>						<i>Remove from list.</i> * 12/13
357	<i>NOAA Environmental Lighted Buoy 46026</i>	37-45-18.21N 122-50-20.84W	FI (4) Y 20s		5	Yellow disc-shaped buoy.	Aid maintained by National Oceanic and Atmospheric Administration. 4/13
		*					
487	<i>Scripps Waverider Lighted Research Buoy 128</i>						<i>Remove from list.</i> * 19/13
665	Cape Kiwanda Bell Buoy CK	45-12-55.49N 123-59-55.17W				Yellow.	 12/13
		*					
694	<i>Scripps Institute Wave Recorder Lighted Buoy 46243/162</i>	46-12-57.30N 124-07-41.28W	FI (5) Y 20s			Yellow sphere-shaped buoy.	Private aid. 15/13
	*	*					
710	<i>Scripps Institute Wave Recorder Lighted Buoy 46248/179</i>	46-08-00.18N 124-38-39.36W	FI (5) Y 20s			Yellow sphere-shaped buoy.	Private aid. 15/13
	*	*					
720 15530	Grays Harbor Light	46-53-17.58N 124-07-00.89W	AI W R 30s 0.1s W fl 14.9s ec. 0.1s R fl 14.9s ec.	123	18	White truncated octagonal pyramid tower.	Lighted throughout 24 hours. 8/13
		*					
1593	<i>Shelter Island Lighted Buoy 2</i>	32-42-16.14N 117-14-01.84W	FI (2) R 5s		3		 5/13
		*					
2288	<i>Scripps Waverider Lighted Research Buoy 093</i>						<i>Remove from list.</i> * 5/13
2289.2	<i>Scripps Waverider Lighted Research Buoy 045</i>						<i>Remove from list.</i> * 7/13
*2289.5	<i>Scripps Waverider Lighted Research Buoy 045</i>	33-10-46.00N 117-28-17.00W	FI (5) Y 20s			Yellow sphere with whip antenna.	Private aid. 7/13
2460	- <i>Channel Lighted Buoy 8</i>	33-36-05.24N 117-53-14.27W	FI R 4s		3	Red.	 14/13
						*	
2560	- Sound Signal						<i>Remove from list.</i> * 9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3175	- Buoy 4	33-46-21.11N 118-14-55.34W				Red nun. *	8/13
3186	- LIGHT B	33-42-46.50N 118-15-47.99W	FI W 4s	15	5	NW on steel post. *	13/13
3187	- LIGHT C	33-42-42.36N 118-16-06.58W *	FI W 2.5s	20	4	NW on post. *	13/13
3187.1	LOS ANGELES SHALLOW WATER HABITAT MARKER LIGHT *	33-42-34.21N 118-16-10.76W	Oc W 3s	25	4	NW on post.	Private aid. 14/13
*3187.5	- LIGHT D	33-42-39.66N 118-16-22.22W	FI W 4s	20	4	NW on post.	13/13
3188	- LIGHT E	33-42-45.86N 118-16-32.65W *	FI W 2.5s	20	4	NW on post. *	13/13
*3189	- LIGHT F	33-42-52.38N 118-16-42.89W	FI W 4s	20	4	NW on post.	13/13
3300	- Lighted Buoy 5						Remove from list. * 14/13
3740	RINCON ISLAND LIGHT						Remove from list. * 15/13
3775	- Lighted Buoy 7	34-24-30.00N 119-41-12.04W *	FI G 6s		4	Green.	Buoys maybe frequently relocated due to changing conditions. 17/13
4187	Scripps Waverider Lighted Research Buoy 142	37-47-30.00N 122-36-24.00W *	FI (5) Y 20s			Yellow sphere with whip antenna.	Private aid. 15/13
4307	FISHERMANS WHARF BREAKWATER LIGHT A	37-48-40.39N 122-25-21.48W	FI Y 2.5s	21	4	On post. *	Ra ref. 9/13
4308	FISHERMANS WHARF BREAKWATER LIGHT B	37-48-42.40N 122-25-16.38W	FI Y 2.5s	21	4	On post. *	Ra ref. 9/13
4630	- Lighted Buoy 3	37-48-29.39N 122-20-39.59W	FI G 4s		5	Green can. *	8/13
5575	- LIGHT 14						Remove from list. * 5/13
5740	POINT POTRERO REACH RANGE FRONT LIGHT	37-54-08.76N 122-21-36.76W *	Q R	23		KRW on pile. On same structure as Richmond Harbor Channel Light 14. *	Visible 1.5° each side of range line. 3/13
5741	POINT POTRERO REACH RANGE REAR LIGHT 311 yards, 098.5° from front light. *	37-54-07.39N 122-21-25.26W *	Iso R 6s	46		KRW on pile.	Visible 1.5° each side of range line. 3/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5830	- RANGE FRONT LIGHT	37-58-15.16N 122-29-48.02W *	Q R	15		KRW on pile.	Visible all around; higher intensity on range line. 19/13
5835	- RANGE REAR LIGHT 332 yards, 293.2° from front light. *	37-58-19.04N 122-30-00.00W *	Oc R 4s	40		KRW on pile.	Visible all around; higher intensity on range line. 19/13
6375	POINT EDITH CROSSING SOUTH RANGE FRONT LIGHT	38-02-56.11N 122-05-23.27W *	Q W	25		KRW on pile.	Visible all around; higher intensity on range line. Ra ref. 19/13
6380	POINT EDITH CROSSING SOUTH RANGE REAR LIGHT 436 yards, 236.2° from front light. *	38-02-48.91N 122-05-36.85W *	Iso W 6s	31		KRW on pile.	Visible all around; higher intensity on range line. Ra ref. 19/13
6509	- Buoy 7						<i>Remove from list.</i> * 16/13
6733	- LIGHT 17A	38-02-00.10N 121-43-34.02W	FI G 2.5s	15	3	SG on pile. *	11/13
6735	- LIGHT 18	38-01-37.77N 121-44-13.98W	FI R 4s	15	3	TR on pile. *	11/13
6745	- LIGHT 21	38-02-29.16N 121-42-00.69W	FI G 6s	20	4	SG on pile. *	11/13
6760	- LIGHT 25	38-03-37.72N 121-40-49.23W	FI G 2.5s	16	3	SG on pile. *	11/13
6785	- LIGHT 30	38-05-28.65N 121-40-38.04W	FI R 4s	15	3	TR on pile. *	11/13
6790	- LIGHT 32	38-05-40.30N 121-40-24.19W	FI R 2.5s	15	4	TR on pile. *	11/13
6797	- LIGHT 33A	38-05-36.85N 121-39-19.53W	FI G 4s	15	4	SG on pile. *	11/13
6880	- LIGHT 54	38-04-34.25N 121-34-06.20W	FI R 2.5s	15	3	TR on pile. *	11/13
6905	- RANGE B FRONT LIGHT	38-03-11.17N 121-30-32.63W *	Q W	21		KRW on white column. *	Visible all around; higher intensity on range line. 19/13
6910	- RANGE B REAR LIGHT 275 yards, 098.3° from front light. *	38-03-10.00N 121-30-22.42W *	Iso W 6s	35		KRW on white column.	Visible all around; higher intensity on range line. 19/13
7100	- RANGE H FRONT LIGHT	37-59-05.64N 121-23-19.58W *	Q G	26		KRW on pile. *	Visible all around; higher intensity on the range line. 19/13
7105	- RANGE H REAR LIGHT 670 yards, 115° from front light. *	37-58-57.23N 121-22-56.85W *	Iso G 6s	47		KRW on skeleton tower.	Visible all around; higher intensity on the range line. 19/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
7120	- RANGE J FRONT LIGHT	37-59-12.00N 121-23-31.83W *	Q W	20		KRW on pile.	Visible all around; higher intensity on the range line. 19/13
7125	- RANGE J REAR LIGHT 547 yards, 317.5° from front light. *	37-59-23.96N 121-23-45.68W *	Iso W 6s	63		KRW on skeleton tower.	Visible all around; higher intensity on the range line. 19/13
7170	- LIGHT 1	38-03-53.83N 121-51-03.90W	FI G 4s	15	4	SG on pile.	* 16/13
7200	- LIGHT 8	38-03-34.52N 121-48-30.69W	FI R 4s	15	4	TR on pile.	* 16/13
7225	- LIGHT 13	38-04-40.57N 121-46-02.26W	FI G 2.5s	15	4	SG on pile.	* 16/13
7230	- LIGHT 14	38-04-35.00N 121-45-57.47W	FI R 2.5s	15	4	TR on pile.	* 16/13
7260	- LIGHT 20	38-06-42.65N 121-42-32.58W	FI R 4s	15	4	TR on pile.	* 16/13
7280	- LIGHT 24	38-07-26.72N 121-41-49.69W	FI R 2.5s	15	4	TR on pile.	* 16/13
7290	- LIGHT 26	38-07-59.14N 121-41-36.39W	FI R 4s	15	4	TR on pile.	* 16/13
7295	- LIGHT 27	38-08-57.74N 121-41-26.10W	FI G 2.5s	15	4	SG on pile	* 16/13
7305	- LIGHT 28	38-08-56.56N 121-41-20.13W	FI R 2.5s	15	4	TR on post.	* 16/13
7360	- LIGHT 40	38-11-18.64N 121-39-30.82W	FI R 4s	25	4	TR on pile.	* 16/13
7420	- LIGHT 51	38-14-14.68N 121-40-26.10W	Q G	25	4	SG on pile.	* 16/13
7435	- LIGHT 54	38-15-21.52N 121-39-58.91W	FI R 4s	15	4	TR on pile.	* 16/13
7470	- LIGHT 60	38-20-00.00N 121-38-47.82W	FI R 4s	25	4	TR on pile.	* 16/13
7485	- LIGHT 62	38-20-29.42N 121-38-37.59W	FI R 4s	25	4	TR on pile.	* 16/13
7785	- CHANNEL RANGE A FRONT LIGHT 3	38-18-19.17N 123-03-24.60W *	Q G	18		KRW on pile, SG facing upstream.	Visible all around; higher intensity on the range line. 5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
7790	- CHANNEL RANGE AB REAR LIGHT 151 yards, 269.1° from Range A Front Light. 191 yards, 209.6° from Range B Front Light. *	38-18-19.10N 123-03-30.28W *	Iso G 6s	30		KRW on frame.	Visible all around; higher intensity on the range lines. 5/13
7800	- CHANNEL RANGE B FRONT LIGHT 5	38-18-24.02N 123-03-26.73W *	Q G	18		KRW on pile, SG facing downstream.	Visible all around; higher intensity on range line. 5/13
7845	- CHANNEL RANGE C FRONT LIGHT 14	38-18-47.45N 123-03-07.92W *	Q R	18		KRW on piles, TR facing downstream.	Visible all around; higher intensity on range line. 5/13
7850	- CHANNEL RANGE C REAR LIGHT 195 yards, 179.3° from front light. *	38-18-41.68N 123-03-07.83W *	Iso R 6s	32		KRW on pile.	Visible all around; higher intensity on range line. 5/13
7960	- CHANNEL RANGE D FRONT LIGHT 37	38-19-57.35N 123-03-09.00W *	Q G	14		KRW on pile; SG facing upstream.	Visible all around; higher intensity on range line. 7/13
7970	- CHANNEL RANGE D REAR LIGHT 268 yards, 359.2° from front light. *	38-20-05.30N 123-03-09.14W *	Iso G 6s	28		KRW on pile.	Visible all around; higher intensity on range line. 6/13
8105	- DIRECTIONAL LIGHT	39-25-38.27N 123-48-27.14W *	F W R G	17		On pile.	White light in center of channel (103.5°-106.5°). Red light when right of inbound channel (100°-103.5°). Green light when left of inbound channel (106.5°-110°). 19/13
8390	- RANGE FRONT LIGHT	41-45-00.00N 124-11-21.11W	FI G 2.5s	23	10	KRG on pile. *	Visible 4° each side of range line. 6/13
8395	- RANGE REAR LIGHT 79 yards, 359.9° from front light.	41-45-02.13N 124-11-21.12W	Oc G 4s	39	10	KRG on pile. *	Visible 4° each side of range line. 6/13
8740	- ENTRANCE RANGE FRONT LIGHT	43-20-58.55N 124-19-31.66W *	Q R	26		KRB on multi-pile structure. On same structure as Coos Bay Inside Range A Front Light. *	Visible 4° each side of range line. Lighted throughout 24 hours. 10/13
8745	- ENTRANCE RANGE REAR LIGHT 891 yards, 115.8° from front light. *	43-20-47.05N 124-18-59.09W *	Iso R 6s	47		KRB on skeleton tower.	Visible 4° each side of range line. Lighted throughout 24 hours. 10/13
8805	- INSIDE RANGE B FRONT LIGHT	43-22-08.17N 124-18-50.56W *	Q W	20		KRB on multi-pile structure. *	Visible 4° each side of range line. 3/13
8810	- INSIDE RANGE B REAR LIGHT 196 yards, 023.3° from front light. *	43-22-13.51N 124-18-47.41W *	Iso W 6s	40		KRB on skeleton tower on multi-pile structure. *	Visible 5.5° each side of range line. 3/13
8845	- RANGE B FRONT LIGHT	43-23-16.66N 124-17-07.14W	Q R	21		KRW on multi-pile structure. *	Visible 1.5° each side of range line. 18/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8850	- RANGE B REAR LIGHT 478 yards, 043.8° from front light.	43-23-26.89N 124-16-53.70W	Iso R 6s	39		KRW on skeleton tower on multi-pile structure. On same structure as Jarvis Lower Range A Rear Light.	Visible 1.5° each side of range line. * 18/13
8865	- B FRONT LIGHT	43-24-49.40N 124-16-20.61W *	Q R	20		KRB on multi-pile structure.	Visible 4° each side of range line. * 8/13
8870	- B REAR LIGHT 509 yards, 024.8° from front light. *	43-25-03.09N 124-16-11.92W	Iso R 6s	38		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line. * 8/13
8935	- Channel Lighted Buoy 18	43-24-46.46N 124-16-33.66W	Q R		4	Red.	 * 13/13
8951	- Channel Lighted Buoy 21	43-25-14.11N 124-16-20.23W *	Fl G 4s		3	Green.	 * 9/13
8960	JARVIS UPPER RANGE B FRONT LIGHT	43-25-41.94N 124-13-22.70W *	Q W	15		KRB on multi-pile structure.	Visible 5.5° each side of range line. * 8/13
8965	JARVIS UPPER RANGE B REAR LIGHT 409 yards, 079.4° from front light. *	43-25-44.16N 124-13-06.36W	Iso W 6s	33		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line. * 9/13
9010	NORTH BEND LOWER RANGE FRONT LIGHT	43-25-29.81N 124-13-01.41W	Q G	15		KRB on multi-pile structure.	Visible all around; higher intensity on range line. * 9/13
9015	NORTH BEND LOWER RANGE REAR LIGHT 159 yards, 112.2° from front light. *	43-25-28.03N 124-12-55.41W	Iso G 6s	30		KRB on skeleton tower on multi-pile structure. On same structure as North Bend Range Rear Light.	Visible all around; higher intensity on range line. * 9/13
9020	NORTH BEND RANGE FRONT LIGHT	43-25-23.15N 124-12-56.49W	Q G	18		KRB on multi-pile structure.	Visible all around; higher intensity on range line. * 9/13
9025	NORTH BEND RANGE REAR LIGHT 167 yards, 009.2° from front light. *	43-25-28.03N 124-12-55.41W	Iso G 6s	30		KRB on skeleton tower on multi-pile structure. On same structure as North Bend Lower Range Rear Light.	Visible all around; higher intensity on range line. * 9/13
9040	NORTH BEND UPPER RANGE FRONT LIGHT	43-23-32.93N 124-12-50.03W *	Q G	20		KRB on multi-pile structure.	Visible 4° each side of range line. * 8/13
9045	NORTH BEND UPPER RANGE REAR LIGHT 236 yards, 163.7° from front light. *	43-23-26.22N 124-12-47.34W	Iso G 6s	33		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line. * 8/13
9050	FERNDAL LOWER RANGE FRONT LIGHT	43-24-03.23N 124-12-51.50W *	Q W	19		KRB on multi-pile structure.	Visible 14° each side of range line. * 9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9055	FERNDALE LOWER RANGE REAR LIGHT 338 yards, 012.9° from front light.	43-24-13.01N 124-12-48.42W	Iso W 6s	33		KRB on multi-pile structure.	Visible 14° each side of range line.
	*	*				*	9/13
9145	- LIGHT 4 20 feet outside channel limit.	43-21-10.30N 124-19-07.51W	FI R 4s	15	3	TR on multi-pile structure.	*
						*	6/13
9230	- Entrance Lighted Buoy 2	43-39-58.37N 124-13-45.95W	FI R 4s		3	Red.	
	*	*	*		*	*	12/13
9265	- CHANNEL RANGE FRONT LIGHT	43-41-20.52N 124-11-08.13W	Q W	24		KRB on multi-pile structure.	Visible 10° each side of range line.
		*		*		*	7/13
9270	- CHANNEL RANGE REAR LIGHT 394 yards, 026.7° from front light.	43-41-30.95N 124-11-00.91W	Iso W 6s	39		KRB on skeleton tower.	Visible 10° each side of range line.
	*	*		*			7/13
9280	- LIGHT 8	43-40-57.21N 124-11-12.49W	FI R 2.5s	22	4	TR on pile structure.	
					*		13/13
9305	BARRETTS RANGE FRONT LIGHT	43-43-52.00N 124-09-58.80W	Q W	19		KRB on multi-pile structure.	Visible all around; higher intensity on range line.
		*		*		*	9/13
9310	BARRETTS RANGE REAR LIGHT 264 yards, 331.2° from front light.	43-43-58.87N 124-10-04.00W	Iso W 6s	40		KRB on skeleton tower.	Visible all around; higher intensity on range line.
	*	*		*			9/13
9346	LEEDS ISLAND RANGE FRONT LIGHT	43-43-20.45N 124-07-36.93W	Q W	21		KRB on skeleton tower.	Visible 4° each side of range line.
		*		*		*	3/13
9347	LEEDS ISLAND RANGE REAR LIGHT 400 yards, 172.6° from front light.	43-43-08.68N 124-07-34.82W	Iso W 6s	35		KRB on skeleton tower.	Visible 4° each side of range line.
	*	*		*		*	3/13
9395	SMITH RIVER LIGHT 2	43-42-22.60N 124-05-12.85W	FI R 4s	16	4	TR on skeleton tower.	
					*	*	7/13
9440	- ENTRANCE RANGE FRONT LIGHT	44-01-01.44N 124-07-49.57W	Q R	35		KRB on skeleton tower. On same structure as Siuslaw River Inner Range Rear Light.	Visible 4° each side of range line.
		*		*			2/13
9445	- ENTRANCE RANGE REAR LIGHT 296 yards, 094.3° from front light.	44-01-00.78N 124-07-37.44W	Iso R 6s	61		KRB on skeleton tower.	Visible 4° each side of range line.
	*	*		*			2/13
9470	- INNER RANGE FRONT LIGHT	44-00-58.68N 124-07-49.62W	Q W	21		KRB on skeleton tower.	Visible all around; higher intensity on range line.
		*		*			2/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9475	- INNER RANGE REAR LIGHT 92 yards, 001.4° from front light.	44-01-01.40N 124-07-49.53W	Iso W 6s	34		KRB on skeleton tower. On same structure as Siuslaw River Entrance Range Front Light.	Visible 14° each side of range line.
	*						2/13
9613	OLD YAQUINA BAY LIGHTHOUSE	44-37-26.98N 124-03-46.87W	F W	165		On white tower.	Private aid.
	*						14/13
9620	- INNER RANGE FRONT LIGHT	44-37-44.24N 124-02-58.95W	Q R	17		KRB on multi-pile structure.	Visible 4° each side of range line.
	*					*	12/13
9625	- INNER RANGE REAR LIGHT 136 yards, 040.8° from front light.	44-37-47.28N 124-02-55.27W	Iso R 6s	30		KRB on skeleton tower on multi-pile structure.	Visible 5.5° each side of range line.
	*	*		*		*	12/13
9635	SOUTHBEACH MARINA LIGHT 2	44-37-25.93N 124-03-14.73W	FI R 4s	14	3	TR on pile.	
	*						12/13
9795	- ENTRANCE RANGE FRONT LIGHT	44-48-33.48N 124-03-42.81W	Q R	34		KWR on skeleton tower.	Visible 4° each side of range line. Lighted throughout 24 hours.
	*			*			9/13
9800	- ENTRANCE RANGE REAR LIGHT 16 yards, 086.2° from front light.	44-48-33.51N 124-03-41.16W	Iso R 6s	46		KWR on skeleton tower.	Visible 4° each side of range line. Lighted throughout 24 hours.
	*	*		*			9/13
9935	<i>Clatsop Spit Lighted Whistle Buoy 8</i>	46-15-00.49N 124-04-43.71W	Q R		4	Red.	
					*		13/13
10305	<i>Jim Crow Lighted Buoy 22</i>	46-15-27.84N 123-32-34.08W	Q R		4	Red.	
					*		13/13
10325	- <i>Channel Lighted Buoy 28</i>	46-16-13.99N 123-29-56.90W	Q R		4	Red.	
					*		5/13
10415	BUGBY HOLE LIGHT 46	46-10-53.82N 123-25-56.62W	Q R	15	3	TR on multi-pile structure.	
		*			*	*	12/13
10543	- Buoy 5						<i>Remove from list.</i>
							*
							17/13
10545	- Buoy 6						<i>Remove from list.</i>
							*
							17/13
10550	- Buoy 7						<i>Remove from list.</i>
							*
							17/13
10551	- Buoy 7A						<i>Remove from list.</i>
							*
							17/13
10805	DIBBLEE DIKE LIGHT 22 190 feet outside channel limit.	46-07-04.14N 122-59-14.24W	FI R 6s	15	4	TR on multi-pile structure.	
						*	*
							14/13
11080	DUCK CLUB LIGHT 4A	45-49-45.17N 122-47-48.13W	FI R 6s	23	4	TR on pile.	
		*		*		*	13/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11095	DUCK CLUB LIGHT 8	45-48-57.07N 122-47-55.28W *	FI R 2.5s	23 *	3	TR on pile. *	13/13
11115	- CROSSING LIGHT 12	45-48-11.22N 122-47-40.32W	FI R 2.5s	37	4 *	TR on multi-pile structure. *	13/13
11135	KNAPP POINT LIGHT 19	45-44-43.72N 122-45-31.50W	FI G 4s	36	4	SG on multi-pile structure. *	* 13/13
11285	- EAST END RANGE REAR LIGHT 93 yards, 238.4° from front light. *	45-36-02.71N 122-38-34.59W *	Iso R 6s	81 *		KRB on pole. *	Visible all around; higher intensity on range line. 14/13
11455	- RANGE FRONT LIGHT	45-34-27.13N 122-26-10.33W *	Q R	36 *		KRB on multi-pile structure. *	Visible all around; higher intensity on range line. 13/13
11460	- RANGE REAR LIGHT 126 yards, 111.9° from front light. *	45-34-25.73N 122-26-05.41W *	Iso R 6s	43 *		KRB on skeleton tower. *	Visible 14° each side of range line. 13/13
11465	- RANGE FRONT LIGHT	45-33-52.21N 122-26-54.67W *	Q R	41 *		KRB on skeleton tower on multi-pile structure. *	Visible all around; higher intensity on range line. 13/13
11470	- RANGE REAR LIGHT 314 yards, 128.7° from front light. *	45-33-46.40N 122-26-44.34W *	Iso R 6s	56 *		KRB on skeleton tower on multi-pile structure. *	Visible 4° each side of range line. 13/13
11480	- UPPER RANGE FRONT LIGHT	45-34-09.85N 122-27-41.71W *	Q R	44 *		KRB on skeleton tower. *	Visible all around; higher intensity on range line. 13/13
11485	- UPPER RANGE REAR LIGHT 171 yards, 290.4° from front light. *	45-34-11.61N 122-27-48.46W *	Iso R 6s	65 *		KRB on skeleton tower. *	Visible all around; higher intensity on range line. 13/13
11490	- RANGE FRONT LIGHT	45-33-46.20N 122-26-51.89W *	Q W	42 *		KRB on multi-pile structure. *	Visible 1.5° each side of range line. 13/13
11495	- RANGE REAR LIGHT 551 yards, 256° from front light. *	45-33-42.26N 122-27-14.42W *	Iso W 6s	68 *		KRB on skeleton tower on multi-pile structure. *	Visible 1.5° each side of range line. 13/13
11510	- UPPER RANGE FRONT LIGHT	45-34-25.79N 122-24-04.02W *	Q G	42 *		KRB on skeleton tower. *	Visible 4° each side of range line. 14/13
11515	- UPPER RANGE REAR LIGHT 266 yards, 262.2° from front light. *	45-34-24.72N 122-24-15.15W *	Iso G 6s	55 *		KRB on skeleton tower. *	Visible 4° each side of range line. 14/13
11530	- LOWER RANGE FRONT LIGHT	45-34-02.40N 122-20-37.13W *	FI G 2.5s	44 *		KRB on multi-pile structure. *	Visible all around, higher intensity on range line. 14/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11535	- LOWER RANGE REAR LIGHT 438 yards, 108.1° from front light.	45-33-58.37N 122-20-19.85W	Iso G 6s	62		KRB on skeleton tower.	Visible 5.5° each side of range line.
	*	*		*			14/13
11615	CAPE HORN RANGE FRONT LIGHT	45-34-04.74N 122-11-36.21W	Q R	43		KRB on multi-pile structure.	Visible all around; higher intensity on range line. Ra ref.
		*		*		*	12/13
11620	- RANGE REAR LIGHT 780 yards, 062.2° from front light.	45-34-15.49N 122-11-07.12W	Iso R 6s	60		KRB on skeleton tower on multi-pile structure.	Visible 5.5° each side of range line.
	*					*	12/13
11630	- LOWER RANGE FRONT LIGHT	45-35-06.41N 122-07-37.67W	Q G	40		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line; higher intensity on range line.
		*		*		*	12/13
11635	- LOWER RANGE REAR LIGHT 684 yards, 077.9° from front light.	45-35-10.66N 122-07-09.45W	Iso G 6s	58		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line.
	*	*		*		*	12/13
11640	CAPE HORN DIKE LIGHT 71	45-34-44.54N 122-10-32.59W	FI G 2.5s	16	4	SG on multi-pile structure.	
		*			*	*	10/13
11665	- BAR RANGE FRONT LIGHT	45-34-50.66N 122-06-28.79W	Q R	53		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line.
		*		*		*	12/13
11670	- BAR RANGE REAR LIGHT 233 yards, 098.5° from front light.	45-34-49.63N 122-06-19.07W	Iso R 6s	72		KRB on skeleton tower.	Visible 4° each side of range line.
	*	*		*			12/13
11795	- LOWER RANGE FRONT LIGHT 8	45-39-32.65N 121-54-02.09W	Q W	43	5	KRB on skeleton tower, TR oriented down channel.	Visible all around; higher intensity on range line.
		*		*			12/13
11800	- LOWER RANGE REAR LIGHT 120 yards, 176.2° from front light.	45-39-29.10N 121-54-01.76W	Iso W 6s	69		KRB on skeleton tower.	Visible 14° each side of range line.
	*						12/13
11840	WIND MOUNTAIN LOWER RANGE FRONT LIGHT 17	45-42-05.86N 121-50-48.54W	Q G	30		KRB on skeleton tower on multi-pile structure, SG oriented up and downstream.	Visible all around; higher intensity on range line.
		*		*		*	14/13
11845	WIND MOUNTAIN LOWER RANGE REAR LIGHT 868 yards, 274.9° from front light.	45-42-08.05N 121-51-25.08W	Iso G 6s	62		KRB on skeleton tower.	Visible 14° each side of range line.
	*	*		*			14/13
11880	COOK POINT RANGE FRONT LIGHT	45-42-29.73N 121-39-41.26W	Q W	29		KRB on rock face.	Visible all around; higher intensity on range line.
		*		*			14/13
11885	COOK POINT RANGE REAR LIGHT 1,010 yards, 067.5° from front light.	45-42-41.16N 121-39-01.79W	Iso W 6s	58		KRB on skeleton tower.	Visible 4° each side of range line.
	*	*					14/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11895	LITTLE WHITE SALMON UPPER RANGE FRONT LIGHT 30	45-42-18.16N 121-36-45.66W	Q R	33		KRB on rock face, TR oriented up channel.	Visible all around; higher intensity on range line. 14/13
		*		*			
11900	LITTLE WHITE SALMON UPPER RANGE REAR LIGHT 470 yards, 087° from front light.	45-42-18.88N 121-36-25.84W	Iso R 6s	56		KRB on skeleton tower.	Visible 4° each side of range line. 14/13
	*	*		*			
11915	HOOD RIVER RANGE FRONT LIGHT	45-43-26.73N 121-29-51.43W	Q W	32		KRB on skeleton tower.	Visible all around; higher intensity on range line. 14/13
		*		*			
11920	HOOD RIVER RANGE REAR LIGHT 289 yards, 091.5° from front light.	45-43-26.50N 121-29-39.23W	Iso W 6s	52		KRB on skeleton tower.	Visible 5.5° each side of range line. 14/13
	*	*		*			
12220	Hells Gate Range A Front Daybeacon	45-39-19.18N 120-54-18.25W				KGB on skeleton tower.	 12/13
		*					
12225	Hells Gate Range A Rear Daybeacon 222 yards, 091.9° from front daybeacon.	45-39-18.96N 120-54-08.86W				KGB on skeleton tower.	 12/13
	*	*					
12595	MESSNER MIDDLE RANGE FRONT LIGHT	45-51-34.86N 119-39-33.96W	Q W	37		KRB on square wooden tower.	Visible all around; higher intensity on range line. 12/13
		*		*		*	
12600	MESSNER MIDDLE RANGE REAR LIGHT 134 yards, 076.2° from front light.	45-51-35.81N 119-39-28.46W	Iso W 6s	55		KRB on skeleton tower.	Visible 5.5° each side of range line. 12/13
	*	*		*			
12690	IRRIGON MIDDLE RANGE FRONT LIGHT 67	45-55-19.20N 119-26-32.58W	Q G	47		KRW on skeleton tower, SG oriented upstream.	Visible all around; higher intensity on range line. 18/13
		*		*			
12695	IRRIGON MIDDLE RANGE REAR LIGHT 317 yards, 064.4° from front light.	45-55-23.25N 119-26-20.45W	Iso G 6s	73		KRW on skeleton tower.	Visible 14° each side of range line. 18/13
	*	*		*			
12715	IRRIGON UPPER RANGE FRONT LIGHT	45-55-09.05N 119-27-29.89W	Q W	49		KRB on skeleton tower.	Visible 4° each side of range line. 18/13
		*		*			
12720	IRRIGON UPPER RANGE REAR LIGHT 663 yards, 268.6° from front light.	45-55-08.56N 119-27-58.03W	Iso W 6s	79		KRB on skeleton tower.	Visible 4° each side of range line. 18/13
	*	*		*			
12765	McNARY RANGE FRONT LIGHT	45-56-21.57N 119-18-36.97W	Q G	58		KRW on skeleton tower.	Visible 4° each side of range line. 18/13
		*		*			
12770	MCNARY RANGE REAR LIGHT 435 yards, 058.8° from front light.	45-56-28.23N 119-18-21.19W	Iso G 6s	63		KRW on skeleton tower.	Visible 4° each side of range line. 18/13
	*	*					

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
13840	- LIGHT 30	46-40-32.83N 117-31-28.08W	FI R 2.5s	18	4	TR on skeleton tower.	
					*	*	12/13
*14721	- Lighted Buoy 2	46-12-45.13N 123-45-21.32W	Q R		4	Red.	
							2/13
14770	- Daybeacon 12						Remove from list. *
							9/13
14895	POST OFFICE RANGE FRONT LIGHT	45-37-47.06N 122-47-37.91W	Q W	36		KRB on multi-pile structure.	Visible all around; higher intensity on range line.
		*		*		*	14/13
14900	POST OFFICE RANGE REAR LIGHT 239 yards, 350° from front light.	45-37-53.95N 122-47-40.23W	Iso W 6s	51		KRB on skeleton tower.	Visible 14° each side of range line.
	*	*		*			14/13
15045	Thesing Range Front Daybeacon	45-25-31.01N 122-39-19.01W				KRB on railroad bridge trestle.	On a higher elevation than rear daybeacon.
		*				*	* 19/13
15050	Thesing Range Rear Daybeacon 272 yards, 223.7° from front daybeacon.	45-25-25.19N 122-39-26.91W				KRB on multi-pile structure.	On a lower elevation than front daybeacon.
	*	*				*	* 19/13
15060	BINGHAM LANDING LIGHT 16	45-23-49.50N 122-38-17.40W	FI R 6s	17	5	TR on skeleton tower.	Obscured to northward of 220°.
				*	*	*	* 17/13
15135	New Era Bar Range Front Daybeacon	45-17-18.69N 122-39-34.14W				KRW on pipe.	
		*				*	19/13
15140	New Era Bar Range Rear Daybeacon 25 yards, 178.6° from front daybeacon.	45-17-17.95N 122-39-34.12W				KRW on pipe.	
	*	*				*	19/13
15497	- Buoy 4						Remove from list. *
							15/13
15500	- LIGHT 6	46-38-24.15N 123-58-20.19W	FI R 4s	21	5	TR on multi-pile structure.	
					*	*	* 7/13
15505	- Buoy 8						Remove from list. *
							15/13
15510	- Buoy 10						Remove from list. *
							15/13
15526	Palix River Buoy 16						Remove from list. *
							15/13
15530 720	- Light	46-53-17.58N 124-07-00.89W	Al W R 30s 0.1s W fl 14.9s ec. 0.1s R fl 14.9s ec.	123	18	White truncated octagonal pyramid tower.	Lighted throughout 24 hours.
		*					8/13
15630	- South Reach Lighted Buoy 15A	46-55-20.75N 124-05-26.46W	FI G 4s		3	Green.	
		*					5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
16221	<i>Race Rocks South Cautionary Lighted Buoy VF (C)</i>	48-14-14.40N 123-31-58.70W	FI Y 4s			Yellow.	RACON: B(- • • •).
							* 7/13
16265	Trial Islands Light (C)	48-23-42.30N 123-18-18.60W	FI G 5s	93	13	White circular tower.	
	*				*		* 7/13
*16890	PIER 15-1/2 BARGE SLIP LIGHT A	47-35-18.00N 122-21-04.00W	FI Y 4s			On multi-pile dolphin.	Private aid.
							16/13
*16895	PIER 15-1/2 BARGE SLIP LIGHT B	47-35-18.00N 122-21-06.90W	FI R 4s			On multi-pile dolphin.	Private aid.
							16/13
18115	- ENTRANCE RANGE FRONT LIGHT	47-40-00.00N 122-24-10.88W	Q R	19		KRW on multi-pile structure.	Visible 4° each side of range line.
	*			*		*	16/13
18120	- ENTRANCE RANGE REAR LIGHT 246 yards, 146.1° from front light.	47-39-53.54N 122-24-04.87W	Iso R 6s	86		KRW on skeleton tower.	Visible 4° each side of range line.
	*	*		*			16/13
18426	HUNGERFORD POINT LIGHT 2	47-12-18.58N 122-56-08.39W	FI R 4s	17	3	TR on multi-pile structure.	
	*						15/13
18590	- LIGHT 8	48-01-06.98N 122-12-48.23W	FI R 4s	15	3	TR on pile.	
					*		16/13
18625	- LIGHT 4	48-07-57.38N 122-30-39.01W	FI R 4s	15	5	TR on skeleton tower.	
	*					*	3/13
18630	ONAMAC POINT LIGHT 6	48-11-01.88N 122-32-12.97W	FI R 6s	15	5	TR on skeleton tower.	
	*					*	3/13
18645	PENN COVE MUSSEL RAFT EAST LIGHTS (4)	48-13-15.66N 122-42-13.49W	FI Y 6s			On aquaculture facility.	Private aids.
	*	*					15/13
*18646	PENN COVE MUSSEL RAFT WEST LIGHTS (4)	48-13-05.15N 122-42-45.45W	FI Y 6s			On aquaculture facility.	Private aids.
							15/13
18724	- NORTH ENTRANCE LIGHT 1	48-17-09.18N 122-38-13.40W	FI G 6s			On pile.	Private aid.
	*						16/13
18725	- NORTH ENTRANCE LIGHT 2	48-17-08.89N 122-38-11.77W	FI R 6s			On breakwater.	Private aid.
	*						16/13
18727	- North Entrance Dabeacon 3	48-17-12.35N 122-38-13.04W				SG on dolphin.	Private aid.
	*						16/13
18730	- BREAKWATER LIGHT						<i>Remove from list.</i>
							* 17/13
18735	- SOUTH ENTRANCE LIGHT 1	48-17-01.64N 122-38-09.32W	FI G 6s			On breakwater.	Private aid.
	*						16/13
18736	- SOUTH ENTRANCE LIGHT 2	48-17-02.38N 122-38-09.55W	FI R 6s			On pile.	Private aid.
	*					*	16/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
18870	- LIGHT 25	48-25-26.63N 122-30-07.62W *	FI G 4s	15	4	SG on pile.	3/13
*Add Heading: Anacortes Marina							
*19057.1	- ENTRANCE LIGHT A	48-30-08.80N 122-36-03.66W	FI W 2s			NW on piling.	Private aid. 17/13
*19057.2	- ENTRANCE LIGHT B	48-30-07.29N 122-36-04.19W	FI W 2s			NW on piling.	Private aid. 17/13
*19057.3	- ENTRANCE LIGHT 2	48-30-08.80N 122-36-05.77W	FI R 2.5s			TR on breakwall.	Private aid. 17/13
*19057.4	- ENTRANCE LIGHT 1	48-30-07.90N 122-36-05.80W	FI G 2.5s			SG on breakwall.	Private aid. 17/13
*19057.5	- INNER LIGHT S	48-30-08.10N 122-36-06.87W	FI Y 2.5s			NY on breakwall.	Private aid. 17/13
*19058.1	- EXIT LIGHT A	48-30-16.37N 122-35-58.11W	FI W 4s			NW on piling.	Private aid. 17/13
*19058.2	- EXIT LIGHT B	48-30-15.39N 122-35-57.96W	FI W 4s			NW on piling.	Private aid. 17/13
*19058.3	- EXIT LIGHT 1	48-30-15.80N 122-36-05.77W	FI G 2.5s			SG on breakwall.	Private aid. 17/13
*19058.4	- INNER LIGHT N	48-30-16.40N 122-36-05.80W	FI Y 2.5s			NY on breakwall.	Private aid. 17/13
*19058.5	- EXIT LIGHT 2	48-30-15.37N 122-36-06.69W	FI R 2.5s			TR on breakwall.	Private aid. 17/13
19340	<i>Kellett Ledge Lighted Buoy 3</i>	48-27-01.56N 122-47-30.94W *	FI G 2.5s		4	Green.	16/13
19595	Minnesota Reef Daybeacon 1	48-32-12.33N 122-59-17.80W *				SG on pile.	Ra ref. 3/13
19655	POLE PASS LIGHT 2	48-36-06.02N 122-59-24.68W *	FI R 4s	15	4	TR on skeleton tower.	3/13
19660	WASP PASSAGE LIGHT 5	48-35-42.39N 122-58-36.61W *	FI G 4s	15	5	SG on pyramidal structure.	3/13
19969	INTERNATIONAL BOUNDARY LIGHT A	49-00-07.48N 123-06-44.19W	FI Y 4s	25	3	NY on concrete structure. *	3/13
19970	INTERNATIONAL BOUNDARY LIGHT B	49-00-07.57N 123-05-34.58W *	FI Y 4s	15	3	NY on multi-pile structure. *	3/13
19972	INTERNATIONAL BOUNDARY LIGHT D	49-00-07.56N 123-01-12.99W	FI Y 4s	36	3	NY on concrete structure. *	3/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
19973	INTERNATIONAL BOUNDARY LIGHT E	49-00-07.72N 122-58-21.36W	FI Y 4s	15	3	NY on multi-pile structure. *	3/13
19974	INTERNATIONAL BOUNDARY LIGHT F	49-00-07.67N 122-55-29.41W *	FI Y 4s	15	3	NY on multi-pile structure. *	3/13
19975	INTERNATIONAL BOUNDARY LIGHT G	49-00-07.81N 122-52-38.10W *	FI Y 4s	15	3	NY on multi-pile structure. *	3/13
19976	INTERNATIONAL BOUNDARY LIGHT H	49-00-07.75N 122-49-46.47W	FI Y 4s	15	3	NY on multi-pile structure. *	3/13
19977	INTERNATIONAL BOUNDARY LIGHT I	49-00-07.62N 122-46-54.82W	FI Y 4s	42	3	NY on concrete structure. *	3/13
22327	- RANGE FRONT LIGHT	55-32-10.11N 131-49-57.06W *	FI W 2.5s	29	7	KRW and NR on skeleton tower. *	7/13
22328	- Range Rear Daybeacon 1,534 yards, 210.5 from front light *	55-31-31.04N 131-50-37.71W *				KRW on skeleton tower. *	7/13
23475	- RANGE FRONT LIGHT	56-14-40.65N 134-39-08.00W *	Q G	21		KRW on skeleton tower on concrete pier. *	Visible all around. 10/13
23480	- RANGE REAR LIGHT 74 yards, 333.9° from front light. *	56-14-42.61N 134-39-09.72W *	Iso G 6s	37		KRW on skeleton tower on concrete pier. *	Visible all around. 10/13
23625	HOLKHAM BAY RANGE FRONT LIGHT	57-46-03.29N 133-38-40.13W *	Q W	73		KRW on skeleton tower. *	Light maintained from May 1 to Oct. 1. 15/13
23630	HOLKHAM BAY RANGE REAR LIGHT 42 yards, 211.7° from front light. *	57-46-02.24N 133-38-41.34W *	F W	101		KRW on skeleton tower. *	Light maintained from May 1 to Oct. 1. 15/13
24112	- RANGE FRONT LIGHT	58-05-07.00N 134-46-27.18W *	Q W	23		KRW on single pile. *	Obscured from 202° to 066°. 12/13
24113	- RANGE REAR LIGHT 400 yards, 178.3° from front light. *	58-04-55.18N 134-46-26.53W *	Iso W 6s	29		KRW on single pile. *	Obscured from 194° to 125°. 12/13
24490	- Entrance Range Front Daybeacon	55-28-29.95N 133-08-31.63W *				KRW on skeleton tower. *	9/13
24495	- Entrance Range Rear Daybeacon 35 yards, 054.2° from front daybeacon. *	55-28-30.55N 133-08-30.16W *				KRW on skeleton tower. *	9/13
24555	Hermanos Island Range Front Daybeacon	55-34-14.84N 133-17-55.19W *				KRW on spindle. *	7/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
24560	Hermanos Island Range Rear Daybeacon 229 yards, 105.1° from front daybeacon. *	55-34-13.07N 133-17-43.66W *				KRW on spindle.	7/13
24710	Chapin Island Range Front Daybeacon *	55-47-45.87N 133-18-41.48W *				KRW on skeleton tower.	7/13
24715	Chapin Island Range Rear Daybeacon 74 yards, 305.4° from front daybeacon. *	55-47-47.14N 133-18-44.66W *				KRW on skeleton tower.	7/13
25100	WHITESTONE POINT LIGHT 14 *	57-14-39.55N 135-33-43.57W *	FI R 2.5s	11	4	TR on steel structure.	Obscured from 170° to 347°. 19/13
25120	- CHANNEL RANGE FRONT LIGHT *	57-15-11.30N 135-34-04.90W *	Q W	27		KRW on pile.	Visible all around. 10/13
25125	- CHANNEL RANGE REAR LIGHT 126 yards, 345° from front light. *	57-15-14.89N 135-34-06.70W *	F W	40		KRW on skeleton tower.	Obscured from 028° to 208°. 10/13
25185	SULOIA POINT LIGHT 5 *	57-23-21.97N 135-39-00.00W *	FI G 2.5s	22	4	SG on steel skeleton tower.	Obscured from 021° to 190°. 19/13
25263	HOGGATT REEF LIGHT 25 *	57-32-47.94N 135-30-48.36W *	FI G 6s	25	4	SG on pile.	19/13
25405	- ENTRANCE RANGE FRONT LIGHT *	58-37-35.63N 137-39-28.61W *	Q W	28		KRW on skeleton tower.	Obscured from 048° to 348°; higher intensity on range line. 9/13
25410	- ENTRANCE RANGE REAR LIGHT 238 yards, 007.8° from front light. *	58-37-42.59N 137-39-26.79W *	Iso W 6s	42		KRW on skeleton tower.	Obscured from 170° to 222°; higher intensity on range line. 9/13
26410	FIRE ISLAND RANGE FRONT LIGHT *	61-10-20.63N 150-12-00.00W *	Q W	83		KRB on multi-pile structure.	Visible 4° each side of range line. 7/13
26415	FIRE ISLAND RANGE REAR LIGHT 510 yards, 242° from front light. *	61-10-13.56N 150-12-27.07W *	Iso W 6s	124		KRB on multi-pile structure.	Visible 4° each side of range line. 7/13
26435	POINT WORONZOF RANGE FRONT LIGHT *	61-12-06.33N 150-01-22.89W *	Oc G 4s	52		KRW on single pile.	Visible 4° each side of range line. Lighted throughout 24 hours. 7/13
26440	POINT WORONZOF RANGE REAR LIGHT 278 yards, 079° from front light. *	61-12-07.90N 150-01-06.20W *	F G	140		KRW on multi-pile structure.	Visible 4° each side of range line. Lighted throughout 24 hours. 7/13
26765	- FRONT RANGE LIGHT *	57-43-24.00N 152-28-50.47W *	Q W	57		KRB on skeleton tower.	6/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
26770	- REAR RANGE LIGHT 661 yards, 211.1° from front light.	57-43-07.27N 152-29-09.34W	Oc W 4s	94		KRB on skeleton tower.	
	*	*	*	*	*		6/13
26980	- RANGE FRONT LIGHT	57-32-44.18N 154-00-12.94W	Q W	56		KRW on skeleton tower.	
		*		*			10/13
26985	- RANGE REAR LIGHT 129 yards, 291.3° from light.	57-32-45.57N 154-00-19.57W	Iso W 6s	76		KRW on skeleton tower.	Obscured from 300° to 287°.
	*	*		*			10/13
*27427	AKUTAN SMALL BOAT HARBOR LIGHT 1	54-07-48.32N 165-49-21.24W	FI G 4s		4	SG on spindle.	
							18/13
*27428	AKUTAN SMALL BOAT HARBOR LIGHT 2	54-07-50.36N 165-49-19.40W	FI R 2.5s		4	TR on spindle.	
							18/13
27542	- RANGE FRONT LIGHT	51-51-09.11N 176-39-14.98W	Q G	36		KRW on pile structure.	
		*		*			9/13
27543	- RANGE REAR LIGHT 494 yards, 253° from front light.	51-51-04.80N 176-39-37.73W	Oc G 4s	101		KRW on pile.	
		*		*			9/13
27826	ST. GEORGE HARBOR RANGE REAR LIGHT 361 yards, 076.4° from front light.	56-34-12.20N 169-39-52.34W	Iso Y 6s	76		KRW on tower.	
	*						9/13
27972	NOME HARBOR RANGE FRONT LIGHT	64-30-14.14N 165-25-22.77W	Iso Y 6s	33		KRW on skeleton tower.	Visible 4° each side of range line.
		*					7/13
27973	NOME HARBOR RANGE REAR LIGHT 167 yards 029.9° from front light	64-30-18.41N 165-25-17.06W	Q Y	66		KRW on skeleton tower.	Visible 4° each side of range line.
	*	*		*			7/13
*28007.43	CDIP Lighted Buoy 187	21-01-04.80N 156-25-30.00W	FI (5) W 20s			Yellow waverider buoy with light antenna 6 feet above waterline.	Private aid.
							11/13
*28053	CDIP Lighted Buoy 188	19-46-48.00N 154-58-12.00W	FI (5) W 20s			Yellow waverider buoy with light antenna 6 feet above waterline.	Private aid.
							11/13
28165	- ENTRANCE DIRECTIONAL LIGHT	19-33-42.89N 155-57-43.43W	Q W (R & G sectors)	23	G 5 R 5 W 7	On same structure as Keauhou Bay Range Rear Daybeacon.	White 1° each side of channel centerline (bearing 069°). Red when right of white beam (068° -064°). Green when left of white beam (070° -074°) when entering from seaward.
		*		*		*	5/13
28170	- Range Front Daybeacon	19-33-42.67N 155-57-44.05W				KRW on post. 12	
		*					6/13
28175	- Range Rear Daybeacon 21 yards, 069.7° from front daybeacon.	19-33-42.89N 155-57-43.43W				KRW on post. On same structure as Keauhou Bay Entrance Light.	
	*	*				*	5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
28271.2	- BREAKWATER LIGHT 5						<i>Remove from list.</i> * 12/13
28271.4	- Breakwater Daybeacon 8						<i>Remove from list.</i> * 11/13
28675.3	<i>CRIMP-3 Lighted Buoy</i>	21-28-49.00N 157-46-56.00W	FI Y 4s				Private aid. * 11/13
*28675.3	<i>CRIMP-3</i>	21-28-49.00N 156-46-56.00W					Private aid. 8/13
28715	ENTRANCE RANGE REAR LIGHT 559 yards, 227.1° from front light.	21-29-33.25N 157-50-11.36W	Iso R 6s	37		KRW on multi-pile structure.	Visible 4° each side of range line. * 3/13
28720	KUALOA POINT RANGE REAR LIGHT 235 yards, 348.9° from front light.	21-29-51.34N 157-50-00.00W	Iso R 6s	55	12	KRW on multi-pile structure.	Visible 4° each side of range line. * 3/13
29070	- Daybeacon 1	21-16-37.80N 157-50-23.60W				SG on pile.	Private aid. * 11/13
29075	- Daybeacon 2	21-16-39.30N 157-50-22.00W				TR on pile.	Private aid. * 11/13
29080	- Daybeacon 3	21-16-42.20N 157-50-25.60W				SG on pile.	Private aid. * 11/13
29085	- Daybeacon 4	21-16-41.60N 157-50-22.80W				SG on pile.	Private aid. * 11/13
30370	- <i>Lighted Buoy 13</i>	09-18-41.11N 167-28-32.29E	FI G 4s		5	Green.	 * 8/13
30375	- <i>Approach Lighted Buoy 2</i>	08-59-56.99N 167-42-43.34E	FI R 4s		3	Red.	 * 8/13
30420	- Buoy 4	08-49-19.59N 167-36-20.59E				Red can.	 * 7/13
30445	Kwajalein Bigej Channel Buoy 5A	08-47-41.98N 167-42-07.23E				Green nun.	 * 8/13
30495	- <i>Channel Lighted Buoy 8</i>	08-44-11.48N 167-43-32.95E	FI R 4s		4	Red.	 * 8/13
30700	- ENTRANCE RANGE FRONT LIGHT	13-27-23.28N 144-40-00.00E	Q G	39		KRW on post.	Visible 4° each side of range line. * 5/13
30705	- ENTRANCE RANGE REAR LIGHT 661 yards, 083.7° from front light.	13-27-25.45N 144-40-19.76E	Iso G 6s	81		KRW on skeleton tower.	Visible 4° each side of range line. * 10/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
SAIPAN (Chart 81076)							
*30852.11	FAD Site AA - Saipan	15-21-35.00N 145-50-05.00W	FI W 4s				Private aid. 16/13
*30852.12	FAD Site BB - Saipan	15-05-24.00N 145-45-48.00W	FI W 4s				Private aid. 16/13
*30852.13	FAD Site CC - Saipan	14-59-30.00N 145-43-48.00W	FI W 4s				Private aid. 16/13
*30852.16	FAD Site FF - Saipan	14-59-54.00N 145-27-42.00W	FI W 4s				Private aid. 16/13
*30852.17	FAD Site GG - Saipan	15-04-36.00N 145-32-56.00W	FI W 4s				Private aid. 16/13
*30852.18	FAD Site HH - Saipan	15-09-51.00N 145-28-15.00W	FI W 4s				Private aid. 16/13
*30852.19	FAD Site II - Saipan	15-14-54.00N 145-29-47.00W	FI W 4s				Private aid. 16/13
*30852.2	FAD Site JJ - Saipan	15-19-19.00N 145-32-20.00W	FI W 4s				Private aid. 16/13
*30852.21	FAD Site KK - Saipan	15-17-11.00N 145-41-20.00W	FI W 4s				Private aid. 16/13
*30852.22	FAD Site LL - Saipan	15-20-45.00N 145-46-00.00W	FI W 4s				Private aid. 16/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES AND THE ST. LAWRENCE RIVER ABOVE THE ST. REGIS RIVER, 2012

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11355	Thunder Bay Traffic Lighted Bell Buoy TB	44-58-41.05N 83-15-17.28W	Mo (A) W		4	Red and white stripes.	Maintained from Apr. 28 to Dec. 1. 19/13
	*						

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.