

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
290	STRAITSMOUTH LIGHT	42-39-44.14N 70-35-17.05W	Fl G 6s	46	6	White cylindrical tower.	HORN: 1 blast ev 15s (2s bl). During periods of reduced visibility, activated for 45 minutes by keying the microphone five times on VHF channel 81A. * 22/13
10005	HOSPITAL POINT RANGE REAR LIGHT 2,032 yards, 276.3° from front light. *	42-32-53.94N 70-52-42.43W	F W	161		White church spire.	Visible 2° each side of range line. * 22/13
15160	- RANGE FRONT LIGHT *	41-17-23.59N 70-05-32.36W	Q W	35		KRW on white wooden skeleton tower.	Higher intensity beam to seaward. Lighted throughout 24 hours. 22/13
15165	- RANGE REAR LIGHT 81 yards, 161.9° from front light. *	41-17-21.32N 70-05-31.38W	F W	51		KRW on white wooden skeleton tower.	Higher intensity beam to seaward. Lighted throughout 24 hours. 22/13
15205.1	Brant Point Station Mooring Buoy West						Remove from list. * 22/13
21825	New London Ledge Light On west side of Southwest Ledge.	41-18-21.14N 72-04-38.78W	Fl (3+1) WR 30s 0.1s W fl 4.9s ec. 0.1s W fl 4.9s ec. 0.1s W fl 9.9s ec. 0.1s R fl 9.9s ec. *	58	W 17 R 14	Red brick dwelling on square pier. 58	Emergency light of Fl (3) W 30s and reduced intensity when main light is extinguished. HORN: 2 blast ev 20s (2s bl-2s si-2s bl-14s si). 22/13
23480	- Channel Buoy 8 *	41-15-46.93N 72-31-33.88W				Red nun.	22/13
26430	- Lighted Buoy 2A Marks shoal. *	40-56-50.47N 73-24-06.53W	Q R		3	Red.	Position frequently changed due to shoaling. Replaced by nun when endangered by ice. 22/13
*Delete Heading and Note: Old Inlet Channel							
<i>Aids maintained from May 20 to Sep. 15.</i>							
30060	- Lighted Buoy 1						Remove from list. * 22/13
30065	- Lighted Buoy 2						Remove from list. * 22/13
30070	- Lighted Buoy 4						Remove from list. * 22/13
30075	- Lighted Buoy 6						Remove from list. * 22/13
30080	- Lighted Buoy 8						Remove from list. * 22/13
30085	- Lighted Buoy 10						Remove from list. * 22/13
37705	- Buoy 1						Remove from list. * 22/13
37710	- Buoy 2						Remove from list. * 22/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
37715	- Buoy 1	41-04-25.55N 73-52-26.29W				Green can.	
	*						22/13
37720	- Buoy 2	41-04-23.68N 73-52-24.20W				Red nun.	
	*						22/13
37725	- Buoy 3	41-04-32.90N 73-52-15.61W				Green can.	
	*						22/13
37730	- Buoy 4	41-04-29.34N 73-52-14.87W				Red nun.	
	*						22/13
37926	<i>Cortlandt Yacht Club Channel Lighted Buoy 1</i>	41-14-44.00N 73-57-24.00W	FI G 2s			Green.	Seasonal. Private aid.
		*	*				22/13
37926.1	<i>Cortlandt Yacht Club Channel Lighted Buoy 2</i>	41-14-42.00N 73-57-23.00W	FI R 2s			Red.	Seasonal. Private aid.
		*	*				22/13
37926.2	<i>Cortlandt Yacht Club Channel Lighted Buoy 3</i>	41-14-45.00N 73-57-16.00W	FI G 4s			Green.	Seasonal. Private aid.
		*					22/13
39500	Allen Point Buoy 1 At south end of 1-foot shoal.	44-35-30.57N 73-18-20.77W				Green can.	Maintained from May 1 to Nov. 1.
							* 22/13
39505	Mallets Bay Rock Buoy Marks south side of submerged rock.	44-34-26.87N 73-12-23.61W				White with orange bands.	Maintained from May 1 to Nov. 1.
							* 22/13
39510	Coates Island Warning Buoy	44-33-34.17N 73-13-40.46W				White can with orange bands.	Maintained from May 1 to Nov. 1.
							* 22/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*2170	Middle Island West Buoy 1	38-36-49.63N 75-06-01.23W				Green can.	
							22/13
*2175	Middle Island West Daybeacon 3	38-36-57.04N 75-05-59.00W				SG on pile.	
							22/13
*2177	Middle Island West Buoy 5	38-37-06.81N 75-05-50.95W				Green can.	
							22/13
*28082	- Channel Buoy 25AA	35-46-31.24N 75-33-34.09W				Green can.	
							22/13
28083	- Channel Buoy 26	35-46-43.12N 75-33-05.98W				Red nun.	
		*					22/13
28485	- CHANNEL LIGHT 22	35-53-04.43N 75-37-33.07W	FI R 2.5s	15	3	TR on multi-pile structure.	Light equipment removed when endangered by ice.
		*					22/13
28699.1	- <i>Lighted Buoy 1SF</i>	35-11-28.41N 75-45-46.42W	FI G 2.5s		4	Green.	
		*					22/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
28700	- Buoy 2SF	35-11-33.02N 75-46-05.47W *				Red nun.	22/13
28701	- <i>Lighted Buoy 3SF</i>	35-11-30.78N 75-46-04.28W *	Fl G 2.5s		4	Green.	22/13
31025	- Buoy 4	33-54-36.78N 78-14-22.92W *				Red nun.	22/13
31035	- Buoy 7	33-54-54.56N 78-14-19.46W *				Green can.	22/13
40190	- Daybeacon 16						<i>Remove from list.</i> *
40235	- Buoy 48	33-55-16.76N 78-14-15.23W *				Red nun with yellow triangle.	22/13

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
120	Georgetown Light	33-13-21.47N 79-11-06.18W	Fl (2) W 15s *	85	15	White cylindrical tower. *	* 19/13
140	East Bank Buoy 2EB On northeasterly side of bank.	33-08-49.56N 79-08-07.28W *				Red nun.	5/13
155	Cape Romain Shoal Buoy 6CR 500 yards outside of shoal.	32-57-39.26N 79-17-08.63W *				Red nun.	6/13
833	<i>NOAA Data Lighted Buoy 41008</i>	31-24-00.00N 80-52-05.26W *	Fl (4) Y 20s			Yellow disc-shaped with mast.	Aid maintained by NOAA. 7/13
840	<i>NOAA Data Lighted Buoy 41009</i>	28-31-18.00N 80-11-18.00W *	Fl (4) Y 20s			Yellow boat shaped buoy.	Aid maintained by NOAA. 5/13
930	TRIUMPH REEF LIGHT 2TR						<i>Remove from list.</i> * 21/13
940	<i>Turtle Harbor Lighted Whistle Buoy 4</i> Marks entrance between shoal patches.						<i>Remove from list.</i> * 21/13
1890	- <i>Channel Lighted Buoy 5</i>	33-11-30.88N 79-08-02.11W	Fl G 2.5s		5	Green.	15/13
1890.5	- <i>Channel Lighted Buoy 5A</i>	33-11-30.42N 79-08-34.15W	Fl G 4s		5	Green.	15/13
1920	- <i>Channel Lighted Buoy 9</i>	33-11-43.59N 79-10-07.75W	Fl G 2.5s		5	Green.	15/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1955	- Channel Lighted Buoy 14	33-12-32.96N 79-11-02.14W	Q R		4	Red.	
					*		15/13
1995	- CHANNEL LIGHT 19	33-15-11.87N 79-12-56.35W	Q G	16	4	SG on dolphin.	
					*		18/13
2060	- Channel Lighted Buoy 22	33-16-01.92N 79-13-56.59W	FI R 2.5s		5	Red.	
					*		11/13
2170	- CHANNEL LIGHT 44	33-21-51.62N 79-17-10.72W	FI R 4s	16	5	TR on pile.	
					*		18/13
2375	- Channel Lighted Buoy 8	32-40-02.90N 79-41-29.41W	FI R 2.5s		5	Red.	
					*		5/13
2400.5	- Channel Lighted Buoy 14	32-42-08.41N 79-45-49.82W	FI R 2.5s		5	Red.	
					*		6/13
2405	- Channel Lighted Buoy 15	32-42-46.54N 79-47-36.50W	FI G 4s		5	Green.	
					*		6/13
2465	- Channel Lighted Buoy 23	32-44-33.68N 79-51-05.43W	FI G 2.5s		5	Green.	
					*		9/13
2585	HOG ISLAND REACH RANGE REAR LIGHT 141 yards, 172.4° from front light.	32-46-47.89N 79-54-57.33W	Iso W 6s	41			Visible 4° each side of range line. Lighted throughout 24 hours.
	*	*		*			4/13
2600	- Lighted Buoy 38	32-47-47.29N 79-54-58.12W	FI R 4s		5	Red.	
					*		19/13
2770	- LIGHT 2	32-49-50.00N 79-56-07.10W	FI R 4s	12	5	TR on pile.	
					*		4/13
2775	- LIGHT 4	32-49-51.13N 79-56-22.18W	FI R 4s	16	5	TR on pile.	
					*		16/13
2780	- Daybeacon 6						<i>Remove from list.</i>
							*
2785	- Daybeacon 8						<i>Remove from list.</i>
							*
2860	- Lighted Buoy 52A	32-51-49.89N 79-57-30.57W	FI R 6s		5	Red.	
					*		14/13
2897	- Lighted Buoy 55	32-52-28.16N 79-57-58.89W	FI G 4s		5	Green.	
					*		6/13
2935	- RANGE A FRONT LIGHT	32-54-36.43N 79-55-38.55W	Q W	29		On skeleton tower on piles.	Visible 4° each side of range line. Lighted throughout 24 hours.
		*		*			12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2940	- RANGE A REAR LIGHT 319 yards, 081.2° from front light. *	32-54-37.88N 79-55-27.46W *	Iso W 6s	39		On white skeleton tower on piles	Visible 4° each side of range line. Lighted throughout 24 hours. 12/13
2945	- Lighted Buoy 64	32-54-27.78N 79-56-22.87W	FI R 2.5s		5	Red. *	6/13
2965	- RANGE B FRONT LIGHT	32-54-24.37N 79-56-08.85W *	Q G	15		KRW on pile.	Visible 2° each side of range line. 12/13
2970	- RANGE B REAR LIGHT 318 yards, 214.3° from front light. *	32-54-16.57N 79-56-15.15W *	Iso G 6s	23		KRW on dolphin.	Visible 2° each side of range line. 12/13
2995	- RANGE C FRONT LIGHT	32-56-01.19N 79-56-22.21W *	Q G	27			Visible 1.5° each side of range line. Lighted throughout 24 hours. 12/13
3000	- RANGE C REAR LIGHT 200 yards, 328.8° from front light. *	32-56-06.27N 79-56-25.86W *	Iso G 6s	34			Visible 1.5° each side of range line. Lighted throughout 24 hours. 12/13
3005	- LIGHT 70	32-55-13.18N 79-55-42.74W	FI R 4s	12	5	TR on dolphin. *	7/13
3040	- RANGE D AND F FRONT LIGHT	32-56-23.33N 79-55-28.65W *	Q W	12		KRW on dolphin.	Visible all around. 12/13
3055	- RANGE E FRONT LIGHT	32-56-07.05N 79-55-50.10W *	Q W	16		KRW on pile.	Visible all around. 14/13
3060	- RANGE E REAR LIGHT 183 yards, 208.4° from front light. *	32-56-02.92N 79-55-52.81W *	Iso W 6s	24		KRW on tower on piles.	Visible all around. 12/13
3555	- LIGHT 16	32-47-07.83N 79-53-11.21W	FI R 4s	12	5	TR on pile. *	16/13
4029	Harbor River Buoy 10	32-22-41.05N 80-29-22.71W *				Red nun.	13/13
4250 35575	- Lighted Buoy 27	32-16-56.72N 80-39-18.19W	FI G 4s		5	Green with yellow triangle. *	13/13
4595	- Lighted Buoy 9	32-00-25.14N 80-47-50.29W *	FI G 2.5s		3	Green.	13/13
4640	- Lighted Bell Buoy 17	32-02-12.01N 80-50-30.93W	FI G 4s		5	Green. *	4/13
*4683	- Lighted Buoy 2	32-03-53.72N 80-49-42.46W	Q R		4	Red.	15/13
4825	- Lighted Buoy 35	32-04-17.00N 80-57-44.68W	FI G 4s		5	Green. *	13/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5090	- LIGHT 22	32-08-41.88N 81-08-25.01W	FI R 6s	16	5	TR on pile.	
					*		9/13
5120	- LIGHT 26	32-09-10.14N 81-08-58.65W	FI R 4s	16	5	TR on pile.	
					*		9/13
5710	- LIGHT 25	31-59-12.71N 81-00-16.40W	FI G 2.5s	16	5	SG on pile.	
		*					16/13
6120	ST. SIMONS NORTH TOWER LIGHT	31-08-55.17N 81-25-06.33W	Iso R 6s	146		On tower.	Visible 2° each side of 303° bearing.
		*		*			9/13
6125	ST. SIMONS SOUTH TOWER LIGHT	31-08-50.60N 81-25-04.52W	Iso R 6s	147		On tower.	Visible 2° each side of 303° bearing.
		*		*			9/13
6130	PLANTATION CREEK RANGE FRONT LIGHT	31-08-13.92N 81-26-00.00W	Q R	16		KRW on dolphin.	Visible 2° each side of range line.
		*		*			20/13
6135	PLANTATION CREEK RANGE REAR LIGHT 1,381 yards, 285° from front light.	31-08-24.52N 81-26-45.74W	Iso R 6s	44		KRW on skeleton tower on piles.	Visible 2° each side of range line.
	*	*		*			20/13
6180 37245	JEKYLL ISLAND RANGE FRONT LIGHT 1	31-06-06.25N 81-26-06.30W	Q G	17		SG-SY and KRW on dolphin.	Visible 1.5° each side of range line. Passing light visible all around.
		*		*			20/13
6183	JEKYLL ISLAND RANGE REAR LIGHT 1127 yards, 217° from front light.	32-05-39.54N 81-26-29.73W	Iso G 6s	47		KRW on skeleton tower on piles.	Visible 1.5° each side of range line.
	*	*					20/13
6185.7 37259	- Lighted Buoy 21	31-06-30.07N 81-25-41.00W	Q G		4	Green.	
					*		9/13
6195	CEDAR HAMMOCK RANGE REAR LIGHT	31-06-00.88N 81-28-05.07W	Q G	16		KRW on dolphin.	Visible 2° each side of range line.
		*		*			20/13
6200	CEDAR HAMMOCK RANGE REAR LIGHT 1,411 yards, 255.3° from front light.	31-05-50.22N 81-28-52.14W	Iso G 6s	45		KRW on skeleton tower on piles.	Visible 2° each side of range line.
	*	*		*			20/13
6205	CEDAR HAMMOCK OUTBOUND FRONT RANGE LIGHT	31-06-37.62N 81-25-23.11W	Q W	18		KRW on dolphin.	
		*		*			17/13
6210	CEDAR HAMMOCK OUTBOUND RANGE REAR LIGHT 191 yards, 075.2° from front light.	31-06-39.07N 81-25-16.73W	Iso W 6s	27		KRW on dolphin.	Visible all around.
	*	*		*			17/13
6225	<i>Brunswick Point Cut Lighted Buoy 27</i>	31-06-32.07N 81-28-02.53W	FI G 2.5s		5	Green.	
					*		12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6227	<i>Brunswick Point Cut Lighted Buoy 29</i>	31-06-55.27N 81-29-02.68W	FI G 2.5s		5	Green.	
					*		12/13
6228	<i>Brunswick Point Cut Lighted Buoy 30</i>	31-07-08.03N 81-29-18.05W	Q R		4	Red.	
					*		12/13
6230 37249	BRUNSWICK POINT CUT RANGE FRONT LIGHT 2	31-05-59.39N 81-26-23.08W	Q W FI R 4s	27		TR-TY on skeleton tower on piles.	Visible 1.5° each side of range line. Secondary light visible all around. Lighted throughout 24 hours.
		*		*			19/13
6235	BRUNSWICK POINT CUT RANGE REAR LIGHT 629 yards, 112.8° from front light.	31-05-52.15N 81-26-03.06W	Iso W 6s	48		KRW on skeleton tower on piles.	Visible 1.5° each side of range line. Lighted throughout 24 hours.
	*	*					19/13
6270	BRUNSWICK HARBOR RANGE FRONT LIGHT	31-09-06.17N 81-30-02.34W	Q R	20		KRW on dolphin.	Visible 1.5° each side of range line.
		*		*			20/13
6275	BRUNSWICK HARBOR RANGE REAR LIGHT 1,416 yards, 343.8° from front light.	31-09-46.55N 81-30-16.02W	Iso R 6s	43		KRW on skeleton tower on piles.	Visible 1.5° each side of range line.
	*	*		*			20/13
6305	ANDREWS ISLAND SPIT RANGE FRONT LIGHT Marks the easterly extremity of shoal.	31-06-56.49N 81-29-33.69W	Q Y	10		KYB on pile.	
		*		*			20/13
6310	ANDREWS ISLAND SPIT RANGE REAR LIGHT 134 yards, 179.7° from front light.	31-06-52.51N 81-29-33.67W	Iso Y 6s	18		KYB on pile.	
	*	*		*			20/13
6322	<i>- Lighted Buoy 2A</i>	31-07-39.34N 81-30-41.08W	FI R 2.5s		5	Red.	
					*		6/13
6324	<i>- Lighted Buoy 3</i>	31-07-29.26N 81-30-41.08W	FI G 2.5s		5	Green.	
					*		6/13
6525	<i>- RANGE FRONT LIGHT</i>	30-42-28.48N 81-27-52.70W	FI W 2.5s (Night) FI W 2.5s (Day)	19 22		KRW on tower. On same structure as Cumberland Sound Obstruction Light.	DAY: Visible on range line only. NIGHT: Visible 4° each side of range line.
		*		*			6/13
6530	<i>- RANGE REAR LIGHT</i> 1,936 yards, 267.8° from front light.	30-42-26.22N 81-28-59.18W	Iso W 6s (Night) Iso W 6s (Day)	95 87		KRW on tower.	DAY: Visible on range line only. NIGHT: Visible 4° each side of range line. Lighted throughout 24 hours.
	*	*		*			6/13
6585	<i>- Lighted Buoy 13</i>	30-42-37.07N 81-22-23.15W	FI G 4s		5	Green.	
					*		10/13
6595	<i>- Lighted Buoy 15</i>	30-42-35.51N 81-23-11.32W	FI G 6s		5	Green.	
					*		6/13
6630	<i>- Lighted Buoy 18</i>	30-42-37.02N 81-24-53.21W	FI R 6s		5	Red.	
					*		10/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6690 37870	- UPPER RANGE A FRONT LIGHT	30-43-30.49N 81-29-41.01W *	Q W	18		KRW-I on tower on piles.	Visible all around; higher intensity on range line. 4/13
6695 37875	- UPPER RANGE A REAR LIGHT 771 yards, 294.3° from front light. *	30-43-39.89N 81-30-05.16W *	Iso W 6s	48		KRW on tower on piles.	Visible all around; higher intensity on range line. 4/13
6700	- Lighted Buoy 22	30-42-41.35N 81-27-26.33W	Q R		4	Red.	 * 12/13
6740 37905	- LOWER RANGE A REAR LIGHT 196 yards, 114.5° from front light. *	30-42-17.35N 81-26-33.63W *	Iso W 6s	34	10	KRW on skeleton tower.	Obscured from 180° to 096°. Higher intensity on range line. 9/13
6745 37860	- RANGE FRONT LIGHT A-1 *	30-43-36.39N 81-29-31.50W *	Q R	17		KRW-I on dolphin.	Visible all around. 9/13
6750 37865	- RANGE REAR LIGHT A-1 316 yards, 301.6° from front light. *	30-43-41.30N 81-29-40.75W *	Iso R 6s	29		KRW on tower on piles.	Visible all around. 9/13
6760 37845	- RANGE FRONT LIGHT A-2 *	30-44-14.24N 81-29-27.18W *	Q W	16		KRW-I on dolphin.	Visible all around; higher intensity on range line. 7/13
6765 37850	- RANGE REAR LIGHT A-2 76 yards, 330° from front light. *	30-44-16.20N 81-29-28.49W *	Iso W 6s	32		KRW on tower on piles.	Visible all around; higher intensity on range line. 7/13
6775 37840	- Lighted Buoy 30	30-43-41.35N 81-28-58.34W	FI R 2.5s		5	Red with yellow square. *	 9/13
6790	- LIGHT 2	30-43-41.88N 81-29-25.53W	FI R 4s	12	5	TR on pile. *	 21/13
6905 37740	- RANGE D FRONT LIGHT *	30-46-44.92N 81-29-17.71W *	Q R	16		KRW-I on pile.	Visible all around; higher intensity on range line. 5/13
6910 37745	- RANGE D REAR LIGHT 1,351 yards, 351.4° from front light. *	30-47-24.58N 81-29-24.69W *	Iso R 6s	38		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line. 5/13
6920 37760	- Lighted Buoy 39	30-45-52.93N 81-29-11.34W	FI G 6s		5	Green with yellow triangle. *	 11/13
6935 37710	- LOWER RANGE E FRONT LIGHT *	30-46-23.62N 81-29-08.99W *	Q W	18		KRW-I on pile.	Light obscured from 250° to 120°. Higher intensity on range line. 4/13
6940 37715	- LOWER RANGE E REAR LIGHT 736 yards, 152.3° from front light. *	30-46-04.02N 81-28-57.23W *	Iso W 6s	55		KRW on skeleton tower. On same structure as Cumberland Sound Range C Rear Light.	Visible all around; higher intensity on range line. 4/13
6945 37700	- UPPER RANGE E FRONT LIGHT *	30-47-34.55N 81-29-52.35W *	Q W	16		KRW-I on dolphin.	Visible all around. 5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6950 37705	- UPPER RANGE E REAR LIGHT 232 yards, 332.1° from front light.	30-47-40.63N 81-29-56.09W	Iso W 6s	34		KRW on dolphin.	Visible all around.
	*	*		*			5/13
6955 37735	- Lighted Buoy 43	30-46-30.18N 81-29-20.49W	FI G 4s		5	Green with yellow triangle.	
					*		14/13
7045 37925	- Lighted Buoy 2	30-42-14.75N 81-27-51.43W	FI R 2.5s		5	Red with yellow triangle.	
					*		10/13
7060 37940	- Lighted Buoy 4	30-41-48.05N 81-27-48.13W	FI R 4s		5	Red with yellow triangle.	
					*		14/13
7270	- Lighted Buoy 22	30-22-54.01N 81-26-55.17W	FI R 4s		5	Red.	
					*		14/13
7280	- Lighted Buoy 24	30-22-58.09N 81-27-20.55W	FI R 4s		5	Red.	
					*		14/13
7470	- Lighted Buoy 51	30-23-47.88N 81-34-23.20W	FI G 4s		5	Green.	
					*		4/13
7855	SWITZERLAND LIGHT 15	30-05-55.59N 81-40-16.97W	FI G 2.5s	16	5	SG on dolphin.	
					*		14/13
8280	- LIGHT 19	29-35-50.70N 81-38-54.78W	FI G 2.5s	12	5	SG on pile.	
					*		7/13
8350	SEVEN SISTERS ISLANDS LIGHT 34	29-33-10.28N 81-42-00.97W	FI R 4s	16	5	TR on pile.	
		*					11/13
8380	NASHUA LIGHT 41	29-30-38.96N 81-40-48.02W	FI G 2.5s	16	5	SG on dolphin.	
					*		7/13
8395	TURKEY ISLAND LIGHT 43	29-29-58.32N 81-42-00.00W	FI G 4s	16	5	SG on dolphin.	
					*		12/13
8600	- Buoy 3	29-14-52.80N 81-38-02.40W				Green can.	Private aid.
		*					13/13
8605	- Buoy 4	29-14-54.36N 81-38-05.96W				Red nun.	Private aid.
		*					13/13
8610	- Buoy 5	29-14-52.80N 81-38-03.93W				Green can.	Private aid.
		*					13/13
8615	- Buoy 6	29-14-53.14N 81-38-14.45W				Red nun.	Private aid.
		*					13/13
8620	- Buoy 7	29-14-51.59N 81-38-16.53W				Green can.	Private aid.
		*					13/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8625	- Buoy 8	29-14-49.44N 81-38-19.71W *				Red nun.	Private aid. 13/13
8630	- Buoy 9	29-14-47.78N 81-38-20.14W *				Green can.	Private aid. 13/13
8640	- Buoy 11	29-14-46.09N 81-38-22.85W *				Green can.	Private aid. 13/13
8645	- Buoy 13	29-14-43.94N 81-38-24.75W *				Green can.	Private aid. 13/13
8650	- Buoy 15	29-14-42.32N 81-38-26.89W *				Green can.	Private aid. 13/13
8655	- Buoy 16	29-14-41.81N 81-38-28.62W *				Red nun.	Private aid. 13/13
8660	- Buoy 17	29-14-41.45N 81-38-28.42W *				Green can.	Private aid. 13/13
8665	- Buoy 18	29-14-41.22N 81-38-30.18W *				Red nun.	Private aid. 13/13
8670	- Buoy 19	29-14-40.83N 81-38-30.05W *				Green can.	Private aid. 13/13
8675	- Buoy 20	29-14-40.79N 81-38-32.18W *				Red nun.	Private aid. 13/13
8680	- Buoy 21	29-14-40.27N 81-38-31.83W *				Green can.	Private aid. 13/13
8685	- Buoy 22	29-14-40.56N 81-38-33.63W *				Red nun.	Private aid. 13/13
8690	- Buoy 23	29-14-40.02N 81-38-33.58W *				Green can.	Private aid. 13/13
8700	- Buoy 25	29-14-39.95N 81-38-35.17W *				Green can.	Private aid. 13/13
8705	- Buoy 27	29-14-40.20N 81-38-36.28W *				Green can.	Private aid. 13/13
8710	- Buoy 1A	29-14-43.19N 81-38-27.88W *				Green can.	Private aid. 13/13
8715	- Buoy 2A	29-14-43.61N 81-38-28.12W *				Red nun.	Private aid. 13/13
8720	- Buoy 3A	29-14-42.72N 81-38-28.96W *				Green can.	Private aid. 13/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8725	- Buoy 5A	29-14-41.95N 81-38-30.55W *				Green can.	Private aid. 13/13
8730	- Buoy 6A	29-14-42.32N 81-38-30.64W *				Red nun.	Private aid. 13/13
8735	- Buoy 8A	29-14-41.85N 81-38-32.87W *				Red nun.	Private aid. 13/13
8745	- Buoy 10A	29-14-42.00N 81-38-35.20W *				Red nun.	Private aid. 13/13
8795	- GUIDE PILES LIGHT 15	29-12-30.66N 81-34-43.56W	FI G 4s	12	5	SG on pile. *	 10/13
9225	ALEXANDER ISLAND LIGHT 114	28-50-45.28N 81-20-52.18W	FI R 4s	17	5	TR on dolphin. *	 5/13
9235	LAKE MONROE LIGHT 116	28-50-26.71N 81-20-05.12W	FI R 4s	17	5	TR on dolphin. *	 5/13
9490	- Buoy 4	29-55-00.01N 81-16-27.13W *				Red nun.	 17/13
9495	- Lighted Buoy 5	29-54-49.33N 81-16-32.35W *	Q G		4	Green.	 17/13
9500	- Lighted Buoy 7	29-54-38.86N 81-16-55.39W *	FI G 4s		5	Green.	 17/13
*9544	- Buoy 7B	29-04-24.86N 80-55-11.89W				Green can.	 21/13
*9546	- Buoy 8A	29-04-33.66N 80-55-14.83W				Red nun.	 21/13
*9547	- Buoy 8B	29-04-26.50N 80-55-16.93W				Red nun.	 21/13
9710	- Entrance Channel Lighted Buoy 20						Remove from list. * 4/13
9980	Fort Pierce Inlet Turning Basin Lighted Buoy A						Remove from list. * 18/13
9983	Fort Pierce Inlet Turning Basin Lighted Buoy B	27-27-28.88N 80-19-14.09W	FI Y 6s *		3	Yellow.	 18/13
9985.1	Fort Pierce City Marina Channel Daybeacon 3						Remove from list. * 9/13
9985.3	Fort Pierce City Marina Channel Daybeacon 4						Remove from list. * 9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9986.5	Fort Pierce City Marina Channel Junction Daybeacon						<i>Remove from list.</i>
							* 9/13
10000	- LIGHT 3	27-09-59.20N 80-08-56.03W	FI G 2.5s	16	5	SG on pile.	* 16/13
10255	- LIGHT 13	26-45-55.25N 80-02-47.48W	FI G 2.5s	16	5	SG on pile.	* 11/13
10290	- ENTRANCE LIGHT 1	26-15-16.99N 80-04-46.92W	FI G 4s	16	5	SG on dolphin.	* 13/13
10695	- LIGHT 15	25-46-19.02N 80-10-35.41W	FI G 6s	16	5	SG on pile.	* 12/13
10800	- LIGHT 4	25-41-06.54N 80-11-01.29W	FI R 2.5s	16	5	TR on pile.	* 9/13
12370	- LIGHT 98	24-54-08.84N 80-43-58.01W	FI R 2.5s	16	5	TR on pile.	* 17/13
12550	- LIGHT 25	24-41-46.45N 81-12-26.83W	FI G 4s	16	5	SG on pile.	* 11/13
13725	- LIGHT 2	24-41-14.55N 81-05-11.58W	FI R 4s	16	5	TR on pile.	* 12/13
13885	- ENTRANCE LIGHT 2	24-37-08.23N 81-24-25.53W	FI R 4s	16	5	TR on pile.	* 12/13
13980	LOGGERHEAD KEY LIGHT 50A	24-35-50.59N 81-27-17.13W	FI R 6s	16	5	TR on pile.	* 12/13
14505	- LIGHT 1	24-32-46.73N 81-43-34.48W	FI G 4s	16	5	SG on pile.	* 15/13
14655	- LIGHT 4	24-33-06.08N 81-43-59.39W	FI R 2.5s	16	5	TR on pile.	* 22/13
14970	- Daybeacon 6	24-34-29.85N 81-47-58.15W				TR on pile.	Maintained by U.S. Navy. Private aid. 20/13
14990	- LIGHT 3	24-35-21.87N 81-48-16.09W	FI G 4s	16	5	SG on pile.	* 15/13
15450	- LIGHT 3	24-38-19.45N 82-51-40.83W	FI G 4s	16	5	SG on dolphin.	* 22/13
15595	ARSENIC BANK LIGHT 2	24-52-17.63N 80-53-11.06W	FI R 4s	16	5	TR on dolphin.	* 20/13
15605	SPRIGGER BANK LIGHT 5	24-54-50.10N 80-56-17.39W	FI G 4s	16	5	SG on pile.	* 20/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
23235	- Lighted Buoy 20	27-50-31.55N 82-26-38.89W	Q R		4	Red.	
					*		5/13
23510	- Lighted Buoy 35	27-54-23.50N 82-26-23.76W	FI G 2.5s		5	Green.	
					*		20/13
23535	- Lighted Buoy 1	27-55-39.13N 82-26-52.98W	Q G		4	Green.	
					*		20/13
23563	- LIGHT 7	27-56-08.51N 82-26-48.03W	FI G 2.5s	16	5	SG on pile.	
					*		11/13
23690	- Lighted Buoy 6G	27-47-20.60N 82-33-18.85W	FI R 4s		4	Red.	
					*		5/13
23695	- Lighted Buoy 7G	27-47-21.51N 82-34-00.75W	Q G		4	Green.	
					*		5/13
23930	- Lighted Buoy 10K	27-51-36.66N 82-33-13.71W	FI R 2.5s		4	Red.	
					*		5/13
23960	- Daybeacon 1A						<i>Remove from list.</i>
							*
25695	- LIGHT 6	27-57-53.87N 82-49-49.39W	FI R 4s	16	5	TR on pile.	
		*					10/13
25695	- LIGHT 6	27-57-54.32N 82-49-49.08W	FI R 4s	16	5	TR on pile.	
					*		9/13
25705	- LIGHT 8	27-57-46.98N 82-49-34.54W	FI R 2.5s	16	5	TR on pile.	
					*		9/13
25730	- LIGHT 2	27-57-47.15N 82-49-08.99W	Q R	16	4	TR on pile.	
	*	*	*	*	*		4/13
25735	- Daybeacon 3	27-57-49.89N 82-49-10.33W				SG on pile.	
	*	*	*	*	*		4/13
25750	- Daybeacon 5	27-57-55.59N 82-49-04.78W				TR on pile.	
		*					4/13
28570.5	- Buoy 57B	28-46-34.71N 82-39-37.93W				Green can.	
		*					17/13
30760	- Lighted Buoy 2	18-28-19.80N 66-07-46.33W	FI R 2.5s		5	Red.	
		*					11/13
30910	- Lighted Buoy 3	18-26-08.26N 66-05-48.94W	FI G 4s		5	Green.	
					*		20/13
30915	- Lighted Buoy 5	18-26-23.16N 66-05-23.22W	Q G		4	Green	
					*		20/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
31360	<i>Bajos Largo Lighted Buoy 3</i>	18-17-41.70N 65-34-50.40W	FI G 2.5s		5	Green.	
					*		11/13
31385	<i>Cabeza de Perro Lighted Buoy 7</i>	18-13-32.85N 65-33-41.58W	FI G 6s		5	Green.	
					*		11/13
31435	- ENTRANCE CHANNEL RANGE FRONT LIGHT						<i>Remove from list.</i>
							*
							16/13
31440	- ENTRANCE CHANNEL RANGE REAR LIGHT 809 yards, 315.2° from front light.						<i>Remove from list.</i>
							*
							16/13
31565	- <i>Lighted Buoy 3</i>	18-09-56.93N 65-31-00.33W	FI G 6s		5	Green.	
		*			*		11/13
31635	<i>Bajo Snapper Lighted Buoy 8</i>	18-17-21.69N 65-16-17.52W	Q R		4	Red.	
		*			*		12/13
31970	- <i>Lighted Buoy 5</i>	17-57-09.02N 66-37-45.36W	FI G 2.5s		5	Green.	
		*					11/13
32075.5	- ENTRANCE RANGE REAR PASSING LIGHT						<i>Remove from list.</i>
							*
							9/13
32305	<i>Canal de la Mona East Shoal Lighted Buoy 4</i>	18-00-23.10N 67-23-00.14W	FI R 6s		5	Red.	
					*		11/13
32365	- <i>Lighted Buoy 5</i>	18-13-13.65N 67-10-35.42W	FI G 4s		5	Green.	
		*			*		10/13
32380	- <i>Lighted Buoy 6</i>	18-12-57.79N 67-09-49.43W	FI R 4s		5	Red.	
					*		10/13
32610	<i>East Gregerie Channel Lighted Buoy WR1</i>	18-18-37.81N 64-56-04.32W	Q G		4	Green.	
					*		13/13
32630	- <i>Lighted Buoy 2</i>	18-18-22.80N 64-58-34.60W	FI R 4s		5	Red.	
					*		11/13
32640	- <i>Lighted Buoy 4</i>	18-19-16.78N 64-57-30.24W	FI R 2.5s		5	Red.	
					*		11/13
32675	<i>Johnson Reef Lighted Buoy 1JR</i>	18-21-53.96N 64-46-25.47W	FI G 4s		5	Green.	
					*		11/13
32700	TWO BROTHERS LIGHT	18-20-34.30N 64-49-02.17W	FI W 6s	23	7	NR on skeleton tower.	
					*		14/13
32705	<i>Mingo Rock Lighted Buoy 2</i>	18-19-22.98N 64-48-12.42W	FI R 4s		5	Red.	
					*		11/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
32770	STEVENS CAY LIGHT	18-19-54.46N 64-48-30.94W	FI W 4s	14	7	NR on skeleton tower.	
					*		14/13
33380	HICACAL BEACH LIGHT	19-56-39.10N 75-09-48.00W	FI W 2.5s	40	7	NB on skeleton tower.	
				*			10/13
33385	- Entrance Lighted Buoy 1	19-54-49.67N 75-10-51.39W	FI G 2.5s		5	Green.	
		*			*		10/13
33390	- Entrance Lighted Buoy 2	19-54-39.43N 75-10-16.78W	FI R 2.5s		5	Red.	
		*			*		10/13
33395	- Lighted Buoy 3	19-54-42.87N 75-11-32.50W	Q G		4	Green.	
		*			*		10/13
33410	- Lighted Buoy 6	19-54-44.49N 75-11-58.94W	FI R 4s		5	Red.	
		*			*		10/13
33425	- Lighted Buoy 3	19-55-20.52N 75-10-45.24W	FI G 2.5s		5	Green.	
		*			*		10/13
33430	- Lighted Buoy 4	19-55-09.51N 75-10-10.00W	FI R 2.5s		5	Red.	
		*			*		10/13
33445	- Lighted Buoy 5	19-55-47.49N 75-09-58.84W	FI G 2.5s		4	Green.	
		*					10/13
33470	- Lighted Buoy 2	19-55-10.44N 75-09-12.94W	Q R		3	Red.	
		*					10/13
33475	- Buoy 4	19-55-04.86N 75-09-11.93W				Red nun.	
		*					10/13
33495	- Buoy 3 Marks shoal.	19-55-13.41N 75-08-56.68W				Green can.	
		*					10/13
33585	- Buoy 6	19-57-48.80N 75-08-47.01W				Red nun.	
		*					10/13
33595	<i>Eagle Channel Lighted Buoy</i> 1	19-57-17.22N 75-08-08.78W	FI G 4s		5	Green.	
		*			*		10/13
34995	- LIGHT 125	32-37-49.78N 80-18-56.51W	FI G 4s	16	5	SG-SY on dolphin.	
					*		16/13
35035	- LIGHT 137	32-37-15.22N 80-21-30.08W	FI G 4s	18	5	SG-SY on dolphin.	
					*		5/13
35285	- LIGHT 198	32-30-34.91N 80-37-52.10W	FI R 4s	12	5	TR-TY on pile.	
					*		17/13
35575 4250	- Lighted Buoy 27	32-16-56.72N 80-39-18.19W	FI G 4s		5	Green with yellow triangle.	
					*		13/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
35705	- LIGHT 22	32-13-35.00N 80-46-46.60W	FI R 4s	16	5	TR-TY on pile.	
					*		21/13
35735	- LIGHT 28	32-12-21.69N 80-47-08.87W	FI R 4s	16	5	TR-TY on pile.	
					*		15/13
35795	- LIGHT 31	32-10-01.45N 80-47-45.51W	FI G 4s	18	5	SG-SY on pile.	
					*		16/13
36160	- LIGHT 71	31-56-02.76N 81-04-28.09W	FI G 4s	12	5	SG-SY on pile.	
					*		16/13
36875	- LIGHT 195	31-19-56.21N 81-19-31.15W	FI G 2.5s	12	3	SG-SY on pile.	
			*				4/13
37060	- LIGHT 223	31-16-37.56N 81-22-59.34W	FI G 4s	16	5	SG-SY on pile.	
					*		9/13
37245 6180	JEKYLL ISLAND RANGE FRONT LIGHT 1	31-06-06.25N 81-26-06.30W	Q G	17		SG-SY and KRW on dolphin.	Visible 1.5° each side of range line. Passing light visible all around.
		*		*			20/13
37249 6230	BRUNSWICK POINT CUT RANGE FRONT LIGHT 2	31-05-59.39N 81-26-23.08W	Q W FI R 4s	27	3	TR-TY on skeleton tower on piles.	Visible 1.5° each side of range line. Secondary light visible all around. Lighted throughout 24 hours.
		*		*			19/13
37259 6185.7	<i>St Simons Sound Lighted Buoy 21</i>	31-06-30.07N 81-25-41.00W	Q G		4	Green.	
					*		9/13
37520	- LIGHT 41	30-54-38.20N 81-28-13.57W	FI G 2.5s	12	5	SG-SY on pile.	
					*		15/13
37555	- LIGHT 50	30-53-14.04N 81-30-55.44W	FI R 4s	16	5	TR-TY on dolphin.	
					*		15/13
37600	- LIGHT 58	30-51-45.54N 81-29-46.26W	FI R 4s	12	5	TR-TY on pile.	
					*		15/13
37610	- LIGHT 60	30-50-56.42N 81-28-41.67W	FI R 4s	12	5	TR-TY on pile.	
		*					9/13
37635	- LIGHT 65	30-50-16.09N 81-29-01.72W	FI G 4s	16	5	SG-SY on pile.	
					*		14/13
37645	- RANGE F FRONT LIGHT	30-49-40.47N 81-29-31.14W	Q R	12		KRW-I on dolphin.	Visible 4° each side of range line.
		*		*			17/13
37650	- RANGE F REAR LIGHT 849 yards, 356.3° from front light.	30-50-05.61N 81-29-33.05W	Iso R 6s	22		KRW on dolphin.	Visible 4° each side of range line.
	*	*		*			17/13
37700 6945	- UPPER RANGE E FRONT LIGHT	30-47-34.55N 81-29-52.35W	Q W	16		KRW-I on dolphin.	Visible all around.
		*					5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
37705 6950	- UPPER RANGE E REAR LIGHT 232 yards, 332.1° from front light. *	30-47-40.63N 81-29-56.09W *	Iso W 6s	34		KRW on dolphin.	Visible all around. 5/13
37710 6935	- LOWER RANGE E FRONT LIGHT *	30-46-23.36N 81-29-08.99W *	Q W	18		KRW-I on pile.	Light obscured from 250° to 120°. Higher intensity on range line. 4/13
37715 6940	- LOWER RANGE E REAR LIGHT 736 yards, 152.3° from front light. *	30-46-04.02N 81-28-57.23W *	Iso W 6s	55		KRW on skeleton tower. On same structure as Cumberland Sound Upper Range C Rear Light.	Visible all around; higher intensity on range line. 4/13
37735 6955	- Lighted Buoy 43 *	30-46-30.18N 81-29-20.49W *	FI G 4s		5	Green with yellow triangle.	 14/13
37740 6905	- RANGE D FRONT LIGHT *	30-46-44.92N 81-29-17.71W *	Q R	16		KRW-I on dolphin.	Visible all around; higher intensity on range line. 5/13
37745 6910	- RANGE D REAR LIGHT 1,351 yards, 351.4° from front light. *	30-47-24.58N 81-29-24.69W *	Iso R 6s	38		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line. 5/13
37760 6920	- Lighted Buoy 39 *	30-45-52.93N 81-29-11.34W *	FI G 6s		5	Green with yellow triangle.	 11/13
37840 6775	- Lighted Buoy 30 *	30-43-41.35N 81-28-58.34W *	FI R 2.5s		5	Red with yellow square.	 9/13
37845 6760	- RANGE FRONT LIGHT A-2 *	30-44-14.24N 81-29-27.18W *	Q W	16		KRW-I on dolphin.	Visible all around; higher intensity on range line. 7/13
37850 6765	- RANGE REAR LIGHT A-2 76 yards, 330° from front light. *	30-44-16.20N 81-29-28.49W *	Iso W 6s	32		KRW on tower on piles.	Visible all around; higher intensity on range line. 7/13
37860 6745	- RANGE FRONT LIGHT A-1 *	30-43-36.39N 81-29-31.50W *	Q R	17		KRW-I on dolphin.	Visible all around. 9/13
37865 6750	- RANGE REAR LIGHT A-1 316 yards, 301.6° from front light. *	30-43-41.30N 81-29-40.75W *	Iso R 6s	29		KRW on tower on piles.	Visible all around. 9/13
37870 6690	- UPPER RANGE A FRONT LIGHT *	30-43-30.49N 81-29-41.01W *	Q W	18		KRW-I on skeleton tower on piles.	Visible all around; higher intensity on range line. 4/13
37875 6695	- UPPER RANGE A REAR LIGHT 771 yards, 294.3° from front light. *	30-43-39.89N 81-30-05.16W *	Iso W 6s	48		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line. 4/13
37905 6740	- LOWER RANGE A REAR LIGHT 196 yards, 114.5° from front light. *	30-42-17.35N 81-26-33.63W *	Iso W 6s	34	10	KRW on skeleton tower.	Obscured from 180° to 096°. Higher intensity on range line. 9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
37925 7045	- Lighted Buoy 2	30-42-14.75N 81-27-51.43W	FI R 2.5s		5	Red with yellow triangle.	
					*		10/13
37940 7060	- Lighted Buoy 4	30-41-48.05N 81-27-48.13W	FI R 4s		5	Red with yellow triangle.	
					*		14/13
38110	- LIGHT 37	30-34-08.06N 81-28-21.56W	FI G 4s	12	5	SG-SY on dolphin.	
					*		9/13
38215	- LIGHT 57	30-29-08.76N 81-27-29.67W	FI G 4s	12	5	SG-SY on pile.	
					*		9/13
38230	- LIGHT 63	30-28-17.39N 81-27-28.35W	FI G 4s	12	5	SG-SY on pile.	
					*		9/13
38705	- LIGHT 23	30-03-43.08N 81-22-08.77W	FI G 4s	16	5	SG-SY on pile.	
					*		17/13
38780	- LIGHT 41	30-00-00.00N 81-20-18.55W	FI G 4s	12	5	SG-SY on pile.	
					*		9/13
38800	- LIGHT 45	29-59-25.22N 81-19-46.52W	FI G 4s	16	5	SG-SY on pile.	
					*		15/13
38815	- LIGHT 49	29-57-33.60N 81-19-19.39W	FI G 4s	16	5	SG-SY on pile.	
					*		15/13
38893	- LIGHT 58A	29-54-41.69N 81-17-54.66W	FI R 2.5s	16	5	TR-TY on pile.	
					*		17/13
39815	- LIGHT 29	29-23-28.30N 81-05-29.76W	FI G 4s	12	5	SG-SY on pile.	
					*		11/13
40655	- LIGHT 30	29-02-08.70N 80-54-21.96W	FI R 4s	16	5	TR-TY on pile.	
					*		11/13
40695	- Daybeacon 4	29-01-43.03N 80-54-45.05W				TR on pile.	
		*					11/13
40950	- LIGHT 13	28-51-39.18N 80-49-31.18W	FI G 4s	16	5	SG-SY on dolphin.	
					*		4/13
41050	- LIGHT 38	28-45-29.90N 80-45-44.91W	FI R 4s	16	5	TR-TY on dolphin.	
					*		4/13
43075	- LIGHT 6	28-07-29.69N 80-37-24.37W	FI R 4s	16	5	TR on pile.	
					*		12/13
43240	- LIGHT 7	28-04-32.03N 80-35-57.40W	Q G	12	3	SG on pile.	
							*
44640	- Daybeacon 9	27-34-57.00N 80-20-33.10W				SG on pile.	Private aid.
		*					12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
44690	- LIGHT 164	27-34-09.57N 80-21-07.48W	FI R 4s	16	5	TR-TY on pile.	
						*	7/13
44705	- LIGHT 167	27-33-57.04N 80-20-58.40W	FI G 4s	12	5	SG-SY on pile.	
						*	7/13
45930	- LIGHT 3	27-09-44.97N 80-10-39.09W	FI G 4s	12	5	SG-SY on pile.	
						*	16/13
45940	- LIGHT 4	27-09-34.79N 80-10-35.23W	FI R 2.5s	13	5	TR-TY on pile.	
				*			16/13
45965	- LIGHT 9	27-09-14.03N 80-10-06.93W	FI G 4s	16	5	SG-SY on pile.	
				*			16/13
46015	- LIGHT 11	27-08-49.18N 80-09-50.27W	FI G 4s	16	5	SG-SY on pile.	
						*	16/13
46035	NORTH JUPITER NARROWS LIGHT 15	27-07-41.61N 80-09-03.17W	FI G 4s	16	5	SG-SY on pile.	
						*	16/13
46050	- LIGHT 19	27-06-51.99N 80-08-40.15W	FI G 4s	12	5	SG-SY on pile.	
						*	16/13
46075	- LIGHT 23	27-06-00.00N 80-08-13.61W	FI G 4s	12	5	SG-SY on pile.	
						*	15/13
46110	- LIGHT 32	27-03-14.03N 80-07-09.85W	FI R 4s	16	5	TR-TY on pile.	
						*	15/13
46135	- LIGHT 37	27-02-14.75N 80-06-27.60W	FI G 4s	12	5	SG-SY on pile.	
						*	15/13
46160	- LIGHT 43	27-00-28.95N 80-05-42.47W	FI G 4s	16	5	SG-SY on pile.	
						*	13/13
46175	- LIGHT 47	26-59-42.80N 80-05-28.92W	FI G 4s	16	5	SG-SY on pile.	
						*	13/13
46190	- LIGHT 50	26-59-11.98N 80-05-27.76W	FI R 4s	16	5	TR-TY on dolphin.	
						*	13/13
46200	- LIGHT 53	26-58-43.02N 80-05-07.56W	FI G 4s	16	5	SG-SY on pile.	
						*	13/13
46225	- LIGHT 59	26-57-26.70N 80-04-43.29W	FI G 4s	16	5	SG-SY on pile.	
						*	13/13
46735	- Daybeacon 3A	26-45-19.12N 80-02-53.64W				SG-SY on pile.	
		*					11/13
*46881	South Cove Danger Daybeacon A	26-42-32.40N 80-02-50.40W				NW on pile worded ROCKS.	Private aid.
							15/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*46881.1	South Cove Danger Daybeacon B	26-42-24.00N 80-02-51.60W				NW on pile worded ROCKS.	Private aid. 15/13
47205	- LIGHT 69	26-16-00.04N 80-04-52.14W	FI G 4s	16	5	SG-SY on pile.	* 4/13
47375	- LIGHT 20	26-06-39.06N 80-07-10.21W *	FI R 4s	16	5	TR-TY on pile.	* 11/13
47695	- LIGHT 49	25-56-39.55N 80-07-39.54W	FI G 4s	16	5	SG-SY on pile.	* 11/13
47810	- LIGHT 5	25-54-32.86N 80-07-31.80W *	FI G 4s	16	5	SG-SY on pile.	* 11/13
*47822	- Buoy 7	25-54-11.96N 80-07-47.68W				Green can with yellow square.	12/13
*47824	- Buoy 7A	25-54-08.95N 80-07-50.40W				Green can with yellow square.	12/13
47828	- Buoy 7B	25-54-06.58N 80-07-52.64W * *				Green can with yellow square.	12/13
48085	Biscayne Bay Pipeline Buoy A						<i>Remove from list.</i> * 12/13
48150	Biscayne Bay Pipeline Buoy E						<i>Remove from list.</i> * 12/13
48155	Biscayne Bay Pipeline Buoy D						<i>Remove from list.</i> * 12/13
48160	Biscayne Bay Pipeline Buoy C						<i>Remove from list.</i> * 12/13
48585	- LIGHT 67	25-45-08.90N 80-11-02.26W	FI G 4s	16	5	SG-SY on pile.	* 12/13
50375	- LIGHT 41	25-08-35.47N 80-25-25.95W	FI G 4s	16	5	SG-SY on dolphin.	* 4/13
50630	- LIGHT 78	24-59-45.06N 80-33-55.36W	FI R 4s	16	5	TR-TY on pile.	* 13/13
50700	- <i>Lighted Buoy 6</i>	27-09-54.64N 80-11-21.96W	FI R 4s		5	Red with yellow triangle.	* 18/13
*50712	- Daybeacon 8A	27-10-00.54N 80-11-33.49W				TR-TY on pile.	5/13
51585	- Daybeacon 48	26-51-23.83N 80-38-28.71W *				TR-TY on pile.	6/13
51745	- Daybeacon 5	26-47-39.44N 80-42-05.08W *				SG on pile.	6/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
51825	- Daybeacon 96	26-43-34.79N 80-50-53.25W *				TR-TY on pile.	5/13
56075	- Daybeacon 61	26-39-21.74N 82-13-06.16W *				SG-SY on pile.	6/13
57075	- Daybeacon 30a					<i>Remove from list.</i> *	4/13
57085	- Daybeacon 32	26-50-42.19N 82-17-24.80W *				TR-TY on pile.	4/13
57360	- LIGHT 24	26-56-24.45N 82-21-25.24W	FI R 6s	16	5	TR-TY on pile. *	8/13
58810	- LIGHT 17	27-24-32.57N 82-36-48.58W	FI G 4s	16	5	SG-SY on pile. *	18/13
60155	- LIGHT 58 *	27-30-37.80N 82-41-22.57W	Q R	15	3	TR-TY on pile. *	9/13
60160	- RANGE REAR LIGHT 265 yards, 144.7° from front light.					<i>Remove from list.</i> *	9/13
60265	- LIGHT 64	27-31-52.44N 82-42-08.79W	FI R 4s	16	5	TR-TY on pile. *	13/13
60290 22395	<i>Mullet Key Channel Lighted Buoy 26</i>	27-36-45.31N 82-40-14.95W	Q R		4	Red with yellow square. *	21/13
60390	- LIGHT 17	27-40-17.57N 82-41-00.00W	FI G 4s	16	5	SG on pile. *	17/13
60900	- LIGHT 32	27-43-57.07N 82-43-43.78W	Q R	16	4	TR-TY on pile. *	8/13
61313	- Daybeacon 1 *	27-48-49.60N 82-45-52.70W				SG on pile.	Private aid. 5/13
61315	- Daybeacon 2 *	27-48-50.59N 82-45-49.87W				TR on pile.	Private aid. 5/13
61320	- Daybeacon 4 *	27-48-52.09N 82-45-50.37W				TR on pile.	Private aid. 5/13
61325	- Daybeacon 6 *	27-48-54.09N 82-45-50.37W				TR on pile.	Private aid. 5/13

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
267	<i>Tana-117-20 Lighted Buoy</i>						<i>Remove from list.</i> * 9/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
335 9580	SHIP ISLAND LIGHT	30-12-45.41N 88-57-58.74W	FI W 6s	82	6	Skeleton tower on block. On same structure as Ship Channel Upper Reach Outbound Range Rear Light.	
		*					6/13
*387	Taylor Energy Lighted Buoy A	28-56-12.62N 88-58-10.30W	FI Y 2.5s			Marks subsea containment system.	SIGN: TAYLOR ENERGY-MC-20. Private aid. 6/13
*637	LLOG-103-6 Lighted Buoy Marks subsea installation	28-21-57.30N 90-12-06.90W	FI W 2.5s			White with orange bands.	SIGN: LLOG-ST-232-1. Private aid. 21/13
700	Ship Shoal Wreck Lighted Buoy WR4 Marks jack up leg and pad.						<i>Remove from list.</i>
							* 5/13
*943	Nippon-102-10 Lighted Buoy	28-21-12.63N 93-01-24.90W	Q G			Marks subsea obstruction.	SIGN: NIPPON-WC-533-A. Private aid. 7/13
965	Gulf Gateway Energy Bridge Deepwater Port Lighted Buoy A						<i>Remove from list.</i>
							* 12/13
*998	Arena Offshore-108-7 Lighted Buoy	28-16-14.95N 93-20-29.66W	FI W 2.5s			White with orange bands.	SIGN: ARENA-WC-564-1. Private aid. 4/13
*1357	Texas A Lighted Oceanographic Buoy X	27-03-57.73N 96-20-17.76W	FI Y 2.5s				Private aid. 17/13
1365 27100	Matagorda Ship Channel Approach Lighted Buoy MSC	28-12-01.03N 96-05-12.88W	Mo (A) W		4	Red and white stripes with red spherical topmark.	
						*	7/13
1385 27110	Matagorda Ship Channel Entrance Light	28-25-18.47N 96-19-05.92W	FI W 10s	64	5	On same structure as Matagorda Ship Channel Range B Rear Light. 52	Obscured from 257° to 040°.
		*					4/13
	*Add Heading: ALABAMA RIVER						
*6801	UNITED LAND COMPANY DOLPHIN LIGHTS (2) LDB Mile 353.3		FI R 2.5s	15		On dolphins.	Private aids. 12/13
	*Add Heading and Note: BLACK WARRIOR RIVER						
	<i>From mile 217 to mile 385.5, the river is marked with numerous unlisted daybeacons and unlighted buoys which are periodically relocated to meet minor changing conditions.</i>						
	<i>Holt Lock and Bankhead Lake buoys and daybeacons have been discontinued and waterways marked with unlisted, unlighted buoys.</i>						
	<i>Mulberry Fork - From mile 385.6 to mile 399.7, the river is marked with numerous unlisted daybeacons and unlighted buoys which are periodically relocated to meet minor changing conditions.</i>						
	<i>Locust Fork - From mile 387.0 to mile 390.8, the river is marked with numerous unlisted daybeacons and unlighted buoys which are periodically relocated to meet minor changing conditions.</i>						
*6802	Lyon Park Range Front Daybeacon					KWR on pile.	Private aid. 12/13
*6803	Lyon Park Range Rear Daybeacon.					KRW on pile.	Private aid. 12/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*7763	<i>Point Aux Pins Special Lighted Buoys (5)</i>	30-22-57.12N 88-18-48.06W	FI Y 2.5s			Mark perimeter of oyster farm.	Private aid. 20/13
7835	<i>Petit Bois Pass Lighted Buoy 1</i>	30-12-13.72N 88-18-58.92W *	FI G 2.5s		4	Green.	21/13
7940	- <i>Lighted Buoy 16</i>	30-12-45.15N 88-30-34.62W *	FI R 2.5s		3	Red.	4/13
*8093	<i>Mississippi Phosphates Lighted Danger Buoy</i>	30-21-07.36N 88-30-20.33W	FI W 2.5s			Marks submerged pipe.	Private aid. 20/13
8305	- Daybeacon 6	30-23-19.20N 88-33-50.95W *				TR on pile.	Ra ref. 6/13
8830	- Daybeacon 1 *	30-23-31.61N 88-48-52.76W *				SG on pile.	Private aid. 11/13
*8830.01	- LIGHT 2	30-23-30.04N 88-48-51.90W	FI R 2.5s			TR on pile.	Private aid. 11/13
*8830.02	- Daybeacon 4	30-23-31.42N 88-48-45.62W				TR on pile.	Private aid. 11/13
*8830.03	- Daybeacon 6	30-23-32.34N 88-48-42.05W				TR on pile.	Private aid. 11/13
*8830.04	- Daybeacon 3	30-23-34.73N 88-48-39.71W				SG on pile.	Private aid. 11/13
*8830.05	- Daybeacon 8	30-23-32.01N 88-48-32.62W				TR on pile.	Private aid. 11/13
*8830.06	- DANGER LIGHT	30-23-33.32N 88-48-29.23W	FI W 2.5s			NW on pile worded DANGER SUBMERGED ROCKS.	Private aid. 11/13
*8830.07	- Daybeacon 10	30-23-29.20N 88-48-19.00W				TR on pile.	Private aid. 11/13
*8830.08	- Daybeacon 12	30-23-28.43N 88-48-11.00W				TR on pile.	Private aid. 11/13
*8830.09	- Daybeacon 14	30-23-28.44N 88-48-06.15W				TR on pile.	Private aid. 11/13
*8830.11	- Daybeacon 5	30-23-29.72N 88-48-05.88W				SG on pile.	Private aid. 11/13
*8830.12	- Daybeacon 16	30-23-28.19N 88-47-57.30W				TR on pile.	Private aid. 11/13
*8830.13	- Daybeacon 18	30-23-27.78N 88-47-51.47W				TR on pile.	Private aid. 11/13
*8830.14	- Daybeacon 7	30-23-28.80N 88-47-50.23W				SG on pile.	Private aid. 11/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*8830.15	- Daybeacon 9	30-23-27.96N 88-47-46.66W				SG on pile.	Private aid. 11/13
*8830.16	- Daybeacon 20	30-23-26.53N 88-47-46.25W				TR on pile.	Private aid. 11/13
*8830.17	- Daybeacon 22	30-23-24.46N 88-47-40.12W				TR on pile.	Private aid. 11/13
*8830.18	- Daybeacon 11	30-23-25.59N 88-47-39.86W				SG on pile.	Private aid. 11/13
*8830.19	- Daybeacon 24	30-23-19.78N 88-47-34.88W				TR on pile.	Private aid. 11/13
*8830.21	- Daybeacon 13	30-23-20.78N 88-47-34.00W				SG on pile.	Private aid. 11/13
*8830.22	- Daybeacon 26	30-23-15.43N 88-47-29.04W				TR on pile.	Private aid. 11/13
8835	- Daybeacon 6						Remove from list. * 10/13
8840	- Daybeacon 8						Remove from list. * 10/13
8845	- Daybeacon 10						Remove from list. * 10/13
8850	- Daybeacon 12						Remove from list. * 10/13
8855	- Daybeacon 13						Remove from list. * 10/13
8860	- Daybeacon 14						Remove from list. * 10/13
8865	- Daybeacon 16						Remove from list. * 10/13
8870	- Daybeacon 17A						Remove from list. * 10/13
8875	- Daybeacon 17B						Remove from list. * 10/13
8880	- Daybeacon 18						Remove from list. * 10/13
8885	- Daybeacon 20						Remove from list. * 10/13
8890	- Daybeacon 22						Remove from list. * 10/13
8895	- Daybeacon 23						Remove from list. * 10/13
8900	- Daybeacon 24						Remove from list. * 10/13
8905	- Daybeacon 26						Remove from list. * 10/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8910	- Daybeacon 27						<i>Remove from list.</i> * 10/13
8915	- Daybeacon 28						<i>Remove from list.</i> * 10/13
8920	- Daybeacon 29						<i>Remove from list.</i> * 10/13
8925	- Daybeacon 30						<i>Remove from list.</i> * 10/13
8930	- Daybeacon 32						<i>Remove from list.</i> * 10/13
8935	- Daybeacon 33						<i>Remove from list.</i> * 10/13
8940	- Daybeacon 34						<i>Remove from list.</i> * 10/13
8945	- Daybeacon 36						<i>Remove from list.</i> * 10/13
9160	- Daybeacon 1	30-25-24.52N 88-51-18.55W				SG on pile.	Private aid.
	*	*				*	11/13
*9160.01	- LIGHT 2	30-25-24.57N 88-51-16.81W	FI R 2.5s			TR on pile.	Private aid. 11/13
*9160.02	- Daybeacon 3	30-25-29.20N 88-51-15.95W				SG on pile.	Private aid. 11/13
*9160.03	- Daybeacon 4	30-25-29.81N 88-51-13.80W				TR on pile.	Private aid. 11/13
*9160.04	- Daybeacon 6	30-25-35.07N 88-51-09.29W				TR on pile.	Private aid. 11/13
*9160.05	- Daybeacon 5	30-25-38.65N 88-51-04.86W				SG on pile.	Private aid. 11/13
*9160.06	- Daybeacon 8	30-25-36.63N 88-51-03.18W				TR on pile.	Private aid. 11/13
*9160.07	- Daybeacon 10	30-25-35.41N 88-50-55.78W				TR on pile.	Private aid. 11/13
*9160.08	- Daybeacon 7	30-25-35.47N 88-50-53.01W				TR on pile.	Private aid. 11/13
*9160.09	- Daybeacon 12	30-25-27.61N 88-50-46.85W				TR on pile.	Private aid. 11/13
*9160.11	- Daybeacon 14	30-25-23.16N 88-50-42.57W				TR on pile.	Private aid. 11/13
*9160.12	- Daybeacon 9	30-25-21.89N 88-50-37.14W				SG on pile.	Private aid. 11/13
*9160.13	- Daybeacon 16	30-25-17.36N 88-50-35.21W				TR on pile.	Private aid. 11/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*9160.14	- Daybeacon 18	30-25-17.16N 88-50-24.69W				TR on pile.	Private aid. 11/13
*9160.15	- Daybeacon 11	30-25-19.40N 88-50-21.25W				SG on pile.	Private aid. 11/13
*9160.17	- Daybeacon 20	30-25-17.36N 88-50-21.61W				TR on pile.	Private aid. 11/13
*9160.18	- LIGHT 22	30-25-16.97N 88-50-18.67W	Fl R 2.5s			TR on pile.	Private aid. 11/13
*9160.19	- Daybeacon 24	30-25-16.13N 88-50-14.72W				TR on pile.	Private aid. 11/13
*9160.21	- Daybeacon 26	30-25-12.81N 88-50-09.51W				TR on pile.	Private aid. 11/13
*9160.22	- Daybeacon 13	30-25-10.51N 88-50-00.48W				SG on pile.	Private aid. 11/13
*9160.23	- Daybeacon 28	30-25-07.11N 88-49-54.78W				TR on pile.	Private aid. 11/13
9165	- Daybeacon 5						Remove from list. * 10/13
9170	- Daybeacon 6						Remove from list. * 10/13
9175	- Daybeacon 7						Remove from list. * 10/13
9180	- Daybeacon 8						Remove from list. * 10/13
9185	- Daybeacon 9						Remove from list. * 10/13
9190	- Daybeacon 10						Remove from list. * 10/13
9195	- Daybeacon 12						Remove from list. * 10/13
9200	- Daybeacon 13						Remove from list. * 10/13
9205	- Daybeacon 14						Remove from list. * 10/13
9210	- Daybeacon 16						Remove from list. * 10/13
9215	- Daybeacon 18						Remove from list. * 10/13
9220	- Daybeacon 20						Remove from list. * 10/13
9225	- Daybeacon 21						Remove from list. * 10/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9230	- Daybeacon 22						<i>Remove from list.</i> * 10/13
9235	- Daybeacon 24						<i>Remove from list.</i> * 10/13
9240	- Daybeacon 26						<i>Remove from list.</i> * 10/13
9245	- Daybeacon 28						<i>Remove from list.</i> * 10/13
9250	- Daybeacon 29						<i>Remove from list.</i> * 10/13
9255	- Daybeacon 30						<i>Remove from list.</i> * 10/13
9580 335	SHIP ISLAND LIGHT	30-12-45.41N 88-57-58.74W	FI W 6s	82	6	Skeleton tower on concrete block. On same structure as Ship Channel Upper Reach Outbound Range Rear Light.	
		*					6/13
11320	- RANGE FRONT LIGHT	30-22-42.54N 90-10-10.17W	Q W	25		KRW on skeleton tower.	Visible all around; higher intensity on range line. * 18/13
11325	- RANGE REAR LIGHT 141 yards, 015° from front light.	30-22-46.58N 90-10-08.84W	Iso W 6s	49		White conical tower.	Visible all around; higher intensity on range line. * 19/13
*11853	ORLEANS LEVEE DISTRICT BAYOU BIENVENUE FLOODGATE LIGHT 2	30-00-09.18N 89-54-08.36W	FI R 2.5s			Marks southeast gate wall.	Private aid. 17/13
*11853.01	ORLEANS LEVEE DISTRICT BAYOU BIENVENUE FLOODGATE LIGHT 1	30-00-08.60N 89-54-08.54W	FI G 2.5s			Marks southwest gate wall.	Private aid. 17/13
*11853.02	ORLEANS LEVEE DISTRICT BAYOU BIENVENUE FLOODGATE LIGHT 3	30-00-08.93N 89-54-09.85W	FI G 2.5s			Marks northwest gate wall.	Private aid. 17/13
*11853.03	ORLEANS LEVEE DISTRICT BAYOU BIENVENUE FLOODGATE LIGHT 4	30-00-09.53N 89-54-09.64W	FI R 2.5s			Marks northeast gate wall.	Private aid. 17/13
12605	PICAYUNE BAYOU LIGHT 9	29-01-36.83N 89-10-54.17W	Iso G 6s	17	4	NB on pile.	Ra ref. * * * 13/13
12610	OYSTERVILLE LIGHT 9A	29-03-12.35N 89-12-13.25W	Iso G 6s	17	4	NB on piles.	* * * 13/13
12620	OLD GRAND BAYOU LIGHT 10	29-04-32.31N 89-12-44.85W	Iso R 6s	17	4	NB on pile.	Ra ref. * * * 13/13
12635	UPPER CAVE LIGHT 11	29-06-02.27N 89-14-09.04W	Iso G 6s	17	4	NB on dolphin.	* * * 13/13
12640	- LIGHT 11A	29-06-52.87N 89-14-32.58W	FI G 2.5s	17	4	NB on pile.	* * * 13/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
12645	- LIGHT 13	29-07-23.09N 89-14-34.52W	Iso G 6s	17	4	NB on pile.	Ra ref.
	*	*	*	*	*		13/13
12650	DEPOT POINT LIGHT 14	29-08-00.00N 89-14-31.84W	Iso R 6s	17	4	NB on skeleton tower on piles.	
	*		*	*	*		13/13
12655	- LIGHT 14A	29-08-24.28N 89-14-47.12W	Iso R 6s	17	4	NB on pile.	
	*		*	*	*		13/13
12665	- LIGHT 15	29-08-28.41N 89-15-00.45W	Iso G 6s	17	4	NB on pile.	Ra ref.
	*		*	*	*		13/13
12670	- LIGHT 16	29-09-05.67N 89-14-58.80W	FI R 2.5s	17	4	NW on pile, worded DANGER SEVERE SHOALING.	Ra ref.
	*		*				13/13
13615	CCI PORT NICKEL DOCK LIGHTS (2) LDB mile 76.4.	29-51-38.40N 89-58-21.80W	FI R 2.5s			On dock.	Private aid.
	*						5/13
13620	CCI PORT NICKEL DOCK LIGHT LDB mile 76.6	29-51-46.20N 89-58-20.30W	FI R 2.5s	12		On dolphin.	Private aid.
	*						5/13
13890 34805	GRETNA WATER INTAKE LIGHT RDB mile 96.7.	29-55-27.00N 90-03-38.00W	FI G 2.5s			On dolphin.	Private aid.
			*				21/13
14600	Upper Grand View Reach Anchorage Lower Daybeacon 147.5	30-02-10.38N 90-41-45.78W				NY on pile.	Ra ref.
	*						20/13
15045	WHITE CASTLE RANGE FRONT LIGHT RDB mile 192.7.	30-10-36.37N 91-08-10.72W	F G			KRW on skeleton tower on piles.	
							*
							21/13
15050	WHITE CASTLE RANGE REAR LIGHT 164 yards, 224° from front light.	30-10-32.87N 91-08-14.60W	F G			KRW on skeleton tower on piles.	
							*
							21/13
15180	PLAQUEMINE LIGHT 209 RDB mile 209.0.	30-17-41.40N 91-14-01.59W	Iso G 6s		4	SG on skeleton tower on pile.	Higher intensity beam up and down river.
		*					15/13
15727	<i>Great Lakes Dredging Lighted Pipeline Buoy</i>						<i>Remove from list.</i>
							*
							19/13
15727.01	<i>Great Lakes Dredging Lighted Pipeline Buoy</i>						<i>Remove from list.</i>
							*
							19/13
15727.02	<i>Great Lakes Dredging Lighted Pipeline Buoy</i>						<i>Remove from list.</i>
							*
							19/13
15727.03	<i>Great Lakes Dredging Lighted Pipeline Buoy</i>						<i>Remove from list.</i>
							*
							19/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
15727.04	Great Lakes Dredging Lighted Pipeline Buoy						<i>Remove from list.</i>
							* 19/13
*15728.25	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-17.87N 89-36-28.04W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.26	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-17.67N 89-36-16.18W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.27	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-15.23N 89-36-16.67W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.28	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-13.41N 89-36-17.03W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.29	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-10.97N 89-36-17.53W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.31	Great Lakes Dredge and Dock Lighted Danger Buoy	29-16-11.05N 89-36-23.55W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.32	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-22.25N 89-35-58.05W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.33	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-22.64N 89-35-57.70W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.34	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-20.52N 89-35-55.21W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.35	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-20.18N 89-35-55.63W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.36	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-18.81N 89-35-53.84W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.37	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-15.95N 89-35-52.61W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.38	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-15.81N 89-35-53.15W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
*15728.39	Great Lakes Dredge and Dock Lighted Danger Buoy	29-18-18.51N 89-35-54.31W	FI W 2.5s			Marks submerged spoil.	Private aid. 19/13
16205.01	- Lighted Buoy 13	29-19-07.56N 89-59-08.28W	FI G 4s			Green.	
	*						12/13
17945	- Shoal Lighted Buoy 3	29-03-57.92N 90-48-03.92W	FI G 2.5s		3	Green.	
		*					18/13
18945	- Lighted Buoy 18	29-32-18.62N 91-16-30.91W	FI R 4s		3	Red.	
		*					15/13
19055	- Buoy 29	29-34-14.05N 91-13-50.85W				Green can.	
		*					15/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
	*Add Heading: Vermilion Bay						
*20573	Vermilion Parish Danger Daybeacons (6)	29-34-17.00N 92-11-16.00W				Marks submerged shoreline erosion protection structures.	Private aids. 12/13
20658	- JUNCTION LIGHT FW	29-46-29.62N 92-10-15.04W *	Fl (2+1) R 6s	17	2	JR-SY on pile.	12/13
20750	- RANGE FRONT LIGHT	29-45-15.67N 93-00-36.40W *	Q R	17		On pile.	Visible all around; higher intensity on range line. 10/13
20755	- RANGE REAR LIGHT 450 yards, 000.7° from front light.	29-45-29.04N 93-00-36.22W *	Iso R 6s	37		On skeleton tower.	Visible 2° each side of range line. 10/13
21080	- A RANGE FRONT LIGHT	30-02-17.00N 92-45-15.85W *	Q W	25		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line. 15/13
21085	- A RANGE REAR LIGHT 255 yards, 255° from front light. *	30-02-15.06N 92-45-24.29W *	Iso W 6s	35		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line. 15/13
21090	- B RANGE FRONT LIGHT	30-03-00.74N 92-42-06.22W *	Q W	17		KRW on dolphin.	Visible all around; higher intensity on range line. 15/13
21095	- B RANGE REAR LIGHT 399 yards, 074.8° from front light. *	30-03-03.84N 92-41-53.09W *	Iso W 6s	37		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line. 15/13
21105	- Daybeacon 6						Remove from list. * 22/13
21115	- Daybeacon 10						Remove from list. * 22/13
21130	- Daybeacon 16						Remove from list. * 22/13
21135	- Daybeacon 18						Remove from list. * 22/13
*22298	MCMICHAEL DOCK LIGHT	30-18-42.00N 93-16-45.00W	Fl R 2.5s			Marks outermost upstream corner of dock.	Private aid. 11/13
22855	- G RANGE REAR LIGHT 429 yards, 339.7° from front light. *	29-49-46.43N 93-57-48.00W *	Iso G 6s (Night) Iso G 6s (Day)	73 71			Lighted throughout 24 hours. Ra ref. 6/13
22910 35715	- H RANGE REAR LIGHT 326 yards, 040° from front light. *	29-52-13.25N 93-55-41.97W *	Iso R 6s	49		KRW on skeleton tower on concrete block.	4/13
22950 35675	- L RANGE REAR LIGHT 957 yards, 037.5° from front light. *	29-56-58.20N 93-51-26.69W *	Iso W 6s	56		KRW on skeleton tower on piles.	4/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
22965 35665	- K RANGE REAR LIGHT 669 yards, 200° from front light. *	29-55-45.82N 93-52-12.96W	Iso W 6s	53		KRW on skeleton tower.	4/13
22975 35635	- M UPPER RANGE REAR LIGHT 745 yards, 020.1° from front light. *	29-58-37.58N 93-51-01.13W	Iso W 6s	40		On skeleton tower on piles. On same structure as Neches River Outer Range R Rear Light.	4/13
23010 35620	- N RANGE REAR LIGHT 972 yards, 250.3° from front light. *	29-57-52.49N 93-52-15.87W	Iso G 6s	85		KRW on skeleton tower on piles.	4/13
23020 35605	- Buoy 68 *	29-58-21.62N 93-50-32.92W				Red nun with yellow square.	17/13
23090 35540	- O RANGE REAR LIGHT 954 yards, 070.3° from front light. *	29-59-40.57N 93-46-31.66W	FI R 4s	54		KRW on skeleton tower on mud sills.	4/13
23125 35515	- P RANGE REAR LIGHT 1,204 yards, 038.9° from front light. *	30-01-34.54N 93-44-50.09W	Iso W 6s	47		KRW-I on skeleton tower on piles.	Visible 4° either side of range line. 4/13
23175 35455	- OUTER Q RANGE REAR LIGHT 464 yards, 231.6° from front light. *	30-02-13.84N 93-44-30.36W	Iso W 6s	49		KRW on skeleton tower on mud sills.	Visible all around; higher intensity on rangeline. 4/13
23325	- OUTER R RANGE REAR LIGHT 711 yards, 100.4° from front light. *	29-58-37.58N 93-51-01.13W	Iso W 6s	49		KRW on skeleton tower on piles. On same structure as Sabine-Neches Canal Upper Range M Rear Light.	5/13
23370	- S RANGE REAR LIGHT 131 yards, 113.2° from front light. *	29-59-19.08N 93-55-33.91W	Iso G 6s	53		KRW on skeleton tower on mud sills.	5/13
23435	- T RANGE REAR LIGHT 283 yards, 107.9° from front light. *	30-00-24.79N 93-58-32.45W	F G F G	55 57		On skeleton tower on block.	Lighted throughout 24 hours. 4/13
23445	- U RANGE REAR LIGHT 562 yards, 287.8° from front light. *	30-01-22.84N 94-02-00.00W	F G	41		KRW on skeleton tower.	Visible 2° each side of rangeline. 5/13
23695	- ENTRANCE CHANNEL RANGE A REAR LIGHT 4,476 yards, 301.1° from front light. *	29-22-19.51N 94-44-54.33W	F W (Night) F W (Day)	125 122		Skeleton tower on block.	Lighted throughout 24 hours. 5/13
24205	UPPER GALVESTON BAY OUTER RANGE FRONT LIGHT *	29-28-55.72N 94-51-23.97W	Q G	35		KRW on skeleton tower on piles.	Visible 2° each side of range line. 22/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
24210	UPPER GALVESTON BAY OUTER RANGE REAR LIGHT 1,492 yards, 146° from front light.	29-28-18.78N 94-50-55.60W	Iso G 6s	65		KRW on skeleton tower on piles.	Visible 2° each side of range line.
		*					22/13
24395	MORGANS POINT APPROACH OUTER RANGE FRONT LIGHT	29-35-46.91N 94-56-56.30W	FI G 2.5s (Night) FI W 2.5s (Day)	40 38		KRW on skeleton tower on piles.	Visible 2° each side of range line.
		*					9/13
24795	- LIGHT 96 120 feet outside the channel limit.	29-41-39.48N 94-59-25.47W	FI R 6s	17	4	TR on pile.	Ra ref.
		*					8/13
25075	LOWER RED LIGHT BEND OUTBOUND RANGE REAR LIGHT 174 yards, 096.8° from front light.	29-41-57.88N 94-59-44.69W	Iso R 6s	32		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line.
		*		*			12/13
*25107	- Daybeacon 2	29-42-13.59N 95-01-22.33W				TR on pile.	Private aid.
							20/13
25110	- Daybeacon 3	29-42-11.08N 95-01-21.02W				SG on pile.	Private aid.
		*					20/13
25115	- Daybeacon 4	29-42-13.59N 95-01-31.85W				TR on pile.	Private aid.
		*					20/13
25120	- Daybeacon 5	29-42-10.24N 95-01-33.94W				SG on pile.	Private aid.
		*					20/13
*25123	- Daybeacon 7	29-42-12.58N 95-01-40.47W				SG on pile.	Private aid.
							20/13
25125	- Daybeacon 6	29-42-15.71N 95-01-39.47W				TR on pile.	Private aid.
		*					20/13
25130	- Daybeacon 8	29-42-17.77N 95-01-47.40W				TR on pile.	Private aid.
		*					20/13
*25132	- Daybeacon 9	29-42-15.34N 95-01-48.18W				SG on pile.	Private aid.
							20/13
25135	- Daybeacon 10	29-42-20.19N 95-01-56.40W				TR on pile.	Private aid.
		*					20/13
*25138	- Daybeacon 11	29-42-17.80N 95-01-57.64W				SG on pile.	Private aid.
							20/13
25140	- Daybeacon 12	29-42-22.86N 95-02-06.19W				TR on pile.	Private aid.
		*					20/13
*25142	- Daybeacon 13	29-42-20.21N 95-02-06.67W				SG on pile.	Private aid.
							20/13
25145	- Daybeacon 14	29-42-25.17N 95-02-14.48W				TR on pile.	Private aid.
		*					20/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
25150	- Daybeacon 15	29-42-22.36N 95-02-14.98W *				SG on pile.	Private aid. 20/13
25155	- Daybeacon 16	29-42-28.05N 95-02-24.80W *				TR on pile.	Private aid. 20/13
*25158	- Daybeacon 17	29-42-25.24N 95-02-25.30W				SG on pile.	Private aid. 20/13
25160	- Daybeacon 18	29-42-30.75N 95-02-35.67W *				TR on pile.	Private aid. 20/13
*25162	- Daybeacon 19	29-42-27.81N 95-02-35.76W				SG on pile.	Private aid. 20/13
25165	- Daybeacon 20	29-42-33.22N 95-02-44.87W *				TR on pile.	Private aid. 20/13
*25168	- Daybeacon 21	29-42-31.59N 95-02-49.76W				SG on pile.	Private aid. 20/13
25170	- Daybeacon 22	29-42-36.28N 95-02-53.57W *				TR on pile.	Private aid. 20/13
25175	- Daybeacon 23	29-42-35.37N 95-03-03.75W *				SG on pile.	Private aid. 20/13
25180	- Daybeacon 24	29-42-39.34N 95-03-02.28W *				TR on pile.	Private aid. 20/13
25185	- Daybeacon 25	29-42-36.53N 95-03-07.47W *				SG on pile.	Private aid. 20/13
25190	- Daybeacon 26	29-42-42.49N 95-03-08.27W *				TR on pile.	Private aid. 20/13
25195	- Daybeacon 27	29-42-39.69N 95-03-13.06W *				SG on pile.	Private aid. 20/13
25200	- Daybeacon 28	29-42-46.34N 95-03-14.91W *				TR on pile.	Private aid. 20/13
25350	- LIGHT 112A	29-43-53.81N 95-01-54.42W *	FI R 2.5s	17	3	TR on pile.	Ra ref. 4/13
26100	TEXAS CITY CUT B OUTER RANGE FRONT PASSING LIGHT	29-22-00.03N 94-49-15.70W *	FI R 4s	17	3	On same structure as Texas City Channel Cut B Outer Range Front Light.	 5/13
27100 1365	- Approach Lighted Buoy MSC	28-12-01.03N 96-05-12.88W	Mo (A) W		4	Red and white stripes with red spherical topmark.	 7/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
27110 1385	- Entrance Light	28-25-18.47N 96-19-05.92W	FI W 10s	64	5	On same structure as Matagorda Ship Channel Range B Rear Light. 52	Obscured from 257° to 040°.
	*	*		*			4/13
27180	- B RANGE REAR LIGHT 1,192 yards, 128.7° from front light.	28-25-18.47N 96-19-05.92W	Oc W 4s	62		KRW on skeleton tower block. On same structure as Matagorda Bay Entrance Light.	
	*	*		*			* 4/13
27520	- D RANGE REAR LIGHT 658 yards, 181.5° from front light.	28-35-26.68N 96-34-02.96W	Oc G 4s	47		KRW on skeleton tower on piles.	
	*	*		*			* 4/13
27525	- D RANGE REAR LIGHT PASSING LIGHT	28-35-26.68N 96-34-02.96W	FI W 4s	18	5	On same structure as Matagorda Ship Channel Range D Rear Light.	
	*	*		*			4/13
28150	HARBOR ISLAND RANGE REAR LIGHT 1,500 yards, 301.2° from front light.	27-51-08.41N 97-04-24.07W	F W (Night) F W (Day)	123 125		Skeleton tower.	Visible 2° each side of range line. Lighted throughout 24 hours. FLY 2.5s exhibited when range light is on emergency power.
	*	*		*			4/13
28300	- Daybeacon 26						<i>Remove from list.</i>
							* 19/13
28310	- CUT A EAST RANGE REAR LIGHT 989 yards, 078.3° from front light.	27-50-47.19N 97-02-44.65W	Iso W 6s	93		KRW on skeleton tower on concrete block.	
	*	*		*			4/13
28845	TULE LAKE CHANNEL LEADING LIGHT	27-48-55.15N 97-27-44.76W	Q W	40	4	NG on skeleton tower on piles.	
					*		10/13
28875	- E RANGE FRONT LIGHT	27-49-01.91N 97-28-18.89W	Q G	26		KRW on skeleton tower.	Lighted throughout 24 hours.
		*		*			4/13
28880	- E RANGE REAR LIGHT 206 yards, 116.7° from front light.	27-48-59.16N 97-28-12.74W	Iso G 6s	37		KRW on skeleton tower on mud sills.	Lighted throughout 24 hours.
				*			5/13
28970	- INNER RANGE FRONT LIGHT	27-52-31.87N 97-15-01.00W	Q G	26		KRW on skeleton tower on piles.	Ra ref.
				*			* 4/13
28975	- INNER RANGE REAR LIGHT 2,136 yards, 336.8° from front light.	27-53-30.19N 97-15-29.10W	Iso G 6s	64		KRW on skeleton tower on piles.	
	*	*		*			* 4/13
30400	- RANGE FRONT LIGHT	29-43-22.79N 84-58-48.43W	Q G	15		KRW-I on dolphin.	Visible all around; higher intensity each side of range line.
		*					* 5/13
30405	- RANGE REAR LIGHT 1,377 yards, 350.3° from front light.	29-44-03.11N 84-58-56.33W	F G	45		KRW-I on skeleton tower on piles.	
	*						* 5/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*33728	SAUNDERS YACHTWORKS BASIN LIGHT 2	30-16-49.00N 87-40-32.50W	FI R 2.5s			Marks dolphin.	Private aid. 14/13
*33728.01	Saunders Yachtworks Basin Daybeacon 1	30-16-49.00N 87-40-33.20W				Marks dolphin.	Private aid. 14/13
33970	- A RANGE FRONT LIGHT	30-17-37.98N 88-07-17.07W *	Q R	17		KRW-I on pile.	Visible 2° each side of range line. 12/13
33975	- A RANGE FRONT PASSING LIGHT	30-17-37.98N 88-07-17.07W *	Q W	18	5	On same structure as Pass Aux Herons A Range Front Light.	 12/13
33980	- A RANGE REAR LIGHT 884 yards, 286.8° from front light.	30-17-45.58N 88-07-46.04W *	Iso R 6s	35		KRW-I on pile structure.	Visible 2° each side of range line. 12/13
34035	- Buoy 14	30-17-11.38N 88-08-14.26W *				Red nun with yellow triangle.	 4/13
34045	- C RANGE FRONT LIGHT	30-16-00.00N 88-11-25.47W	Q W	15		KRW-I on dolphin.	 * 5/13
34055	- C RANGE REAR LIGHT 2,599 yards, 247.1° from front light.	30-15-29.62N 88-12-47.37W *	Iso W 6s	57		KRW-I on piles.	 * 5/13
34060	-C RANGE REAR PASSING LIGHT	30-15-29.62N 88-12-47.37W *	Q W	14	5	On same structure as Pass Aux Herons C Range Rear Light.	 5/13
*34237	<i>Mobile Oyster Company Special Lighted Buoys (4)</i>	30-15-20.38N 88-11-27.93W	FI Y 2.5s			Marks perimeter of aquaculture farm.	Private aid. 13/13
34370	SHIP ISLAND LIGHT S	30-17-11.00N 88-52-00.00W *	Mo (A) W	17	5	MR-I on pile.	Ra ref. 21/13
*34717	ORLEANS LEVEE DISTRICT ICWW SURGE BARRIER SECTOR GATE LIGHT 2	30-00-54.77N 89-54-00.77W	FI R 2.5s			Flashing red light marks northeast gate wall when open. Fixed red light marks closed gate.	Private aid. 17/13
*34717.01	ORLEANS LEVEE DISTRICT ICWW SURGE BARRIER SECTOR GATE LIGHT 1	30-00-52.20N 89-54-01.46W	FI G 2.5s			Flashing green light marks southeast gate wall when open. Fixed red light marks closed gate.	Private aid. 17/13
*34717.02	ORLEANS LEVEE DISTRICT ICWW SURGE BARRIER SECTOR GATE LIGHT 4	30-00-50.02N 89-54-11.96W	FI R 2.5s			Flashing red light marks northwest gate wall when open. Fixed red light marks closed gate.	Private aid. 17/13
*34717.03	ORLEANS LEVEE DISTRICT ICWW SURGE BARRIER SECTOR GATE LIGHT 3	30-00-49.13N 89-54-09.15W	FI G 2.5s			Flashing green light marks southwest gate wall when open. Fixed red light marks closed gate.	Private aid. 17/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*34717.04	ORLEANS LEVEE DISTRICT ICWW SURGE BARRIER BYPASS GATE LIGHT 2A	30-00-51.31N 89-54-01.08W	FI R 2.5s			Flashing red light marks northeast gate wall when bypass gate is open for navigation.	Private aid. 17/13
*34717.05	ORLEANS LEVEE DISTRICT ICWW SURGE BARRIER BYPASS GATE LIGHT 1A	30-00-49.53N 89-54-00.00W	FI G 2.5s			Flashing green light marks southeast gate wall when bypass gate is open for navigation.	Private aid. 17/13
*34717.06	ORLEANS LEVEE DISTRICT ICWW SURGE BARRIER BYPASS GATE LIGHT 4A	30-00-48.53N 89-54-08.88W	FI R 2.5s			Flashing red light marks northwest gate wall when bypass gate is open for navigation.	Private aid. 17/13
*34717.07	ORLEANS LEVEE DISTRICT ICWW SURGE BARRIER BYPASS GATE LIGHT 3A	30-00-46.13N 89-54-07.66W	FI G 2.5s			Flashing green light marks southwest gate wall when bypass gate is open for navigation.	Private aid. 17/13
34805 13890	GRETNA WATER INTAKE LIGHT RDB mile 96.7.	29-55-27.00N 90-03-38.00W	FI G 2.5s			On dolphin.	Private aid. 21/13
			*				21/13
35330	Mermentau-Gibbstown Buoy 1	29-55-44.78N 92-57-13.16W				Green and yellow square.	10/13
	*		*		*		10/13
35455 23175	- Q RANGE REAR LIGHT 464 yards, 231.6° from front light.	30-02-13.84N 93-44-30.36W	Iso W 6s	49		KRW-I on skeleton tower on mud sills.	Visible all around; higher intensity on range line. 4/13
	*						4/13
35515 23125	- P RANGE REAR LIGHT 1,204 yards, 038.9° from front light.	30-01-34.54N 93-44-50.09W	Iso W 6s	47		KRW-I on skeleton tower on piles.	Visible 4° either side of range line. 4/13
	*						4/13
35540 23090	- O RANGE REAR LIGHT 954 yards, 070.3° from front light.	29-59-40.57N 93-46-31.66W	FI R 4s	54		KRW on skeleton tower on mud sills.	Passing light visible all around. 4/13
	*						4/13
35605 23020	- Buoy 68	29-58-21.62N 93-50-32.92W				Red nun with yellow square.	17/13
	*						17/13
35620 23010	- N RANGE REAR LIGHT 972 yards, 250.3° from front light.	29-57-52.49N 93-52-15.87W	Iso G 6s	85		KRW on skeleton tower on piles.	4/13
	*						4/13
35635 22975	- M UPPER RANGE REAR LIGHT 745 yards, 020.1° from front light.	29-58-37.58N 93-51-01.13W	Iso W 6s	40		On skeleton tower on piles. On same structure as Neches River Outer Range R Rear Light.	4/13
	*						4/13
35665 22965	- K RANGE REAR LIGHT 669 yards, 200° from front light.	29-55-45.82N 93-52-12.96W	Iso W 6s	53		KRW on skeleton tower.	4/13
	*						4/13
35675 22950	- L RANGE REAR LIGHT 957 yards, 037.5° from front light.	29-56-58.20N 93-51-26.69W	Iso W 6s	56		KRW on skeleton tower on piles.	4/13
	*						4/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
35715 22910	- H RANGE REAR LIGHT 326 yards, 040° from front light.	29-52-13.25N 93-55-41.97W	Iso R 6s	49		KRW on skeleton tower on concrete block.	
	*						* 4/13
36645	- F RANGE FRONT LIGHT	29-17-24.92N 94-55-04.42W	Q W	15		KRW-I on pile structure.	For eastbound traffic.
	*						* 5/13
36650	- F RANGE REAR LIGHT 935 yards, 079.9° from front light.	29-17-29.79N 94-54-33.22W	Iso W 6s	35		KRW-I on skeleton tower on piles.	
	*						* 5/13
37095	- INNER A RANGE REAR LIGHT 600 yards, 345.7° from front light.	29-11-18.03N 95-08-29.82W	Iso W 6s	36		KRW on skeleton tower on pile.	Visible all around; higher intensity on range line.
	*						5/13
37125	- OUTER RANGE REAR LIGHT 745 yards, 142.8° from front light.	29-10-09.63N 95-07-51.42W	Iso W 6s	40		KRW on skeleton tower on piles.	Visible all around; higher intensity on range line.
	*						5/13
37340	- B RANGE FRONT LIGHT	29-08-36.28N 95-09-45.33W	Q W	15		KRW-I on tower.	For westbound traffic. Visible all around; higher intensity on range line.
	*						5/13
37345	- B RANGE REAR LIGHT 699 yards, 235.4° from front light.	29-08-24.49N 95-10-04.80W	Iso W 6s	30		KRW-I on skeleton tower on piles.	Visible all around; higher intensity on range line.
	*						5/13
38450.01	- Daybeacon 17	28-16-01.49N 96-44-20.78W				SG on pile.	Ra ref.
	*						8/13
40130	- Buoy 53						<i>Remove from list.</i>
	*						* 14/13
*40130.01	- Daybeacon 45	27-36-11.01N 97-15-22.31W				SG-SY on pile.	
	*						14/13
40470	- Buoy 69						<i>Remove from list.</i>
	*						* 14/13
*40470.01	- Daybeacon 53	27-34-18.98N 97-16-22.28W				SG-SY on pile.	
	*						14/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8930	JARVIS LOWER RANGE B REAR LIGHT 292 yards, 008.7° from front light.	43-25-16.26N 124-16-30.90W	Iso R 6s	48		KRB on skeleton tower. On same structure as Jarvis Upper Range A Rear Light.	Visible 4° each side of range line.
	*	*		*			22/13
8950	JARVIS UPPER RANGE A REAR LIGHT 312 yards, 259.4° from front light.	43-25-16.29N 124-16-30.89W	Iso R 6s	48		KRB on skeleton tower. On same structure as Jarvis Lower Range B Rear Light.	Visible 1.5° each side of range line.
	*	*		*			22/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9515	- RANGE A REAR LIGHT 105 yards, 349.4° from front light.	44-00-09.28N 124-07-23.54W	Iso W 6s	33		KRB on skeleton tower on multi-pile structure.	Visible 5.5° each side of range line.
	*	*		*		*	22/13
9830	- ENTRANCE LEADING LIGHT	45-34-05.53N 123-56-27.99W	Oc Y 4s	79		On skeleton tower.	Visible from 271.5° to 272.5° .
		*		*			* 22/13
10280	- UPPER RANGE REAR LIGHT 1,075 yards, 083.7° from front light.	46-15-42.12N 123-30-10.32W	Iso R 6s	57		KRB on skeleton tower on multi-pile structure.	Visible 4° each side of range line.
	*	*		*			22/13
15585	POINT CHEHALIS RANGE FRONT LIGHT	46-54-30.67N 124-07-23.65W	FI R 2.5s	32		KRB on skeleton tower on multi-pile structure.	Visible 1.5° each side of range line.
				*		*	22/13
15590	POINT CHEHALIS RANGE REAR LIGHT 348 yards, 092.8° from front light.	46-54-30.15N 124-07-08.61W	Iso R 6s	67		KRB on skeleton tower on multi-pile structure.	Visible 1.5° each side of range line.
	*	*		*		*	22/13
15715	- NORTH CHANNEL RANGE C FRONT LIGHT	46-57-55.20N 123-58-23.51W	Q W	27		KRB on multi-pile structure.	Visible all around; higher intensity on range line. Ra ref.
				*			22/13
15720	- NORTH CHANNEL RANGE C REAR LIGHT 905 yards, 042.5° from front light.	46-58-14.98N 123-57-57.08W	Iso W 6s	64		KRB on multi-pile structure.	Visible 10° each side of range line. Ra ref.
	*			*			* 22/13
15735	- NORTH CHANNEL RANGE D FRONT LIGHT	46-57-33.52N 123-59-27.56W	Q W	32		KRB on multi-pile structure.	Visible 4° each side of range line.
				*			22/13
15740	- NORTH CHANNEL RANGE D REAR LIGHT 339 yards, 259.8° from front light.	46-57-31.73N 123-59-42.00W	Iso W 6s	53		KRB on multi-pile structure.	Visible 4° each side of range line.
	*			*			22/13
28710	ENTRANCE AND KUALOA POINT RANGE FRONT LIGHT	21-29-44.50N 157-49-58.29W	Q R	25		KRW on multi-pile structure.	Visible all around with higher intensity beam on range line.
		*		*			22/13
28715	ENTRANCE RANGE REAR LIGHT 559 yards, 227.3° from front light.	21-29-33.23N 157-50-11.32W	Iso R 6s	57		KRW on multi-pile structure.	Visible 4° each side of range line.
	*	*		*			22/13
28720	KUALOA POINT RANGE REAR LIGHT 235 yards, 348.9° from front light.	21-29-51.37N 157-50-00.00W	Iso R 6s	40		KRW on multi-pile structure.	Visible 4° each side of range line.
		*		*			22/13
29140	- ENTRANCE DIRECTIONAL LIGHT	21-17-38.77N 157-51-27.94W	F WRG	47		On monopole.	Alternating RW when right of inbound channel (023° M - 022° M), FR when right of inbound channel (022° M - 021° M). Alternating GW when left of inbound channel (023° M - 023.5° M), F G when left of inbound channel (023.5° M - 024° M).
		*		*		*	22/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
29185	- ENTRANCE CHANNEL RANGE FRONT LIGHT	21-18-19.11N 157-51-55.80W	F R	46		KRW on concrete structure.	Visible 4° each side of range line. Lighted throughout 24 hours. 22/13
		*		*			
29705	- RANGE REAR LIGHT 286 yards, 128.9° from front light.	21-35-37.76N 158-06-04.56W	Iso G 6s	45		KRW on post.	Visible 4° each side of range line. 22/13
			*				
29950	- Range Front Daybeacon	28-13-51.62N 177-21-17.20W				KRW on multi-pile structure.	 22/13
		*		*			
29955	- Range Rear Daybeacon 601 yards, 359.8° from front beacon.	28-14-09.47N 177-21-17.27W		51		KRW on pile structure.	 22/13
	*	*					
30190	- RANGE FRONT LIGHT	14-16-08.28S 170-40-27.22W	Q R	37		KRW on skeleton tower.	Visible 4° each side of range line. 22/13
		*		*			
30195	- RANGE REAR LIGHT 212 yards, 342° from front light.	14-16-02.29S 170-40-29.21W	Iso R 6s	182		KRW on square structure.	Visible 4° each side of range line. 22/13
	*	*		*			

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2100	<i>Oswego Canal Channel Lighted Buoy 6</i>	43-27-36.20N 76-30-37.80W	FI R 6s		4	Red.	
	*	*	*		*		*
*16494.5	<i>University of Minnesota Lighted Research Buoy 2</i>	46-48-42.00N 91-50-06.00W	FI Y 2s				Maintained from May 1 to Nov. 1. Private aid. 22/13
18315	South Fox Island Shoals Buoy 3	45-17-27.21N 85-50-56.58W				Green can.	 22/13
		*					
18320	South Fox Island Shoals Buoy 4	45-18-56.41N 85-51-05.66W				Red nun.	 22/13
		*					
*18647	<i>Grand Valley State University AXYS Lighted Buoy</i>	43-16-00.00N 86-32-00.00W	FI Y 20s				Maintained from Apr. 1 to Jan. 1. Private aid. 22/13
*18648	<i>Great Lakes Environmental Research Laboratory Muskegon Lighted Buoy</i>	43-11-17.40N 86-20-38.40W	FI Y 4s				Secured with two point mooring system, FI Y 4s spar buoys marking mooring locations. Private aid. 22/13
18702	<i>Grand Valley State University AXYS Lighted Buoy</i>						<i>Remove from list.</i> 22/13
							*
18704	<i>GLERL Muskegon</i>						<i>Remove from list.</i> 22/13
							*
18785	- LIGHT 1	43-13-20.50N 86-17-38.10W	Q G	10 3		SG on pile.	Private aid. 22/13
			*				

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
18790	- LIGHT 2	43-13-20.50N 86-17-40.10W	Q R	11 3		TR on pile.	Private aid.
			*	*			22/13
18795	- LIGHT 3	43-13-15.50N 86-17-38.10W	FI G 2.5s	10 3		SG on pile.	Private aid.
			*	*			22/13
18805	- LIGHT 5	43-13-09.50N 86-17-38.10W	FI G 4s	10 3		SG on pile.	Private aid.
				*			22/13
18810	- LIGHT 6	43-13-09.50N 86-17-40.10W	FI R 4s	10 3		TR on pile.	Private aid.
			*	*			22/13
*20878	CITY CENTRE PILE 1 LIGHT	44-05-49.50N 87-39-56.04W	FI W 2.5s				Private aid.
							22/13
*20879	CITY CENTRE PILE 2 LIGHT	44-05-49.44N 87-39-56.70W	FI W 2.5s				Private aid.
							22/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.