

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5940	Halftide Ledge Daybeacon 22	43-53-45.77N 69-46-20.79W				TR on pile.	Maintained from Apr. 15 to Oct. 15. * 29/13
5970	Carleton Ledges Jetty Daybeacon 33	43-54-07.09N 69-47-14.04W				SG on wooden spindle.	Maintained from Apr. 15 to Oct. 15. * 29/13
7890	- Buoy 2	43-31-44.80N 70-19-26.21W *				Red nun.	29/13
13050	CAPE COD CANAL BREAKWATER LIGHT 6	41-46-47.22N 70-29-23.28W	FI R 5s	43	9	TR on red cylindrical tower. 43	HORN: 1 blast ev 15s (2s bl). * 29/13
14871.4	- Lighted Buoy 6	41-33-30.70N 70-31-01.10W	FI R 2.5s			Red.	Private aid. * 29/13
14871.6	- Lighted Buoy 8	41-33-35.00N 70-30-56.00W	FI R 2.5s			Red.	Private aid. * 29/13
*15302.3	Eel Point Buoy 7A	41-18-01.20N 70-12-15.60W				Green can.	Private aid. 29/13
*15303.1	Eel Point Buoy 8A	41-17-38.90N 70-12-22.90W				Red nun.	Private aid. 29/13
*17047.5	- Buoy 16	41-36-07.00N 70-50-43.00W				Red nun.	Private aid. 29/13
17795	Castle Hill Light	41-27-43.80N 71-21-46.50W	Iso R 6s	40	12	Conical granite tower, upper half white. 34	HORN: 1 blast ev 10s (1s bl). Activated for 45 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A. * 29/13
17841	- Cable Crossing Buoy A						Remove from list. * 29/13
17841.1	- Cable Crossing Buoy B						Remove from list. * 29/13
17841.3	- Cable Crossing Buoy C						Remove from list. * 29/13
17841.35	- Cable Crossing Buoy D						Remove from list. * 29/13
17841.4	- Cable Crossing Buoy E						Remove from list. * 29/13
17841.5	- Cable Crossing Buoy F						Remove from list. * 29/13
17841.7	- Cable Crossing Buoy G						Remove from list. * 29/13
*18779	- Fairway Channel Lighted Buoy 6	41-44-00.40N 71-17-40.56W	F R			Red.	Private aid. 29/13
*18779.1	- Fairway Channel Lighted Buoy 7	41-44-00.40N 71-17-41.16W	F G			Green.	Private aid. 29/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
18780	- Buoy 8	41-44-37.62N 71-18-29.04W				Red nun.	Private aid. 29/13
	*						
18989.1	- North Obstruction Buoy						<i>Remove from list.</i> * 29/13
*19469.1	Quonochontaug Pond Buoy 3	41-20-17.46N 71-43-25.14W				Green can.	Private aid. 29/13
*19469.2	Quonochontaug Pond Buoy 4	41-20-17.70N 71-43-24.06W				Red nun.	Private aid. 29/13
19825	<i>Valiant Rock Lighted Whistle Buoy 11</i>	41-13-46.36N 72-03-59.97W	Q G		3	Green.	RACON: B (- • • •). * 29/13
20419	Watch Hill Speed Buoy						<i>Remove from list.</i> * 29/13
35720	- Buoy 8	40-26-37.00N 74-04-23.00W				Red nun.	 * 29/13
36635	Outerbridge Crossing Sound Signal	40-31-29.00N 74-14-49.00W				On bridge abutment.	Private aid. HORN: 1 blast ev 15s (5s bl). * 29/13
38050	Newburgh-Beacon Bridge Sound Signal	41-31-12.00N 73-59-58.00W				On bridge.	RACON: N(- •). Private aid. HORN: 1 blast ev 20s (2s bl). * 29/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*2166	- Channel Buoy 24	38-36-40.29N 75-05-37.17W				Red nun.	 29/13
2170	Middle Island West Buoy 1						<i>Remove from list.</i> * 29/13
2175	Middle Island West Daybeacon 3						<i>Remove from list.</i> * 29/13
2177	Middle Island West Buoy 5						<i>Remove from list.</i> * 29/13
4400	- Buoy 11	38-36-26.26N 75-04-51.70W				Green can.	 * 29/13
4410	- Buoy 14	38-36-24.63N 75-05-16.65W				Red nun.	 * 29/13
4415	- Buoy 15	38-36-19.60N 75-05-15.16W				Green can.	 * 29/13
4415.1	- Buoy 15A						<i>Remove from list.</i> * 29/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4417	- Buoy 16	38-36-19.01N 75-05-42.26W *				Red nun.	Maintained from May 1 to Nov. 15. 29/13
4420	- Buoy 17	38-36-16.77N 75-05-06.07W *				Green can.	Maintained from May 1 to Nov. 15. 29/13
4420.1	- Buoy 17A						<i>Remove from list.</i> * 29/13
4430	<i>Indian River Junction Lighted Buoy IR</i>	38-36-28.15N 75-05-36.21W *	Fl (2+1) R 6s		3	Red and green bands.	Maintained from May 1 to Nov. 15. 29/13
*4433	- Buoy 18	38-36-16.77N 75-06-06.07W				Red nun.	Maintained from May 1 to Nov. 15. 29/13
4435	- Buoy 19	38-36-13.32N 75-05-56.04W *				Green can.	Maintained from May 1 to Nov. 15. 29/13
*4436	<i>Middle Island West Channel Junction Lighted Buoy MI</i>	38-36-22.37N 75-06-22.20W	Fl (2+1) R 6s		3	Red and green bands.	Maintained from May 1 to Nov. 15. 29/13
*4437	Middle Island West Buoy 1	38-36-30.63N 75-06-17.90W				Green can.	Maintained from May 1 to Nov. 15. 29/13
*4438	Middle Island West Channel Buoy 3	38-36-38.56N 75-06-03.05W				Green can.	Maintained from May 1 to Nov. 15. 29/13
*4439	Middle Island West Channel Daybeacon 5	38-36-57.04N 75-05-59.00W				SG on pile.	 29/13
*4439.5	Middle Island West Channel Buoy 7	38-37-06.81N 75-05-50.95W				Green can.	Maintained from May 1 to Nov. 15. 29/13
10500	- RANGE REAR LIGHT 278 yards, 177.7° from front light. *	36-54-33.56N 76-10-34.85W	F G	76		Skeleton tower.	Lighted throughout 24 hours. Visible 0.5° either side of rangeline. 29/13
13090	- CHANNEL LIGHT 21	37-05-47.81N 76-19-51.55W	Fl G 4s	15	4	SG on pile.	Light equipment removed when endangered by ice. * 29/13
29584	- Junction Buoy B *	34-40-19.10N 77-05-42.94W *				Red and green band; nun. *	 29/13
30794	LOWER BRUNSWICK SOUTH RANGE REAR LIGHT 267 yards, 153.2° from front light. *	34-08-05.71N 77-56-42.74W *	Iso W 6s (NIGHT) Iso W 6s (DAY)	41 39		Skeleton tower on multi-pile structure.	Lighted throughout 24 hours. DAY: Visible 1.5° either side of rangeline. NIGHT: Visible all around; higher intensity 1.5° either side of rangeline. 29/13
30794.1	LOWER BRUNSWICK SOUTH RANGE REAR PASSING LIGHTS (2) *	34-08-05.71N 77-56-42.74W *	Fl W 4s	15	3	On same structure as Lower Brunswick South Range Rear Light.	 29/13
31925	- LIGHT 4	35-54-35.82N 75-44-27.80W	Fl R 4s	20	5	TR on multi-pile structure. *	Light equipment removed when endangered by ice. 29/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
39050	- Buoy 45A	34-40-24.34N 77-05-56.67W *				Green can with yellow square.	29/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1875	- RANGE A FRONT LIGHT	33-11-34.02N 79-10-40.77W *	FI W 2.5s (NIGHT) FI W 2.5s (DAY)	13 19 *		Skeleton tower on piles.	DAY: Visible 0.5° each side of range line. NIGHT: Visible 10° each side of range line. Lighted throughout 24 hours. 29/13
1880	- RANGE A REAR LIGHT 875 yards, 270° from front light. *	33-11-34.02N 79-10-35.66W *	Iso W 6s (Night) Iso W 6s (Day)	40 44 *		Skeleton tower on piles.	DAY: Visible 0.5° each side of range line. NIGHT: Visible 10° each side of range line. Lighted throughout 24 hours. 29/13
1910	- RANGE B FRONT LIGHT	33-11-58.14N 79-10-55.06W *	Q G	20 *		KRW on dolphin.	Visible 1.5° each side of range line. 29/13
1915	- RANGE B REAR LIGHT 308 yards, 285.1° from front light. *	33-12-00.52N 79-11-05.57W *	Iso G 6s	48 *		KRW on skeleton tower on piles.	Visible 1.5° each side of range line. 29/13
1940	- RANGE C FRONT LIGHT	33-14-28.67N 79-11-50.03W *	Q W	21 *		KRW on square skeleton tower on piles. On same structure as Winyah Bay Lower Range E Front Light.	Visible 4° each side of range line. 29/13
1945	- RANGE C REAR LIGHT 1,218 yards, 341.9° from front light. *	33-15-03.04N 79-12-03.37W *	Iso W 6s	48 *		KRW on square skeleton tower on piles.	Visible 4° each side of range line. 29/13
1970	- RANGE D FRONT LIGHT	33-15-25.86N 79-12-59.70W *	Q W	22 *		KRW on dolphin.	Visible 4° each side of range line. 29/13
1975	- RANGE D REAR LIGHT 696 yards, 322.5° from front light. *	33-15-42.26N 79-13-14.67W *	Iso W 6s	40 *		KRW on square skeleton tower.	Visible 4° each side of range line. 29/13
2000	- LOWER RANGE E FRONT LIGHT	33-14-28.69N 79-11-50.05W *	Q W	22 *		KRW on skeleton tower on piles. On same structure as Winyah Bay Range C Front Light.	Visible 2° each side of range line. 29/13
2005	- LOWER RANGE E REAR LIGHT 777 yards, 130.4° from front light. *	33-14-13.73N 79-11-29.16W *	Iso W 6s	46 *		KRW on skeleton tower on piles.	Visible 2° each side of range line. 29/13
2050	- UPPER RANGE E REAR LIGHT 569 yards, 310.4° from front light. *	33-18-33.01N 79-17-31.89W *	Iso W 6s	41 *		KRW on square skeleton tower.	Visible 1.5° each side of range line. 29/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2120	RABBIT ISLAND CHANNEL RANGE REAR LIGHT 1,130 yards, 009.1° front light.	33-20-56.42N 79-16-49.56W	Iso R 6s	48		KRW on tower on pile.	Visible 1.5° each side of range line. 29/13
		*		*			
4535	- FRONT LIGHT	32-00-25.64N 80-48-44.25W	Q W	35		KRW on skeleton tower.	Visible 2° each side of range line. 29/13
		*		*			
4585	- FRONT LIGHT	32-02-33.13N 80-49-41.60W	FI W 2.5s (NIGHT) FI W 2.5s (DAY)	15 13		On square skeleton tower on piles.	DAY: Visible 0.5° each side of range line. NIGHT: Visible 10° each side of range line. 29/13
		*					
4590	- REAR LIGHT 2,152 yards, 322.3° from front light.	32-03-23.68N 80-50-27.44W	Iso W 6s (NIGHT) Iso W 6s (DAY)	52 54		On square skeleton tower on piles.	DAY: Visible 0.5° each side of range line. NIGHT: Visible 4° each side of range line. 29/13
	*	*		*			
4625	- FRONT LIGHT	32-02-31.86N 80-51-10.73W	Q W	19			Visible 2° each side of range line. Lighted throughout 24 hours. 29/13
		*		*			
4630	- REAR LIGHT 599 yards, 288.9° from front light.	32-02-37.62N 80-51-30.49W	Iso W 6s	42			Visible 1.5° each side of range line. Lighted throughout 24 hours. 29/13
	*						
4980	- FRONT LIGHT	32-05-23.31N 81-01-10.85W	Q R	23		KRW on skeleton tower on piles.	Visible 2° each side of range line. 29/13
		*					
4985	- REAR LIGHT 513 yards, 066.8° from front light.	32-05-29.31N 81-00-54.41W	Iso R 6s	36		KRW on skeleton tower on concrete base.	Visible 2° each side of range line. 29/13
	*						
5010	FIG ISLAND LIGHT 57 120 feet outside channel limit.	32-04-47.47N 81-03-36.64W	FI G 4s	16	5	SG on dolphin.	 29/13
		*					
*10125	- Buoy 5	27-09-59.68N 80-09-08.35W				Green can.	 29/13
*10130	- Buoy 6	27-10-01.54N 80-09-15.33W				Red nun.	 29/13
10135	- Buoy 7	27-09-59.68N 80-09-33.56W				Green can.	 29/13
	*	*				*	
10140	- <i>Lighted Buoy 8</i>	27-10-10.91N 80-09-36.04W	Q R		4	Red.	 29/13
	*	*					
15100	Sand Key Preferred Channel Buoy						<i>Remove from list.</i> * 29/13
15140	- Buoy D						<i>Remove from list.</i> * 29/13
15145	- Buoy E						<i>Remove from list.</i> * 29/13
15150	- Buoy F						<i>Remove from list.</i> * 29/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
16945	- LIGHT 2 *	25-58-15.37N 81-46-16.53W	FI R 2.5s *	16	5	TR on pile. *	29/13
16947	- LIGHT 2						<i>Remove from list.</i> * 29/13
19890	- LIGHT 5	26-28-49.92N 82-03-37.60W	FI G 4s	16	5	SG on pile. *	29/13
23025	- <i>Lighted Buoy 10</i>	27-48-34.29N 82-27-04.70W	FI R 2.5s		5	Red. *	29/13
23195	- <i>Lighted Buoy 11</i>	27-48-43.64N 82-27-09.86W	Q G		4	Green. *	29/13
31415	- <i>Lighted Buoy 2</i>	18-10-06.08N 65-36-23.05W	FI R 2.5s		5	Red. *	29/13
32325	<i>Bajo Enmedio South Lighted Buoy 1</i> At south end of shoal.	18-00-44.87N 67-12-29.65W	FI G 4s		5	Green. *	29/13
32470	CURRENT ROCK LIGHT	18-18-53.76N 64-50-04.07W	FI W 6s	20	7	NR on skeleton tower. *	Higher intensity beams toward Buck Island and Two Brothers. 29/13
32885	- <i>Lighted Buoy 4</i> At northeast point of shoal. *	17-45-36.90N 64-41-47.21W	FI R 4s *		5	Red. *	29/13
32890	- <i>Lighted Buoy 6</i>	17-45-32.76N 64-41-45.19W	Q R		4	Red. *	29/13
32895	- LIGHT 7	17-45-25.81N 64-41-40.04W	FI G 4s	16	5	SG on dolphin. *	29/13
32905	<i>Round Reef Northeast Junction Lighted Buoy RR</i>	17-45-24.59N 64-41-45.28W	FI (2+1) G 6s		5	Green and red bands. *	29/13
32910	- LIGHT 9	17-45-22.72N 64-41-54.36W	FI G 2.5s	16	5	SG on dolphin. *	29/13
32915	- LIGHT 10	17-45-26.50N 64-42-01.06W	FI R 2.5s	17	5	TR on pile. *	29/13
32920	- LIGHT 11	17-45-20.27N 64-41-56.77W	Q G	10	4	SG on dolphin. *	29/13
33340	SOUTHWEST CAPE LIGHT	17-40-39.76N 64-53-59.40W	FI W 6s	45	7	Gray skeleton tower. *	29/13
34505	- <i>Lighted Buoy 116</i>	32-48-31.05N 79-45-21.66W	FI R 4s	16	5	Red with TY. *	29/13
37110	- LIGHT 234A *	31-14-54.94N 81-25-13.31W	Q R *	10	4	TR-TY on pile. *	29/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
37115	- Range Rear Daybeacon A 175.4 yards, 293.7° from front light.						<i>Remove from list.</i>
							* 29/13
37465	Satilla River Cut Daybeacon A16	30-59-43.25N 81-30-48.02W				TR-TY on pile.	
		*					29/13
37625	- LIGHT 63A	30-50-33.49N 81-28-49.06W	Fl G 4s	12	5	SG-SY on pile.	
						*	29/13
38300	- LIGHT 74	30-26-34.14N 81-27-05.76W	Fl R 4s	16	5	TR-TY on pile.	
						*	29/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*7748	CITY OF BAYOU LA BATRE DANGER LIGHT	30-22-04.86N 88-16-36.57W	Fl W 2.5s			Marks submerged outfall diffuser.	Private aid.
							29/13
23095 33877	- O RANGE REAR PASSING LIGHT	29-59-40.57N 93-46-31.66W	Fl R 4s	10	4	On same structure as Neches Canal Range O Rear Light.	
				*			29/13

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
159	<i>Scripps Waverider Lighted Research Buoy 193</i>						<i>Remove from list.</i>
							* 29/13
298	<i>NOAA Environmental Lighted Buoy 46114</i>	36-42-58.60N 122-20-54.90W	Fl (5) Y 20s			Yellow spherical buoy with whip antenna.	Aid maintained by NOAA.
						*	* 29/13
1540	- LIGHT V	32-40-54.76N 117-13-24.62W	Fl W 4s	17	6	NW on post worded DANGER SUBMERGED JETTY.	
				*			29/13
1593	<i>Shelter Island Lighted Buoy 2</i>	32-42-16.14N 117-14-01.84W	Fl (2) R 5s		3	Red.	
						*	29/13
3971.4	<i>- Bay Special Purpose Buoy MY4</i>						<i>Remove from list.</i>
							* 29/13
4785	BALLENA BAY ESTUARY LIGHT						<i>Remove from list.</i>
							* 29/13
5835	- RANGE REAR LIGHT 332 yards, 293.2° from front light.	37-58-19.04N 122-30-00.00W	Oc R 4s	56		KRW on pile.	Visible all around; higher intensity on range line.
				*			29/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8150	- ENTRANCE LIGHT 3	40-46-07.89N 124-14-19.55W	FI G 2.5s	37	4	SG on white cylindrical structure worded NORTH. *	29/13
8155	- ENTRANCE LIGHT 4	40-45-52.56N 124-14-37.74W	FI R 2.5s	57	5	TR on white cylindrical structure worded SOUTH. *	HORN: 1 blast ev 10s (1s bl). Operates continuously. 29/13
8840	- Channel Lighted Buoy 12	43-22-58.22N 124-17-28.24W	Q R		4	Red. *	29/13
9644	- Channel Lighted Buoy 9	44-37-34.95N 124-03-14.92W	FI G 2.5s		4	Green. *	29/13
14720	- LIGHT 2	46-12-45.88N 123-45-23.24W *	Q R	18	6	TR on pole. *	29/13
14721	- Lighted Buoy 2						<i>Remove from list.</i> * 29/13
15540	- BAR RANGE FRONT LIGHT	46-55-50.06N 124-09-33.37W *	Q R	32		KRB on skeleton tower.	Visible 1.5° each side of range line. Lighted throughout 24 hours. 29/13
15545	- BAR RANGE REAR LIGHT 544 yards, 039.1° from front light. *	46-56-02.55N 124-09-18.53W *	Iso R 6s	74		KRB on skeleton tower.	Visible 1.5° each side of range line. Lighted throughout 24 hours. 29/13
15565	- Entrance Lighted Gong Buoy 5	46-54-49.52N 124-12-35.03W	FI G 4s		4	Green. *	29/13
15685	- NORTH CHANNEL RANGE B FRONT LIGHT	46-55-27.42N 124-01-40.85W	Q W	25		KRB on skeleton tower, on multi-pile structure. *	Visible all around; higher intensity on range line. 29/13
15690	- NORTH CHANNEL RANGE B REAR LIGHT 602 yards, 222.2° from front light. *	46-55-14.24N 124-01-58.33W *	Iso W 6s	50		KRB on skeleton tower, on multi-pile structure. *	Visible all around; higher intensity on range line. 29/13
15745	- NORTH CHANNEL RANGE E FRONT LIGHT	46-58-13.46N 123-55-05.70W	Q G	20		KRB on skeleton tower, on multi-pile structure. *	Visible 4° each side of range line. 29/13
15750	- NORTH CHANNEL RANGE E REAR LIGHT 666 yards, 075.3° from front light. *	46-58-18.47N 123-54-37.82W *	Iso G 6s	50		KRB on skeleton tower, on multi-pile structure. *	Visible 4° each side of range line. 29/13
*16460	Discovery Bay Seafarm Lighted Buoy A	48-00-26.75N 122-50-22.11W	FI Y 6s			Yellow.	Private aid. 29/13
*16461	Discovery Bay Seafarm Lighted Buoy B	48-00-22.64N 122-50-35.36W	FI Y 6s			Yellow.	Private aid. 29/13
*17230	Day Island Lagoon Daybeacon 1	47-14-34.57N 122-33-40.06W				SG on pile.	Private aid. 29/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*17231	Day Island Lagoon Daybeacon 3	47-14-31.67N 122-33-40.09W		1	2	SG on pile.	Private aid. 29/13
*17232	Day Island Lagoon Daybeacon 5	47-14-28.50N 122-33-39.23W				SG on pile.	Private aid. 29/13
28007.39	<i>FAD Site MFH1</i>	21-17-30.00N 156-16-00.00W				Blue skiff.	Swing circle radius of up to 3.5 NM from charted position. Private aid. 29/13
	*						
28340	- ENTRANCE RANGE FRONT LIGHT	20-53-26.78N 156-28-19.52W	F R	49		KRW on post.	Visible 4° each side of range line. Lighted throughout 24 hours. 29/13
				*			
28345	- ENTRANCE RANGE REAR LIGHT 454 yards, 176.8° from front light.	20-53-13.30N 156-28-18.74W	F R	91		KRW on post.	Visible 4° each side of range line. Lighted throughout 24 hours. 29/13
				*			

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2005	Calf Island Spit Buoy 5	43-51-23.25N 76-23-26.42W				Green can.	 29/13
		*					
2065.1	- <i>Detached Breakwater West End Lighted Buoy 1</i>	42-28-35.19N 76-30-58.88W	FI G 4s		5	Green.	Replaced by can from Nov. 14 to May 21. 29/13
		*					
6935	- LIGHT 10	41-57-48.00N 83-07-17.00W	FI R 2.5s	44 13	7	Cylindrical tower with red band on platform.	 29/13
					*		
12905	SWEETS POINT LIGHT 13 Marks north side of shoal.	46-02-19.39N 83-56-09.71W	FI G 2.5s	20 6	6	White cylindrical tower with green stripe in middle.	Higher intensity beam on bearings 316° and 121° diminishing around remainder of horizon. 29/13
					*		
13165	- <i>Lighted Buoy 25</i>	46-16-00.95N 84-06-55.62W	FI G 4s		4	Green.	Year-round lighted buoy. 29/13
					*		*
13245	- <i>Lighted Buoy 35</i>	46-18-00.95N 84-07-10.77W	FI G 4s		4	Green.	Year-round lighted buoy. 29/13
					*		*
13465	- LIGHT 80	46-23-36.00N 84-13-47.87W	FI R 2.5s	27 8	4	TR on post.	 29/13
					*		
13605	- LIGHT 30	46-16-56.14N 84-12-28.69W	F R	31 9	6	TR on post.	 29/13
					*		
13690	- LIGHT 14	46-13-10.09N 84-09-58.23W	Q R	24 7	4	TR on post.	 29/13
					*		
19840	CALUMET PIERHEAD LIGHT	41-44-01.49N 87-31-44.48W	Iso R 6s	31 9	6	TR on post.	Obscured from 240° to 060°. 29/13
					*		

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES, 2013

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
21550	Whiskey Island Shoal Buoy 6	45-47-16.66N 85-37-58.58W *				Red nun.	

29/13

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
 Denotes a new entry when preceding the station number.