

Chart 18652 (Page E)

NM 38/15

SUISUN BAY AND SAN JOAQUIN RIVER							
TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO FEB 2015							
CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)					PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)
SUISUN PT. REACH	45	48	50	2-15	300	0.8	35
BULLS HEAD CHANNEL	36	36	35	2-15	300-350	1.2	35
EAST BULLS HEAD CHANNEL	34	34	34	2-15	350	1.1	35
PT. EDITH CROSSING RANGE	35	35	28	2-15	350	1.1	35
PRESTON PT. REACH	33	35	25	2-15	350	0.9	35
ROE ISLAND CHANNEL	33	34	34	2-15	350	1.1	35
PORT CHICAGO REACH	38	37	37	2-15	350	0.52	35
MIDDLE GROUND CHANNEL							
WEST REACH	36	37	36	2-15	350	1.29	35
EAST REACH	36	37	36	2-15	350	1.09	35
NEW YORK SLOUGH							
WEST REACH	34	35	35A	2-15	400	1.3	35
EAST REACH	34	35	33	2-15	400	1.7	35
SAN JOAQUIN RIVER							
ANTIOCH REACH	31.0	33.0	32.0	4-14	400	3.3	35

A. AN OBSTRUCTION WITH A DEPTH OF 36 FEET IS LOCATED AT 38°02'41.2" N 121°53'21.32" W
NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

Chart 18656

NM 38/15

SUISUN BAY							
TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO FEB 2015							
CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)					PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)
SUISUN PT. REACH	45	48	50	2-15	300	0.8	35
BULLS HEAD CHANNEL	36	36	35	2-15	300-350	1.2	35
EAST BULLS HEAD CHANNEL	34	34	34	2-15	350	1.1	35
PT. EDITH CROSSING RANGE	35	35	28	2-15	350	1.1	35
PRESTON PT. REACH	33	35	25	2-15	350	0.9	35
ROE ISLAND CHANNEL	33	34	34	2-15	350	1.1	35
PORT CHICAGO REACH	38	37	37	2-15	350	0.52	35
MIDDLE GROUND CHANNEL							
WEST REACH	36	37	36	2-15	350	1.29	35
EAST REACH	36	37	36	2-15	350	1.09	35
NEW YORK SLOUGH							
WEST REACH	34	35	35A	2-15	400	1.3	35
EAST REACH	34	35	33	2-15	400	1.7	35

A. AN OBSTRUCTION WITH A DEPTH OF 36 FEET IS LOCATED AT 38°02'41.2" N 121°53'21.32" W
NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

Chart 18657

NM 38/15

SUISUN BAY							
TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO FEB 2015							
CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)					PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)
SUISUN PT. REACH	45	48	50	2-15	300	0.8	35
BULLS HEAD CHANNEL	36	36	34	2-15	300-350	1.2	35
EAST BULLS HEAD CHANNEL	34	34	34	2-15	350	1.1	35
PT. EDITH CROSSING RANGE	35	35	28	2-15	350	1.1	35

NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

SECTION I

NM 38/15

Chart 18658

NM 38/15

SUISUN BAY							
TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO FEB 2015							
CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)					PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)
BULLS HEAD CHANNEL	36	36	35	2-15	300-350	1.2	35
EAST BULLS HEAD CHANNEL	34	34	34	2-15	350	1.1	35
PT. EDITH CROSSING RANGE	35	35	28	2-15	350	1.1	35
PRESTON PT. REACH	33	35	25	2-15	350	0.9	35
ROE ISLAND CHANNEL	33	34	34	2-15	350	1.1	35
PORT CHICAGO REACH	38	37	37	2-15	350	0.52	35
MIDDLE GROUND CHANNEL							
WEST REACH	36	37	36	2-15	350	1.29	35
EAST REACH	36	37	36	2-15	350	1.09	35

NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

Chart 18659

NM 38/15

SUISUN BAY							
TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO FEB 2015							
CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)					PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)
NEW YORK SLOUGH							
WEST REACH	34	35	35A	2-15	400	1.3	35
EAST REACH	34	35	33	2-15	400	1.7	35

A. AN OBSTRUCTION WITH A DEPTH OF 36 FEET IS LOCATED AT 38° 02' 41.2"N 121° 53' 21.32"W.

NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

Chart 18666

NM 38/15

SUISUN BAY							
TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO FEB 2015							
CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)					PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)
MIDDLE GROUND CHANNEL							
WEST REACH	36	37	36	2-15	350	1.29	35
EAST REACH	36	37	36	2-15	350	1.09	35
NEW YORK SLOUGH							
WEST REACH	34	35	35A	2-15	400	1.3	35
EAST REACH	34	35	33	2-15	400	1.7	35

A. AN OBSTRUCTION WITH A DEPTH OF 36 FEET IS LOCATED AT 38° 02' 41.2"N 121° 53' 21.32"W.

NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION