

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
35 5590	<b>Seguin Light</b>	43-42-26.90N 69-45-28.90W	F W	180	18	Brick conical tower. 53	Emergency light of reduced intensity when main light is extinguished. Two emergency lights may be visible from 340° and 160°. HORN: 2 blasts ev 20s (2s bl-2s si-2s bl-14s si). Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.  * 7/16
60 7520	<b>Cape Elizabeth Light</b>	43-33-57.86N 70-12-00.21W	Fl (4) W 15s 0.3s fl 2.2s ec. 0.3s fl 2.2s ec. 0.3s fl 2.2s ec. 0.3s fl 7.2s ec.	129	15	White conical tower. 67	Lighted throughout 24 hours. Emergency light of reduced intensity when main light is extinguished. HORN: 2 blasts ev 60s (3s bl-3s si-3s bl-51s si). Horn located 266 yards, 146° from light tower. Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.  * 7/16
3585	<b>Fort Point Light</b>	44-28-01.68N 68-48-42.06W	F W	88	15	White house. 31	Lighted throughout 24 hours. HORN: 1 blast ev 10s (1s bl). Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.  * 7/16
3965	<b>Browns Head Light</b>	44-06-42.35N 68-54-34.19W	F W (2R sectors)	39	W 14 R 11 R 11	White cylindrical tower. 24	Red from 001° to 050°, and from 061° to 091°, fairway between. Lighted throughout 24 hours. Emergency light of reduced intensity when main light is extinguished. HORN: 1 blast ev 10s (1s bl). Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.  * 7/16
4105	<b>Owls Head Light</b>	44-05-32.06N 69-02-38.49W	F W	100	16	White tower. 30	Obscured from 324° to 354° by Monroe Island. Lighted throughout 24 hours. Emergency light of reduced intensity when main light is extinguished. HORN: 2 blast ev 20s (2s bl-2s si-2s bl-14s si). Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.  * 7/16
4780	<b>Marshall Point Light</b>	43-55-02.72N 69-15-40.57W	F W	30	13	White cylindrical tower. 31	Emergency light of reduced intensity when main light is extinguished. Lighted throughout 24 hours. HORN: 1 blast ev 10s (1s bl). Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.  * 7/16

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5590 35	<b>Seguin Light</b>	43-42-26.90N 69-45-28.90W	F W	180	18	Brick conical tower. 53	Emergency light of reduced intensity when main light is extinguished. Two emergency lights may be visible from 340° to 160°. HORN: 2 blasts ev 20s (2s bl-2s si-2s bl-14s si). Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.  * 7/16
7520 60	<b>Cape Elizabeth Light</b>	43-33-57.86N 70-12-00.21W	FI (4) W 15s 0.3s fl 2.2s ec. 0.3s fl 2.2s ec. 0.3s fl 2.2s ec. 0.3s fl 7.2s ec.	129	15	White conical tower. 67	Located 266 yards, 146° from light tower. Lighted throughout 24 hours. Emergency light of reduced intensity when main light is extinguished. HORN: 2 blasts ev 60s (3s bl-3s si-3s bl-51s si). Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.  * 7/16
7610	SPRING POINT LEDGE LIGHT	43-39-07.61N 70-13-26.06W	FI W 6s (2R sectors)	54	W 12 R 10 R 10	White tower.	White from 331° to 337° covers fairway entrance, white from 074° to 288°; red in intervening sectors. Lighted throughout 24 hours. Emergency light of reduced intensity when main light is extinguished. HORN: 1 blast ev 10s (1s bl). Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.  * 7/16
7700	STATE PIER LIGHT						<i>Remove from list.</i>  * 7/16
11645	- Channel Lighted Buoy 2	42-18-08.41N 70-55-30.55W	FI R 4s		3	Red.	Replace by nun when endangered by ice. AIS: MMSI 993672282 (21).  * 7/16
11655	- Channel Lighted Buoy 4	42-17-51.64N 70-55-24.45W	Q R		3	Red.	Replaced by nun when endangered by ice. AIS: MMSI 993672102 (21).  * 7/16
11665	- Channel Lighted Buoy 6	42-17-39.11N 70-55-30.18W	FI R 4s		3	Red.	Replaced by nun when endangered by ice. AIS: MMSI 993672283 (21).  * 7/16
11685	- Channel Lighted Buoy 9	42-17-03.06N 70-55-47.24W	FI G 2.5s		3	Green.	Replaced by can when endangered by ice. AIS: MMSI 993672284 (21).  * 7/16
11695	Western Way Lighted Buoy WW	42-16-38.82N 70-55-55.82W	FI (2+1) R 6s		3	Red and green bands.	Replaced by nun when endangered by ice. AIS: MMSI 993672281 (21).  * 7/16
11706	- Channel Lighted Buoy 12	42-16-23.47N 70-55-54.12W	FI R 2.5s		3	Red.	Replaced by nun when endangered by ice. AIS: MMSI 993672285 (21).  * 7/16

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

## CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11712	- Channel Lighted Buoy 14	42-16-11.74N 70-55-58.45W	FI R 4s		3	Red.	Replaced by nun when endangered by ice. AIS: MMSI 993672286 (21). * 7/16
11730	- Channel Lighted Buoy 18	42-15-43.38N 70-56-20.86W	FI R 6s		3	Red.	Replaced by nun when endangered by ice. AIS: MMSI 993672287 (21). * 7/16
11735	- Channel Lighted Buoy 19	42-15-24.03N 70-56-29.42W	FI G 2.5s		3	Green.	Replaced by can when endangered by ice. AIS: MMSI 993672288 (21). * 7/16
11740	- Channel Lighted Buoy 22	42-15-18.01N 70-56-41.98W	Q R		3	Red.	Replaced by nun when endangered by ice. AIS: MMSI 993672289 (21). * 7/16
11755	- Channel Lighted Buoy 26	42-15-04.02N 70-57-14.46W	FI R 4s		3	Red.	Replaced by nun when endangered by ice. AIS: MMSI 993672290 (21). * 7/16
11760	- Channel Lighted Buoy 28	42-14-53.10N 70-57-43.11W	FI R 2.5s		3	Red.	Replaced by nun when endangered by ice. AIS: MMSI 993672291 (21). * 7/16
11825	- Channel Buoy 2	41-14-57.06N 70-57-59.89W				Red nun.	AIS: MMSI 993672292 (21). * 7/16
11835	- Channel Buoy 4	42-15-02.26N 70-58-16.90W				Red nun.	AIS: MMSI 993672293 (21). * 7/16
11845	- Channel Buoy 7	42-15-09.75N 70-58-31.83W				Green can.	AIS: MMSI 993672294 (21). * 7/16
11850	- Channel Buoy 9	42-15-13.80N 70-58-35.95W				Green can.	AIS: MMSI 993672295 (21). * 7/16
11855	- Channel Buoy 11	42-15-56.21N 70-55-50.84W				Green can.	AIS: MMSI 993672296 (21). * 7/16
11870	- Channel Buoy 16	42-15-16.68N 70-59-03.44W				Red nun.	AIS: MMSI 993672297 (21). * 7/16
11885	- Channel Lighted Buoy 1	42-15-56.22N 70-55-50.84W	FI G 2.5s		3	Green.	Replaced by LIB from Dec. 1 to Apr. 15. AIS: MMSI 993672298 (21). * 7/16
11895	- Channel Buoy 3	42-15-54.69N 70-55-28.76W				Green can.	AIS: MMSI 993672299 (21). * 7/16
11900	- Channel Lighted Buoy 4	42-15-52.38N 70-55-25.69W	FI R 4s		3	Red.	Replaced by LIB from Dec. 1 to Apr. 15. AIS: MMSI 993672302 (21). * 7/16
11905	- Channel Buoy 6	42-15-44.30N 70-55-16.50W				Red nun.	AIS: MMSI 993672303 (21). * 7/16

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11910	- Channel Buoy 7	42-15-42.23N 70-55-12.24W				Green can.	AIS: MMSI 993672304 (21).  * 7/16
11915	- Channel Lighted Buoy 8	42-15-30.55N 70-55-07.08W	FI R 4s		3	Red.	Replaced by LIB from Dec. 1 to Apr. 15. AIS: MMSI 993672305 (21).  * 7/16
11920	- Channel Buoy 10	42-15-25.05N 70-55-08.32W				Red nun.	AIS: MMSI 993672306 (21).  * 7/16
11925	- Channel Buoy 12	42-15-19.30N 70-55-11.17W				Red nun.	AIS: MMSI 993672307 (21).  * 7/16
35160	- Lighted Buoy 14	40-29-02.16N 74-00-44.50W	Q R		3	Red.	Replaced by LIB of reduced intensity when endangered by ice.  * 7/16

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5315	<i>Chincoteague Channel Lighted Buoy 11</i>	37-52-55.45N 75-24-51.42W	Q G		4	Green.	  * 7/16
16080	- LIGHT 4	37-40-38.80N 76-18-57.62W	FI R 4s	15	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.  * 7/16
*21987	- Buoy 4A	37-43-18.90N 75-48-26.18W				Red nun.	  * 7/16
22140	- Daybeacon 4						<i>Remove from list.</i>  * 7/16
28020	- Buoy 11	35-46-34.99N 75-31-46.62W				Green can.	  * 7/16
28025	- Lighted Buoy 12	35-46-37.57N 75-31-51.48W	FI R 2.5s		4	Red.	  * 7/16
28430	- CHANNEL LIGHT 16	35-50-36.50N 75-36-22.68W	FI R 2.5s	15	4	TR on pile.	  * 7/16
30037	- Buoy 11	34-20-40.62N 77-40-12.85W				Green can.	  * 7/16
30055	- LIGHT 2	34-21-13.55N 77-38-52.20W	FI R 4s	15	4	TR on pile.	  * 7/16
30075	- LIGHT 6	34-21-48.58N 77-38-07.91W	FI R 4s	15	4	TR on pile.	  * 7/16
30140 39520	NEW RIVER TO CAPE FEAR RIVER JUNCTION LIGHT BC	34-24-37.82N 77-35-41.27W	FI (2+1) G 6s	15	4	JG-SY on pile.	  * 7/16

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2016**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
35631	- Buoy 156A	39-27-17.74N 74-23-33.96W				Red nun with yellow triangle.	Maintained from May 1 to Nov. 1. Removed when endangered by ice.  * 7/16
35649	- Buoy 161	39-26-55.01N 74-23-30.93W				Green can with yellow square.	Maintained from May 1 to Nov. 1. Removed when endangered by ice.  * 7/16
37415	- LIGHT 46	36-35-39.35N 76-03-35.29W	FI R 4s	15	4	TR-TY on pile.	
				*	*		7/16
37420	- LIGHT 47	36-35-42.91N 76-03-31.46W	Q G	15	4	SG-SY on pile.	
				*	*		7/16
39205	- LIGHT 55	34-38-34.53N 77-10-48.27W	FI G 4s	15	4	SG-SY on pile.	
		*					7/16
39520 30140	- JUNCTION LIGHT BC	34-24-37.82N 77-35-41.27W	FI (2+1) G 6s	15	4	JG-SY on pile.	
					*		7/16
40095	- LIGHT 18	33-55-44.31N 78-10-17.82W	FI R 4s	15	4	TR-TY on multi-pile structure.	
		*			*		* 7/16
40100	- LIGHT 24	33-55-36.46N 78-11-21.97W	FI R 4s	18	4	TR-TY on multi-pile structure.	
		*					7/16

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2016**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
10245	- LIGHT 11	26-46-07.67N 80-02-40.22W	FI G 4s	16	5	SG on pile.	
					*		7/16
17190	- Daybeacon 13	25-59-51.47N 81-44-38.61W				SG on pile.	
		*					7/16
22460 60470	- Lighted Buoy 6A	27-38-02.21N 82-37-27.87W	Q R		4	Red with yellow triangle.	
					*		7/16
47340	- LIGHT 9	26-06-55.22N 80-07-33.60W	FI G 4s	16	5	SG on pile.	
					*		7/16
60470 22460	- Lighted Buoy 6A	27-38-02.21N 82-37-27.87W	Q R		4	Red with yellow triangle.	
					*		7/16

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2016**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9785	- Entrance Lighted Bell Buoy 2	44-48-28.62N 124-04-27.54W	FI R 4s		3	Red.	
		*					7/16

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2016**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11385	<i>Lieser Point Channel Lighted Buoy 18</i> 25 yards outside channel limit.	45-36-00.93N 122-34-15.06W	FI R 6s		4	Red.	
						*	7/16
11800	- LOWER RANGE REAR LIGHT 120 yards, 176.2° from front light.	45-39-29.10N 121-54-01.76W	Iso W 6s	69		KRB on skeleton tower.	Visible 10° each side of range line.
							*
							7/16
15795	- <i>North Channel Lighted Buoy 44</i>	46-58-02.09N 123-54-09.80W	FI R 2.5s		4	Red.	
						*	7/16
16745	- <i>Traffic Separation Lane Lighted Buoy SF</i>	47-45-54.35N 122-26-15.48W	FI Y 2.5s		5	Yellow.	RACON: G (— — *).
						*	7/16
18412	<i>Kamilche Sea Farm Lighted Buoy A</i>	47-07-31.38N 123-01-05.12W	FI Y 5s			Yellow.	Private aid.
		*	*				7/16
18750	CRESCENT HARBOR NAVY PIER BREAKWATER LIGHT *	48-17-05.92N 122-37-07.70W *	FI Y 6s			On end of breakwater.	Maintained by U.S. Navy.
						*	7/16
30811	<i>Agat Harbor Entrance Lighted Buoy AG</i>	13-22-03.68N 144-38-30.73E	Mo (A) W		4	Red and white stripes with red spherical topmark.	
						*	7/16

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES, 2016**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8080	- <i>Lighted Buoy 21</i>	42-11-54.81N 83-08-53.84W *	FI G 4s		4	Green.	Replaced by can from Dec. 14 to Apr. 7.
							7/16

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.