

## SECTION II

## CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2016

| (1)<br>No. | (2)<br>Name and Location  | (3)<br>Position                   | (4)<br>Characteristic   | (5)<br>Height | (6)<br>Range      | (7)<br>Structure     | (8)<br>Remarks  |
|------------|---------------------------|-----------------------------------|-------------------------|---------------|-------------------|----------------------|---|
| 3760       | HERON NECK LIGHT          | 44-01-30.40N<br>68-51-43.80W      | F R<br>(W sector)       | 92            | W 9<br>R 7        | White conical tower. | White sector from 030° to 063°.<br>Emergency light of reduced intensity when main light is extinguished.<br>HORN: 1 blast ev 30s (3s bl).<br>Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.<br>* 8/16                                  |
| 4580       | WHITEHEAD LIGHT           | 43-58-43.37N<br>69-07-27.40W      | Oc G 4s                 | 75            | 6                 | Gray granite tower.  | Emergency light of reduced intensity when main light is extinguished.<br>HORN: 2 blasts ev 30s (2s bl-2s sl-2s bl-24s sl). Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.<br>* 8/16  |
| 5520       | BURNT ISLAND LIGHT        | 43-49-30.70N<br>69-38-24.80W      | FI R 6s<br>(2W sectors) | 61            | W 8<br>W 8<br>R 6 | White conical tower. | White from 307° to 316°, and from 355° to 008°, covers fairways.<br>Emergency light of reduced intensity when main light is extinguished.<br>HORN: 1 blast ev 10s (1s bl).<br>Activated for 60 minutes during periods of reduced visibility by keying the microphone five times on VHF channel 83A.<br>* 8/16 |
| 16360      | - Buoy 8                  | 41-32-32.54N<br>70-39-18.32W<br>* |                         |               |                   | Red nun.             | Private aid.<br>8/16  |
| 16365      | - Buoy 9                  | 41-32-34.57N<br>70-39-16.28W<br>* |                         |               |                   | Green can.           | Private aid.<br>8/16  |
| 16640      | - Buoy 8                  | 41-41-14.39N<br>70-37-50.10W<br>* |                         |               |                   | Red nun.             | 8/16  |
| 29125      | - Lighted Buoy 4          | 40-37-33.26N<br>73-19-14.35W<br>* | FI R 2.5s               |               | 3                 | Red.                 | Replaced by nun when endangered by ice.<br>8/16   |
| 36840      | - Channel Lighted Buoy 38 | 40-36-17.13N<br>74-12-07.77W<br>* | FI R 4s                 |               | 3                 | Red.                 | 8/16  |

## CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2016

| (1)<br>No. | (2)<br>Name and Location                           | (3)<br>Position                   | (4)<br>Characteristic | (5)<br>Height | (6)<br>Range | (7)<br>Structure                            | (8)<br>Remarks  |
|------------|--|-----------------------------------|-----------------------|---------------|--------------|---|---|
| 1275       | - Lighted Buoy 2                                   | 39-16-57.55N<br>74-31-35.11W<br>* | FI R 2.5s             |               | 5            | Red.  | 8/16  |
| 2880       | - FRONT LIGHT                                      | 39-38-19.42N<br>75-34-33.20W      | Iso R 2s              | 23            |              | On multi-pile structure.                    | Lighted throughout 24 hours.<br>DAY: Visible 1.5° either side of range line.<br>NIGHT: Visible all around, higher intensity 1.5° either side of range line.<br>* 8/16 |
| 2885       | - REAR LIGHT<br>2034 yards, 008° from front light. | 39-39-19.13N<br>75-34-22.19W      | F R                   | 44            |              | On black skeleton tower, small white house. | Lighted throughout 24 hours.<br>Visible 1.5° either side of range line.<br>* 8/16   |

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2016

| (1)<br>No. | (2)<br>Name and Location   | (3)<br>Position                   | (4)<br>Characteristic            | (5)<br>Height | (6)<br>Range | (7)<br>Structure                        | (8)<br>Remarks  |
|------------|--|-----------------------------------|----------------------------------|---------------|--------------|---|---|
| 2975       | - FRONT LIGHT  | 39-45-02.17N<br>75-29-39.05W      | Iso R 2s                         | 50            |              | Skeleton tower on multi-pile structure. | Visible on range line only. Lighted throughout 24 hours. Visible 1.5° either side of range line.<br><br>* 8/16  |
| 3765       | MUD ISLAND LOWER RANGE FRONT LIGHT                                       | 40-02-04.39N<br>74-59-51.74W      | Q W (Night)<br>Q W (Day)         | 18<br>21      |              | On multi-pile structure.                | Lighted throughout 24 hours. DAY: Visible 0.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line.<br><br>* 8/16 |
| 3770       | MUD ISLAND LOWER RANGE REAR LIGHT<br>313 yards, 232.5° from front light. | 40-01-58.71N<br>75-00-01.30W      | Oc W 4s (Night)<br>Oc W 4s (Day) | 48<br>45      |              | Skeleton tower on multi-pile structure. | Lighted throughout 24 hours. Visible 1.5° either side of range line.<br><br>* 8/16  |
| 3840       | ENTERPRISE UPPER RANGE FRONT LIGHT                                       | 40-04-29.27N<br>74-55-04.02W      | FI W 2.5s                        | 28            |              | On skeleton tower.                      | Lighted throughout 24 hours. Visible 1.5° either side of range line.<br><br>* 8/16  |
| 3890       | EDGEWATER UPPER RANGE FRONT LIGHT  | 40-04-54.13N<br>74-52-26.34W      | Q G                              | 29            |              | Skeleton tower on multi-pile structure. | Lighted throughout 24 hours. DAY: Visible 1.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line.<br><br>* 8/16 |
| 3895       | EDGEWATER UPPER RANGE REAR LIGHT<br>344 yards, 069.81° from front light. | 40-04-57.69N<br>74-52-13.91W      | Oc G 4s                          | 49            |              | Skeleton tower on multi-pile structure. | Lighted throughout 24 hours. Visible 1.5° either side of range line.<br><br>* 8/16  |
| 5397       | - <i>Lighted Buoy 28</i>   | 37-55-46.43N<br>75-23-27.07W<br>* | FI R 4s                          |               |              | Red.                                    | <br><br><br>* 8/16  |
| 7545       | HOLLAND ISLAND BAR LIGHT   | 38-04-07.35N<br>76-05-44.91W      | FI W 2.5s                        | 37            | 7            | NB on skeleton tower on piles.          | <br><br>* 8/16  |
| 12946      | - Channel Daybeacon 9A   | 37-06-35.51N<br>76-17-34.22W<br>* |                                  |               |              | SG on pile.                             | <br><br><br>* 8/16  |
| 12947      | - Channel Day beacon 9B  | 37-06-32.84N<br>76-17-41.25W<br>* |                                  |               |              | SG on pile.                             | <br><br><br>* 8/16  |
| 13710      | - ENTRANCE LIGHT 2   | 37-14-46.00N<br>76-29-09.80W      | FI R 4s                          | 15            | 3            | TR on pile.                             | <br><br>* 8/16  |
| 13925      | - LIGHT 13   | 37-21-49.96N<br>76-38-14.25W      | FI G 4s                          | 15            | 4            | SG on pile.<br><br>*                    | <br><br><br>* 8/16  |
| 15070      | - ENTRANCE LIGHT 8R  | 37-36-06.04N<br>76-21-18.58W      | FI R 2.5s                        | 15            | 4            | TR on pile.<br><br>*                    | <br><br><br>* 8/16  |
| 18735      | - <i>Lighted Buoy 3</i>  | 38-51-47.70N<br>77-00-35.81W      | FI G 4s                          |               | 4            | Green.                                  | Maintained from Mar. 15 to Dec. 1. V-AIS: MMSI 993672308.<br><br>* 8/16   |
| 21970      | - Junction Daybeacon PC<br><br>*   | 37-43-35.96N<br>75-48-35.23W      |                                  |               |              | JR on pile structure.<br><br>*          | <br><br><br>* 8/16  |

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

## SECTION II

## CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2016

| (1)<br>No.     | (2)<br>Name and Location  | (3)<br>Position                   | (4)<br>Characteristic | (5)<br>Height | (6)<br>Range | (7)<br>Structure                        | (8)<br>Remarks  |
|----------------|---|-----------------------------------|-----------------------|---------------|--------------|---|---|
| 21990          | - Daybeacon 6<br>*  | 37-43-18.06N<br>75-48-27.54W      | *                     | *             | *            | TR on multi-pile structure.             | 8/16  |
| 29395          | FORT MACON REACH<br>RANGE FRONT LIGHT   | 34-42-04.91N<br>76-40-22.47W      | Q W                   | 23            |              | On skeleton tower.                      | Lighted throughout 24 hours.<br>DAY: Visible 1.5° either side of range line.<br>NIGHT: Visible all around; higher intensity 1.5° either side of range line.<br>* 8/16 |
| 29400          | FORT MACON REACH<br>RANGE REAR LIGHT<br>245 yards, 338.8° from front light.                       | 34-42-11.76N<br>76-40-25.46W      | Iso W 6s              | 34            |              | On skeleton tower.                      | Lighted throughout 24 hours.<br>DAY: Visible 1.5° either side of range line.<br>NIGHT: Visible all around; higher intensity 1.5° either side of range line.<br>* 8/16 |
| 30385          | SMITH ISLAND RANGE<br>FRONT LIGHT   | 33-53-36.12N<br>78-00-17.09W      | Iso R 2s              | 18            |              | On multi-pile structure.                | Lighted throughout 24 hours.<br>DAY: Visible 1.5° either side of range line.<br>NIGHT: Visible all around; higher intensity 1.5° either side of range line.<br>* 8/16 |
| 30667<br>30912 | UPPER MIDNIGHT<br>CHANNEL SOUTH RANGE<br>FRONT LIGHT  | 34-00-07.88N<br>77-56-23.39W      | FI R 2.5s             | 21            |              | Skeleton tower on multi-pile structure. | Lighted throughout 24 hours.<br>DAY: Visible 0.5° either side of range line.<br>NIGHT: Visible all around higher intensity 4.0° either side of range line.<br>* 8/16  |
| 30669<br>30914 | UPPER MIDNIGHT<br>CHANNEL SOUTH RANGE<br>REAR LIGHT<br>833 yards, 178.9 degrees from front light. | 33-59-54.33N<br>77-56-23.25W      | Iso R 6s              | 46            |              | Skeleton tower on multi-pile structure. | Lighted throughout 24 hours.<br>Visible 1.5° either side of range line.<br>* 8/16   |
| 30870          | - North Range Front<br>Daybeacon  |                                   |                       |               |              |   | Remove from list.<br>* 8/16   |
| 30875          | - North Range Rear<br>Daybeacon   |                                   |                       |               |              |   | Remove from list.<br>* 8/16   |
| 30912<br>30667 | UPPER MIDNIGHT<br>CHANNEL SOUTH RANGE<br>FRONT LIGHT  | 34-00-07.88N<br>77-56-23.39W      | FI R 2.5s             | 21            |              | Skeleton tower on multi-pile structure. | Lighted throughout 24 hours.<br>DAY: Visible 0.5° either side of range line.<br>NIGHT: Visible all around higher intensity 4.0° either side of range line.<br>* 8/16  |
| 30914<br>30669 | UPPER MIDNIGHT<br>CHANNEL SOUTH RANGE<br>REAR LIGHT<br>833 yards, 178.9 degrees from front light. | 33-59-54.33N<br>77-56-23.25W      | Iso R 6s              | 46            |              | Skeleton tower on multi-pile structure. | Lighted throughout 24 hours.<br>Visible 1.5° either side of range line.<br>* 8/16   |
| 31175          | WHALE HEAD BAY LIGHT 2  | 36-22-18.57N<br>75-50-10.70W      | FI R 4s               | 15            | 4            | TR on multi-pile structure.             | * 8/16  |
| 39550          | - LIGHT 100   | 34-20-38.57N<br>77-42-01.51W<br>* | FI R 4s               | 18            | 4            | TR-TY on pile.                          | 8/16  |
| 39597          | - Buoy 121  | 34-14-59.71N<br>77-46-56.97W<br>* |                       |               |              | Green can with yellow square.           | 8/16  |

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2016

| (1)<br>No. | (2)<br>Name and Location              | (3)<br>Position              | (4)<br>Characteristic | (5)<br>Height | (6)<br>Range | (7)<br>Structure | (8)<br>Remarks           |
|------------|---------------------------------------|------------------------------|-----------------------|---------------|--------------|------------------|--------------------------|
| 1820       | - Buoy 16                             | 33-33-03.94N<br>79-01-30.19W |                       |               |              | Red nun.         |                          |
|            | *                                     |                              |                       |               |              | *                | 8/16                     |
| 6605       | - <i>Lighted Buoy 17</i>              | 30-42-33.29N<br>81-23-57.79W | FI G 2.5s             |               | 5            | Green.           |                          |
|            |                                       |                              |                       |               |              | *                | 8/16                     |
| 6670       | - <i>Turning Basin Lighted Buoy E</i> | 30-42-25.55N<br>81-26-54.86W | FI Y 2.5s             |               | 5            | Yellow.          |                          |
|            |                                       |                              |                       |               |              | *                | 8/16                     |
| 21635      | - Channel Daybeacon 8                 |                              |                       |               |              |                  | <i>Remove from list.</i> |
|            |                                       |                              |                       |               |              |                  | *                        |
|            |                                       |                              |                       |               |              |                  | 8/16                     |
| 24960      | - JUNCTION LIGHT S                    | 27-45-32.51N<br>82-36-41.25W | FI (2+1) G 6s         | 16            | 4            | JG on pile.      |                          |
|            |                                       |                              |                       |               |              | *                | 8/16                     |
| 38910      | - <i>Lighted Buoy 60</i>              | 29-54-31.53N<br>81-17-43.86W | Q R                   |               | 4            | Red.             | AIS: MMSI 993672021.     |
|            |                                       |                              |                       |               |              | *                | 8/16                     |

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2016

| (1)<br>No. | (2)<br>Name and Location | (3)<br>Position              | (4)<br>Characteristic | (5)<br>Height | (6)<br>Range | (7)<br>Structure | (8)<br>Remarks |
|------------|--------------------------|------------------------------|-----------------------|---------------|--------------|------------------|----------------|
| 2675.01    | - Buoy 23                | 29-51-04.83N<br>84-40-57.27W |                       |               |              | Green can.       |                |
|            |                          | *                            |                       |               |              |                  | 8/16           |

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2016

| (1)<br>No.  | (2)<br>Name and Location  | (3)<br>Position               | (4)<br>Characteristic | (5)<br>Height | (6)<br>Range | (7)<br>Structure  | (8)<br>Remarks  |
|-------------|---------------------------|-------------------------------|-----------------------|---------------|--------------|---|---|
| 365<br>4245 | <b>Mile Rocks Light</b>   | 37-47-34.16N<br>122-30-37.35W | FI W 5s               | 49            | 14           | On cylindrical structure with white and orange bands.<br>49 | AIS MMSI: 993692039.<br>HORN: 1 blast ev 30s (2s bl).<br>Operates continuously.   |
|             |                           |                               |                       |               |              |   | *   |
|             |                           |                               |                       |               |              |   | 8/16  |
| 370<br>4220 | <b>Point Bonita Light</b> | 37-48-56.12N<br>122-31-46.27W | Oc W 4s               | 124           | 18           | White tower on building.<br>33                              | Emergency light of reduced intensity when main light is extinguished.<br>AIS: MMSI 993692000.<br>HORN: 2 blasts ev 30s (2s bl-2s si-2s bl-24s si). Activated by keying the microphone 5 times within 10 seconds on VHF channel 81A. |
|             |                           |                               |                       |               |              |   | *   |
|             |                           |                               |                       |               |              |   | 8/16  |
| 4220<br>370 | <b>Point Bonita Light</b> | 37-48-56.12N<br>122-31-46.27W | Oc W 4s               | 124           | 18           | White tower on building.<br>33                              | Emergency light of reduced intensity when main light is extinguished.<br>AIS: MMSI 993692000.<br>HORN: 2 blasts ev 30s (2s bl-2s si-2s bl-24s si). Activated by keying the microphone 5 times within 10 seconds on VHF channel 81A. |
|             |                           |                               |                       |               |              |   | *   |
|             |                           |                               |                       |               |              |   | 8/16  |
| 4245<br>365 | <b>Mile Rocks Light</b>   | 37-47-34.16N<br>122-30-37.35W | FI W 5s               | 49            | 14           | On cylindrical structure with white and orange bands.<br>49 | AIS MMSI: 993692039.<br>HORN: 1 blast ev 30s (2s bl).<br>Operates continuously.   |
|             |                           |                               |                       |               |              |   | *   |
|             |                           |                               |                       |               |              |   | 8/16  |

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2016

| (1)<br>No. | (2)<br>Name and Location  | (3)<br>Position               | (4)<br>Characteristic | (5)<br>Height | (6)<br>Range | (7)<br>Structure  | (8)<br>Remarks            |
|------------|---|-------------------------------|-----------------------|---------------|--------------|---|---------------------------|
| 9707       | - Lighted Buoy WR23   | 44-35-04.37N<br>124-01-19.56W | Q G                   |               | 4            | Green.  |                           |
|            |   |                               |                       |               | *            |   | 8/16                      |
| 10015      | Desdemona Sands Lighted Buoy 29<br>100 yards outside channel limit. | 46-11-31.38N<br>123-54-10.52W | Q G                   |               | 4            | Green.  |                           |
|            |   |                               |                       |               | *            |   | 8/16                      |
| 11630      | - LOWER RANGE FRONT LIGHT   | 45-35-06.41N<br>122-07-37.67W | Q G                   | 40            |              | KRB on skeleton tower on multi-pile structure.                                |                           |
|            |   |                               |                       |               |              |   | *<br>8/16                 |
| 11840      | WIND MOUNTAIN LOWER RANGE FRONT LIGHT 17                            | 45-42-05.86N<br>121-50-48.54W | Q G                   | 30            |              | KRB on skeleton tower on multi-pile structure, SG oriented up and downstream. |                           |
|            |   |                               |                       |               |              |   | *<br>8/16                 |
| 19705      | ZERO ROCK LIGHT (C)   | 48-31-25.30N<br>123-17-30.70W | FI W 4s               | 28            | 7            | White cylindrical tower with green band on top.                               | Ra ref.                   |
|            |   |                               |                       |               | *            |   | 8/16                      |
| 26430      | - Virtual Buoy 9  |                               |                       |               |              |   | Remove from list.<br>*    |
|            |   |                               |                       |               |              |   | 8/16                      |
| 26448      | - Virtual Buoy 11   |                               |                       |               |              |   | Remove from list.<br>*    |
|            |   |                               |                       |               |              |   | 8/16                      |
| 29367      | Papa Hotel Approach Point V-AIS                                     | 21-16-06.00N<br>157-56-23.00W |                       |               |              |   | AIS: MMSI 993692044.<br>* |
|            |   |                               |                       |               |              |   | 8/16                      |
| 29783      | - Lighted Buoy 4<br>*   | 21-57-16.00N<br>159-21-02.90W | FI R 2.5s             |               | 4            | Red nun.  |                           |
|            |   |                               |                       |               |              |   | 8/16                      |
| 29785      | - Lighted Buoy 6<br>*   | 21-57-09.65N<br>159-21-07.75W | FI R 4s               |               | 4            | Red nun.  |                           |
|            |   |                               |                       |               |              |   | 8/16                      |

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES, 2016

| (1)<br>No. | (2)<br>Name and Location | (3)<br>Position              | (4)<br>Characteristic | (5)<br>Height | (6)<br>Range | (7)<br>Structure                               | (8)<br>Remarks   |
|------------|--------------------------|------------------------------|-----------------------|---------------|--------------|--|--|
| 20635      | - Breakwater Light       | 43-01-36.99N<br>87-52-54.93W | FI (2) R 10s          | 61<br>19      | 14           | Black lantern on white square structure.<br>61 | HORN: 2 blasts ev 20s (2s bl-2s si-2s bl-14s si). Operates by keying the microphone five times on VHF channel 83A. |
|            |                          |                              |                       |               |              |  | *<br>8/16  |
| 22240      | - Lighted Buoy 23        | 44-34-01.01N<br>87-59-21.71W | FI G 4s               |               | 4            | Green.   | Replaced by can from Dec. 1 to Apr. 28.  |
|            |                          | *                            |                       |               |              |  | 8/16   |

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.