

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
105 8100	Goat Island Light	43-21-28.30N 70-25-30.30W	FI W 6s	38	12	25	HORN: 1 blast ev 15s (2s bl). Activated for 60 minutes during times of reduced visibility by keying the microphone five times on VHF channel 83A. * 10/16
1040	West Quoddy Head Light	44-48-54.39N 66-57-02.42W	FI (2) W 15s 2s fl 2s ec. 2s fl 9s ec.	83	18	White tower with red stripes. 49	Lighted throughout 24 hours. Emergency light of reduced intensity when main light is extinguished. HORN: 2 blasts ev 30s (2s bl- 2s si-2s bl-24s si). Activated for 60 minutes during times of reduced visibility by keying the microphone five times on VHF channel 83A. * 10/16
	Damariscotta River						
*5319	<i>University of Maine Research Lighted Buoy D</i>	43-50-40.00N 69-34-09.00W	FI Y 4s			Yellow.	Private aid. 10/16
	Saco River						
*7939	<i>University of Maine Research Lighted Buoy C</i>	43-28-37.00N 70-19-09.00W	FI Y 4s			Yellow.	Private aid. 10/16
8100 105	Goat Island Light	43-21-28.30N 70-25-30.30W	FI W 6s	38	12	25	HORN: 1 blast ev 15s (2s bl). Activated for 60 minutes during times of reduced visibility by keying the microphone five times on VHF channel 83A. * 10/16
11765	- Channel Buoy 31	42-14-11.16N 70-57-55.85W				Green can.	Maintained from May 1 to Oct. 15. * 10/16
24675	- Entrance Lighted Buoy 2A	41-08-11.70N 73-13-01.07W	FI R 4s		3	Red nun.	 * 10/16
29135	- Lighted Buoy 6	40-37-49.17N 73-19-19.81W	Q R		3	Red.	Replaced by nun when endangered by ice. * 10/16

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3230	- FRONT LIGHT	39-51-14.00N 75-19-53.00W	Iso G 2s	62		On square skeleton tower.	Visible on range line only. Lighted throughout 24 hours. Visible 1.5° either side of range line. * 10/16
*5017	- Channel Buoy 7	38-18-30.67N 75-06-43.70W				Green can.	10/16
10605	- Channel Daybeacon 11	36-57-45.60N 76-17-47.45W				SG on pile.	10/16
	*		*	*	*		10/16
13200	- Warning Daybeacon A						<i>Remove from list.</i> * 10/16
14720	- Channel Buoy 5	37-32-48.96N 76-19-20.09W				Green can.	10/16
		*					10/16

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
22100	- LIGHT 2	37-43-37.06N 75-54-36.83W	FI R 4s	15	4	TR on multi-pile structure.	
					*		10/16
22365	- SHOAL LIGHT 8	37-52-27.56N 75-49-24.22W	FI R 4s	15	4	TR on multi-pile structure.	
					*		10/16
22370	- SHOAL LIGHT 9	37-53-48.54N 75-48-39.87W	FI G 2.5s	15	4	SG on multi-pile structure.	
					*		10/16
22850	BROAD CREEK NORTH ENTRANCE LIGHT 1	37-57-09.47N 75-51-55.16W	FI G 2.5s	15	4	SG on pile.	
					*		10/16
24605	- Channel Daybeacon 6	38-20-35.91N 76-14-22.92W				TR on pile.	
	*		*	*	*	*	10/16
30310	- ENTRANCE RANGE FRONT LIGHT	33-52-23.50N 78-01-09.49W	Iso W 2s	23		Skeleton tower on platform.	Lighted throughout 24 hours. DAY: Visible 1.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line.
							* 10/16
39720	- LIGHT 153	34-05-13.62N 77-52-49.90W	FI G 4s	15	4	SG-SY on multi-pile structure.	
					*		10/16

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
570 7110	St. Johns Lighted Buoy STJ	30-23-35.37N 81-19-08.40W	Mo (A) W		6	Red and white stripes with red spherical topmark.	AIS: MMSI 993672320.
							* 10/16
7110 570	St. Johns Lighted Buoy STJ	30-23-35.37N 81-19-08.40W	Mo (A) W		6	Red and white stripes with red spherical topmark.	AIS: MMSI 993672320.
							* 10/16
11055	- Daybeacon 15	25-22-56.78N 80-13-18.21W				SG on pile.	
							* 10/16
11060	- Daybeacon 16	25-23-00.66N 80-13-23.04W				TR on pile.	
							* 10/16
11065	- Daybeacon 17	25-22-59.53N 80-13-29.48W				SG on pile.	
							* 10/16
18107	- LIGHT 5	26-27-56.86N 81-58-09.88W	FI G 4s	16	5	SG on pile.	
					*		10/16
21720	- CHANNEL LIGHT 16	27-20-26.98N 82-33-53.81W	FI R 2.5s	12	5	TR on pile.	
					*		10/16

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8115	- C RANGE REAR LIGHT 1,381 yards, 319.8° from front light.	30-21-16.28N 88-34-45.64W	F R (Night) F W (Day)	122 120		On pile.	Lighted throughout 24 hours. Visible 2° each side of range line. * 10/16
27120	- A RANGE FRONT LIGHT	28-26-34.41N 96-20-42.44W	Iso W 2s (Night) Iso W 2s (Day)	22 24		On pile with platform.	Visible all around; higher intensity 1.5° each side of range line. * 10/16

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
415	<i>Arena Cove Lighted Bell Buoy A</i>	38-54-39.21N 123-43-34.97W	Mo (A) W		4	Red and white stripes with red spherical topmark.	 * 10/16
*4745.5	<i>Harley Marine Lighted Mooring Buoy</i>	37-46-50.34N 122-20-15.18W	FI W 2s			White cylindrical hull, worded HARLEY MARINE.	Private aid. 10/16
9955	<i>Clatsop Spit Lighted Whistle Buoy 10</i>	46-15-14.24N 124-03-14.34W	FI R 4s		4	Red.	 * 10/16
11405	- MIDDLE RANGE FRONT LIGHT	45-35-14.39N 122-31-54.88W	Q R	40		KRB on multi-pile structure.	Visible all around. * 10/16
11430	FISHER QUARRY CHANNEL RANGE FRONT LIGHT	45-34-37.76N 122-28-05.45W	Q G	39		KRB on multi-pile structure.	Visible all around. * 10/16
11550	- UPPER RANGE FRONT LIGHT	45-33-06.41N 122-20-23.30W	Q R	17		KRB on multi-pile structure. On same structure as Reed Island Range Front Light.	Visible all around. * 10/16
11570	REED ISLAND RANGE FRONT LIGHT	45-33-06.41N 122-20-23.30W	Q R	17		KRB on multi-pile structure. On same structure as Washougal Upper Range Front Light.	Visible all around. * 10/16
15700	- <i>North Channel Lighted Bell Buoy 26</i>	46-56-12.37N 124-00-28.06W	FI R 2.5s		4	Red.	 * 10/16
Keehi Lagoon							
*29315	- BARGE TURNING CHANNEL RANGE FRONT LIGHT	21-19-47.77N 157-53-57.75W	Q G	16			Private aid. 10/16
*29320	- BARGE TURNING CHANNEL RANGE REAR LIGHT	21-19-53.08N 157-54-00.54W	F G	22			Private aid. 10/16

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
20705	- Tanker Pier Buoy 1						<i>Remove from list.</i> * 10/16

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII GREAT LAKES, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
20710	- Tanker Pier Buoy 2						<i>Remove from list.</i> *

10/16

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.