

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME I ATLANTIC COAST, 2016**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6935.5	Mere Point Brunswick PD Boat Launch Buoy 5						<i>Remove from list.</i> * 15/16
6935.6	Mere Point Brunswick PD Boat Launch Buoy 6						<i>Remove from list.</i> * 15/16
29425	- Buoy 3	40-40-03.39N 73-14-38.44W *				Green can.	Maintained from Apr. 1 to Nov. 15. 15/16
30680	- Buoy 10	40-50-33.43N 72-32-25.84W *				Red nun.	Maintained from Apr. 15 to Nov. 1. 15/16
31435	- Buoy 75	40-38-39.96N 73-16-32.38W *				Green can.	Maintained from Apr. 1 to Nov. 15. 15/16
31436	- Buoy 76	40-38-34.95N 73-15-56.39W *				Red nun.	Maintained from Apr. 1 to Nov. 15. 15/16

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2016**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
445	- <i>Lighted Buoy 7</i>	36-51-31.32N 75-50-55.16W	FI G 2.5s		6	Green.	* 15/16
475	- <i>Lighted Buoy 13</i>	36-54-03.21N 75-54-21.78W	FI G 4s		6	Green.	* 15/16
710 29125	<i>Cape Lookout Breakwater Lighted Buoy 2</i>	34-37-06.92N 76-33-45.92W *	Q R		3	Red.	15/16
1910	- Buoy 43	39-22-08.36N 75-02-07.76W *				Green can.	15/16
4845	- <i>Lighted Wreck Buoy WR7A</i>						<i>Remove from list.</i> * 15/16
8560	POOLES ISLAND SOUTH RANGE REAR LIGHT 1,183 yards, 000° from front light.	39-18-07.02N 76-14-11.66W	Oc W 4s	72		On skeleton tower.	Lighted throughout 24 hours. DAY: Visible 1.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line. * 15/16
8695	POOLES ISLAND NORTH RANGE FRONT LIGHT	39-18-31.43N 76-13-37.31W	FI W 2.5s (Night) FI W 2.5s (Day)	35 33		On skeleton tower on caisson.	Lighted throughout 24 hours. DAY: Visible 1.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line. * 15/16
8700	POOLES ISLAND NORTH RANGE REAR LIGHT 1,221 yards, 227° from front light.	39-18-07.02N 76-14-11.66W	Oc W 4s (Night) Oc W 4s (Day)	69 72		On same structure as Pooles Island South Range Rear Light.	Lighted throughout 24 hours. DAY: Visible 1.5° either side of range line. NIGHT: Visible 4.0° either side of range line. * 15/16

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2016**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
13496	- EAST RANGE FRONT LIGHT	37-15-01.95N 76-20-49.89W	Q W (Night) F W (Day)	20 23		On multi-pile structure.	Lighted throughout 24 hours. DAY: Visible 1.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line.  * 15/16
13497	- EAST RANGE REAR LIGHT 1,398 yards, 076.6° from front light.	37-15-04.85N 76-20-32.98W	Iso W 6s (Night) F W (Day)	57 54		Skeleton tower on multi-pile structure.	Lighted throughout 24 hours. DAY: Visible 1.5° either side of range line. NIGHT: Visible all around; higher intensity 1.5° either side of range line.  * 15/16
17125	- Channel Buoy 3A	38-13-58.82N 76-44-33.50W				Green can.	Maintained from Mar. 15 to Dec. 1.  * 15/16
17205	- Buoy 9	38-13-18.83N 76-45-59.39W *				Green can.	Maintained from Mar. 15 to Dec. 1.  15/16
20485	- Buoy 14	39-12-36.64N 76-27-29.21W *				Red nun.	15/16
21975	- Daybeacon 1P *	37-43-30.63N 75-48-30.71W				SG on pile.	15/16
23060	- Channel Daybeacon 16 *	37-58-26.41N 76-00-07.70W				TR on pile.	15/16
23095	- Channel Daybeacon 27 *	37-59-22.45N 76-00-37.16W				SG on pile.	15/16
23510	- CHANNEL LIGHT 6 *	38-07-39.91N 75-56-47.71W	FI R 4s	16	3	TR on slatted pile structure.	15/16
24995	HAMBROOKS BAR WARNING LIGHT *	38-35-42.24N 76-04-51.14W	FI W 2.5s (R sector)	19	W 6 R 5	NW on white cylindrical structure on red base worded DANGER. *	Red from 312° to 335° covers shoal south side of river at entrance to Cambridge.  15/16
26095	- Daybeacon 12 *	38-48-38.06N 76-12-33.56W				TR on pile. *	15/16
29125 710	Cape Lookout Breakwater Lighted Buoy 2 *	34-37-06.92N 76-33-45.92W	Q R		3	Red.	15/16
29345	- Channel Lighted Buoy 7	34-38-53.36N 76-40-38.09W	Q G		5	Green. *	15/16
34745	- LIGHT 58	34-42-07.96N 76-36-45.55W	FI R 2.5s	15	4	TR on pile. *	15/16
35205	- LIGHT 56	39-41-22.11N 74-09-44.05W	FI R 4s	15	4	TR-TY on pile. *	15/16

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II ATLANTIC COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
35647	- Buoy 160A	39-26-47.52N 74-23-28.92W				Red nun with yellow triangle.	Maintained from May 1 to Nov. 1. Removed when endangered by ice.  * 15/16

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3750.7	- Buoy 16	32-38-43.21N 79-58-24.41W *				Red nun.	15/16
10680.5	LUMMUS ISLAND TURNING BASIN LIGHT D	25-45-58.27N 80-10-12.68W	Q Y	16	4	NY on pile. *	15/16
11455	- WEST SHOAL PREFERRED CHANNEL LIGHT	25-18-15.65N 80-12-50.27W	FI (2+1) G 6s	16	4	JG on pile. *	15/16
15005	- LIGHT 8	24-35-39.95N 81-48-01.59W	FI R 4s	12	5	TR on pile. *	15/16
35410	- Daybeacon 1						<i>Remove from list.</i> * 15/16
35415	- Daybeacon 2						<i>Remove from list.</i> * 15/16
50125	- LIGHT 10	25-22-47.59N 80-16-17.28W	FI R 6s	16	5	TR-TY on pile. *	15/16
50235	- LIGHT 26	25-16-36.35N 80-22-02.82W	FI R 6s	16	5	TR-TY on pile. *	15/16

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV GULF OF MEXICO, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
655	<i>Fugro Mecocean Lighted Buoy</i>	26-41-28.45N 90-27-27.82W *	FI Y 2.5s			Yellow.	SIGN: FUGRO-WR-294. Private aid.  15/16
12022	MOEM BONNIES BAY PIPELINE LIGHT A *	29-23-55.98N 89-34-19.96W	FI Y 2.5s			Marks submerged pipeline.	Private aid.  15/16
12022.01	MOEM BONNIES BAY PIPELINE LIGHT B *	29-23-57.09N 89-34-21.35W	FI Y 2.5s			Marks submerged pipeline.	Private aid.  15/16
12032	MOEM GASPER BAY PIPELINE LIGHT A *	29-27-46.53N 89-34-50.70W	FI Y 2.5s			Marks submerged pipeline.	Private aid.  15/16
12072	MOEM LONG BAY PIPELINE LIGHT A *	29-29-31.64N 89-34-39.86W	FI Y 2.5s			Marks submerged pipeline.	Private aid.  15/16

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2016

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8792	- Channel Lighted Buoy 6	43-21-03.89N 124-19-52.08W	FI R 2.5s		4	Red.	
					*		15/16
11680	- DIKE LIGHT 82	45-34-54.68N 122-06-24.77W	FI R 4s	18	4	TR on dolphin.	
					*		15/16
13385	- LIGHT 35	46-26-07.85N 118-38-38.72W	FI G 2.5s	21	4	SG on tower.	
					*		15/16
13425	- LIGHT 47	46-30-01.57N 118-37-13.55W	FI G 2.5s	18	5	SG on platform.	
					*		* 15/16
13470	- LIGHT 56	46-31-58.21N 118-33-59.68W	FI R 4s	13	5	TR on platform.	
					*		* 15/16
15571	- Entrance Lighted Whistle Buoy 8	46-54-28.59N 124-11-00.30W	Q R		4	Red.	
		*					15/16
* 17208	- Obstruction V-AIS 3	47-16-28.45N 122-22-54.97W					AIS: MMSI 993692046 (21). 15/16
18115	- ENTRANCE LEADING LIGHT	47-39-59.67N 122-24-10.74W	Oc R 4s	22		NR on multi-pile structure.	Visible 1.5° each side of range line.
		*		*			15/16
18820	- RANGE FRONT LIGHT	48-21-32.95N 122-33-57.67W	Q W	17		KRW on multi-pile structure.	Visible all around; higher intensity on range line.
		*		*			15/16
18825	- RANGE REAR LIGHT 1,081 yards, 252° from front light.	48-21-21.94N 122-34-48.33W	Iso W 6s	55		KRW on skeleton tower on multi-pile structure.	Visible 14° each side of range line.
		*		*			15/16
19455	BLACK ROCK LIGHT 9	48-32-45.17N 122-45-56.95W	FI G 4s	10	4	SG on skeleton tower.	
		*					15/16

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.