

SECTION II
NAVIGATION PUBLICATIONS

NM 30/16

SAILING DIRECTIONS CORRECTIONS

PUB 120 12 Ed 2015 LAST NM 10/16

Pub. 120 has been updated to 2 July 2016, including Notice to Mariners 27/2016, and can be downloaded from the NGA Maritime Website:

<http://msi.nga.mil/NGAPortal/MSI.portal>

(NGA)

30/16

PUB 142 14 Ed 2015 LAST NM 48/15

Pub. 142 has been updated to 25 June 2016, including Notice to Mariners 26/2016, and can be downloaded from the NGA Maritime Website:

<http://www.msi.nga.mil/NGAPortal/MSI.portal>

(NGA)

30/16

COAST PILOT CORRECTIONS

COAST PILOT 4 47 Ed 2015 03 JUL 2016

LAST NM 28/16

Chapter 12—Paragraph 302; read:

⁽³⁰²⁾ Main Street Bridge at Mile 829.7 has a bascule span with a clearance of 22 feet at the center. (See 117.1 through 117.59 and 117.261, chapter 2, for drawbridge regulations.) Broadway Bridge has a fixed span that crosses the waterway at Mile 830.1 with a clearance of 63 feet (65 feet at center). Veterans Memorial Bridge at Mile 830.6 was under construction in 2016.

(L 491-2016; LNM 26/16 CG7)

30/16

COAST PILOT 5 44 Ed 2016 03 JUL 2016

LAST NM 23/16

Chapter 5—Paragraph 311; read:

⁽³¹¹⁾ Johns Pass, about 3 miles N of Blind Pass, between Treasure Island and Sand Key, affords passage for small craft from the Gulf to the N part of Boca Ciega Bay. A marked channel leads from the Gulf of Mexico through Johns Pass thence N to the Intracoastal Waterway. The channel is reportedly subject to considerable shoaling between Daybeacon 1 and Buoy 3. Extreme caution and local knowledge of the channel conditions is advised. The entrance to the channel is marked by a light and the channel is marked by lights, buoys and daybeacons. In Johns Pass the flood current sets NE at an average velocity of 2.0 knots and ebbs SW at an average velocity of 1.5 knots. (See Tidal Current Tables for daily predictions.)

(LNM 24/16 CG7; NOS 11411)

30/16

Chapter 13—Paragraph 131; read:

⁽¹³¹⁾ Puerto San Juan Light (18°28'15"N., 66°07'24"W.), 169 feet above the water, is shown from a buff-colored tower on the summit of Castillo del Morro.

(LNM 24/16 CG7)

30/16

Chapter 13—Paragraph 490; read:

⁽⁴⁹⁰⁾ Punta Tuna Light (17°59'19"N., 65°53'07"W.), 111 feet above the water, is shown from a white octagonal tower on a dwelling, near the end of the point. The point projects as a high cliff; a 400-foot hill 0.5 mile N is prominent.

(LNM 24/16 CG7)

30/16

COAST PILOT 6 46 Ed 2016 03 JUL 2016
LAST NM 19/16

Chapter 10—Paragraph 66; read:

⁽⁶⁶⁾ A dredged entrance channel leads north from deep water in Lake Huron to a harbor basin and anchorage area formed by two breakwaters. The harbor entrance is marked by lights on the outer ends of the breakwaters. In 2016, the controlling depth was 7 feet in the entrance channel to the basin, thence depths of 7 to 8 feet were available in the basin.

(DD 27329)

30/16

DIGITAL PUBS - QUARTERLY CORRECTIONS

DIGITAL PUBS - QUARTERLY **162 Ed 2016**
(2ND QUARTER) **NEW EDITION**
(NGA) N30/16